

SAFETY DATA SHEET

Page 1 of 4

1. IDENTIFICATION

PRODUCT NAME: MICROTECH ENCAPSULATED MANUAL UTENSIL PRESOAK

RECOMMENDED USE: SOLID FLATWARE PRESOAK & DETARNISHER

RESTRICTIONS ON USE: DO NOT USE IN A MANNER INCONSISTENT WITH THE LABEL.

LABEL BRAND: U S CHEMICAL SDS 5345016M CODE 5345032

USCHEMICAL 316 HART STREET WATERTOWN, WI 53094 USA

1-866-923-4913 USA

MEDICAL EMERGENCY: SPILL EMERGENCY: 1-800-424-9300 USA

PRODUCT INFORMATION: 1-800-558-9566 USA (8 A.M. TO 5 P.M. CST MONDAY TO FRIDAY)

INTERNET ADDRESS: WWW.USCHEMICAL.COM

2. HAZARD(S) IDENTIFICATION

CLASSIFICATION: SKIN CORROSION (CATEGORY 1C), EYE DAMAGE (CATEGORY 1)

ACUTE TOXICITY: ORAL (CATEGORY 4)

LABEL ELEMENTS

SIGNAL WORD: DANGER

PICTOGRAMS: CORROSION, EXCLAMATION MARK

HAZARD STATEMENTS: CAUSES SEVERE SKIN BURNS AND SERIOUS EYE DAMAGE.

HARMFUL IF SWALLOWED.

PRECAUTIONARY STATEMENTS: Wear chemical-splash safety goggles, chemical-resistant protective gloves and protective footwear. Avoid contact with eyes, skin and clothing. Do not breathe dusts. Do not eat, drink, or smoke when using this product. Wash hands and affected areas thoroughly after handling.

FIRST AID: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing for at least 15 minutes. IF ON SKIN (OR HAIR): Take off immediately all contaminated clothing. Rinse skin with water for at least 15 minutes. Wash contaminated clothing before reuse. IF SWALLOWED: Rinse mouth. Call a Poison Center or physician if you feel unwell. Do NOT induce vomiting. If conscious, dilute by drinking up to a cupful of milk or water as tolerated. IF INHALED: Remove person to fresh air and keep comfortable for breathing.

START FIRST AID. IMMEDIATELY CALL A POISON CENTER OR PHYSICIAN.

EMERGENCY TELEPHONE: 1-866-923-4913

Storage: Store tightly closed only in original corrosive-resistant plastic container. Store locked up. **Disposal:** Dispose of contents in accordance with all federal, state and local applicable laws and regulations. KEEP OUT OF REACH OF CHILDREN. FOR COMMERCIAL AND INDUSTRIAL USE ONLY.

HAZARDS NOT OTHERWISE CLASSIFIED: Not applicable.

3. COMPOSITION / INFORMATION ON INGREDIENTS

HAZARDOUS INGREDIENT(S)	CAS#	WEIGHT %
SODIUM METASILICATE	6834-92-0	48.0
SODIUM CARBONATE	497-19-8	15.0

STATE RIGHT TO KNOW: SEE SECTION 15 FOR STATE RTK CHEMICAL NAMES IN MIXTURE.

4. FIRST-AID MEASURES

Page 2 of 4

IF IN EYES: RINSE CAUTIOUSLY WITH WATER FOR SEVERAL MINUTES. REMOVE CONTACT LENSES, IF PRESENT AND EASY TO DO. CONTINUE RINSING FOR AT LEAST 15 MINUTES. IF ON SKIN (OR HAIR): TAKE OFF IMMEDIATELY ALL CONTAMINATED CLOTHING. RINSE SKIN WITH WATER FOR AT LEAST 15 MINUTES. WASH CONTAMINATED CLOTHING BEFORE REUSE. IF SWALLOWED: RINSE MOUTH. Do NOT INDUCE VOMITING. IF CONSCIOUS, DILUTE BY DRINKING UP TO A CUPFUL OF MILK OR WATER AS TOLERATED.

IF INHALED: REMOVE PERSON TO FRESH AIR AND KEEP COMFORTABLE FOR BREATHING. START FIRST AID. IMMEDIATELY CALL A POISON CENTER OR PHYSICIAN.

EMERGENCY TELEPHONE: 1-866-923-4913

MOST IMPORTANT SYMPTOMS / EFFECTS: CAUSES SEVERE SKIN BURNS AND SERIOUS EYE DAMAGE. MAY CAUSE BLINDNESS WITHOUT IMMEDIATE FIRST AID. HARMFUL IF SWALLOWED. CAUSES BURNS AND SERIOUS DAMAGE TO MOUTH, THROAT AND STOMACH. CORROSIVE TO ALL BODY TISSUES.

MEDICAL CONDITIONS AGGRAVATED: NONE KNOWN.

NOTE TO PHYSICIAN: CALL 1-866-923-4913 FOR EXPOSURE MANAGEMENT ASSISTANCE.

5. FIRE-FIGHTING MEASURES

CHEMICAL HAZARDS: CORROSIVE, NON-FLAMMABLE.

COMBUSTION PRODUCT HAZARDS: OXIDES OF CARBON AND OTHER FUMES.
METHODS: SELECT EXTINGUISHER AND METHODS BASED ON FIRE SIZE AND TYPE.
EQUIPMENT: WEAR SCBA AND FULL PROTECTIVE GEAR AS CONDITIONS WARRANT.
NFPA RATING: HEALTH-3/FLAMMABILITY-0/ INSTABILITY-0/SPECIAL HAZARD-N.AP.
SUITABLE EXTINGUISHERS: WATER, DRY CHEMICAL, CO2 OR FOAM SUITABLE FOR FIRE.
UNSUITABLE EXTINGUISHERS: NO RESTRICTIONS BASED ON CHEMICAL HAZARDS.

6. ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS: EVACUATE UNPROTECTED PERSONNEL FROM AREA. WEAR PERSONAL PROTECTION INCLUDING RUBBER BOOTS. SEE SECTION 8. VENTILATE AREA IF NEEDED. BE CAREFUL NOT TO SLIP. WASH THOROUGHLY AFTER CLEAN-UP. ENVIRONMENTAL PRECAUTIONS: PREVENT SPILL FROM ENTERING DRAIN, STORM SEWER OR SURFACE WATERWAY. PREVENT WATER AND SOIL CONTAMINATION. CLEAN-UP METHODS: THIS MATERIAL IS A SOLID IN A PLASTIC CANISTER WHICH CANNOT BE SPILLED OR LEAK. HOWEVER, DURING USE THE PRODUCT IS DISSOLVED AND THIS DILUTED SOLUTION SHOULD BE TREATED AS FOLLOWS: FLUSH SMALL SPILLS WITH WATER TO LOCAL SANITARY SEWER AS PERMITTED. AFTER SPILL COLLECTION, FLUSH AREA WITH WATER AND FOLLOW WITH NORMAL CLEAN-UP PROCEDURES. BE CAREFUL AS SPILLS ARE SLIPPERY.

7. HANDLING AND STORAGE

HANDLING: FOLLOW ALL LABEL DIRECTIONS. INSTRUCT PERSONNEL ABOUT PROPER USE, HAZARDS, PRECAUTIONS, AND FIRST AID MEASURES. AVOID INHALATION, INGESTION, AND CONTACT WITH SKIN, EYES AND CLOTHING. DO NOT TASTE OR SWALLOW. REMOVE AND WASH CONTAMINATED CLOTHING AND FOOTWEAR BEFORE REUSE. PRODUCT RESIDUE MAY REMAIN IN EMPTY CONTAINERS. HANDLE CAREFULLY TO AVOID DAMAGING CONTAINER.

STORAGE: STORE TIGHTLY CLOSED ONLY IN ORIGINAL CORROSIVE-RESISTANT PLASTIC CONTAINER. STORE LOCKED UP. STORE AT AMBIENT TEMPERATURES IN A DRY AREA OUT OF DIRECT SUNLIGHT. PROTECT FROM FREEZING. ROTATE STOCK REGULARLY. KEEP AWAY FROM FOOD AND DRINK. KEEP OUT OF REACH OF CHILDREN.

MICROTECH ENCAPSULATED MANUAL UTENSIL PRESOAK SDS 5345016M

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Page 3 of 4

EXPOSURE LIMITS: SODIUM METASILICATE = NONE

SODIUM CARBONATE = NONE

ENGINEERING CONTROLS: NONE REQUIRED. GENERAL ROOM VENTILATION IS TYPICALLY ADEQUATE.

PERSONAL PROTECTION

EYES: SAFETY GOGGLES (INDIRECT-VENTED OR NON-VENTED) AND AN EYE-WASH STATION.

HANDS: CHEMICAL-RESISTANT PROTECTIVE GLOVES (RUBBER OR NEOPRENE).

RESPIRATORY: WEAR DUST MASK IF HANDLING CREATES AIR-BORNE DUST.

FEET: RUBBER BOOTS DURING SPILL CLEAN-UP AND WHEN EXPOSURE IS POSSIBLE. **BODY:** RUBBER FULL-COVER PROTECTIVE CLOTHING WHEN EXPOSURE IS POSSIBLE.

9. PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE: GREEN SOLID AUTO-IGNITION

ODOR: NONE

pH CONCENTRATE: ABOVE 12.5

pH @ 2500 PPM SOLUTION: 11.6 (BASIC)

pH @ USE DILUTION: N.AV.

PHYSICAL STATE: SOLID

RELATIVE DENSITY (WATER): 1.500

SOLUBILITY (WATER): >20%

VAPOR PRESSURE: N.AV.

VAPOR DENSITY: N. AV.

VISCOSITY: N.AP.

AUTO-IGNITION TEMPERATURE: N.AV.
DECOMPOSITION TEMPERATURE: N.AV.

EVELOSIVE LIMITS (LEL/LIEL). NONE

EXPLOSIVE LIMITS (LEL/UEL): NONE

EVAPORATION RATE: N.AV.

FLAMMABILITY (SOLID, GAS): N.AP.

FLASH POINT: NONE

INITIAL BOILING POINT/RANGE: N.AV.

MELTING POINT/FREEZING POINT: >140°F

ODOR THRESHOLD: N.AV.

PARTITION COEFF. (N-OCTANOL/WATER): N.AV

OTHER: N.AV.

10. STABILITY AND REACTIVITY

REACTIVITY: MIXING WITH INCOMPATIBLES CAN RELEASE HEAT + HAZARDOUS GASES.

CHEMICAL STABILITY: STABLE.

POSSIBILITY OF HAZARDOUS REACTIONS: SEE REACTIVITY. WILL NOT POLYMERIZE.

CONDITIONS TO AVOID: TEMPERATURES BELOW 1.7°C (35°F) OR ABOVE 49°C (120°F).

MATERIALS TO AVOID: ACIDS AND OTHER CHEMICALS. MIX ONLY WITH WATER.

HAZARDOUS DECOMPOSITION PRODUCTS: NONE UNDER NORMAL CONDITIONS.

11. TOXICOLOGICAL INFORMATION

ROUTES OF EXPOSURE: EYES, SKIN, INGESTION, INHALATION.

INFORMATION ON ROUTES OF EXPOSURE: NO LC50/LD50 TEST DATA ON MIXTURE.

ACUTE EFFECTS /SYMPTOMS: CORROSIVE TO ALL BODY TISSUES.

EYES: CAUSES SERIOUS EYE DAMAGE. MAY CAUSE PAIN, REDNESS AND WATERING.

SKIN: CAUSES SEVERE SKIN BURNS. MAY CAUSE DELAYED PAIN, REDNESS AND BLISTERING.

INGESTION: CAUSES BURNS AND SERIOUS DAMAGE TO MOUTH, THROAT AND STOMACH.

INHALATION: MAY CAUSE CORROSIVE EFFECTS TO NOSE, THROAT, AND RESPIRATORY SYSTEM.

CHRONIC / OTHER EFFECTS: NO REPORTABLE GERM CELL MUTAGENS, SKIN SENSITIZERS,

RESPIRATORY SENSITIZERS, REPRODUCTIVE TOXINS OR ASPIRATION HAZARDS.

SPECIFIC TARGET ORGANS (SINGLE/REPEATED): NONE KNOWN.

NUMERICAL MEASURES OF TOXICITY: ATEmix (ORAL-RAT) = 1950 MG / KG

CARCINOGENS: NO REPORTABLE ACGIH, IARC, NTP, OR OSHA CARCINOGENS.

MICROTECH ENCAPSULATED MANUAL UTENSIL PRESOAK SDS 5345016M

12. ECOLOGICAL INFORMATION

Page 4 of 4

ECOTOXICITY / CHEMICAL FATE: NOT AVAILABLE.

13. DISPOSAL CONSIDERATIONS

DISPOSAL METHOD: UNDILUTED PRODUCT IS REGULATED UNDER ENVIRONMENTAL AND TRANSPORTATION LAWS AS A CORROSIVE WASTE (RCRA CLASS D002). DISPOSE OF CONTENTS IN ACCORDANCE WITH ALL FEDERAL, STATE, AND LOCAL APPLICABLE LAWS AND REGULATIONS. CONSULT STATE AND LOCAL AUTHORITIES FOR RESTRICTIONS ON DISPOSAL OF CHEMICAL WASTE. MANAGE CHEMICAL WASTES THROUGH AN APPROVED WASTE TREATMENT FACILITY. DO NOT REUSE EMPTY CONTAINER. RINSE EMPTY CONTAINER THOROUGHLY WITH WATER BEFORE DISCARDING CONTAINER IN ACCORDANCE WITH CURRENT LOCAL COMMUNITY CODES. PLEASE RECYCLE EMPTY CONTAINER WHENEVER POSSIBLE.

14. TRANSPORT INFORMATION

DOT / IMDG / TDG: UN3253, DISODIUM TRIOXOSILICATE MIXTURE, 8, III, LTD. QTY.

15. REGULATORY INFORMATION

EPA CERCLA RQ: NO
EPA REGISTERED: NO
OSHA HAZARDOUS: YES

PHOSPHORUS CONTENT: SEE LABEL

PROPOSITION 65: NO

SARA 311/312 HAZARDS: ACUTE

SARA 313 CHEMICALS: NO

STATE RIGHT TO KNOW: SODIUM METASILICATE/6834-92-0, WATER/7732-18-5,

SODIUM CITRATE/68-04-2, POLYACRYLIC ACID/66019-18-9, SODIUM CARBONATE/497-19-8

TSCA INVENTORY STATUS: ALL COMPONENTS ARE LISTED ON THE INVENTORY.

VOC: 0.00% CALCULATION METHOD USED IS BASED ON CALIFORNIA ARB STANDARD.

16. OTHER INFORMATION

PREPARATION DATE: 6-6-14 **PREPARED BY:** RC **ABBREVIATIONS:** N.AV. = NOT AVAILABLE REVISED SECTION: 16 N.AP. = NOT APPLICABLE

NOTICE TO READER

THIS DOCUMENT HAS BEEN PREPARED USING DATA FROM SOURCES CONSIDERED TECHNICALLY RELIABLE. IT DOES NOT CONSTITUTE A WARRANTY, EXPRESS OR IMPLIED, AS TO THE ACCURACY OF THE INFORMATION CONTAINED WITHIN. ACTUAL CONDITIONS OF USE AND HANDLING ARE BEYOND SELLER'S CONTROL. USER IS RESPONSIBLE FOR EVALUATING ALL AVAILABLE INFORMATION WHEN USING PRODUCT FOR ANY PARTICULAR USE AND TO COMPLY WITH ALL FEDERAL, STATE, PROVINCIAL AND LOCAL LAWS AND REGULATIONS.