



MATERIAL SAFETY DATA SHEET

REVISION DATE: 04/19/2012

REVISION NUMBER: 8

DATE PRINTED: 04/19/2012

1. CHEMICAL PRODUCT

PRODUCT NAME: **MIDFLOC 1500L, Heavy Metal Precipitant**

PRODUCT CODE: 117789

NFPA/HMIS HAZARD CODES(minimal=0; slight=1; moderate=2; serious=3; severe=4)

Health: 2/2

Fire: 1/1

Reactivity: 0/0

Special/Protective Equipment: ALK/B

NAME OF THE MANUFACTURER: Rochester Midland Corporation
155 Paragon Drive
Rochester, New York 14624
USA

Emergency Phone:
INFOTRAC: 1-800-535-5053
OUTSIDE US: 1-352-323-3500

2. HAZARDS IDENTIFICATION

EFFECTS FROM ACUTE EXPOSURE:

INGESTION: Harmful if swallowed. May cause severe irritation. May cause burns to mucous membranes of mouth, throat, and digestive tract.

SKIN CONTACT: Causes moderate skin irritation. May cause skin burns.

INHALATION: None in normal use. Inhalation of spray mist may be irritating.

EYE CONTACT: Causes moderate eye irritation. May Cause Eye Burns.

CHRONIC EFFECTS: None known.

EFFECTS/CARCINOGENICITY: California Proposition 65 Warning (applicable in California only) - This product contains (a) chemical(s) known to state of California to cause cancer and birth defects or other reproductive harm.

ROUTES OF ENTRY: Routes of entry for solids and liquids include eye and skin contact, ingestion and inhalation.

3. COMPOSITION/INFORMATION ON INGREDIENTS

PRODUCT COMPOSITION CAS#	%	ACGIH TLV	OSHA PELs
Sodium dimethyldithiocarbamate 128-04-1	30	Not applicable	Not applicable
SODIUM SULPHIDE 1313-82-2	7.5	No aplicable	No aplicable

4. FIRST AID MEASURES

INGESTION: DO NOT INDUCE VOMITING. Drink several glasses of water or milk. Get immediate medical attention. Never give anything by mouth to an unconcious person.

SKIN: Flush with water for at least 15 minutes while removing all contaminated clothing and shoes. Get medical attention if irritation or burns develop.

INHALATION: If inhaled, remove to fresh air. If not breathing give artificial respiration, preferably mouth-to-mouth. If breathing is difficult give oxygen. Get medical attention.

EYES: In case of contact, or suspected contact, immediately flush eyes with plenty of water for at least 15 minutes and get medical attention immediately after flushing.

NOTES TO PHYSICIAN: None.

MIDFLOC 1500L, Heavy Metal Precipitant

5. FIRE AND EXPLOSION HAZARD DATA

FLASH POINT:	(F): > 200 F (C): Not determined
METHOD:	PMCC
FLAMMABLE LIMITS IN AIR	
LOWER (%):	NE
UPPER (%):	NE
SENSITIVITY TO MECHANICAL IMPACT(Y/N):	NO
SENSITIVITY TO STATIC DISCHARGE:	Sensitivity to static discharge is not expected.
SUITABLE EXTINGUISHING MEDIA:	As for surrounding fire. Product will not burn.
FIRE FIGHTING PROCEDURES:	Fire-fighters should wear self-contained breathing apparatus and full protective clothing when fighting chemical fires. Cool exposed containers with water spray.

6. ACCIDENTAL RELEASE MEASURES

SPILL PROCEDURES:	
SMALL SPILLS:	Reclaim as much as possible.
LARGE SPILLS:	Dike to contain. Pick up with absorbant material. Put in suitable container for disposal. Keep out of drains, sewers, streams, or other bodies of water.
PERSONAL PRECAUTIONS:	Not applicable
ENVIRONMENTAL PRECAUTIONS:	Not applicable
METHODS FOR CLEANING UP:	Not applicable

7. HANDLING AND STORAGE

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE:	WARNING Alkaline liquid. Avoid contact with eyes, skin and clothing. Keep container closed when not in use. Store in a cool, dry area.
OTHER PRECAUTIONS:	Keep out of reach of children.
SPECIFIC USE(S):	Not applicable.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

PROTECTIVE EQUIPMENT:	
EXPOSURE CONTROLS:	None known.
RESPIRATORY PROTECTION:	None normally required.
PROTECTIVE GLOVES:	Rubber gloves.
EYE PROTECTION:	Goggles. Face shield.
OTHER PERSONAL PROTECTION EQUIPMENT:	Rubber boots. Chemical resistant materials are required to prevent prolonged or repeated skin contact. Eyewash fountains and safety showers must be easily accessible.
VENTILATION:	General mechanical and/or local exhaust as needed to meet exposure limits if mist in air.

9. PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE AND ODOR:	Clear. Light yellow liquid. Slight sulfide odor.
BOILING POINT (F):	212 F (C) Not determined
VAPOR PRESSURE:	15.7 mm Hg @ 22.2C
VAPOR DENSITY (AIR=1):	0.625
SOLUBILITY IN WATER:	Not determined
SPECIFIC GRAVITY:	1.21 (typical)
VOC Content (%):	NE
EVAPORATION RATE:	(BuAc = 1) : 1.26
PH:	13.2

MIDFLOC 1500L, Heavy Metal Precipitant

9. PHYSICAL AND CHEMICAL PROPERTIES

10. STABILITY AND REACTIVITY

STABILITY DATA: STABLE
POLYMERIZATION: Will Not Occur.
HAZARDOUS DECOMPOSITION: When heated to high temperatures, the following may be produced: Hydrogen sulfide. Contact with strong acids produce: Carbon disulfide. Dimethylnitrosoamines may be produced on contact with a combination of a strong acids and nitrosating compounds.
INCOMPATIBILITY (MATERIALS TO AVOID): Avoid contact with: Acids. Strong oxidents, such as nitric acid, or hypochlorites.
CONDITIONS/HAZARDS TO AVOID: Extreme heat, direct sunlight.

11. TOXICOLOGICAL INFORMATION

ACUTE TOXICITY: Not Established
EFFECTS OF CHRONIC EXPOSURE: Not established.
OTHER TOXIC EFFECTS: Not established.

12. ECOLOGICAL INFORMATION

ECOTOXICOLOGICAL INFORMATION: No data at this time
CHEMICAL FATE INFORMATION: No data at this time.
MOBILITY: Not applicable.
PERSISTENCE/DEGRADABILITY: Not applicable
BIOACCUMULATIVE POTENTIAL: Not applicable
OTHER ADVERSE EFFECTS: Not applicable

13. DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHODS: Dispose in accordance with Federal, State and Local regulations.

14. TRANSPORT INFORMATION

Please refer to the Bill of Lading/Receiving documents for up to date shipping information.

15. REGULATORY INFORMATION

PRODUCT COMPOSITION CAS#	%	TSCA:	EINECS:	Canada DSL:	CA PROP 65:
Sodium dimethyldithiocarbamate 128-04-1	30	Listed	Listed	Listed	Developmental
SODIUM SULPHIDE 1313-82-2	7.5	Listed	Listed	Listed	Not Listed

PRODUCT COMPOSITION CAS#	%	CERCLA:	SARA 302:	SARA 313:
Sodium dimethyldithiocarbamate 128-04-1	30	Not Listed	Not Listed	Listed
SODIUM SULPHIDE 1313-82-2	7.5	Not Listed	Not Listed	Not Listed

The following components of this material are included in the Massachusetts Substance List and are present at or above reportable levels.

MIDFLOC 1500L, Heavy Metal Precipitant

PRODUCT COMPOSITION CAS#	%	MARTK:
SODIUM SULPHIDE 1313-82-2	7.5	Listed

The following components of this material are included in the New Jersey Substance List and are present at or above reportable levels.

PRODUCT COMPOSITION CAS#	%	NJRTK:
Sodium dimethyldithiocarbamate 128-04-1	30	Listed
SODIUM SULPHIDE 1313-82-2	7.5	Listed

None of the components of this material are included in the Pennsylvania Substance List nor are present at or above reportable levels.

16. OTHER INFORMATION

This information was compiled from current, reliable sources and is believed to be correct. As data, and/or regulations change, and conditions of use and handling are beyond our control, no warranty, express or implied, is made as to completeness or continuing accuracy of this information.

*** END OF MSDS ***