SAFETY DATA SHEET



1. Identification

Product identifier MILFORM® 6265

STAMPING AND DRAWING FLUID

Other means of identification

SDS number Not applicable Product code B00462

Recommended use STAMPING AND DRAWING FLUID

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Company name CIMCOOL® Industrial Products LLC

3000 Disney Street Cincinnati, Ohio 45209

Telephone (General

Information)

513-458-8100

Emergency telephone

number

1-800-424-9300 (CHEMTREC)

Emergency telephone number (outside USA)

1-703-527-3887 (CHEMTREC)

Supplier

Company name Milacron Canada Corp.

Address 1175 Appleby Line Road, Unit B-1

Burlington Ontario L7L5H9 Canada

Telephone (General

Information)

905-319-1919

Emergency telephone number (outside USA)

1-703-527-3887 (CHEMTREC)

Supplier Not available.

2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Serious eye irritation Category 2A

Sensitization, skin Category 1

Environmental hazards

Label elements



Not classified.

Signal word Warning

Hazard statement Causes serious eye irritation. May cause an allergic skin reaction.

Precautionary statement

Prevention Avoid breathing mist or vapor. Wash thoroughly after handling. Contaminated work clothing

should not be allowed out of the workplace. Wear eye protection/face protection. Wear protective

gloves.

Material name: MILFORM® 6265

Version #: 01 Issue date: 05-07-2017

1 / 8

IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical Response

advice/attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical

advice/attention. Take off contaminated clothing and wash it before reuse.

Storage

Store away from incompatible materials.

Disposal

Dispose of contents/container in accordance with local/regional/national/international regulations.

Other hazards

None known.

Supplemental information

<@P001>% of the mixture consists of component(s) of unknown acute oral toxicity. <@P001>% of the mixture consists of component(s) of unknown acute dermal toxicity.

This product should be mixed/diluted according to the manufacturer's recommendations and is intended for use only in closed or semi-enclosed machines. Semi-enclosed machines are machines that provide effective mist containment.

The classified hazards shown on this SDS are associated with the product concentrate. These hazards are not expected under recommended use conditions and dilution.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
TRIETHANOLAMINE		102-71-6	≤30
4,4-DIMETHYLOXAZOLIDINE		51200-87-4	≤3
4-(2-NITROBUTYL)MORPHOLINE	Ē	2224-44-4	≤1
Other components below reportab	le levels		≤95

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Move to fresh air. Call a physician if symptoms develop or persist. Under normal conditions of Inhalation

intended use, this material is not expected to be an inhalation hazard.

Skin contact Rinse skin with water. If skin irritation or rash occurs: Get medical advice/attention. Wash

contaminated clothing before reuse.

Eye contact Rinse with water. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical

attention if irritation develops and persists.

Ingestion Rinse mouth thoroughly. Drink 1 or 2 glasses of water. Do not induce vomiting. If vomiting occurs,

keep head low so that stomach content doesn't get into the lungs. Get medical advice/attention if

you feel unwell.

Most important

symptoms/effects, acute and

delayed

Direct contact with eyes may cause temporary irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause an allergic skin reaction.

Indication of immediate medical attention and special

treatment needed

Provide general supportive measures and treat symptomatically. Symptoms may be delayed.

General information

If exposed or concerned: Get medical advice/attention. Show this safety data sheet to the doctor in attendance.

5. Fire-fighting measures

Suitable extinguishing media

Alcohol resistant foam. Dry powder. Carbon dioxide (CO2). Use extinguishing measures that are

appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing

media

Not applicable, non-combustible.

Specific hazards arising from

the chemical

During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters Wear suitable protective equipment.

Fire fighting equipment/instructions Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk.

Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials. In the event of fire and/or explosion do not breathe fumes.

General fire hazards No unusual fire or explosion hazards noted.

Material name: MILFORM® 6265 SDS Canada

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Local authorities should be advised if significant spillages cannot be contained. This product is miscible in water. Clean up in accordance with all applicable regulations.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.

Environmental precautions

Contact local authorities in case of spillage to drain/aquatic environment. Avoid discharge into drains, water courses or onto the ground. Use appropriate containment to avoid environmental contamination.

7. Handling and storage

Precautions for safe handling

Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Do not get in eyes, on skin, or on clothing. Avoid breathing mist or vapor. Avoid prolonged exposure. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Store in original tightly closed container. Store away from incompatible materials (see Section 10 of the SDS). Do not allow material to freeze. If frozen, product may separate. Thaw completely at room temperature and stir thoroughly prior to use.

8. Exposure controls/personal protection

Occupational exposure limits

US. ACGIH Threshold Limit Values

	Туре	Value
TRIETHANOLAMINE (CAS 102-71-6)	TWA	5 mg/m3
Canada. Alberta OELs (Occupation	nal Health & Safety Code, Sc	hedule 1, Table 2)
	Туре	Value
TRIETHANOLAMINE (CAS 102-71-6)	TWA	5 mg/m3
Canada. British Columbia OELs. (0 Safety Regulation 296/97, as amen		ts for Chemical Substances, Occupational Health and
	Туре	Value
TRIETHANOLAMINE (CAS 102-71-6)	TWA	5 mg/m3
Canada. Manitoba OELs (Reg. 217	2006. The Workplace Safety	And Health Act)
	Туре	Value
TRIETHANOLAMINE (CAS 102-71-6)	TWA	5 mg/m3
Canada. Ontario OELs. (Control of	Exposure to Biological or C	hemical Agents)
	Туре	Value
TRIETHANOLAMINE (CAS 102-71-6)	TWA	3.1 mg/m3
,		0.5 ppm
Canada. Quebec OELs. (Ministry o	f Labor - Regulation Respec	ting the Quality of the Work Environment)
	Туре	Value
TRIETHANOLAMINE (CAS 102-71-6)	TWA	5 mg/m3
ogical limit values No bi	ological exposure limits noted	for the ingredient(s).

Material name: MILFORM® 6265 Version #: 01 Issue date: 05-07-2017

Appropriate engineering

controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash fountain and emergency showers are recommended.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles). Do not get in eyes. Eye wash fountain is

recommended.

Skin protection

Hand protection Use protective gloves made of: Nitrile.

Other Wear appropriate chemical resistant clothing.

Respiratory protection In case of insufficient ventilation, wear suitable respiratory equipment.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

When using, do not eat, drink or smoke. Do not get in eyes, on skin, on clothing. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance CLEAR
Physical state Liquid.

Form Liquid.

ColorNot available.OdorChemicalOdor thresholdNot available.

pH 8.4

Melting point/freezing point $< 32 \,^{\circ}\text{F} (< 0 \,^{\circ}\text{C})$ Initial boiling point and boiling $> 212 \,^{\circ}\text{F} (> 100 \,^{\circ}\text{C})$

range

Flash point Not Applicable

Evaporation rate Like water when diluted

Flammability (solid, gas) Not applicable.

Upper/lower flammability or explosive limits

Flammability limit - lower

(%)

5)

Flammability limit - upper

(%)

Not available.

Not available.

Explosive limit - lower (%) Not available.

Explosive limit - upper (%) Not available.

Vapor pressure Not available.

Vapor density Not available.

Relative density Not available.

Solubility(ies)

Solubility (water) 100 % Water Miscible

Partition coefficient

(n-octanol/water)

Not available.

Auto-ignition temperatureNot available.Decomposition temperatureNot available.ViscosityNot available.

Other information

Explosive properties Not explosive.

Oxidizing properties Not oxidizing.

pH in aqueous solution 8.2 @ 10%

1.039 Specific gravity

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Material is stable under normal conditions. **Chemical stability**

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Heat, flames and sparks. Contact with incompatible materials.

Incompatible materials Acids. Oxidizing agents. Do not add sodium nitrite or other nitrosating agents which may form

cancer causing nitrosamines.

Hazardous decomposition

products

Smoke, fumes, oxides of nitrogen, and oxides of carbon

11. Toxicological information

Information on likely routes of exposure

Inhalation Not classified.

Skin contact May cause an allergic skin reaction.

Causes eye irritation. Eye contact

Ingestion Not classified.

Symptoms related to the physical, chemical and toxicological characteristics Direct contact with eyes may cause temporary irritation. Symptoms may include stinging, tearing,

redness, swelling, and blurred vision. May cause an allergic skin reaction.

Information on toxicological effects

Acute toxicity Not known.

Components **Species Test Results**

4,4-DIMETHYLOXAZOLIDINE (CAS 51200-87-4)

Acute

Oral Liquid

LD50 Rat 1308 mg/kg

TRIETHANOLAMINE (CAS 102-71-6)

Acute

Dermal

2000 mg/kg LD50 Rabbit

Oral

Liquid

LD50 Rat 4190 mg/kg

Skin corrosion/irritation Not classified.

Serious eye damage/eye Causes eye irritation.

irritation

Respiratory or skin sensitization

Canada - Alberta OELs: Irritant

TRIETHANOLAMINE (CAS 102-71-6) Irritant

Canada - Quebec OELs: Sensitizer

TRIETHANOLAMINE (CAS 102-71-6) Sensitizer.

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization May cause an allergic skin reaction.

No data available to indicate product or any components present at greater than 0.1% are Germ cell mutagenicity

mutagenic or genotoxic.

Carcinogenicity This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.

IARC Monographs. Overall Evaluation of Carcinogenicity

TRIETHANOLAMINE (CAS 102-71-6) 3 Not classifiable as to carcinogenicity to humans.

Material name: MILFORM® 6265 SDS Canada 5/8

^{*} Estimates for product may be based on additional component data not shown.

Reproductive toxicityThis product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard

Not an aspiration hazard.

Chronic effects

Not classified.

Further information

The classification for health and environmental hazards is derived by a combination of calculation

methods and test data, if available.

12. Ecological information

EcotoxicityContains a substance which causes risk of hazardous effects to the environment.

Components		Species	Test Results
4,4-DIMETHYLOXAZO	OLIDINE (CAS 512	00-87-4)	
Aquatic			
Acute			
Crustacea	EC50	Daphnia	45 mg/l, 48 hours
Fish	LC50	Bluegill (Lepomis macrochirus)	59 mg/l, 96 hours
TRIETHANOLAMINE	(CAS 102-71-6)		
Aquatic			
Crustacea	EC50	Water flea (Ceriodaphnia dubia)	565.2 - 658.3 mg/l, 48 hours

^{*} Estimates for product may be based on additional component data not shown.

Persistence and degradability

Bioaccumulative potential

Fish

Partition coefficient n-octanol / water (log Kow)

TRIETHANOLAMINE

LC50

Mobility in soil This product is miscible in water.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

Fathead minnow (Pimephales promelas) 10610 - 13010 mg/l, 96 hours

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of

contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

14. Transport information

TDG

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Annex II of MARPOL 73/78 and

Not established.

the IBC Code

Material name: MILFORM® 6265 SDS Canada

15. Regulatory information

Canadian regulations

This product has been classified in accordance with the hazard criteria of the HPR and the SDS contains all the information required by the HPR.

Controlled Drugs and Substances Act

Not regulated.

Export Control List (CEPA 1999, Schedule 3)

Not listed.

Greenhouse Gases

Not listed.

Precursor Control Regulations

Not regulated.

International regulations

Stockholm Convention

Not applicable.

Rotterdam Convention

Not applicable.

Kyoto protocol

Not applicable.

Montreal Protocol

Not applicable.

Basel Convention

Not applicable.

International Inventories Country(s) or region

Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	Yes
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

Toxic Substances Control Act (TSCA) Inventory

16. Other information

Issue date 05-07-2017

Version # 01

United States & Puerto Rico

Health: 1 NFPA ratings

Flammability: 0 Instability: 0

Inventory name

Disclaimer The information provided in this Safety Data Sheet is correct to the best of our knowledge,

information and belief at the date of its publication. The information given is designed only as a quidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other

materials or in any process, unless specified in the text.

Material name: MILFORM® 6265 7/8

Yes

On inventory or exempt (yes/no)*

Revision information

Product and Company Identification: Product and Company Identification

Hazards Identification: US Hazard Categories

Composition / Information on Ingredients: Component Summary Physical & Chemical Properties: Multiple Properties Regulatory Information: United States Material Attributes & Uses; Experimental Data: Product Uses HazReg Data: North America

GHS: Classification

Material name: MILFORM® 6265 SDS Canada 8/8