

MSDS Name: BLACK TIRE PAINT CONCENTRATE
MSDS Number: P-9413
Version Number
MSDS Date: APR-01-2014
Page Number: 1 of 5

SECTION I - PRODUCT AND COMPANY INFORMATION

Product Name: BLACK TIRE PAINT CONCENTRATE
CAS Number MIXTURE
Hazard Rating: Health: 1 Fire: 0 Reactivity: 0 PPI: H

Company Identification: Akron Paint & Varnish, Inc.
DBA APV Engineered Coatings
1390 Firestone Parkway
Akron OH 44301

Contact: James K. Mosey
Telephone/Fax: (330) 773-8911 (330) 773-1028
Emergency Phone (24 Hour): EVENING ADMINISTRATOR
(330) 773-8911
Chemtrec (24 Hour): (800) 424-9300

Product Class NOVOC PAINT
Trade Name
Product Code P-9413
DOT Hazard Class
UN Number
UN Pack Group
UN Class
Shipping Name BLACK TIRE PAINT CONCENTRATE
Technical Name

ADDITIONAL INFORMATION

SECTION II - INGREDIENT AND HAZARD INFORMATION

Ingredient Name	CAS Number	Percent	TSCA
(No hazardous ingredients known at this time.)			

ADDITIONAL INFORMATION

SECTION 313 SUPPLIER NOTIFICATION: THIS PRODUCT MAY CONTAIN TOXIC
CHEMICALS SUBJECT TO THE REPORTING REQUIREMENTS OF SECTION 313 OF THE
EMERGENCY PLANNING AND COMMUNITY RIGHT TO KNOW ACT OF 1986 AND 40 CFR
372.

MATERIAL SAFETY DATA SHEET

MSDS Name: BLACK TIRE PAINT CONCENTRATE
MSDS Number: P-9413
Version Number
MSDS Date: APR-01-2014
Page Number: 2 of 5

CAUTION: THIS PRODUCT MAY BECOME A DUST NUISANCE WHEN REMOVED BY
SANDING, ABRADING OR SANDBLASTING. DUST MASKS SHOULD BE WORN DURING
THESE OPERATIONS.

NE = not established

NA = not available

NR = not regulated.

ALL COMPONENTS OF THIS MIXTURE ARE LISTED ON THE TSCA INVENTORY.

SECTION III - PHYSICAL DATA

Form:	LIQUID
Appearance/Color:	BLACK
Odor:	SLIGHT
pH Value:	7.8-9.2 0.
Boiling Range:	21.°F - 212.°F (-6.11°C - 100.°C)
Vapor Pressure (mmHg):	Not Available
Melting Point:	Not Applicable
Evaporation Rate:	0.33 times Slower than n-Butyl Acetate
Vapor Density:	Lighter than air
Partition Coefficient	Not Applicable
% Volatile Weight	80.46%
% Volatile Volume	86.19%
Specific Gravity:	1.06599
VOC	.09 W/ .56 D
Molecular Weight:	
Heavy Elements (ppm)	0.

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

Flammability Class	IIIB
Flash Range:	>200 F
	Setaflash
Explosive Range:	0.%
	0.%

EXTINGUISHING MEDIA:

Carbon Dioxide---Dry Chemical---Foam---Water Fog

MATERIAL SAFETY DATA SHEET

MSDS Name: BLACK TIRE PAINT CONCENTRATE
MSDS Number: P-9413
Version Number
MSDS Date: APR-01-2014
Page Number: 3 of 5

Use water for cooling material stored in vicinity of fire.

SPECIAL FIREFIGHTING PROCEDURES:

Use self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.

UNUSUAL FIRE & EXPLOSION HAZARDS:

During emergency conditions, overexposure to decomposition products may cause a health hazard. Symptoms may not be immediately apparent. Obtain medical attention.

SECTION V - HEALTH HAZARD DATA

Route	Species	Exposure and Dose
-------	---------	-------------------

PERMISSIBLE EXPOSURE LEVEL:

Refer to Section II

EFFECTS OF OVEREXPOSURE:

EYES: Can cause redness, irritation, swelling and blurred vision.

SKIN: Prolonged or repeated contact can cause slight irritation, or dermatitis.

BREATHING: Not normally affected

SWALLOWING: Can cause gastrointestinal irritation, nausea, vomiting & diarrhea.

FIRST AID:

EYES: Flush with large amounts of water.

SKIN: Wash thoroughly with soap and water.

SWALLOWING: The decision to induce vomiting or not must be made by a physician after careful consideration of all materials ingested.

SECTION VI - REACTIVITY DATA

Stability: This product is stable

Hazardous Polymerization: Hazardous polymerization will not occur

INCOMPATIBILITY

NONE

CONDITIONS TO AVOID:

NONE

MATERIAL SAFETY DATA SHEET

MSDS Name: BLACK TIRE PAINT CONCENTRATE
MSDS Number: P-9413
Version Number
MSDS Date: APR-01-2014
Page Number: 4 of 5

HAZARDOUS DECOMPOSITION PRODUCTS:

May form carbon monoxide and dioxide, various hydrocarbons, etc.

SECTION VII - SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

Dike area of spill to prevent spreading----

pump liquid into salvage tank----

remaining liquid may be taken up with; sand, floor absorbent

or other absorbent material and shoveled into containers---

prevent run-off to sewers and bodies of water---notify proper
authorities as required by local, state and federal regulations.

WASTE DISPOSAL METHOD:

Dispose of in accordance with federal, state and local regulations.

SECTION VIII - SPECIAL PROTECTION INFORMATION

Occupational Exposure Limits

ACGIH TLV	ACGIH TLV-C	ACGIH STEL	OSHA STEL	OSHA PEL
-----------	-------------	------------	-----------	----------

RESPIRATORY PROTECTION:

None normally required

VENTILATION:

General ventilation

PROTECTIVE GLOVES:

None normally required.

EYE PROTECTION:

Chemical splash goggles in compliance with OSHA regulations are advised; however, OSHA regulations also permit other type of safety glasses. (Consult your safety equipment supplier)

OTHER PROTECTIVE EQUIPMENT:

Normal protective clothing.

SECTION IX - SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING:

Do not drop containers. KEEP FROM FREEZING.

MATERIAL SAFETY DATA SHEET

MSDS Name: BLACK TIRE PAINT CONCENTRATE
MSDS Number: P-9413
Version Number
MSDS Date: APR-01-2014
Page Number: 5 of 5

OTHER PRECAUTIONS:

The information contained herein is, to the best of our knowledge and belief, accurate. However, since the conditions of handling and use are beyond our control, we make no guarantee of results, and assume no liability for damages incurred by use of this material. It is the responsibility of the user to comply with all applicable federal, state and local laws and regulations.

SECTION X - ADDITIONAL REGULATORY INFORMATION

SARA TITLE III SECTION 313:

CONTAINS NO SARA TITLE III SECTION 313 REPORTABLE CONCENTRATION.

PROP 65 (CARCINOGEN):

PROP 65 (TERATOGEN):

PROP 65 (BOTH CARCINOGEN AND TERATOGEN):