# ProGuard Met-Protect LT MATERIAL SAFETY DATA SHEET

### Section 1 Product and Company Identification

Lyden Oil Company Phone: 517-485-2285 <u>Emergency Phone Numbers</u>
419 Spring Street Fax: 517-485-0605 517-485-2285 Normal Business Hrs.
Lansing, MI 48912 PERS 800-728-2482 24 Hours
United States of America

Product Name: ProGuard Met-Protect LT Chemical Family: Straight Oil

Prepared by: Richard Thatcher 10/10/07

#### **Section 2 Composition / Hazardous Ingredients Information**

Ingredient WT % TLV / PEL\* CAS #

Severely Hydrotreated Naphthenic Oil <45 5mg/m³\* 64742-53-6 Aliphatic Hydrocarbon Solvent <20 300 PPM\*\* 64742-47-8

\*\* The Exxon Corporation recommends this value. \*\*

\* This value applies to any oil, which is misted into the air.

## **Section 3 Physical and Chemical Properties**

Color: Green Vapor Pressure: N/A °F Solubility in Water: Not Soluble

Appearance:Opaque Liquid% Volatile by Volume:17Evaporation RateOdor:CharacteristicVapor Density (air = 1):>1(Water = 1):<1</td>Boiling Point:>360° FReactivity in Water:Non-reactiveSpecific Gravity:0.9243

## **Section 4 Fire Fighting Measures**

Flammable Properties:

Flash point: 142°F (ASTM D-56) Flammable limits in air: 0.6 LEL 7.0 UEL Auto ignition temperature: 650 ° F

Extinguishing media: CO<sub>2</sub>, dry chemical, foam

Special fire fighting measure:

Procedures for an oil fire should be followed. Use self-contained breathing apparatus. Uses foams or dry chemical to extinguish fire.

Water may be used <u>only</u> to keep surrounding containers cool.

#### **Section 5 Hazards Identification**

**Primary Routes of Entry:** 

Skin: Tests on similar materials indicate that no significant adverse health effects are expected to occur with short-term exposure.

Eyes: Tests on similar materials suggests that minimal irritation may occur on contact.

**Ingestion:** Tests on similar materials indicate no significant adverse effects expected. Practically non-toxic.

Inhalation: Tests on similar materials indicate no acute effects are expected.

#### **Section 6 First Aid Measures**

**Eyes:** Flush eyes immediately with water for at least 15minutes or until irritation subside. If irritation persists, consult a physician.

**Skin:** Immediately remove soaked or contaminated clothing. Wash skin thoroughly with soap and water. Launder all contaminated clothing before reuse. If skin irritation or rash develops obtain medical assistance.

Ingestion: Product is practically non-toxic. Do not induce vomiting. Obtain emergency medical attention.

Inhalation: Not likely to occur except as a mist. Move to fresh air and provide oxygen if necessary. Obtain emergency medical

attention.

### **Section 7 Personal Protection/ Exposure Controls**

Engineering Controls: Use adequate ventilation to keep oil mists of this material below applicable standards.

**Respiratory Protection: Not** required if adequate ventilation. If occupational exposure limits are exceeded wear NIOSH approved apparatus.

**Skin Protection:** Avoid prolonged and/or repeated skin contact. If prolonged contact cannot be avoided, wear protective impervious gloves and clothing. Acceptable materials for gloves are polyvinyl chloride; neoprene; polyvinyl alcohol; nitrile; vitron.

Eye Protection: Glasses or goggles. Have suitable eye wash water available.

**Other/General Protection:** If there is a likelihood of splashing, an oil resistant clothing should be worn. Never wear oil soaked clothing. Launder or dry-clean before wearing. Discard oil soaked shoes.

#### **Section 8 Handling and Storage**

**Handling and Storage Precautions:** Keep away from flames, sparks or hot surfaces. Never use a torch to cut or weld on or near container. Empty containers can contain explosive vapors. NFPA Class IIIB storage.

Do not allow product to freeze. If product freezes allow product to thaw completely prior to use.

**Work/Hygienic Practices:** Wash thoroughly after handling. Do not use gasoline, solvents, kerosene, or harsh abrasive skin cleaners for washing exposed skin areas. Take a shower after work if general contact occurs. Remove oil-soaked clothing and launder before reuse. Launder or discard contaminated shoes and leather gloves.

#### **Section 9 Accidental Release Measures**

- Eliminate ignition sources.
- Absorb spillage with inert material.
- Contain spill and keep from entering waterways or sewers.
- Advise EPA/state agency if required.
- Use personal protective equipment.
- Shovel, sweep or vacuum spill.

#### **Section 10 Toxicological Information**

**Acute Studies:** Tests on similar materials show a low order of acute oral and dermal toxicity.

Eye Effects: Minimal irritation on contact.

Skin Effects: Practically non-toxic if absorbed. May cause mild irritation with prolonged and repeated contact.

Acute Oral Effects: Tests on similar materials indicate low order of acute oral toxicity.

**Acute Inhalation Effects:** Low acute toxicity expected on inhalation.

This product is not listed as a carcinogenic or a potential carcinogen by the National Toxicology Program, by the I.A.R.C. monographs or by OSHA.

## **Section 11 Stability and Reactivity**

Stability: Stable Conditions to avoid: Sources of ignition. Incompatibility: Strong oxidizing or reducing agents. Decomposition Products: Oxides of Carbon, Hydrogen, Calcium. Hazardous Polymerization: Will not occur.

#### **Section 12 Ecological Information**

No Data available

## **Section 13 Disposal Considerations**

Follow federal, state and local regulations. Not a RCRA hazardous waste if uncontaminated. If "used" RCRA criteria must be determined. Do no flush into drain/storm sewer use an authorized disposal service. If permitted incineration may be practical. Recommend recycling.

# **Section 14 Transportation Information**

Proper Shipping Name: Lubricating Oils. N.O.S.

**Shipping Class: 65** 

**Dot Identification Number:** N/A

**Dot Shipping Label:** Not regulated by DOT.

#### **Section 15 Regulatory Status**

#### U.S. Federal Regulatory Information:

SARA 302 Threshold Planning Quantity: N/A SARA 304 Reportable Quantity: N/A

SARA 311 Categories:

Acute Health Effects: None
Chronic Health Effects: None
Fire Hazard: No
Sudden Release of Pressure Hazard: No
Reactivity Hazard: No

**EPA/TSCA Inventory:** The components of this product are listed on the EPA/TSCA inventory of chemicals.

**EPA Hazard Classification Code:** Not applicable

**CERCLA:** No chemicals in this product are subject to the reporting requirements of CERCLA.

**SARA Title III - Section 313 Supplier Notification:** 2-butoxy ethanol less than 1%.

WHMIS Classification: Not controlled.

#### **Section 16 Other Information**

#### NFPA Hazard Rating:

Health:	1	Slight
Flammability:	2	Slight
Reactivity:	0	Negligible

Supersedes MSDS Dated: Original

\*Threshold Limit Value/Personal Exposure Limit

N/A = Not ApplicableN/E = Not Established

#### **Disclaimer of Express or Implied Warranties**

The information on this MSDS was obtained from sources we believe to be reliable. However, this information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use and disposal of the product are beyond our control and beyond our knowledge. For this and other reasons, Lyden Oil does not assume responsibility and expressly disclaim liability for loss, damage, or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This MSDS was prepared and is to be used only for this product. If the product is used as a component in another product, this MSDS information may not be applicable. Lyden Oil Company, Inc. believes this information is accurate but not all-inclusive in all circumstances. It is the responsibility of the user to determine suitability of the material for their purposes. No warranty, expressed or implied, is given.