

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS & 2001/58 EC Standards

MSDS Revision: 2.0

MSDS Revision Date: 03/16/2007

1. PRODUCT IDENTIFICATION

1.1	Product Name: ACRYLIC NAIL BASE COAT
1.2	Chemical Name: SOLVENT MIXTURE
1.3	Synonyms: NA
1.4	Trade Names: NTT20, NTT24
1.5	Product Use: COSMETIC USE ONLY
1.6	Manufacturer's Name: OPI PRODUCTS, INC.
1.7	Manufacturer's Address: 13034 SATICOY STREET, NO. HOLLYWOOD, CA 91605 USA
1.8	Emergency Phone: CHEMTREC: +1 (703) 527-3887 / +1 (800) 424-9300
1.9	Business Phone: +1 (818) 759-2400 / +1 (800)-341-9999

2. HAZARD IDENTIFICATION

2.1	Hazard Identification: Flammable liquid. This product is classified as a hazardous substance and as dangerous goods according to the classification criteria of NOHSC and ADG Code (Australia).					
2.2	Routes of Entry:	Inhalation:	YES	Absorption:	YES	Ingestion:
2.3	Effects of Exposure: INGESTION: If product is swallowed, may cause nausea, vomiting and/or diarrhea and central nervous system depression. SKIN & EYES: Irritating to the eyes. Symptoms of overexposure may include redness, itching, irritation and watering. May be irritating to skin in some sensitive individuals, especially after prolonged and/or repeated contact. INHALATION: Vapors of this product may be slightly irritating to the nose, throat and other tissues of the respiratory system. Symptoms of overexposure can include coughing, wheezing, nasal congestion, and difficulty breathing. Inhalation of vapors exceeding the levels listed in Section 2 (Composition and Ingredient Information) can cause central nervous system depression (e.g., drowsiness, dizziness, headaches, nausea).					
2.4	Symptoms of Overexposure: Symptoms of skin overexposure in individuals may include redness, itching, and irritation of affected areas. Overexposure in eyes may cause redness, itching and watering.					
2.5	Acute Health Effects: Mild to moderate irritation to eyes and skin near affected areas. Additionally, high concentrations of vapors can cause drowsiness, dizziness, headaches and nausea.					
2.6	Chronic Health Effects: None known.					
2.7	Target Organs: Eyes, skin and respiratory system.					

NA = Not Available; ND = Not Determined; NE = Not Established; C = Ceiling Limit; See Section 16 for Additional Definitions of Terms Used

NOTE: all WHMIS required information is included. It is located in appropriate sections based on the ANSI Z400.1-2004 format.

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS & 2001/58 EC Standards

MSDS Revision: 2.0

MSDS Revision Date: 03/16/2007

3. COMPOSITION & INGREDIENT INFORMATION

CHEMICAL NAME(S)	CAS No.	RTECS No.	EINECS No.	%	EXPOSURE LIMITS IN AIR (mg/m ³)					
					ACGIH - ppm		OSHA - ppm			OTHER
					TLV	STEL	PEL	STEL	IDLH	
BUTYL ACETATE	123-86-4	AF7350000	204-658-1	≤ 40.0	150	200	200	200	1700	
ETHYL ACETATE	141-78-6	AH5425000	201-550-6	≤ 20.0	400	NE	400	NE	2000	
SD ALCOHOL 40B	64-17-5	KQ6300000	200-578-6	≤ 15.0	1000	NA	1000	NA	NA	
HEPTANE	142-82-5	MI7700000	205-563-8	≤ 10.0	400	500	500	NA	750	
NITROCELLULOSE	9004-70-0	QW0970000	NA	≤ 10.0	NE	NE	NE	NE	NE	
ISOPROPYL ALCOHOL	67-63-0	NT8050000	200-661-7	≤ 5.0	400	500	400	500	2000	
ADIPIC ACID/NEOPENTYL GLYCOL/TRIMELLITIC ANHYDRIDE COPOLYMER	28407-73-0	NA	NA	≤ 5.0	NE	NE	NE	NE	NE	
TRIMETHYL PENTANYL DIISOBUTYRATE	6846-50-0	SA142000	229-937-9	≤ 5.0	NA	NA	NA	NA	NA	
CAMPHOR	76-22-2	EX1225000	200-945-0	≤ 1.0	(2)	NA	(2)	NA	NA	
DIACETONE ALCOHOL	123-44-2	SA9100000	204-626-7	≤ 1.0	NE	NE	NE	NE	NE	
STEARALKONIUM BENTONITE	71011-24-0	NA	NA	≤ 1.0	NA	NA	NA	NA	15	
STEARALKONIUM HECTORITE	1302-78-9	CT9450000	215-108-5	≤ 1.0	(10)	NA	(15)	NA	NA	
TITANIUM DIOXIDE	1317-70-0	BV6550000	215-280-1	≤ 1.0	NE	NE	NE	NE	NE	
TRIPHENYL PHOSPHATE	115-86-6	TC8400000	NA	≤ 1.0	3	NA	3	NA	NA	
HYDRATED SILICA	1343-98-2	VV8853000	215-683-2	≤ 1.0	NE	NE	NE	NE	NE	
ETHYL TOSYLAMIDE	1077-56-1	NA	214-073-3	≤ 1.0	NA	NA	NA	NA	NA	
POLYVINYL BUTYRAL	63148-65-2	TR49550000	NA	≤ 1.0	NA	NA	NA	NA	NA	
BENZOPHENONE-1	131-56-6	DJ0700000	205-029-4	≤ 1.0	NE	NE	NE	NE	NE	
CITRIC ACID	77-92-9	GE7350000	201-069-1	≤ 1.0	NE	NE	NE	NE	NE	
HYDROLYZED WHOLE WHEAT PROTEIN	70084-87-6	NA	NA	≤ 1.0	NA	NA	NA	NA	NA	

4. FIRST AID MEASURES

4. FIRST AID MEASURES																	
4.1	<p>First Aid:</p> <p>INGESTION: If ingested, do not induce vomiting. If product has been swallowed, drink plenty of water or milk IMMEDIATELY. If the patient is vomiting, continue to offer water or milk. Never give water or milk to an unconscious person. Contact the nearest Poison Control Center or local emergency number. Provide an estimate of the time at which the material was ingested and the amount of the substance that was swallowed.</p> <p>EYES: Splashes are not likely; however, if product gets in the eyes, flush with copious amounts of lukewarm water for at least 15 minutes. If irritation occurs, contact a physician.</p> <p>SKIN: If irritation occurs and product is on the skin, rinse thoroughly with lukewarm water, followed by a thorough washing of the effected area with soap and water. If irritation, redness or swelling persists, contact a physician immediately.</p> <p>INHALATION: Remove victim to fresh air at once.</p>																
4.2	<p>Medical Conditions Aggravated by Exposure:</p> <p>None known.</p>																
	<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td style="background-color: blue; color: white; text-align: center; padding: 5px;">HEALTH</td><td style="border: none; text-align: center; padding: 5px;">1</td></tr> <tr> <td style="background-color: red; color: white; text-align: center; padding: 5px;">FLAMMABILITY</td><td style="border: none; text-align: center; padding: 5px;">3</td></tr> <tr> <td style="background-color: yellow; color: black; text-align: center; padding: 5px;">REACTIVITY</td><td style="border: none; text-align: center; padding: 5px;">0</td></tr> <tr> <td style="background-color: cyan; color: black; text-align: center; padding: 5px;">PROTECTIVE EQUIPMENT</td><td style="border: none; text-align: center; padding: 5px;">A</td></tr> <tr> <td style="background-color: cyan; color: black; text-align: center; padding: 5px;">EYES</td><td style="border: none; text-align: center; padding: 5px;"></td></tr> <tr> <td style="background-color: cyan; color: black; text-align: center; padding: 5px;">FACE</td><td style="border: none; text-align: center; padding: 5px;"></td></tr> <tr> <td style="background-color: cyan; color: black; text-align: center; padding: 5px;">HANDS</td><td style="border: none; text-align: center; padding: 5px;"></td></tr> <tr> <td style="background-color: cyan; color: black; text-align: center; padding: 5px;">CLOTHING</td><td style="border: none; text-align: center; padding: 5px;"></td></tr> </table>	HEALTH	1	FLAMMABILITY	3	REACTIVITY	0	PROTECTIVE EQUIPMENT	A	EYES		FACE		HANDS		CLOTHING	
HEALTH	1																
FLAMMABILITY	3																
REACTIVITY	0																
PROTECTIVE EQUIPMENT	A																
EYES																	
FACE																	
HANDS																	
CLOTHING																	

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS & 2001/58 EC Standards | MSDS Revision: 2.0 | MSDS Revision Date: 03/16/2007

5. FIREFIGHTING MEASURES

5.1	Flashpoint & Method: -4 °C (24 °F) estimated.				
5.2	Autoignition Temperature: NA				
5.3	Flammability Limits:	Lower Explosive Limit (LEL):	NE	Upper Explosive Limit (UEL):	NE
5.4	Fire & Explosion Hazards: WARNING: Flammable! Keep away from heat, lit cigarettes, sparks & open flame. Keep container closed.				
5.5	Extinguishing Methods: HazChem Code: 3YE Hazard Identification Number: 33 CO₂, Halon, Dry Chemical, Foam				
5.6	Firefighting Procedures: This product is a Class IB flammable liquid. When involved in a fire, this product will ignite readily and decompose to produce carbon oxides. Vapors of this product are heavier than air and may travel to a source of ignition and flash back to a leaking or open container. First responders should wear eye protection. Structural firefighters must wear SCBAs and full protective equipment. Use a water spray or fog to reduce or direct vapors. Water may not be effective in actually extinguishing a fire involving this product.				



6. ACCIDENTAL RELEASE MEASURES

6.1	Spills: Before cleaning any spill or leak, individuals involved in spill cleanup must wear appropriate Personal Protective Equipment. For small spills (e.g., <1 gallon) wear appropriate personal protective equipment (e.g., goggles, gloves). Maximize ventilation (open doors and windows) and secure all sources of ignition. Remove spilled material with absorbent material and place into appropriate closed container(s) for disposal. Dispose of properly in accordance with local, state and federal regulations. Wash all affected areas and outside of container with plenty of warm water and soap. Remove any contaminated clothing and wash thoroughly before reuse. For spills ≥ 1 gallon, deny entry to all unprotected individuals. Dike and contain spill with inert material (e.g., sand or earth). Use ONLY non-sparking tools for recovery and cleanup. Transfer liquid to containers for recovery or disposal and solid diking material to separate containers for proper disposal. Remove contaminated clothing promptly and wash affected skin areas with soap and water. Keep spills and cleaning runoffs out of municipal sewers and open bodies of water.
-----	---

7. HANDLING & STORAGE INFORMATION

7.1	Work & Hygiene Practices: Avoid prolonged contact with the product. Avoid breathing vapors of this product. Use in a well-ventilated location (e.g., local exhaust ventilation, fans). After use, wash hands and exposed skin with soap and water. Do not eat, drink or smoke while handling product.
7.2	Storage & Handling: Keep this material away from heat, sparks and open flame. Open containers slowly on a stable surface. Keep container closed tightly when not in use. Empty container may contain residual amounts of this product; therefore, empty containers should be handled with care. Store containers in a cool, dry location, away from direct sunlight, other light sources, or sources of intense heat. Store away from incompatible materials (see Section 10).
7.3	Special Precautions: Open containers slowly on a stable surface. Keep container tightly closed when not in use. Empty containers may contain residual amounts of this product; therefore, empty containers should be handled with care.

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS & 2001/58 EC Standards | MSDS Revision: 2.0 | MSDS Revision Date: 03/16/2007

8. EXPOSURE CONTROLS & PERSONAL PROTECTION

8.1	Ventilation & Engineering Controls: When working with large quantities of product, provide adequate ventilation (e.g., local exhaust ventilation, fans). Ensure that an eyewash station, sink or washbasin is available in case of exposure to eyes.
8.2	Respiratory Protection: No special respiratory protection is required under typical circumstances of use or handling. If necessary, use only respiratory protection authorized per U.S. OSHA's requirement in 29 CFR §1910.134, or applicable U.S. state regulations, or the appropriate standards of Canada, its provinces, E.C. member states, or Australia.
8.3	Eye Protection: Depending on the use of this product, splash or safety glasses may be worn. If necessary, refer to U.S. OSHA 29 CFR §1910.133, Canadian standards, or the European Standard EN166.
8.4	Hand Protection: If anticipated that prolonged & repeated skin contact will occur during use of this product, wear latex or rubber gloves for routine industrial use. If necessary, refer to U.S. OSHA 29 CFR §1910.138, the appropriate standards of Canada, of the E.C. member states.
8.5	Body Protection: No special body protection is required under typical circumstances of use and handling. If necessary, refer to appropriate standards of Canada, the E.C. member states, or U.S. OSHA.

9. PHYSICAL & CHEMICAL PROPERTIES

9.1	Density:	0.9998 – 1.0008
9.2	Boiling Point:	171 - 640°F
9.3	Melting Point:	NE
9.4	Evaporation Rate:	NA
9.5	Vapor Pressure:	NA
9.6	Molecular Weight:	NE
9.7	Appearance & Color:	Viscous liquid, ester (fruity) odor
9.8	Odor Threshold:	ND
9.9	Solubility:	Insoluble
9.10	pH	NA
9.11	Viscosity:	1000 cPs to 3000 cPs
9.12	Other Information:	NA

10. STABILITY & REACTIVITY

10.1	Stability: Stable under ambient conditions when stored properly (see Section 7, Storage and Handling).
10.2	Hazardous Decomposition Products: If exposed to extremely high temperatures, the products of thermal decomposition may include irritating vapors and carbon oxide gases (e.g., CO, CO₂).
10.3	Hazardous Polymerization: May occur, if exposed to extremely high temperatures.
10.4	Conditions to Avoid: This product is incompatible with strong oxidizers (e.g., peroxides, superoxides), strong acids (e.g., hydrochloric or muriatic acids), or strong bases (e.g., lye, potassium hydroxide).
10.5	Incompatible Substances: None known.

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS & 2001/58 EC Standards | MSDS Revision: 2.0 | MSDS Revision Date: 03/16/2007

11. TOXICOLOGICAL INFORMATION

11.1	Toxicity Data: This product has NOT been tested on animals to obtain toxicology data. There are toxicology data for the components of the product, which are found in scientific literature. These data have not been presented in this document.
11.2	Acute Toxicity: See Section 2.5
11.3	Chronic Toxicity: See Section 2.6
11.4	Suspected Carcinogen: This product contains Isopropyl Alcohol, which is not carcinogenic to humans but are listed as Group 3 carcinogens by the IARC.
11.5	Reproductive Toxicity: This product is not reported to cause reproductive toxicity in humans.
	Mutagenicity: This product is not reported to produce mutagenic effects in humans.
	Embryotoxicity: This product is not reported to produce embryotoxic effects in humans.
	Teratogenicity: This product is not reported to cause teratogenic effects in humans.
	Reproductive Toxicity: This product is not reported to cause reproductive effects in humans.
11.6	Irritancy of Product: See Section 2.3
11.7	Biological Exposure Indices: NE
11.8	Physician Recommendations: Treat symptomatically.

12. ECOLOGICAL INFORMATION

12.1	Environmental Stability: The components of this product will slowly degrade over time into a variety of organic compounds. Specific environmental data available for the components of this product are as follows: Ethyl Acetate: $K_{OC} = 0.73$. Water solubility: 64,000 mg/l. Bioconcentration Factor = 4-14. Bioconcentration is not anticipated to be significant. This compound can be removed from contaminated environments from volatilization, and biodegradation. This compound's half-life in water is 6.1 hours. Butyl Acetate: $K_{OC} = 1.82$. Water solubility: 120 parts H ₂ O at 25°C (77°F). Bioconcentration Factor = 4-14. Bioconcentration is not anticipated to be significant. This compound can be removed from contaminated environments from volatilization, and biodegradation. This compound's half-life in water is 6.1 hours. Isopropyl Alcohol: Log $K_{OW} = 0.05-0.14$. Isopropyl alcohol occurs naturally; it is generated during microbial degradation of plant and animal wastes. When released on land or water, it is apt to volatilize and biodegrade. The estimated half-life in water is 5.4 days. Isopropyl alcohol is not expected to bioconcentrate.
12.2	Effects on Plants & Animals: There are no specific data available for this product.
12.3	Effects on Aquatic Life: There are no specific data available for this product; however, very large releases of this product may be harmful or fatal to overexposed aquatic life.

13. DISPOSAL CONSIDERATIONS

13.1	Waste Disposal: Waste disposal must be in accordance with appropriate Federal, state, and local regulations.
13.2	Special Considerations: U.S. EPA WASTE NUMBER: D001 (characteristic - ignitable)

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS & 2001/58 EC Standards

MSDS Revision: 2.0

MSDS Revision Date: 03/16/2007

14. TRANSPORTATION INFORMATION

The basic description (ID Number, proper shipping name, hazard class & division, packing group) is shown for each mode of transportation. Additional descriptive information may be required by 49 CFR, IATA/ICAO, IMDG and the TDGR.

14.1	49 CFR (GND): CONSUMER COMMODITY, ORM-D (≤ 1.0 L) UN1263, PAINT, 3, II (> 1.0 L)	
14.2	IATA (AIR): CONSUMER COMMODITY, 9, ID8000 (≤ 0.5 L) UN1263, PAINT, 3, II (> 0.5 L)	
14.3	IMDG (OCN): UN1263, PAINT, 3, II, LTD QTY (≤ 1.0 L) UN1263, PAINT, 3, II (> 1.0 L)	
14.4	TDGR (Canadian GND): MARK PACKAGE "LIMITED QUANTITY" or "QUANTITÉ LIMITÉE" or "LTD QTY" or "QUANT LTÉE" (≤ 1.0 L) UN1263, PAINT, 3, II (> 1.0 L)	
14.5	ADR/RID (EU): UN1263, PAINT, 3, II, ADR, LTD QTY (≤ 1.0 L)	
14.6	MEXICO (SCT): UN1263, PINTURA, 3, II, CANTIDAD LIMITADA (≤ 1.0 L)	

15. REGULATORY INFORMATION

15.1	SARA Reporting Requirements: SARA 304 (40 CFR Table 302.4) – Butyl Acetate, Ethyl Acetate	
15.2	SARA Threshold Planning Quantity: There are no specific Threshold Planning Quantities for the components of this product.	
15.3	TSCA Inventory Status: The components of this product are listed on the TSCA Inventory.	
15.4	CERCLA Reportable Quantity (RQ): Butyl Acetate: 5000 lbs.; Ethyl Acetate: 5000 lbs.	
15.5	Other Federal Requirements: This product complies with the appropriate sections of the Food and Drug Administration's 21 CFR subchapter G (Cosmetics).	
15.6	Other Canadian Regulations: This product has been classified according to the hazard criteria of the CPR and the MSDS contains all of the information required by the CPR. The components of this product are listed on the DSL/NDSL. None of the components of this product are listed on the Priorities Substances List. Class B2 Flammable Liquid.	 
15.7	State Regulatory Information: Ingredients in this mixture are found on the following state criteria lists:	
	California OSHA Hazardous Substances List	Butyl Acetate, Ethyl Acetate, Isopropanol, Diacetone Alcohol, Propyl Acetate
	Delaware Air Quality Management List	Butyl Acetate, Ethyl Acetate, Nitrocellulose
	Massachusetts Hazardous Substances List	Butyl Acetate, Ethyl Acetate, Isopropanol, Nitrocellulose, Silica, Camphor, Diacetone Alcohol
	Michigan Critical Substances List	Propyl Acetate
	Minnesota Hazardous Substances List	Butyl Acetate, Ethyl Acetate, Isopropanol, Silica, Camphor, Diacetone Alcohol, Propyl Acetate
	New Jersey Right to Know Hazardous Substances List	Isopropanol, Nitrocellulose, Diacetone Alcohol, Propyl Acetate
	New York List of Hazardous Substances	Butyl Acetate, Ethyl Acetate
	Pennsylvania Hazardous Substances List	Butyl Acetate, Ethyl Acetate, Isopropanol, Nitrocellulose, Silica, Camphor, Diacetone Alcohol, Propyl Acetate
	Washington Permissible Exposure Limits for Air Contaminants	Butyl Acetate, Ethyl Acetate, Isopropanol
	Wisconsin Hazardous Substances List	Ethyl Acetate

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS & 2001/58 EC Standards | MSDS Revision: 2.0 | MSDS Revision Date: 03/16/2007

15. REGULATORY INFORMATION - continued

15.8	67/548/EEC (European Union) Requirements: The primary component of this product is not listed in Annex I of EU Directive 67/548/EEC: Ethyl Acetate: Flammable (F). R: 11-36/37/38 – Highly flammable. Irritating to eyes, respiratory system and skin. S: 2-16-23-29-33 – Keep out of the reach of children. Keep away from sources of ignition - No smoking. Do not breathe gas, fumes, vapor or spray. Do not empty into drains. Take precautionary measures against static discharges. Butyl Acetate: Flammable (F). R: Flammable. S: 9-16-33 - Keep container in a well-ventilated place. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges.	 
------	---	---

16. OTHER INFORMATION

16.1	Other Information: EXTREMELY FLAMMABLE! Keep away from heat or flame. Use only as directed. Avoid eye contact. If contact occurs, flush eye thoroughly with running water. Use only in a well-ventilated area. If redness or other signs of adverse reaction occur, discontinue use immediately. Keep container closed. Store in a cool place. KEEP OUT OF REACH OF CHILDREN.
16.2	Terms & Definitions: See last page of this MSDS.
16.3	Disclaimer: This Material Safety Data Sheet is offered pursuant to OSHA's Hazard Communication Standard, 29 CFR §1910.1200. Other government regulations must be reviewed for applicability to this product. To the best of ShipMate's & OPI Products' knowledge, the information contained herein is reliable and accurate as of this date; however, accuracy, suitability or completeness are not guaranteed and no warranties of any type, either expressed or implied, are provided. The information contained herein relates only to the specific product(s). If this product(s) is combined with other materials, all component properties must be considered. Data may be changed from time to time. Be sure to consult the latest edition.
16.4	Prepared for: OPI Products, Inc. 13034 Saticoy Street No. Hollywood, CA 91605 USA +1 (818) 759-2400 phone +1 (818) 759-5770 fax http://www.opi.com/
16.5	Prepared by: ShipMate, Inc. 18436 Hawthorne Boulevard, Suite 201 Torrance, CA 90504 +1 (310) 360-3700 phone +1 (310) 360-5700 fax http://www.shipmate.com/

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS & 2001/58 EC Standards

MSDS Revision: 2.0

MSDS Revision Date: 03/16/2007

DEFINITION OF TERMS

A large number of abbreviations and acronyms appear on a MSDS. Some of these that are commonly used include the following:

GENERAL INFORMATION:

CAS No.	Chemical Abstract Service Number
---------	----------------------------------

EXPOSURE LIMITS IN AIR:


ACGIH	American Conference on Governmental Industrial Hygienists
TLV	Threshold Limit Value
OSHA	U.S. Occupational Safety and Health Administration
PEL	Permissible Exposure Limit
IDLH	Immediately Dangerous to Life and Health

FIRST AID MEASURES:

CPR	Cardiopulmonary resuscitation - method in which a person whose heart has stopped receives manual chest compressions and breathing to circulate blood and provide oxygen to the body.
-----	--


HAZARDOUS MATERIALS IDENTIFICATION SYSTEM: HMIS

0	Minimal Hazard
1	Slight Hazard
2	Moderate Hazard
3	Severe Hazard
4	Extreme Hazard



PERSONAL PROTECTION RATINGS:

A	
B	
C	
D	
E	
F	
G	
H	
I	
J	
K	
X	Consult your supervisor or S.O.P. for special handling directions.



Note: the dotted circle indicates that this respiratory protective equipment is required for high concentrations or for large volume spills or releases of product.

OTHER STANDARD ABBREVIATIONS:

NA	Not Available
NR	No Results
NE	Not Established
ND	Not Determined
ML	Maximum Limit
SCBA	Self-Contained Breathing Apparatus


NATIONAL FIRE PROTECTION ASSOCIATION: NFPA

FLAMMABILITY LIMITS IN AIR:

Autoignition Temperature	Minimum temperature required to initiate combustion in air with no other source of ignition
LEL	Lower Explosive Limit - lowest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source
UEL	Upper Explosive Limit - highest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source

HAZARD RATINGS:

0	Minimal Hazard
1	Slight Hazard
2	Moderate Hazard
3	Severe Hazard
4	Extreme Hazard



TOXICOLOGICAL INFORMATION:

LD ₅₀	Lethal Dose (solids & liquids) which kills 50% of the exposed animals
LC ₅₀	Lethal concentration (gases) which kills 50% of the exposed animal
ppm	Concentration expressed in parts of material per million parts
TD _{lo}	Lowest dose to cause a symptom
TC _{lo}	Lowest concentration to cause a symptom
TD _{lo} , LD ₅₀ , & LD ₀ or TC, TC _o , LC _{lo} , & LC ₀	Lowest dose (or concentration) to cause lethal or toxic effects
IARC	International Agency for Research on Cancer
NTP	National Toxicology Program
RETECS	Registry of Toxic Effects of Chemical Substances
BCF	Bioconcentration Factor
TL _m	Median threshold limit
log K _{ow} or log K _{oc}	Coefficient of Oil/Water Distribution

REGULATORY INFORMATION:

WHMIS	Canadian Workplace Hazardous Material Information System
DOT	U.S. Department of Transportation
TC	Transport Canada
EPA	U.S. Environmental Protection Agency
DSL	Canadian Domestic Substance List
NDSL	Canadian Non-Domestic Substance List
PSL	Canadian Priority Substances List
TSCA	U.S. Toxic Substance Control Act
EU	European Union (European Union Directive 67/548/EEC)

EC INFORMATION:

C	E	F	N	O	T+	Xi	Xn

Corrosive Explosive Flammable Harmful Oxidizing Toxic Irritant Harmful