MATERIAL SAFETY DATA SHEET

Page 1 of 8 MSDS-067G

Prep	pared to OSHA, ACC, ANSI, NOHSC, WHMIS & 2001/58 EC Standards	MSDS Revision: 2.0	MSDS	Revision Date:	: 03/16/2007	
	1. PRODUCT ID	ENTIFICATION				
1.1	Product Name:					
	NAIL ENVY NATURAL NAIL STRENGTHENER – C	ORIGINAL FORM	ULA			
1.2	Chemical Name: SOLVENT MIXTURE					
1.3	Synonyms: NA					
1.4	Trade Names: NTT80, NTT84					
1.5	Product Use: COSMETIC USE ONLY					
1.6	Manufacturer's Name: OPI PRODUCTS, INC.					
1.7	Manufacturer's Address: 13034 SATICOY STREET, NO. HOLLYWOOD, CA 91605 USA					
1.8	Emergency Phone: CHEMTREC: +1 (703) 527-3887 / +1 (800) 424-9300					
1.9	Business Phone:					
	+1 (818) 759-2400 / +1 (800) 341-9999					
	2. HAZARD IDI	NTIFICATION				
2.1	Hazard Identification:					
	Flammable liquid. This product is classified as a hazardous substrof NOHSC and ADG Code (Australia).	ınce and as dangerous	goods accord	ing to the clas	sification criteria	
2.2	Routes of Entry: Inhalation: YES	Absorption:	YES	Ingestion:	YES	
2.3	Effects of Exposure:	710301711011.		i iigestieri.		
	INGESTION: If product is swallowed, may cause nausea, vomit	ng and/or diarrhea and	d central nervo	us system dep	ression.	
	SKIN & EYES: Irritating to the eyes. Symptoms of overexposu irritating to skin in some sensitive individuals, espe-				tering. May be	
	INHALATION: Vapors of this product may be slightly irritating to the nose, throat and other tissues of the respiratory system. Symptoms of overexposure can include coughing, wheezing, nasal congestion, and difficulty breathing. Inhalation of vapors exceeding the levels listed in Section 2 (Composition and Ingredient Information) can cause central nervous system depression (e.g., drowsiness, dizziness, headaches, nausea).					
2.4	Symptoms of Overexposure:					
	Symptoms of skin overexposure in individuals may include redness, itching, and irritation of affected areas. Overexposure in eyes may cause redness, itching and watering.					
2.5	Acute Health Effects: Mild to moderate irritation to eyes and skin near affected areas. dizziness, headaches and nausea.	Additionally, high co	ncentrations of	vapors can c	ause drowsiness,	
2.6	Chronic Health Effects: None known.					
2.7	Target Organs: Eyes, skin and respiratory system.					
	The second secon					
NIA	Net Available, ND Net Determined NE Net Fetalelished C Co	llin a Linait. Co a Caption	14 for Addition	al Definitions	f Tawasa I laa al	

NA = Not Available; ND = Not Determined; NE = Not Established; C = Ceiling Limit; See Section 16 for Additional Definitions of Terms Used NOTE: all WHMIS required information is included. It is located in appropriate sections based on the ANSI Z400.1-2004 format.

MATERIAL SAFETY DATA SHEET

Page 2 of 8

MSDS-067G

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS & 2001/58 EC Standards MSDS Revision: 2.0 MSDS Revision Date: 03/16/2007

O, WHINIS & 2001/30 EO Standards HINISES REVISION, 2.0 WISES REVISION Butte. 00/10/2001

			2 001	ADOCITIO	10 141 0 14	DIEVI	LINIFOR	AAA A TI C	NNI .				
			3. COI	MEOSIIIOI	N & INGRE	DIENI	INFO						
									EXPOSURE LIMITS IN AIR (mg/m³)			1	
						%		l - ppm		SHA - p		OT	THER
	CHEMICAL NA	ME(S)	CAS No.	RTECS No.	EINECS No.		TLV	STEL	PEL	STEL	IDLH	400 -	
	ACETATE		141-78-6	AH5425000	201-550-6	≤ 30.0	400	NE	400	NE	2000	400 T	
	ACETATE		123-86-4	AF7350000	204-658-1	≤ 25.0	150	200	200	200	1700	150 T	WA
	CELLULOSE		9004-70-0	QW0970000	NA	≤ 15.0	(10)	NE	(10)	NE	NE		
	YL ACETATE		109-60-4	AJ3675000	203-686-1	≤ 15.0	200	250	200	840	1700		
RESIN	LAMIDE/FORMA	LDEHYDE	1338-51-8	NA	NA	≤ 10.0	NA	NA	NA	NA	NA		
ISOPR	OPYL ALCOHO	L	67-63-0	NT8050000	200-661-7	≤ 10.0	400	500	400	500	2000	400 T	WA
	ENYL PHOSPHAT		115-86-6	TC8400000	NA	≤ 5.0	3	NA	3	NA	NA		
	THYL PENTANYL BUTYRATE		6846-50-0	SA142000	229-937-9	≤ 5.0	NA	NA	NA	NA	NA		
N-BU1	IAL VICOHOL		71-36-3	EO1400000	200-751-6	≤ 2.0	50	NA	100	NA	NA		
FOR <i>M</i>	ALDEHYDE		50-00-0	LP8925000	200-001-8	≤ 2.0	(0.3)	NA	(0.75)	NA	NA	(0.01	6)
STEAR	RALKONIUM BEN	ITONITE	71011-24-0	NA	NA	≤ 2.0	NA	NA	NA	NA	15	DUST	1
CAMI	PHOR		76-22-2	EX1225000	200-945-0	≤ 1.0	(2)	NA	(2)	NA	NA		
DIAC	ETONE ALCOHO	L	123-42-2	SA9100000	NA	≤ 1.0	50	240	20	240	1800		
ETHYL	. TOSYLAMIDE		1077-56-1	NA	214-073-3	≤ 1.0	NA	NA	NA	NA	NA		
BENZ	OPHENONE-1		131-56-6	DJ0700000	205-029-4	≤ 1.0	NE	NE	NE	NE	NE		
CITRIC	CACID		77-92-9	GE7350000	201-069-1	≤ 1.0	NE	NE	NE	NE	NE		
HYDR PROTI	OLYZED WHOLE EIN	WHEAT	70084-87-6	NA	NA	≤ 1.0	NA	NA	NA	NA	NA		
DIME	THICONE		9006-65-9	NA	63148-62-9	≤ 1.0	NA	NA	NA	NA	NA		
CALC	IUM PANTOTHE	NATE	137-08-6	RU4375000	205-278-9	≤ 1.0	NA	NA	NA	NA	NA		
CI 60	725 (VIOLET #2)		81-48-1	CB7700000	201-353-5	≤ 1.0	NE	NE	NE	NE	NE		
CI 77	891 (TITANIUM D	OOXIDE)	81-48-1	CB7700000	201-353-5	≤ 1.0	NE	NE	NE	NE	NE		
OTHER COMPONENTS PRESENT IN LESS THAN 1% CONCENTRATION BAL THE REMAINING COMPONENTS DO NOT CONTRIBUTE SIGNIFICANT ADDITIONAL HAZARDS					E ANY								
				A EI	RST AID N	EACII	DEC						
4.1	First Aid:			4. 11	KSI AID N	ILAJU	NLJ						
	INGESTION: If ingested, do not induce vomiting. If product has been swallowed, drink plenty of water or milk IMMEDIATELY. If the patient is vomiting, continue to offer water or milk. Never give water or milk to an unconscious person. Contact the nearest Poison Control Center or local emergency number. Provide an estimate of the time at which the material was ingested and the amount of the substance that was swallowed.												
	EYES: Splashes are not likely; however, if product gets in the eyes, flush with copious amounts of lukewarm water for at least 15 minutes. If irritation occurs, contact a physician.												
	SKIN: If irritation occurs and product is on the skin, rinse thoroughly with lukewarm water, followed by a thorough washing of the effected area with soap and water. If irritation, redness or swelling persists, contact a physician immediately.												
	INHALATION:	Remove vi	ctim to fresh a	ir at once.									
4.2	Medical Condition	s Aggravated b	y Exposure:					HEA	LTH			4	1
	None known.								MMAB	II ITY_			3
													0
				REACTIVITY 0 PROTECTIVE EQUIPMENT A									
								-	IECIIV		OIF INCIN	1 /	^
								EYES					

()•P•I

MATERIAL SAFETY DATA SHEET

Page 3 of 8

MSDS-067G

NE

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS & 2001/58 EC Standards MSDS Revision: 2.0 MSDS Revision Date: 03/16/2007

5. FIREFIGHTING MEASURES

NE

Flashpoint & Method: 5.1

-4 °C (24 °F) estimated.

Autoignition Temperature: 5.2

Flammability Limits:

NA

5.3

5.4

Fire & Explosion Hazards

Lower Explosive Limit (LEL):

WARNING: Flammable! Keep away from heat, lit cigarettes, sparks & open flame. Keep container closed.

Extinguishing Methods 5.5

HazChem Code: 3YE

Hazard Identification Number: 33 CO₂, Halon, Dry Chemical, Foam

5.6 Firefighting Procedures

> This product is a Class IB flammable liquid. When involved in a fire, this product will ignite readily and decompose to produce carbon oxides. Vapors of this product are heavier than air and may travel to a source of ignition and flash back to a leaking or open container.

> First responders should wear eye protection. Structural firefighters must wear SCBAs and full protective equipment. Use a water spray or fog to reduce or direct vapors. Water may not be effective in actually extinguishing a fire involving this product.



Upper Explosive Limit (UEL):

6. ACCIDENTAL RELEASE MEASURES

6.1

Before cleaning any spill or leak, individuals involved in spill cleanup must wear appropriate Personal Protective Equipment.

For small spills (e.g., <1 gallon) wear appropriate personal protective equipment (e.g., goggles, gloves). Maximize ventilation (open doors and windows) and secure all sources of ignition. Remove spilled material with absorbent material and place into appropriate closed container(s) for disposal. Dispose of properly in accordance with local, state and federal regulations. Wash all affected areas and outside of container with plenty of warm water and soap. Remove any contaminated clothing and wash thoroughly before reuse.

For spills ≥ 1 gallon, deny entry to all unprotected individuals. Dike and contain spill with inert material (e.g., sand or earth). Use ONLY non-sparking tools for recovery and cleanup. Transfer liquid to containers for recovery or disposal and solid diking material to separate containers for proper disposal. Remove contaminated clothing promptly and wash affected skin areas with soap and water. Keep spills and cleaning runoffs out of municipal sewers and open bodies of water.

7. HANDLING & STORAGE INFORMATION

Work & Hygiene Practices:

Avoid prolonged contact with the product. Avoid breathing vapors of this product. Use in a well-ventilated location (e.g., local exhaust ventilation, fans). After use, wash hands and exposed skin with soap and water. Do not eat, drink or smoke while handling product.

7.2 Storage & Handling

> Keep this material away from heat, sparks and open flame. Open containers slowly on a stable surface. Keep container closed tightly when not in use. Empty container may contain residual amounts of this product; therefore, empty containers should be handled with care. Store containers in a cool, dry location, away from direct sunlight, other light sources, or sources of intense heat. Store away from incompatible materials (see Section 10).

Special Precautions:

Open containers slowly on a stable surface. Keep container tightly closed when not in use. Empty containers may contain residual amounts of this product; therefore, empty containers should be handled with care.

MATERIAL SAFETY DATA SHEET

Page 4 of 8

MSDS-067G

Prep	pared to OSHA, ACC, ANSI,	NOHSC, WHMIS & 2001/58 EC Standards MSDS Revision: 2.0 MSDS Revision Date: 03/16/2007			
		8. EXPOSURE CONTROLS & PERSONAL PROTECTION			
8.1	Ventilation & Engineering Controls	:			
		quantities of product, provide adequate ventilation (e.g., local exhaust ventilation, fans). Ensure that an			
		vashbasin is available in case of exposure to eyes.			
8.2	Respiratory Protection:				
	protection authorized pe	rotection is required under typical circumstances of use or handling. If necessary, use only respiratory or U.S. OSHA's requirement in 29 CFR §1910.134, or applicable U.S. state regulations, or the appropriate provinces, E.C. member states, or Australia.			
8.3	Eye Protection:				
		f this product, splash or safety glasses may be worn. If necessary, refer to U.S. OSHA 29 CFR §1910.133, ne European Standard EN166.			
8.4	Hand Protection:				
		ged & repeated skin contact will occur during use of this product, wear latex or rubber gloves for routine y, refer to U.S. OSHA 29 CFR §1910.138, the appropriate standards of Canada, of the E.C. member states.			
8.5	Body Protection:				
	No special body protection of Canada, the E.C. mem	on is required under typical circumstances of use and handling. If necessary, refer to appropriate standards ber states, or U.S. OSHA.			
		9. PHYSICAL & CHEMICAL PROPERTIES			
9.1	Density:	0.9998 - 1.0008			
9.2	Boiling Point:	171 - 640°F			
9.3	Melting Point:	NE NE			
9.4	Evaporation Rate:	NA NA			
9.5	Vapor Pressure:	NA NA			
9.6	Molecular Weight:	NE NE			
9.7	Appearance & Color:	Viscous liquid, various colors			
9.8	Odor Threshold:	ND			
9.9	Solubility:	Insoluble			
9.10	pH	NA NA			
9.11	Viscosity:	1000 - 3000 cPs			
9.12	Other Information:	NA			
	1	NA			
		10. STABILITY & REACTIVITY			
10.1	Stability: Stable under ambient conditions when stored properly (see Section 7, Storage and Handling).				
10.2	Hazardous Decomposition Produc				
	If exposed to extremely high temperatures, the products of thermal decomposition may include irritating vapors and carbon oxide gases (e.g., CO, CO ₂).				
10.3	Hazardous Polymerization:				
		extremely high temperatures.			
10.4	Conditions to Avoid:				
	strong bases (e.g., lye, po	ole with strong oxidizers (e.g., peroxides, superoxides), strong acids (e.g., hydrochloric or muriatic acids), or stassium hydroxide).			
10.5	Incompatible Substances:				
	None known.				

MATERIAL SAFETY DATA SHEET

Page 5 of 8

MSDS-067G

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS & 2001/58 EC Standards MSDS Revision: 2.0 MSDS Revision Date: 03/16/2007 11. TOXICOLOGICAL INFORMATION Toxicity Data: 11.1 This product has NOT been tested on animals to obtain toxicology data. There are toxicology data for the components of the product, which are found in scientific literature. These data have not been presented in this document. 11.2 Acute Toxicity See Section 2.5 11.3 Chronic Toxicity: See Section 2.6 11 4 Suspected Carcinogen: This product contains Formaldehyde which is listed as an OSHA carcinogen, Group 1 carcinogen (IARC) and a Group 2 carcinogen (NTP). This product contains Formaldehyde, a substance known to the State of California to cause cancer (California Proposition 65). This product also contains Isopropyl Alcohol, which is not carcinogenic to humans, but is listed as Group 3 carcinogens by IARC. Reproductive Toxicity: This product is not reported to cause reproductive toxicity in humans. This product is not reported to produce mutagenic effects in humans. This product is not reported to produce embryotoxic effects in humans. This product is not reported to cause teratogenic effects in humans. Reproductive Toxicity This product is not reported to cause reproductive effects in humans. Irritancy of Product: 11.6 See Section 2.3 Biological Exposure Indices: 11.7 NE 11.8 Physician Recommendations: Treat symptomatically. 12. ECOLOGICAL INFORMATION 12.1 Environmental Stability: The components of this product will slowly degrade over time into a variety of organic compounds. Specific environmental data available for the components of this product are as follows: Ethyl Acetate: K_{OC} = 0.73. Water solubility: 64,000 mg/l. Bioconcentration Factor = 4-14. Bioconcentration is not anticipated to be significant. This compound can be removed from contaminated environments from volatilization, and biodegradation. This compound's half-life in water is 6.1 hours. Butyl Acetate: Koc = 1.82. Water solubility: 120 parts H₂O at 25°C (77°F). Bioconcentration Factor = 4-14. Bioconcentration is not anticipated to be significant. This compound can be removed from contaminated environments from volatilization, and biodegradation. This compound's half-life in water is 6.1 hours. Isopropyl Alcohol: Log Kow = 0.05-0.14. Isopropyl alcohol occurs naturally; it is generated during microbial degradation of plant and animal wastes. When released on land or water, it is apt to volatilize and biodegrade. The estimated half-life in water is 5.4 days. Isopropyl alcohol is not expected to bioconcentrate. Effects on Plants & Animals: There are no specific data available for this product. 12.3 Effects on Aquatic Life: There are no specific data available for this product; however, very large releases of this product may be harmful or fatal to overexposed aquatic life. 13. DISPOSAL CONSIDERATIONS 13.1 Waste Disposal: Waste disposal must be in accordance with appropriate Federal, state, and local regulations. 13.2 Special Considerations:

U.S. EPA WASTE NUMBER: D001 (characteristic - ignitable)

$\mathbf{O} \cdot \mathbf{P} \cdot \mathbf{I}$

MATERIAL SAFETY DATA SHEET

Page 6 of 8

MSDS-067G

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS & 2001/58 EC Standards

MSDS Revision: 2.0

MSDS Revision Date: 03/16/2007

14. TRANSPORTATION INFORMATION

The basic description (ID Number, proper shipping name, hazard class & division, packing group) is shown for each mode of transportation. Additional descriptive information may be required by 49 CFR, IATA/ICAO, IMDG and the CTDGR.

14.1	49 CFR (GND): CONSUMER COMMODITY, ORM-D (≤ 1.0 L) UN1263, PAINT, 3, II (> 1.0 L)
14.2	IATA (AIR): CONSUMER COMMODITY, 9, ID8000 (≤ 0.5 L) UN1263, PAINT, 3, II (> 0.5 L)
14.3	IMDG (OCN): UN1263, PAINT, 3, II, LTD QTY (≤ 1.0 L) UN1263, PAINT, 3, II (> 1.0 L)
14.4	TDGR (Canadian GND): MARK PACKAGE "LIMITED QUANTITY" or "QUANTITÉ LIMITÉE" or "LTD QTY" or "QUANT LTÉE" (≤ 1.0 L) UN1263, PAINT, 3, II (> 1.0 L)
14.5	ADR/RID (EU): UN1263, PAINT, 3, II, ADR, LTD QTY (≤ 1.0 L)
14.6	MEXICO (SCT):



15. REGULATORY INFORMATION

15.1 SARA Reporting Requirements:

SARA 304 (40 CFR Table 302.4) – Butyl Acetate, Ethyl Acetate

UN1263, PINTURA, 3, II, CANTIDAD LIMITADA (≤ 1.0 L)

15.2 SARA Threshold Planning Quantity:

There are no specific Threshold Planning Quantities for the components of this product.

15.3 TSCA Inventory Status:

The components of this product are listed on the TSCA Inventory.

15.4 CERCLA Reportable Quantity (RQ):

Butyl Acetate: 5000 lbs.; Ethyl Acetate: 5000 lbs.

15.5 Other Federal Requirements:

This product complies with the appropriate sections of the Food and Drug Administration's 21 CFR subchapter G (Cosmetics).

15.6 Other Canadian Regulations:

This product has been classified according to the hazard criteria of the CPR and the MSDS contains all of the information required by the CPR. The components of this product are listed on the DSL/NDSL. None of the components of this product are listed on the Priorities Substances List. Class B2 Flammable Liquid.



15.7 State Regulatory Information

Ingredients in this mixture on found on the following state criteria lists:

California OSHA Hazardous Substances List

California Proposition 65 (Cancer)
Delaware Air Quality Management List
Massachusetts Hazardous Substances List

Michigan Critical Substances List Minnesota Hazardous Substances List

New Jersey Right to Know Hazardous Substances List

New York List of Hazardous Substances Pennsylvania Hazardous Substances List

Washington Permissible Exposure Limits for Air Contaminants

Wisconsin Hazardous Substances List

Butyl Acetate, Ethyl Acetate, Isopropanol, Formaldehyde,

Diacetone Alcohol, Propyl Acetate

Formaldehyde

Butyl Acetate, Ethyl Acetate, Nitrocellulose, Formaldehyde Butyl Acetate, Ethyl Acetate, Isopropanol, Formaldehyde,

Nitrocellulose, Camphor, Triphenyl Phosphate

Formaldehyde, Diacetone Alcohol, Propyl Acetate

Butyl Acetate, Ethyl Acetate, Isopropanol, Formaldehyde,

Camphor, Triphenyl Phosphate, Diacetone Alcohol, Propyl Acetate Isopropanol, Nitrocellulose, Formaldehyde, Diacetone Alcohol,

Propyl Acetate

Butyl Acetate, Ethyl Acetate, Formaldehyde

Butyl Acetate, Ethyl Acetate, Isopropanol, Formaldehyde,

Nitrocellulose, Camphor, Triphenyl Phosphate

Butyl Acetate, Ethyl Acetate, Isopropanol, Formaldehyde,

Triphenyl Phosphate

Ethyl Acetate, Formaldehyde, Diacetone Alcohol, Propyl Acetate

MATERIAL SAFETY DATA SHEET

Page 7 of 8

MSDS-067G

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS & 2001/58 EC Standards

MSDS Revision: 2.0

MSDS Revision Date: 03/16/2007

15. REGULATORY INFORMATION - continued

67/548/EEC (European Union) Requirements

The primary component of this product is not listed in Annex I of EU Directive 67/548/EEC:

Butyl Acetate: Flammable (F). R: Flammable. S: 9-16-33 - Keep container in a well-ventilated place. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharaes.

Ethyl Acetate: Flammable (F). R: 11-36/37/38 – Highly flammable. Irritating to eyes, respiratory system and skin. S: 2-16-23-29-33 – Keep out of the reach of children. Keep away from sources of ignition - No smoking. Do not breathe gas, tumes, vapor or spray. Do not empty into drains. Take precautionary measures against static discharges.



16. OTHER INFORMATION

16.1 Other Information

> EXTREMELY FLAMMABLE! Keep away from heat or flame. Use only as directed. Avoid eye contact. If contact occurs, flush eye thoroughly with running water. Use only in a well-ventilated area. If redness or other signs of adverse reaction occur, discontinue use immediately. Keep container closed. Store in a cool place. KEEP OUT OF REACH OF CHILDREN.

16.2 Terms & Definitions:

See last page of this MSDS.

This Material Safety Data Sheet is offered pursuant to OSHA's Hazard Communication Standard, 29 CFR §1910.1200. Other government regulations must be reviewed for applicability to this product. To the best of ShipMate's & OPI Products' knowledge, the information contained herein is reliable and accurate as of this date; however, accuracy, suitability or completeness are not guaranteed and no warranties of any type, either expressed or implied, are provided. The information contained herein relates only to the specific product(s). If this product(s) is combined with other materials, all component properties must be considered. Data may be changed from time to time. Be sure to consult the latest edition.

16.4 Prepared for

> OPI Products, Inc. 13034 Saticoy Street No. Hollywood, CA 91605 USA +1 (818) 759-2400 phone +1 (818) 759-5770 fax

 $0.6 \cdot 1$

http://www.opi.com/ 16.5 Prepared by:

ShipMate, Inc. 18436 Hawthorne Boulevard, Suite 201 Torrance, CA 90504 +1 (310) 360-3700 phone

+1 (310) 360-5700 fax

http://www.shipmate.com/



MATERIAL SAFETY DATA SHEET

Page 8 of 8

MSDS-067G

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS & 2001/58 EC Standards MSDS Revision: 2.0

MSDS Revision Date: 03/16/2007

DEFINITION OF TERMS

A large number of abbreviations and acronyms appear on a MSDs. Some of these that are commonly used include the following:

GENERAL INFORMATION:

CAS No.	Chemical Abstract Service Number
---------	----------------------------------

EXPOSURE LIMITS IN AIR:

ACGIH	American Conference on Governmental Industrial Hygienists	
TLV Threshold Limit Value		
OSHA	OSHA U.S. Occupational Safety and Health Administration	
PEL Permissible Exposure Limit		
IDLH Immediately Dangerous to Life and Health		

FIRST AID MEASURES:

CPR	Cardiopulmonary resuscitation - method in which a person
	whose heart has stopped receives manual chest
	compressions and breathing to circulate blood and provide
	oxygen to the body.


HAZARDOUS MATERIALS IDENTIFICATION SYSTEM: HMIS


HEALTH, FLAMMABILITY & REACTIVITY RATINGS:

0	Minimal Hazard	
1 Slight Hazard		
2 Moderate Hazard		
3 Severe Hazard		
4 Extreme Hazard		



PERSONAL PROTECTION RATINGS:







Vapor Respirator







Dust & Vapor Respirator





or SCBA

Note: the dotted circle indicates that this respiratory protective equipment is required for high concentrations or for large volume spills or releases of product.

OTHER STANDARD ABBREVIATIONS:

NA	Not Available
NR	No Results
NE	Not Established
ND	Not Determined
ML	Maximum Limit
SCBA	Self-Contained Breathing Apparatus


NATIONAL FIRE PROTECTION ASSOCIATION: NFPA

FLAMMABILITY LIMITS IN AIR:

Autoignition Minimum temperature required to initiate combust		
Temperature	perature in air with no other source of ignition	
LEL Lower Explosive Limit - lowest percent of vapor in air, b		
volume, that will explode or ignite in the presence		
	an ignition source	
UEL	Upper Explosive Limit - highest percent of vapor in air,	
	Upper Explosive Limit - highest percent of vapor in air, by volume, that will explode or ignite in the presence of	
	an ignition source	

HAZARD RATINGS:

0	Minimal Hazard
1	Slight Hazard
2	Moderate Hazard
3	Severe Hazard
4	Extreme Hazard
ACD	Acidic
ALK	Alkaline
COR	Corrosive
-W-	Use No Water
OX	Oxidizer



TOXICOLOGICAL INFORMATION:

LD ₅₀	Lethal Dose (solids & liquids) which kills 50% of the exposed animals s
LC ₅₀	Lethal concentration (gases) which kills 50% of the exposed animal
ppm	Concentration expressed in parts of material per million parts
TD _{lo}	Lowest dose to cause a symptom
TCLo	Lowest concentration to cause a symptom
TD _{Io} , LD _{Io} , & LD _o Or TC, TC _o , LC _{Io} , & LC _o	Lowest dose (or concentration) to cause lethal or toxic effects
IARC	International Agency for Research on Cancer
NTP	National Toxicology Program
RTECS	Registry of Toxic Effects of Chemical Substances
BCF	Bioconcentration Factor
TLm	Median threshold limit
log Kow or log Koc	Coefficient of Oil/Water Distribution

REGULATORY INFORMATION:

WHMIS	Canadian Workplace Hazardous Material Information System				
DOT	U.S. Department of Transportation				
TC	Transport Canada				
EPA	U.S. Environmental Protection Agency				
DSL	Canadian Domestic Substance List				
NDSL	Canadian Non-Domestic Substance List				
PSL	Canadian Priority Substances List				
TSCA	U.S. Toxic Substance Control Act				
EU	European Union (European Union Directive 67/548/EEC)				

EC INFORMATION:

T.		*	*		X	X	×
С	E	F	N	0	T+	Xi	Xn
Corrosive	Explosive	Flammable	Harmful	Oxidizing	Toxic	Irritant	Harmful