$O \cdot P \cdot I$

MATERIAL SAFETY DATA SHEET

Page 1 of 8

MSDS-174

Prep	ared to OSHA,	ACC, ANSI, NOHSC, WHMIS	& 2001/58 EC	Standards	MSE	OS Revision: 1.0	MSDS	Revision Date	: 08/01/2007
			1. PROD	UCT IDE	NTIFI	CATION			
1.1	Product Name:								
	NIC'S STIC	CKS TOP IT OFF TOP	COAT						
1.2	Chemical Name:								
	SOLVENT MIXT	URE							
1.3	Synonyms: NA								
1.4	Trade Names:								
1.5	Product Use:								
	COSMETIC USI	E ONLY							
1.6	Manufacturer's Na								
	OPI PRODUCTS								
1.7	Manufacturer's Ac		CA 01405 USA						
1.8	Emergency Phone	Y STREET, NO. HOLLYWOOD,	, CA 71605 03A						
		: +1 (703) 527-3887 / +	1 (800) 424-	9300					
1.9	Business Phone:	11 (700) 027 0007 7	1 (000) -12-1	7000					
	+1 (818) 759-2	2400 / +1 (800) 341-9999							
			2. HAZA	RD IDE	NTIFIC	CATION			
2.1	Hazard Identificati								
		quid. This product is class HSC and ADG Code (Austra		araous sub	ostance	e ana as aang	erous goods c	iccording to t	ne classification
2.2	Routes of Entry:		Inhalation:	YES		Absorption:	YES	Ingestion:	YES
2.3	Effects of Exposure	::			•	•			
	INGESTION:	If product is swallowed, m			_				
	SKIN & EYES: Irritating to the eyes. Symptoms of overexposure may include redness, itching, irritation and watering. May be irritating to skin in some sensitive individuals, especially after prolonged and/or repeated contact.								
	INHALATION:			-	-		-		niratory system
	INHALAHON.	Symptoms of overexposur							
		vapors exceeding the lev	els listed in Se	ction 3 (Co	omposit	tion and Ingred			
0.4	0 1 60	system depression (e.g., d	lrowsiness, dizz	iness, head	laches,	, nausea).			
2.4	Symptoms of Over	skin overexposure in indivi	duals may inc	lude redne	es itch	ina and irritati	on of affected	areas Overs	exposure in eves
		dness, itching and watering	-	iode redire	33, 11011	mig, and iman	on or unecleu	areas. Overe	Aposole ili eyes
2.5	Acute Health Effec	ots:							
		rate irritation to eyes and sl daches and nausea.	kin near affect	ed areas.	Additio	onally, high cor	centrations of	vapors can co	ause drowsiness,
2.6	Chronic Health Effe	ects:							
0.7	None known.								
2.7	Target Organs: Fves skin and	l respiratory system.							
		indepitatory dystern.							
NA =	Not Available	; ND = Not Determined; NE =	= Not Establishe	ed: C = Ceil	ling I im	nit: See Section	16 for Addition	al Definitions c	of Terms Used
		quired information is include			_				

$O \cdot P \cdot I$

MATERIAL SAFETY DATA SHEET

Page 2 of 8

MSDS-174

					1			1			
Prepared to OSI	IA, ACC, ANSI,	NOHSC, WHM	IS & 2001/58 E	C Standards	MSDS F	Revision: 1	.0	MSDS F	Revision D	ate: 08/0	1/2007
			ADOCITIO	N. A. INI G. D.F.			\	<u> </u>			
		3. COI	MPOSIIIO	N & INGRE	DIENI	INFOR	MAIIC)N			
									TS IN AIR		OTHER
					%	ACGIH	ACGIH - ppm		OSHA - ppm		
CHEMICAL	NAME(S)	CAS No.	RTECS No.	EINECS No.		TLV	STEL	PEL	STEL	IDLH	
BUTYL ACETATE		123-86-4	AF7350000	204-658-1	≤ 45.0	150	200	200	200	1700	150 TWA
ALCOHOL DENAT	URED	64-17-5	KQ6300000	200-578-6	≤ 20.0	1000	NA	1000	NA	NA	400 ====
THYL ACETATE		141-78-6	AH5425000	201-550-6	≤ 20.0	400	NE	400	NE	2000	400 TWA
CELLULOSE ACETA		9004-36-8	NA	NA	≤ 20.0	NA	NA	NA	NA	NA	
ACRYLATES COPO		25133-97-5	NA	NA	≤ 5.0	NA	NA	NA	NA	NA	
RIMETHYL PENTA DIISOBUTYRATE	NIL	6846-50-0	SA142000	229-937-9	≤ 5.0	NA	NA	NA	NA	NA	
SUCROSE BENZO	ATE .	12738-64-6	NA	235-795-5	≤ 2.0	NA	NA	NA	NA	NA	
RIPHENYL PHOSP	HATE	115-86-6	TC8400000	204-112-2	≤ 2.0	3	NA	3	NA	NA	
DIMETHICONE		9006-65-9	NA	63148-62-9	≤ 1.0	NA	NA	NA	NA	NA	
CI 60725		81-48-1	CB7700000	201-353-5	NA	NA	NA	NA	NA	NA	
OTHER COMPONENTS PRESENT IN LESS THAN 1% CONCENTRATION BAL THE REMAINING COMPONENTS DO NOT CONTRIBUTED SIGNIFICANT ADDITIONAL HAZARDS			RIBUTE AN								
			4. FI	RST AID M	IEASU	RES					
4.1 First Aid:											
INGESTION: If ingested, do not induce vomiting. If product has been swallowed, drink plenty of water or milk IMMEDIATELY. If the patient is vomiting, continue to offer water or milk. Never give water or milk to an unconscious person. Contact the nearest Poison Control Center or local emergency number. Provide an estimate of the time at which the material was											
ingested and the amount of the substance that was swallowed. EYES: Splashes are not likely; however, if product gets in the eyes, flush with copious amounts of lukewarm water for at least 15 minutes. If irritation occurs, contact a physician.											
SKIN:	If irritation	occurs and pred area with so	oduct is on the	e skin, rinse the							
INHALATIC	N: Remove v	ictim to fresh a	ir at once.								
4.2 Medical Cond None know	litions Aggravated	by Exposure:					HEA	LTH			1
HOHE KIN	****						FLA	MMAB	ILITY		3
							REA	CTIVIT	Υ		0
							PRC	TECTIV	/E EQU	IIPMEN	IT A

EYES

SKIN

LUNGS

$0.9 \cdot 1$

MATERIAL SAFETY DATA SHEET

Page 3 of 8

MSDS-174

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS & 2001/58 EC Standards MSDS Revision: 1.0 MSDS Revision Date: 08/01/2007 5. FIREFIGHTING MEASURES Flashpoint & Method: 5.1 -4 °C (24 °F) estimated. Autoignition Temperature: 5.2 NA Flammability Limits: 5.3 Lower Explosive Limit (LEL): Upper Explosive Limit (UEL): NE 5.4 Fire & Explosion Hazards WARNING: Flammable! Keep away from heat, lit cigarettes, sparks & open flame. Keep container closed. 5.5 Extinguishing Methods HazChem Code: 3YE Hazard Identification Number: 33

CO₂, Halon, Dry Chemical, Foam
5.6 Firefighting Procedures:

This product is a Class IB flammable liquid. When involved in a fire, this product will ignite readily and decompose to produce carbon oxides. Vapors of this product are heavier than air and may travel to a source of ignition and flash back to a leaking or open container.

First responders should wear eye protection. Structural firefighters must wear SCBAs and full protective equipment. Use a water spray or fog to reduce or direct vapors. Water may not be effective in actually extinguishing a fire involving this product.



6. ACCIDENTAL RELEASE MEASURES

6.1 Spills

Before cleaning any spill or leak, individuals involved in spill cleanup must wear appropriate Personal Protective Equipment.

For small spills (e.g., <1 gallon) wear appropriate personal protective equipment (e.g., goggles, gloves). Maximize ventilation (open doors and windows) and secure all sources of ignition. Remove spilled material with absorbent material and place into appropriate closed container(s) for disposal. Dispose of properly in accordance with local, state and federal regulations. Wash all affected areas and outside of container with plenty of warm water and soap. Remove any contaminated clothing and wash thoroughly before reuse.

For spills ≥ 1 gallon, deny entry to all unprotected individuals. Dike and contain spill with inert material (e.g., sand or earth). Use ONLY non-sparking tools for recovery and cleanup. Transfer liquid to containers for recovery or disposal and solid diking material to separate containers for proper disposal. Remove contaminated clothing promptly and wash affected skin areas with soap and water. Keep spills and cleaning runoffs out of municipal sewers and open bodies of water.

7. HANDLING & STORAGE INFORMATION

7.1 Work & Hygiene Practices:

Avoid prolonged contact with the product. Avoid breathing vapors of this product. Use in a well-ventilated location (e.g., local exhaust ventilation, fans). After use, wash hands and exposed skin with soap and water. Do not eat, drink or smoke while handling product.

7.2 Storage & Handling

Keep this material away from heat, sparks and open flame. Open containers slowly on a stable surface. Keep container closed tightly when not in use. Empty container may contain residual amounts of this product; therefore, empty containers should be handled with care. Store containers in a cool, dry location, away from direct sunlight, other light sources, or sources of intense heat. Store away from incompatible materials (see Section 10).

7.3 Special Precautions:

Open containers slowly on a stable surface. Keep container tightly closed when not in use. Empty containers may contain residual amounts of this product; therefore, empty containers should be handled with care.

$0.6 \cdot 1$

Incompatible Substances: **None known.**

MATERIAL SAFETY DATA SHEET

Page 4 of 8

MSDS-174

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS & 2001/58 EC Standards MSDS Revision: 1.0 MSDS Revision Date: 08/01/2007 8. EXPOSURE CONTROLS & PERSONAL PROTECTION Ventilation & Engineering Controls: 8.1 When working with large quantities of product, provide adequate ventilation (e.g., local exhaust ventilation, fans). Ensure that an eyewash station, sink or washbasin is available in case of exposure to eyes. 8.2 Respiratory Protection No special respiratory protection is required under typical circumstances of use or handling. If necessary, use only respiratory protection authorized per U.S. OSHA's requirement in 29 CFR §1910.134, or applicable U.S. state regulations, or the appropriate standards of Canada, its provinces, E.C. member states, or Australia. 8.3 Depending on the use of this product, splash or safety glasses may be worn. If necessary, refer to U.S. OSHA 29 CFR §1910.133, Canadian standards, or the European Standard EN166. 8.4 If anticipated that prolonged & repeated skin contact will occur during use of this product, wear latex or rubber gloves for routine industrial use. If necessary, refer to U.S. OSHA 29 CFR §1910.138, the appropriate standards of Canada, of the E.C. member states. 8.5 **Body Protection** No special body protection is required under typical circumstances of use and handling. If necessary, refer to appropriate standards of Canada, the E.C. member states, or U.S. OSHA. 9. PHYSICAL & CHEMICAL PROPERTIES 9.1 Density: 0.9980 - 1.0008 Boiling Point: NA 9.3 Melting Point ΝE 9.4 Evaporation Rate: NΑ 9.5 Vapor Pressure: NA Molecular Weight 9.6 9.7 Appearance & Color: Viscous liquid with solvent odor 9.8 Odor Threshold: ND Solubility: 99 Insoluble in water NA 9.11 Viscosity 1000 cPs to 3000 cPs 9 12 Other Information: NA 10. STABILITY & REACTIVITY 10.1 Stable under ambient conditions when stored properly (see Section 7, Storage and Handling) 10.2 Hazardous Decomposition Products If exposed to extremely high temperatures, the products of thermal decomposition may include irritating vapors and carbon oxide gases (e.g., CO, CO₂). 10.3 Hazardous Polymerization May occur, if exposed to extremely high temperatures. This product is incompatible with strong oxidizers (e.g., peroxides, superoxides), strong acids (e.g., hydrochloric or muriatic acids), or strong bases (e.g., lye, potassium hydroxide).

$O \cdot P \cdot I$

MATERIAL SAFETY DATA SHEET

Page 5 of 8

MSDS-174

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS & 2001/58 EC Standards MSDS Revision: 1.0 MSDS Revision Date: 08/01/2007 11. TOXICOLOGICAL INFORMATION Toxicity Data: 11.1 This product has NOT been tested on animals to obtain toxicology data. There are toxicology data for the components of the product, which are found in scientific literature. These data have not been presented in this document. 11.2 Acute Toxicity See Section 2.5 11.3 Chronic Toxicity: See Section 2.6 11 4 Suspected Carcinogen: 11.5 Reproductive Toxicity: This product is not reported to produce reproductive toxicity in humans. This product is not reported to produce mutagenic effects in humans. Embryotoxicity This product is not reported to produce embryotoxic effects in humans. Teratogenicity: This product is not reported to cause teratogenic effects in humans. Reproductive Toxicity This product is not reported to cause reproductive effects in humans. Irritancy of Product: See Section 2.3 11.7 Biological Exposure Indices: NF 11.8 Physician Recommendations: Treat symptomatically. 12. ECOLOGICAL INFORMATION The components of this product will slowly degrade over time into a variety of organic compounds. Specific environmental data available for the components of this product are as follows: Ethyl Acetate: Koc = 0.73. Water solubility: 64,000 mg/l. Bioconcentration Factor = 4-14. Bioconcentration is not anticipated to be significant. This compound can be removed from contaminated environments from volatilization, and biodegradation. This compound's half-life in water is 6.1 hours. Butyl Acetate: K_{OC} = 1.82. Water solubility: 120 parts H₂O at 25°C (77°F). Bioconcentration Factor = 4-14. Bioconcentration is not anticipated to be significant. This compound can be removed from contaminated environments from volatilization, and biodegradation. This compound's half-life in water is 6.1 hours. Effects on Plants & Animals: 12.2 There are no specific data available for this product. 12.3 Effects on Aquatic Life: There are no specific data available for this product; however, very large releases of this product may be harmful or fatal to overexposed aquatic life. 13. DISPOSAL CONSIDERATIONS 13.1 Waste Disposal Waste disposal must be in accordance with appropriate Federal, state, and local regulations. 13.2 Special Considerations: U.S. EPA WASTE NUMBER: D001 (characteristic - ignitable)

$0.9 \cdot 1$

MATERIAL SAFETY DATA SHEET

Page 6 of 8

MSDS-174

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS & 2001/58 EC Standards

MSDS Revision: 1.0

MSDS Revision Date: 08/01/2007

14. TRANSPORTATION INFORMATION

The basic description (ID Number, proper shipping name, hazard class & division, packing group) is shown for each mode of transportation. Additional descriptive information may be required by 49 CFR, IATA/ICAO, IMDG and the CTDGR.

, , ,	mieriai accomplive ilicinialisti maj percepanca by 17 ci m, ilicine, te fimb e ana tile e ib em
14.1	49 CFR (GND): CONSUMER COMMODITY, ORM-D (≤ 1.0 L) UN1263, PAINT, 3, II (> 1.0 L)
14.2	IATA (AIR): CONSUMER COMMODITY, 9, ID8000 (≤ 0.5 L) UN1263, PAINT, 3, II (> 0.5 L)
14.3	IMDG (OCN): UN1263, PAINT, 3, II, LTD QTY (≤ 1.0 L) UN1263, PAINT, 3, II (> 1.0 L)
14.4	TDGR (Canadian GND): MARK PACKAGE "LIMITED QUANTITY" or "QUANTITÉ LIMITÉE" or "LTD QTY" or "QUANT LTÉE" (≤ 1.0 L) UN1263, PAINT, 3, II (> 1.0 L)
14.5	ADR/RID (EU): UN1263, PAINT, 3, II, ADR, LTD QTY (≤ 1.0 L)
14.6	MEXICO (SCT):



15. REGULATORY INFORMATION

15.1 SARA Reporting Requirements:

SARA 304 (40 CFR Table 302.4) – Butyl Acetate, Ethyl Acetate

UN1263, PINTURA, 3, II, CANTIDAD LIMITADA (≤ 1.0 L)

15.2 SARA Threshold Planning Quantity

There are no specific Threshold Planning Quantities for the components of this product.

15.3 TSCA Inventory Status:

The components of this product are listed on the TSCA Inventory.

15.4 CERCLA Reportable Quantity (RQ):

Butyl Acetate: 5000 lbs.; Ethyl Acetate: 5000 lbs.

15.5 Other Federal Requirements:

This product complies with the appropriate sections of the Food and Drug Administration's 21 CFR subchapter G (Cosmetics).

15.6 Other Canadian Regulations:

This product has been classified according to the hazard criteria of the CPR and the MSDS contains all of the information required by the CPR. The components of this product are listed on the DSL/NDSL. None of the components of this product are listed on the Priorities Substances List. Class B2 Flammable Liquid.



15.7 State Regulatory Information:

Ingredients in this mixture on found on the following state criteria lists:

California OSHA Hazardous Substances List

California Right to Know

Delaware Air Quality Management List Massachusetts Hazardous Substances List

Massachusetts Right to Know List Minnesota Hazardous Substances List

Minnesota Right to Know List New Jersey Right to Know List

New York List of Hazardous Substances

Pennsylvania Hazardous Substances List

Pennsylvania Right to Know List

Washington Permissible Exposure Limits for Air Contaminants

Wisconsin Hazardous Substances List

Butyl Acetate, Ethyl Acetate

Triphenyl Phosphate

Butyl Acetate, Ethyl Acetate

Ethanol, Butyl Acetate, Ethyl Acetate

Triphenyl Phosphate

Ethanol, Butyl Acetate, Ethyl Acetate, Triphenyl Phosphate

Triphenyl Phosphate
Triphenyl Phosphate

Butyl Acetate, Ethyl Acetate

Ethanol, Butyl Acetate, Ethyl Acetate, Triphenyl Phosphate

Triphenyl Phosphate

Butyl Acetate, Ethyl Acetate, Triphenyl Phosphate

Ethyl Acetate

 $\mathbf{D} \cdot \mathbf{P} \cdot \mathbf{I}$

MATERIAL SAFETY DATA SHEET

Page 7 of 8

MSDS-174

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS & 2001/58 EC Standards

MSDS Revision: 1.0

MSDS Revision Date: 08/01/2007

15. REGULATORY INFORMATION - continued

67/548/EEC (European Union) Requirements:

The primary component of this product is not listed in Annex I of EU Directive 67/548/EEC:

Ethyl Acetate: Flammable (F). R: 11-36/37/38 – Highly flammable. Irritating to eyes, respiratory system and skin. S: 2-16-23-29-33 – Keep out of the reach of children. Keep away from sources of ignition - No smoking. Do not breathe gas, fumes, vapor or spray. Do not empty into drains. Take precautionary measures against static discharges.

Butyl Acetate: Flammable (F). R: Flammable. S: 9-16-33 - Keep container in a well-ventilated place. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges.



16. OTHER INFORMATION

Other Information: 16.1

> EXTREMELY FLAMMABLE! Keep away from heat or flame. Use only as directed. Avoid eye contact. If contact occurs, flush eye thoroughly with running water. Use only in a well-ventilated area. If redness or other signs of adverse reaction occur, discontinue use immediately. Keep container closed. Store in a cool place. KEEP OUT OF REACH OF CHILDREN.

Terms & Definitions: 16.2

See last page of this Material Safety Data Sheet.

16.3

This Material Safety Data Sheet is offered pursuant to OSHA's Hazard Communication Standard, 29 CFR §1910.1200. government regulations must be reviewed for applicability to this product. To the best of ShipMate's & OPI Products' knowledge, the information contained herein is reliable and accurate as of this date; however, accuracy, suitability or completeness are not guaranteed and no warranties of any type, either expressed or implied, are provided. The information contained herein relates only to the specific product(s). If this product(s) is combined with other materials, all component properties must be considered. Data may be changed from time to time. Be sure to consult the latest edition.

Prepared for:

OPI Products, Inc. 13034 Saticoy Street No. Hollywood, CA 91605 USA +1 (818) 759-2400 phone +1 (818) 759-5770 fax http://www.opi.com/

 $0.b \cdot I$

16.5 Prepared by:

ShipMate, Inc.

18436 Hawthorne Boulevard, Suite 201 Torrance, CA 90504

+1 (310) 360-3700 phone

+1 (310) 360-5700 fax

http://www.shipmate.com/



MATERIAL SAFETY DATA SHEET

Page 8 of 8

MSDS-174

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS & 2001/58 EC Standards MSDS Revision: 1.0

MSDS Revision Date: 08/01/2007

DEFINITION OF TERMS

A large number of abbreviations and acronyms appear on a MSDs. Some of these that are commonly used include the following:

GENERAL INFORMATION:

CAS No.	Chemical Abstract Service Number
---------	----------------------------------

EXPOSURE LIMITS IN AIR:

ACGIH	ACGIH American Conference on Governmental Industrial Hygienists		
TLV Threshold Limit Value			
OSHA U.S. Occupational Safety and Health Administration			
PEL Permissible Exposure Limit			
IDLH Immediately Dangerous to Life and Health			

FIRST AID MEASURES:

CPR	Cardiopulmonary resuscitation - method in which a person
	whose heart has stopped receives manual chest
	compressions and breathing to circulate blood and provide
	oxygen to the body.


HAZARDOUS MATERIALS IDENTIFICATION SYSTEM: HMIS


HEALTH, FLAMMABILITY & REACTIVITY RATINGS:

0	Minimal Hazard		
1	1 Slight Hazard		
2	2 Moderate Hazard		
3 Severe Hazard			
4 Extreme Hazard			



PERSONAL PROTECTION RATINGS:







Vapor Respirator









Respirator





Note: the dotted circle indicates that this respiratory protective equipment is required for high concentrations or for large volume spills or releases of product.

OTHER STANDARD ABBREVIATIONS:

NA	Not Available
NR	No Results
NE	Not Established
ND	Not Determined
ML	Maximum Limit
SCBA	Self-Contained Breathing Apparatus


NATIONAL FIRE PROTECTION ASSOCIATION: NFPA

FLAMMABILITY LIMITS IN AIR:

Autoignition	Minimum temperature required to initiate combustion		
Temperature	in air with no other source of ignition		
LEL Lower Explosive Limit - lowest percent of vapor in air, &			
	volume, that will explode or ignite in the presence of		
	an ignition source		
UEL	Upper Explosive Limit - highest percent of vapor in air,		
	by volume, that will explode or ignite in the presence of		
	an ignition source		

HAZARD RATINGS:

0	Minimal Hazard
1	Slight Hazard
2	Moderate Hazard
3	Severe Hazard
4	Extreme Hazard
ACD	Acidic
ALK	Alkaline
COR	Corrosive
-W-	Use No Water
OX	Oxidizer



TOXICOLOGICAL INFORMATION:

LD ₅₀	Lethal Dose (solids & liquids) which kills 50% of the exposed animals s
LC ₅₀	Lethal concentration (gases) which kills 50% of the exposed animal
ppm	Concentration expressed in parts of material per million parts
TD _{lo}	Lowest dose to cause a symptom
TCLo	Lowest concentration to cause a symptom
TD _{Io} , LD _{Io} , & LD _o Or TC, TC _o , LC _{Io} , & LC _o	Lowest dose (or concentration) to cause lethal or toxic effects
IARC	International Agency for Research on Cancer
NTP	National Toxicology Program
RTECS	Registry of Toxic Effects of Chemical Substances
BCF	Bioconcentration Factor
TLm	Median threshold limit
log Kow or log Koc	Coefficient of Oil/Water Distribution

REGULATORY INFORMATION:

WHMIS	Canadian Workplace Hazardous Material Information System			
DOT	U.S. Department of Transportation			
TC	Transport Canada			
EPA	U.S. Environmental Protection Agency			
DSL	Canadian Domestic Substance List			
NDSL	NDSL Canadian Non-Domestic Substance List			
PSL	SL Canadian Priority Substances List			
TSCA	TSCA U.S. Toxic Substance Control Act			
EU	European Union (European Union Directive 67/548/EEC)			

EC INFORMATION:

T.		M	*		®	X	X
С	E	F	N	0	T+	Xi	Xn
Corrosive	Explosive	Flammable	Harmful	Oxidizing	Toxic	Irritant	Harmful