

MATERIAL SAFETY DATA SHEET

CHLORALLOY[®] 240

1. General

Date Prepared: 05/01/08

Trade Name CHLORALLOY[®] 240 CPE SHOWER PAN LINER

Manufacturer's Name
THE NOBLE COMPANY

Address
7300 Enterprise Drive
Spring Lake, MI 49456

Emergency Telephone Number (231) 799-8000

Telephone Number for Information (231) 799-8000

DOT Hazard Classification NON-HAZARDOUS

2. Hazardous Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity; Common Names(s))	ACGIH TLV	OTHER LIMITS RECOMMENDED	% (optional)
BARIUM COMPLEX	0.5 MG / M3	AS BARUIM	< 0.1 %

*TOXIC CHEMICAL AS DEFINED BY OSHA, 29 CFR 1910, 1200 AND SUBJECT TO THE REPORTING REQUIREMENTS OF SEC. 313 OF TITLE III OF THE SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT OF 1986 AND 40 CFR PART 372.

NOTE: THRESHOLD LIMIT VALUES ARE FOR AIRBORNE DUSTS OR MIST NOT APPLICABLE TO SHEET GOODS.

3. Physical/Chemical Characteristics

Boiling Point N/A	Specific Gravity (H₂O = 1) 1.29	Vapor Pressure (mm Hg.) N/A	Melting Point N/A
-----------------------------	--	---------------------------------------	-----------------------------

Vapor Density (AIR = 1) N/A	Evaporation Rate (Butyl Acetate = 1) NONE	Solubility in Water INSOLUBLE
---------------------------------------	---	---

Appearance and Odor OPAQUE LIGHT GREY ROLL OR SHEET

VOC Statement: ZERO VOC's (calculated)

4. Fire and Explosion Hazard Data

Flash Point (Method Used) GREATER THAN 600°F	Flammable Limits N/A
--	--------------------------------

Extinguishing Media
WATER, CO 2, DRY CHEMICAL, FOAM

Special Fire Fighting Procedures
WEAR SELF-CONTAINED POSITIVE PRESSURE BREATHING APPARATUS

Unusual Fire and Explosion Hazards
BURNING PRODUCT LIBERATES HCL GAS

CHLORALLOY[®] 240 (CON'T.)

5. Reactivity Data

STABILITY	Unstable	Conditions to Avoid
	Stable X	COMBUSTION LIBERATE HCL GAS

Hazardous Decomposition or Byproducts
HCL, CO₂ CO

Hazardous Polymerization May Occur
Will Not Occur X

6. Health Hazard Data

Health Hazards (Acute and Chronic)

CONTAINS PVC WHICH MAY CONTAIN VINYL CHLORIDE MONOMER, A CANCER SUSPECT AGENT. CHECK OSHA VCM REGULATION 29 CFR, TITLE 29, CHAPTER XVII PART 1910.

Signs and Symptoms of Exposure

BASED ON AVAILABLE DATA, REPEATED EXPOSURES ARE NOT ANTICIPATED TO CAUSE ANY SIGNIFICANT EFFECTS.

7. Precautions for Safe Handling and Use

Steps to Be Taken in Case Material Is Released or Spilled

RETURN TO CONTAINER, VACUUM, SWEEP OR SHOVEL UP.
NOT CLASSIFIED AS A HAZARDOUS WASTE UNDER RCRA.

Waste Disposal Method

BURN IN ADEQUATE INCINERATOR OR BURY IN LANDFILL IN ACCORDANCE WITH APPLICABLE FEDERAL, STATE AND LOCAL REGULATIONS.

Precautions to Be Taken in Handling and Storing

N/A

Other Precautions

AVOID BREATHING VAPORS WHEN CEMENTING WITH SOLVENTS

8. Control Measures

Respiratory Protection (Specify Type)

SELF-CONTAINED BREATHING APPARATUS IN PRESENCE OF BURNING MATERIAL

VENTILATION	Local Exhaust	Special
	GOOD AIR EXCHANGE IN WORK PLACE	AVOID BREATHING DECOMPOSITION PRODUCTS

Protective Gloves

N/A

Eye Protection

USE SAFETY GLASSES

Other Protective Clothing or Equipment

N/A

Work/Hygienic Practices

WASH WITH SOAP AND WATER AFTER HANDLING

THE INFORMATION PRESENTED HEREIN, WHILE NOT GUARANTEED, WAS PREPARED BY TECHNICALLY KNOWLEDGEABLE PERSONNEL AND TO THE BEST OF OUR KNOWLEDGE IS TRUE AND ACCURATE. IT IS NOT INTENDED TO BE ALL-INCLUSIVE, AND THE MANNER AND CONDITIONS OF USE AND HANDLING MAY INVOLVE OTHER OR ADDITIONAL CONSIDERATIONS. CONSULT **NOBLE MANUFACTURING COMPANY** FOR FURTHER INFORMATION.