

Material Safety Data Sheet

Premium (High) Vacuum Pump Oil

(13201, 13203, 13204)

Date:

12/01/98

Synonyms:

Lubricating Oil

Phone:

(For Info.)

(419) 485-5561

CAS No.:

(Cherntrec Emergency) (800) 424-9300

(Refer to Section 1)

64741-88-4

(Robinair Index No.113)

Material Hazard Evaluation

(Per OSHA Hazard Communication Standard [29 CFR Part 1910.12001]) (OHCS)

Health: Non-hazardous (OHCS).

Precautionary Statement: None.

HMIS Rating': Health 0, Flammability 1, Reactivity 0

1.0 Generic Composition/Components

Components

CAS#

Hazard Data:

Oral LD50 (rat): > 15g/kg

Refined Petroleum Oil(s)

64741-88-4

100

Eve: Practically Non-Irritating Skin: Practically Non-Irritating

Thin LC50/4H(rat): >5.000 mg/m³

0 Physical Data

Physical Hazard Classification (per 29 CFR Part 1910, 1200)

No	Combustible	No	Flammable	No	Pyrophoric
No	Compressed Gas	No	Organic Peroxide	No	Reactivity
No	Explosive	No	Oxidizer	Yes	Stable

Boiling Point, 760 mmHg. °C (°F):

Specific Gravity (60/60°F) H O = 1):

Vapor Density (Air = 1):

% Volatiles by Volume: Melting Point. °C (°F):

~373 (~703) 0.87

> 1

Negligible

Vapor Pressure. mmHg (25°C):

Solubility in H.O. % by weight: Evaporation Rate (Butyl Acetate = 1): < 1

pH of Undiluted Product: Appearance and Odor

Negligible

NA

~4 x 10⁻³

Faint yellow/amber liquid, bland odor

3.0 Fire and Explosion Data

Flash Point. COC, °C (°F) Flash Point. PMC. °C (°F)

224 (435) 218 (424)

Fire Point, CQC, °C (°F)

252 (485) NFPA Rating 2: Health: 0, Flammability: 1, Reactivity: 0 Flammable Limits (% by volume in air): Lower: NA, Upper: NA CO, dry chemical, foam, water fog Extinguishing Media:

Special Fire Fighting Procedure: None

Unusual Fire or Explosion Hazard:

Water may cause frothing

4.0 Reactivity Data

Stability:

Stable

Conditions Contributing to Instability:

Incompatibility:

None

Hazardous Decomposition Products (thermal, unless otherwise specified): Strong Oxidants, Strong acids, and caustics, CO., CO Conditions Contributing to Hazardous Polymerization:

Hazard Rating: least - 0; slight - 1; moderate - 2; high - 3; extreme - 4 Robinair assignment based on our evaluation per NFPA and NPCA Guidelines.

50 Spill or Leak Procedures

edures if Material is Spilled:

Remove sources of heat or ignition, provide adequate ventilation, contain leak

- Small Spills: Absorb with suitable material such as rags, straw, or sand.
- Large spills: Contain spill in earthen dikes for later recovery
- Report spills as required to appropriate authorities.

Waste Disposal:

- It is the responsibility of the user to determine if the material is a hazardous waste at the time of disposal.
- Check before disposing to be sure you are in compliance with all applicable laws and regulations.
- Chemtrec/RCRA Emergency Hotline Number: 1-800-424-9346

Protective Measures During Repair and Maintenance of Contaminated Equipment:

- Refer to Section VII Special Protection Information
- · Avoid prolonged contact with used oil.
- Wash exposed skin thoroughly with soap and water.

6.0 Health Hazard Data

Health Hazard Classification

(ner 29 CFR Part 1910 1200)

	CTR FAIL 1910.1200)						
No	Carcinogen	No	Согтовіче	No	Mutagen	INo	Teratogen
No	Animal Carcinogen	No	Irritant	No	Highly Toxic	No	Target Organ
No	Suspect Carcinogen	No	Sensitizer	No	Toxic	1.40	TerBox Cultur

Product listed as Carcinogen or Potential Carcinogen by: NTP No IARC No OSHA No Other No

Toxicity Summary: Practically non-toxic
Major Route(s) of Entry: Inhalation of incidental mists or vapors

Acute Exposure Symptoms

Inhalation

risk at ambient temperatures. In enclosed spaces or when hot, we may reach concentrations sufficient to cause drowsiness, dizziness, headache, nausea, or lung irritation. Mists above TLV may cause chemical pneumonitis.

Dermal Contact:

Transient, slight irritation.

Eye Contact:

Practically non-irritant.

Ingestion:

Low toxicity. Very large amounts may cause generalized depression, headache, drowsiness, nausea, vomiting or diarrhea. Small doses may produce irritation and diarrhea.

Chronic Exposure

Prolonged and/or frequent contact may cause drying, cracking (dermatitis) or folliculitis. Repeated excessive exposure to mists or fumes may induce pulmonary irritation or chronic bronchitis.

Other Special Effects

None expected.

Medical Conditions Aggravated by Exposure
None

First Aid and Emergency Procedures for Acute Effect

Inhalation:

Remove to fresh air. Respiratory support, if necessary. Seek medical aid.

Dermal

Wash with soap and water. Do not wear heavily contaminated clothing before laundering.

Fuer

Flush with large volumes of water. Seek physician if any complications arise. Ingestion:

Do not induce vomiting. Seek medical aid.

Injection.

Subcutaneous injection is a medical emergency. Seek medical aid immediately.

Notes to Physician:

Following ingestion at a viscosity of around 200 SUS (100° F), there may be a minimal risk of aspiration into the lungs. For quantities above a few drops, careful cuffed tube lavage may still be considered. Aspirated material may cause chemical pneumonitis or lipoid pneumonia. Subcutaneous or intramuscular injection requires prompt surgical debridement. If not familiar with technique, seek skilled advice.



Special Protection Information

Ventilation Requirements:

Use in well ventilated area. In confined space, mechanical ventilation may be required to keep levels of certain components below mandated standards as evaluated by designated personnel.

Permitted Threshold Air Concentrations

Mineral Oil Mist

TLV-TWA TLV-STEL TLV-Ceiling

10 mg/m² ND

OSHA-PEL OSHA-STEL OSHA-Ceiling 5 mg/m³ ND

OSHA-Peak

ND

ND

Specific Personal Protective Equipment:

Respiratory

Normally none required. If high vapor or mist concentration expected, use respirator approved for organic vapors and mists.

Eves:

Safety goggles, or chemical splash goggles if splashing is anticipated.

Dermal:

Oil imperious gloves if frequent or prolonged contact is expected.

Other Clothing or Equipment:

Wear body-covering work clothes to avoid prolonged or repeated exposure. Launder soiled work clothes before reuse.

8.0 Transportation and Special Precautions

Storage:

Do not apply high heat or flame to container. Keep separate from g oxidizing agents.

Caution:

Empty containers may contain product residue which could include flammable or explosive vapors.

DOT Information

Proper Shipping Name: Hazard Class:

Petroleum Lubricating Oil Non-Hazardous None assigned

Hazard Identification Number: Placard:

Section 311 - Hazard Categories

Not Applicable

Reactive Hazard

Fire Hazard

None

Consult appropriate Federal, State and local authorities before reusing, reconditioning, reclaiming, recycling or disposing of empty containers and/or waste residues of this product.

9.0 Environmental Data

Product Name: Premium Vacuum Pump Oil (13201, 13203, 13204)

SARA TITLE III

Section 313 - Toxic Chemicals

This product does not contain toxic chemicals of Section 313 of Title III of Superfund Ammedments and Reauthorization Act of 1986 (SARA) and 40 CFR Part 372.

CAS#

Components None

Section 302/(A) - Extremely Hazardous Substance

(RQ = Reportable Quantity)

(TPQ = Threshold Planning Quantity)

This product does not contain Extremely Hazardous Substances of Section 302/(A)

Component None

CAS#

RQ lbs.

TPQ lbs.

Yes

Νo

No

No

No

Clean Water Act

Under Section 311 (b) (4) of the Clean Water Act, discharges of crude oil and petroleum products in any kind or form to surface waters must be immediately reported to the National Response Center: 800-424-8802.

New Jersey Worker & Community Right-To-Know Act Petroleum Oil

Acute (Immediate Health Hazard)

Chronic (Delayed Health Hazard)

Sudden Release of Pressure Hazard

Comprehensive Environmental Response, Compensation, and 'ability Act (CERCLA) - Section 102 Hazardous Substances mponent CAS# %

retroleum and petroleum fractions are excluded from the list of CERCLA hazardous substances by Section 101(14) of CERCLA.

ROBINAIR

10.0 Labeling

NOTE:

This product has been determined not to be a physical or a health hazard as defined by the OSHA Hazard Communication Standard.

ALL STATEMENTS, INFORMATION, AND DATA PROVIDED IN THIS MATERIAL SAFETY DATA SHEET ARE BELIEVED TO BE ACCURATE AND RELIABLE, BUT ARE PRESENTED WITHOUT GUARANTEE, REPRESENTATION, WARRANTY, OR RESPONSIBILITY OF ANY KIND, EXPRESSED OR IMPLIED. ANY AND ALL REPRESENTATIVES AND/OR WARRANTIES OF MERCHANTIBILITY OR FITNESS FOR A PARTICULAR PURPOSE ARE SPECIFICALLY DISCLAIMED. USERS SHOULD MAKE THEIR OWN INVESTIGATIONS TO DETERMINE THE SUITABILITY OF THE INFORMATION OR PRODUCTS FOR THEIR PARTICULAR PURPOSE.

Steve Moore		
Name		
Safety and Environmental Administrator		
Title	_	
Steve Moore	12/15/98	
Signature	Date	



ROBINAIR

SPX Corporation
1224 Robinair Way
Montpelier, OH 43543-1952
Phone 419-485-5561
Fax 419-485-8300