MATERIAL SAFETY DATA SHEET West System Inc.

CHEMICAL PRODUCT AND COMPANY IDENTIFICATION 1.

PRODUCT NAME: WEST SYSTEM® 551 Yellow QA Dye for Resins.

PRODUCT CODE:551 CHEMICAL FAMILY: Alcohol.

FORMULA:No information.

MANUFACTURER: **EMERGENCY TELEPHONE NUMBERS:**

West System Inc. 102 Patterson Ave. Bay City, MI 48706, U.S.A.

CHEMTREC:800-424-9300 (U.S.)

Phone: 866-937-8797 or 989-684-7286 Non-transportation

Poison Hotline:800-222-1222 www.westsystem.com

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

HMIS Hazard Rating: Health - 2 Flammability - 1 Physical Hazards - 0

Transportation

703-527-3887 (International)

WARNING! Severe eye irritant. Causes skin irritation. Exposure to vapors may be harmful. May be harmful if swallowed. Yellow liquid with aromatic odor.

POTENTIAL HEALTH EFFECTS:

ACUTE INHALATION: Concentrated vapors may cause headache, dizziness and nausea.

Overexposure may cause central nervous system depression.

ACUTE SKIN CONTACT: May cause irritation.

dermatitis. Sensitive individuals can develop skin rash.

EYE CONTACT: Severe eye irritation and possible tearing.

INGESTION: Harmful if swallowed.

SYMPTOMS OF OVEREXPOSURE: Headache, dizziness and nausea. Eye irritation. Drying skin.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE: Dermatitis.

COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

CONCENTRATION **INGREDIENT NAME** CAS#

Benzyl alcohol 100-51-6 >95 Solvent Yellow Dye no information <5

FIRST AID MEASURES

FIRST AID FOR EYES: Immediately flush eyes with water for at least 15 minutes. Get medical

attention.

FIRST AID FOR SKIN:.....Flush skin with water. If effects develop and persist, get medical attention.

persist.

FIRST AID FOR INGESTION:

medical personnel. Induce vomiting only if conscious.

MSDS# 551w-11a Last Revised: 06FEB11

5.	FIRE FIGHTING MEASURES	
	FLASH POINT:	210°F (TCC).
	EXTINGUISHING MEDIA:	. CO ₂ , foam or dry chemical.
		Water can be used to cool the fire; for extinguishing, foam or dry chemical /ear a self-contained breathing apparatus and full fire fighting protective her potentially toxic vapors including benzaldehyde.
6.	ACCIDENTAL RELEASE MEASURES	
	SPILL OR LEAK PROCEDURES: Prevent flow into sewers and public waters. Recover and recycle if po	. Remove sources of ignition, stop release and provide adequate ventilation. ossible. Soak up remaining with absorbent material.
7.	HANDLING AND STORAGE	
	STORAGE TEMPERATURE (min./max.):	. 40°F (4°C)/100°F (38°C).
	STORAGE:	. Store as an NFPA Class IIIB (combustible liquid). Store away from ignition fluorinated polymers and polypropylene.
	HANDLING PRECAUTIONS:	. Provide ventilation and avoid skin and eye contact.
8.	EXPOSURE CONTROLS/PERSONAL PROTECTION	
	EVE PROTECTION OURSELINES	0
	EYE PROTECTION GUIDELINES:	. Chemical splash goggles or face shield.
	SKIN PROTECTION GUIDELINES: against skin contact. Neoprene, nitrile or butyl rubber gloves.	. Use chemical resistant gloves and other impervious clothing to protect
		. Work environments should be maintained below applicable exposure levels ventilation. If this is not feasible, use a NIOSH approved respirator with an
	hygiene. Wash hands before eating, drinking, smoking or using the to	. Avoid breathing concentrated vapors and mist. Practice good industrial bilet facilities. Promptly remove contaminated clothing and launder before autionary measures will greatly minimize the potential for harmful exposure to
	OCCUPATIONAL EXPOSURE LIMITS: Exposure Level (PEL) or the ACGIH Guidelines for information on spe	
9.	PHYSICAL AND CHEMICAL PROPERTIES	
	PHYSICAL FORM COLOR ODOR BOILING POINT MELTING POINT/FREEZE POINT pH SOLUBILITY IN WATER SPECIFIC GRAVITY BULK DENSITY VAPOR PRESSURE VAPOR DENSITY % VOLATILE BY WEIGHT	. Yellow Aromatic odor 401°F (205°C) . 4.5°F (-15°) . No data Moderate 1.05 . 8.76 pounds/gallon No data 3.7 (air = 1)
10.	STABILITY AND REACTIVITY	
	STABILITY:	. Stable.
	HAZARDOUS POLYMERIZATION:	. Will not occur.
	INCOMPATIBILITIES: heat.	. Strong oxidizing agents. May react with strong mineral acids generating
	DECOMPOSITION PRODUCTS: potentially toxic vapors including benzaldehyde.	. Incomplete combustion will produce carbon monoxide (CO) and other
44	TOYICOLOGICAL INFORMATION	

Oral:LD₅₀ = 1,230 mg/kg

Dermal:Inhalation:	LD ₅₀ = 1,000 – 5,000 mg/kg (guinea pigs)LC ₅₀ = 4-hr $>$ 5.4 mg/l (practically non-toxic)
CARCINOGENICITY:	No.
14.00	N 1

No ingredient of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA, NTP or IARC.

12. ECOLOGICAL INFORMATION

LC50 Tidewater silversides:

EC50 Daphnia magna:

LC50 Fathead minnows and bluegill sunfish:

15 mg/l, slightly toxic

55 mg/l, slightly toxic

10-460 mg/l, moderately toxic

This material is readily biodegraded in both aerobic and anaerobic systems. Do not contaminate any streams, lakes or other natural waterways with this material.

13. DISPOSAL CONSIDERATIONS:

WASTE DISPOSAL METHOD:Knowledge of materials reveals that this product is not a hazardous waste in its purchased form as per RCRA criteria, either by characteristics or by listing. However, it is the responsibility of the end user to determine proper disposal methods. Incineration or fuel blending are preferred disposal methods.

14. TRANSPORTATION INFORMATION

DOT

D.O.T. SHIPPING NAME:
TECHNICAL SHIPPING NAME:
Not applicable.
D.O.T. HAZARD CLASS:
Not applicable.
U.N./N.A. NUMBER:
Not applicable.
PACKING GROUP:
Not applicable.

IATA

SHIPPING NAME: Not regulated.
TECHNICAL SHIPPING NAME: Not applicable.
HAZARD CLASS: Not applicable.
U.N. NUMBER: Not applicable.
PACKING GROUP: Not applicable.

15. REGULATORY INFORMATION

OSHA STATUS: Hazardous. Irritant.

TSCA STATUS: All components of this product are in compliance with TSCA Inventory requirements.

Canada WHIMIS Classification: D2B

SARA TITLE III:

SECTION 313 TOXIC CHEMICALS......None.

STATE REGULATORY INFORMATION:

The following chemicals are specifically listed or otherwise regulated by individual states. For details on your regulatory requirements you should contact the appropriate agency in your state.

COMPONENT NAME

 /CAS NUMBER
 CONCENTRATION
 STATE CODE

 Benzyl alcohol
 100-51-6
 95.75%
 MA, PA, NJ

16. OTHER INFORMATION

REASON FOR ISSUE: Changes made in Sections 5, 8, 11, 14 & 15.

PREPARED BY: G M. House

 APPROVAL DATE:
 February 6, 2011

 SUPERSEDES DATE:
 January 3, 2008

 MSDS NUMBER:
 551p-11a

Note: The Hazardous Material Indexing System (HMIS), cited in the Emergency Overview of Section 3, uses the following index to assess hazard rating: 0 = Minimal; 1 = Slight; 2 = Moderate; 3 = Serious; and 4 = Severe.

This information is furnished without warranty, expressed or implied, except that it is accurate to the best knowledge of West System Inc. The data on this sheet is related only to the specific material designated herein. West System Inc. assumes no legal responsibility for use or reliance upon these data.

MSDS# 551w-11a Last Revised: 06FEB11