

MATERIAL SAFETY DATA SHEET

KERFKORE[®] COMPANY

2630 Sidney Lanier Drive, Brunswick, Georgia 31525

Ph: 912-264-6496 FAX: 912-262-9763

www.kerfkore.com

Material Safety Data Sheet		U.S. Department of Labor			
May be used to comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200. Standard must be consulted for specific requirements.		Occupational Safety and Health Administration (Non-Mandatory Form) OMB No. 1218-0072			
IDENTITY (as used on Label and List)		Covers the following Item Numbers			
KERFKORE		SK25PB	SK50PB	SK62PB	SK 75PB
		KK25PB	KK50PB	KK62PB	KK75PB
DESCRIPTION:		SK25FB	SK50FB	SK62FB	SK 75FB
Kerfed particleboard or fiber board substrate with paper face and/or paper back		KK25FB	KK50FB	KK62FB	KK75FB
SECTION I- Chemical Product and Company Identification					
Manufacturer's Name		Kerfkore Company			
Address		2630 Sidney Lanier Drive, Brunswick, GA, 31525			
Emergency Telephone Number		912-264-6496			
Telephone Number for Information		912-264-6496			
Date Prepared		December 18, 2008			
SECTION II- Hazardous Ingredients/ Identity Information					
Hazardous Components (Specific Chemical Identity, Common Name (s))	CAS Number	Percentage by weight	OSHA PEL	ACGIH TLV-TWA	
Wood	Mixed	≈ 97	10mg/m ³	<1mg/m ³	
Formaldehyde	50.00.0	Less than .1	.72ppm	none	
Vinyl Acetate	108.05.4	Less than .4	none	none	
Paper	Mixed	≈ 2	none	none	
NOTE: Product complies with CARB Phase 1 Requirements					
SECTION III- Physical Chemical Characteristics					
Boiling Point	Not Applicable				
Vapor Pressure (mm Hg)	Not Applicable				
Vapor Density (AIR = 1)	Not Applicable				
Solubility in Water	Not Applicable				
Appearance and Odor	Light to dark tan. Color/Odor are dependent on wood				
Specific Gravity (H2O = 1)	Variable depends on wood, species and moisture				
Melting Point	Not Applicable				
Evaporation Rate (Butyl Acetate = 1)	Not Applicable				

SECTION IV-Fire and Explosion Hazard Data	
Flash Point (Method Used)	Not Applicable
Flammable Limits	Not Applicable
LEL	Not Applicable
UEL	Not Applicable
Extinguishing Media	Water, Carbon Dioxide, and Sand
Special Fire Fighting Procedures	Self Contained Breathing Apparatus recommended.
Unusual Fire and Explosion Hazards	In presence of ignition source wood dust may explode.
SECTION V-Reactivity Data	
Stability	Stable
Incompatibility (Materials to Avoid)	Oxidizing agents and drying oils
Hazardous Decomposition or Byproducts	This is a combustible product, keep in a cool dry place away from ignition sources.
Hazardous Polymerization	Will not occur
Conditions to Avoid	Excessive wood dust generated from machining.
SECTION VI- Health Hazard Data	
Route (s) to Entry	Inhalation and skin contact
Health Hazards (Acute and Chronic)	
Acute: Wood dust can irritate the eyes and breathing passages. Some wood may cause skin irritation.	
Chronic: Wood dust, may cause allergic dermatitis and respiratory sensitization with repetitive contact.	
Carcinogen	Not Applicable
NTP	Not Applicable
IARC Monographs	Not Applicable
OSHA Regulated	Not Applicable
Signs and Symptoms of Exposure	Severe coughing and breathing, or irritation of skin.
Medical Conditions	Generally aggravated by exposure.
Emergency and First Aid Procedures	Remove to fresh air, wash skin with soap and water
SECTION VII- Precautions for Safe Handling and Use	
Steps to be taken in case material is released	
Not Applicable	
Waste disposal method	
This product is not considered to be hazardous under Federal Hazardous Waste Regulations.	
Precautions to be taken in handling and storing	
This is not a DOT Hazardous Material. Avoid sparks, flames, and exposure to excessive heat.	
Other Precautions	
Store in a cool dry place between 40 degrees fahrenheit and 100 degrees fahrenheit.	
SECTION VIII-Control Measures	
Respiratory protection (specify type)	Not applicable in purchased form
Ventilation	Dust exhaust ventilation required when machining.
Protective gloves	Not Required. Use cloth or leather gloves if desired
Eye protection	Goggles or safety glasses recommended to process
Other protective clothing or equipment	None required.
Work/hygienic practices	None required.