

**CEMENT & CONCRETE PRODUCTS™
ANCHORING EPOXY****MATERIAL SAFETY DATA SHEET
(Complies with OSHA 29 CFR 1910.1200)****SECTION I: PRODUCT IDENTIFICATION**

The QUIKRETE® Companies
One Securities Centre
3490 Piedmont Road, Suite 1300
Atlanta, GA 30329

Emergency Telephone Number
(770) 216-9580

Information Telephone Number
(770) 216-9580

MSDS X4
Revision: Mar-13

QUIKRETE® Product Name

QUIKRETE® FASTSET™ ANCHORING EPOXY
QUIKRETE® HIGH STRENGTH ANCHORING EPOXY
QUIKRETE® DOT ANCHORING EPOXY

Code #

8620-30
8620-31
8620-36, -37

Part A

HEALTH	2
FLAMMABILITY	1
PHYSICAL HAZARD	0
PERSONAL PROTECTION Safety Glasses, Gloves	

Part B

HEALTH	2
FLAMMABILITY	1
PHYSICAL HAZARD	0
PERSONAL PROTECTION Safety Glasses, Gloves	

Product Use: Two component epoxies for general construction

SECTION II - HAZARD IDENTIFICATION

Known Hazards: **Part A:** Skin and eye irritation. Sensitizer; **Part B:** Corrosive

Signs and Symptoms of Exposure: **Part A:** Eyes: Irritation. Corneal injury is not expected. Skin: Irritation. Can cause allergic skin reactions in susceptible individuals, e.g. itching, redness, swelling, etc. Inhalation: No ill effects expected. Heated vapors can cause irritation. **Part B:** Eyes: Irritation. Possible eye burns. Skin: Can cause irritation and skin burns. Inhalation: No ill effects expected. Heated vapors can cause irritation.

Medical Conditions Aggravated by Exposure: Skin, eye, and respiratory conditions

Routes of Exposure: Dermal. Inhalation.

Carcinogenicity: This product contains no listed carcinogens according to IARC, ACGIH, NTP and/or OSHA in concentrations of 0.1 percent or greater.

SECTION III - HAZARDOUS INGREDIENTS/IDENTITY INFORMATION

Part A: Hazardous Component	CAS #	% By Weight	PEL	TLV	STEL
Diglycidyl Ether of Bisphenol A	25085-99-8	> 40%	NE	NE	NE
Titanium Dioxide	13463-67-7	<10	NE	5mg/m ³	NE

Part B: Hazardous Component	CAS #	% By Weight	PEL	TLV	STEL
n-aminoethylpiperazine	140-31-8	10% – 30%	NE	NE	NE
Nonyl phenol-	84852-15-3	10% – 30%	NE	NE	NE

SECTION IV – First Aid Measures

Inhalation: Move to fresh air; give oxygen if breathing is difficult. Call a physician if symptoms persist.

Eyes: Immediately flush eyes with plenty of water for at least 15 minutes. Call a physician if symptoms persist.

Skin: Wash with mild soap and water. Launder contaminated clothing before reuse.

Ingestion: If conscious, give plenty of water; do not induce vomiting unless directed to by a physician. Call a physician.

Other: Referral to a physician is recommended if there is any question about the seriousness of the injury/exposure. If Sensitization occurs, future contact with the material should be avoided.

SECTION V - FIRE AND EXPLOSION HAZARD DATA

Flash Point: Part A: > 300° F. Part B: > 200° F

Flammable Limits: N/A

Extinguisher Media: Carbon Dioxide, Dry Chemical, Water Spray, Foam

Special Fire Fighting Procedures: Use a self-contained breathing apparatus when fighting fires involving chemicals.

Unusual fire and Explosion Hazards: None known. Thermal decomposition products can be formed.

SECTION VI – ACCIDENTAL RELEASE MEASURES

Avoid all personal contact, scoop up with spade and place in disposable metal container. Flush contaminated areas.

SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND STORAGE

Avoid contact with eyes, skin and clothing. Avoid prolonged inhalation of vapors. Use with adequate ventilation. Wash thoroughly after handling. Store in a cool dry place out of direct rays of the sun. Keep from freezing. Recommended storage temperature range in between 40° and 95° F.

SECTION VIII – EXPOSURE CONTROL MEASURES

Respiratory Protection: None normally required. Use a NIOSH –approved organic vapor chemical cartridge respirator when air movement is inadequate to control vapor build-up.

Ventilation: General (natural or mechanical induced fresh air movements)

Eye Protection: Wear splash proof chemical goggles

Protective Gloves: Cloth or impermeable (neoprene or rubber) gloves

Other Protective Clothing or Equipment: Wear appropriate apparel to prevent skin contact

SECTION IX - PHYSICAL/CHEMICAL CHARACTERISTICS

CEMENT & CONCRETE PRODUCTS™

	Part A:	Part B:
Appearance:	White Paste	Black Paste
Odor:	Slight Odor	Slight Amine Odor
Vapor Density:	Non-volatile	Non-volatile
VOC Content: 0 g/l		

SECTION X - REACTIVITY DATA

Hazardous Polymerization: Will not occur

Stability: Stable

Incompatibility: Strong acids, peroxides, and other oxidizing agents

Hazardous Decomposition Products: Thermal decomposition can yield CO, CO₂ and organic Nitrogen compounds.

Conditions to Avoid: Exposure to excessive heat and storage above 95° F will shorten shelf life.

SECTION XI – TOXICOLOGICAL INFORMATION

Part A:

Acute Oral Toxicity: LD50: > 2,000 mg/kg

Acute Dermal Toxicity: LD50: > 2,000 mg/kg

Chronic Health Hazard: Many studies have been conducted to assess the potential carcinogenicity of diglycidyl ether of bisphenol A (DGEBA). Indeed, the most recent review of the available data by the International Agency for Research on Cancer (IARC) has concluded that DGEBA is not classified as a carcinogen. Although some weak evidence of carcinogenicity has been reported in animals, when all of the data are considered, the weight of evidence does not show that DGEBA is carcinogenic.

Developmental Toxicity: Resins based on the diglycidyl ether of bisphenol A (DGEBA) did not cause birth defects or other adverse effects on the fetus when pregnant rabbits were exposed by skin contact, the most likely route of exposure, or when pregnant rats or rabbits were exposed orally.

Reproductive Toxicity: In animal studies, did not interfere with reproduction.

Genetic Toxicology: In vitro genetic toxicity studies were negative in some cases and positive in other cases. Animal genetic toxicity studies were negative.

Potential Health Effects:

Inhalation: Not expected to be a relevant route of exposure, however, under conditions where exposure to vapors or mists is possible, could cause respiratory tract irritation.

Skin: May be mildly irritating to the skin. Contact with hot material can cause thermal burns which may result in permanent damage. May cause skin sensitization.

Eyes: May be mildly irritating to the eyes. Contact with hot material can cause thermal burns which may result in permanent damage or blindness.

Ingestion: Not likely to be a relevant route of exposure.

Part B:

Eye irritation/corrosion: Eye irritation.

Acute dermal irritation/corrosion: Moderate skin irritation.

CEMENT & CONCRETE PRODUCTS™

Sensitization: May cause sensitization by skin contact. Sensitization has occurred in laboratory animals after repeated exposures.

Oral: LD50 2.15 g/kg (rat) slightly toxic

Inhalation: Not determined.

Dermal: LD50 .90 g/kg (rabbit) moderately toxic

Skin: (Draize) 8.00 /8.0 (rabbit) corrosive

Eyes: (Draize) Believed to be > 80.00 - 110.00 /110 (rabbit) extremely irritating

Sensitization: (Buehler) Negative - skin (guinea pig)

SECTION XII – ECOLOGICAL INFORMATION

Ecotoxicity: Not Available

BOD5 and COD: Not Available

Products of Biodegradation: Not available

Toxicity of the Products of Biodegradation: Not available

Special Remarks on the Products of Biodegradation: Not available

SECTION XIII – DISPOSAL CONSIDERATIONS

Waste Disposal Method: If the material as supplied becomes a waste, dispose in accordance with federal, state and local regulations.

SECTION XIV – TRANSPORT INFORMATION

DOT Shipping Information: Consumer commodity, ORM-D

IMDG Shipping name: Corrosive Liquids, NOS (aminoethylpiperazine, nonylphenol), Class 8, UN 1760, PG III, Ltd Qty

IATA Shipping name: Corrosive Liquids, NOS (aminoethylpiperazine, nonylphenol), Class 8, UN 1760, PG III

SECTION XV – OTHER REGULATORY INFORMATION

US OSHA 29CFR 1910.1200: Considered non-hazardous under this regulation

SARA (Title III) Sections 311 & 312: Not listed

SARA (Title III) Section 313: Not subject to reporting requirements

TSCA (May 1997): All components are on the TSCA inventory list

Federal Hazardous Substances Act: Considered non-hazardous under this regulation

California Proposition 65: WARNING: Sanding, cutting, or grinding these products will expose you to chemicals known to the State of California to cause cancer.

Canadian Environmental Protection Act: Not listed

Canadian WHMIS: This product has been classified according to the hazard criteria of the CPR and the MSDS contains all the information required by the CPR.

SECTION XVI – OTHER INFORMATION

CEMENT & CONCRETE PRODUCTS™**Abbreviations:**

PEL = OSHA Permissible Exposure Limit
TLV = ACGIH Threshold Limit Value
C = Ceiling
STEL = Short Term Exposure Limit
NE = None Established
NA = Not Applicable
ND = Not Determined
ppm = parts per million

HMIS-III:	Health –	0 = No significant health risk
		1 = Irritation or minor reversible injury possible
		2 = Temporary or minor injury possible
		3 = Major injury possible unless prompt action is taken
		4 = Life threatening, major or permanent damage possible
	Flammability-	0 = Material will not burn
		1 = Material must be preheated before ignition will occur
		2 = Material must be exposed to high temperatures before ignition
		3 = Material capable of ignition under normal temperatures
		4 = Flammable gases or very volatile liquids; may ignite spontaneously
	Physical Hazard-	0 = Material is normally stable, even under fire conditions
		1 = Material normally stable but may become unstable at high temps
		2 = Materials that are unstable and may undergo react at room temp
		3 = Materials that may form explosive mixtures with water
		4 = Materials that are readily capable of explosive water reaction

Last Updated: March 22, 2013

NOTE: The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, express or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to silica contained in our products. END OF MSDS.