

# **Safety Data Sheet**

## **Marathon Liquid Skin Protectant**

## Section 1. Identification

Product Identifier Marathon Liquid Skin Protectant

Synonyms MSD\_SDS0017; MSC093001XL; MSC093005; MSC093001

Manufacturer Stock MSC093001XL; MSC093001; MSC093005

Numbers

Recommended use N/A Uses advised against N/A

Manufacturer Contact

Address Medline Industries, Inc.

3 Lakes Drive Northfield, IL, 60093

USA

Phone Emergency Phone Fax

(800) 633-5460 (800) 424-9300 (847) 643-4436

CHEMTREC

Website

www.Medline.com

## Section 2. Hazards Identification

Classification No OSHA Hazard Classifications Applicable - Category N.A.

Signal Word Pictogram

Hazard Statements

No OSHA Hazard Classifications Applicable

**Precautionary Statements** 

Response N/A
Prevention N/A
Storage N/A

Disposal N/A

Ingredients of unknown

toxicity

0%

Hazards not Otherwise Classified

No Data Available

## Section 3. Ingredients

CAS	Ingredient Name	Weight %
6606-65-1	n-Butyl cyanoacrylate	1% - 100%
133978-15-1	2-Octyl cyanoacrylate	1% - 100%

Occupational exposure limits, if available, are listed in Section 8.

#### Section 4. First-Aid Measures

**Eye Contact:** If eyelids are bonded, release eyelashes with a pad soaked in warm water.

> Cyanoacrylate that has bonded to eye protein will produce tears, which will assist in the debonding process. Keep eye covered with a wet pad until debonding is complete, usually within 1 to 3 days – do not force eye open. Seek medical advice if solid particles of cyanoacrylate are trapped behind

eyelid - this may cause abrasive damage.

Skin Contact: Do not force separation. Peel or roll skin apart in warm soapy water using a

blunt instrument such as a spoon. Pre-soaking in a solution of 5% sodium

bicarbonate will assist separation.

Ingestion: Do not induce vomiting. Give 1 – 3 glasses of water to drink to dilute stomach

> contents. Do not give anything by mouth if victim is unconscious or convulsing. Obtain immediate medical attention. Saliva should lift adhesive in 12 to 48 hours. Avoid swallowing adhesive after detachment. Lips may become bonded together, apply copious amounts of warm water and encourage wetting/pressure from saliva inside mouth. Peel or roll lips apart gently. Call a

physician.

Inhalation: Remove to fresh air. If symptoms persist, call a physician.

## **Section 5. Fire Fighting Measures**

Suitable Extinguishing

Water spray, CO<sub>2</sub> (Carbon dioxide), Foam, Dry Chemical

Media

Unsuitable Extinguishing

N.D.

Media

Special Fire Fighting Procedures:

Wear full protective equipment including self-contained breathing apparatus.

Unusual Fire and **Explosion Hazards:**  Water may spread fire. Product floats on water when cured. Acrid smoke and irritating fumes (oxides of carbon – oxides of nitrogen) occur in fire conditions.

#### Section 6. Accidental Release Measures

Use water spray to polymerise and scrape off floor. Solidified material may be scraped from surfaces for disposal. Wear appropriate protective clothing. Prevent material from entering drains and watercourses.

## Section 7. Handling and Storage

Precautions for Safe Handling:

Avoid contact with eyes, skin and clothing. Avoid inhaling vapours on application. Avoid moisture, direct UV sunlight and prolonged storage above 25°C (77°F).

## Section 8. Exposure Controls/Personal Protection

Occupational Exposure

Limits

 Ingredient Name
 ACGIH TLV
 OSHA PEL
 STEL

 n-Butyl cyanoacrylate
 N/A
 N/A
 N/A

 2-Octyl cyanoacrylate
 N/A
 N/A
 N/A

Personal Protective

Equipment

N/A

Respiratory Protection: Normally not necessary. A NIOSH approved organic vapour cannister may be

used.

Ventilation: Local exhaust to prevent eye irritation.

Protective gloves: Chemical resistant gloves – polyethylene recommended.

Other protective clothing or Chemical goggles, safety glasses with side shields, rubber apron.

equipment:

## Section 9. Physical and Chemical Properties

Physical State	Liquid
Color	Clear liquid
Odor	Slightly
	pungent/sharp
	odor
Odor Threshold	N.D.
Solubility	Negligible,
	polymerizes in
	H2O
Partition coefficient Water/n-octanol	N.D.
VOC%	N/A
Viscosity	N.D.
Specific Gravity	1.444
Density lbs/Gal	N/A
Pounds per Cubic Foot	N/A
Flash Point	85 - 112°C

FP Method	Closed Cup Method
рН	N.A.
Melting Point	N.D.
Boiling Point	>150°C (302°F)
Boiling Range	N.D.
LEL	N/A
UEL	N/A
Evaporation Rate	N.D.
Flammability	N.D.
Decomposition Temperature	N.D.
Auto-ignition Temperature	N.D.
Vapor Pressure	N.D.
Vapor Density	N.D.

## Section 10. Stability and Reactivity

Stability: Stable.

Incompatibility (Materials to Amines, Alcohols, Water, cotton, wool bases

avoid):

Hazardous decomposition Combustible by-products of carbon monoxide and dioxide

or By-products:

Hazardous Polymerization: May not occur.

Conditions to avoid: Temperatures >38°C (100°F)

## Section 11. Toxicological Information

General Information: Cyanoacrylate vapours are irritating to eyes and mucous membranes;

prolonged and repeated overexposure may result in allergic reactions (rhinitis) with asthma-like symptoms in certain individuals. In the event of fire or heating, cyanoacrylate adhesives increase their volatility and this increases the risk of respiratory irritation and sensitization. Contact dermatitis may occur after chronic repetitive exposure of the skin to liquid monomer. Weeping, tears and double vision may be experienced until polymerization has occurred. If cured cyanoacrylate enters the eye, there is a chance of corneal damage due to abrasion. Irritation with pain, corneal abrasions, keratoconjunctivitis and eyelash loss occurs. This product in not expected to cause long-term adverse health effects. This product in not expected to cause reproductive and

developmental health effects.

Carcinogenicity: Not considered carcinogenic by NTP, IARC and OSHA.

IARC Monographs: No. OSHA Regulated: No.

LD50: Lethal dose 50%

LC50: Lethal concentration 50%

## Section 12. Ecological Information

Toxicity: N.D. Persistence and N.D.

degradability:

Bioaccumulative potential: N.D.

Mobility in soil: N.D.

Other adverse effects: N.D.

## Section 13. Disposal

This product is not a hazardous waste. Flood with water to polymerize. Soak up with an inert absorbent (earth or sand). Dispose of in an approved landfill in accordance with local authority regulations.

## Section 14. Transport Information

UN Number N/A

UN Proper Shipping Name Not Regulated DOT Classification Not Regulated Packing Group Not Regulated

DOT: Not regulated for transport.

IATA: Not regulated for transport.

IMDG: Not regulated for transport.

## Section 15. Regulatory Information

SARA 311/312: Refer to Section 2 of the SDS.

SARA 302: N.A. SARA 304: N.A. SARA 313: N.A.

TSCA: All components are listed or exempt.

CERCLA Hazardous N.A.

Substance List:

Clean Air Act (CAA) Section N.A.

112, 112 (r):

State Regulations: N.A.

#### Section 16. Other Information

Revision Date 3/20/2019

Legend N.A. - Not Applicable

N.E. - Not Established N.D. - Not Determined

#### **Additional Information**

The information contained herein is furnished without warranty or legal responsibility of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees