



SAFETY DATA SHEET

Issue Date 2003 07 01

Revision Date 2015 07 09

Version 9.11

1. IDENTIFICATION

Product identifier

Product Name McLUBE 1725L AEROSOL

Other means of identification

Product Code 1725LC

Synonyms Mixture

Recommended use of the chemical and restrictions on use

Recommended Use Mold Release.
Dry lubricant.
Aerosol.

Uses advised against

Details of the supplier of the safety data sheet

Manufacturer Address McGee Industries, Inc.
9 Crozerville Rd
P.O. Box 2425
Aston, PA 19014

E-mail address info@mclube.com

Emergency telephone number

Company Phone Number 1-800-262-5823 (Within US)
1-610-459-1890

Emergency Telephone CHEMTREC:
1-800-424-9300 (Within US)
1-703-527-3887 (Outside US)

2. HAZARDS IDENTIFICATION

Classification

OSHA Regulatory Status

This material is considered hazardous. This information is supplied under the OSHA Hazard Communication Standard (29 CFR 1910.1200), and is offered in good faith based on data available to us that we believe to be true and accurate.

Skin corrosion/irritation	Category 2
Specific target organ toxicity (single exposure)	Category 3
Aspiration toxicity	Category 1
Flammable aerosols	Category 1
Gases under pressure	Compressed gas
Chronic aquatic toxicant	Category 1

Label elements

Emergency Overview

Danger

Hazard statements

H222: Extremely flammable aerosol.
H229: Pressurized container: May burst if heated
H304: May be fatal if swallowed and enters airways
H316: Causes mild skin irritation
H336: May cause drowsiness or dizziness
H410: Very toxic to aquatic life with long lasting effects



Vapors may travel considerable distances to ignition sources and flash back. Hazardous gases can be produced requiring respirator. Heating above 500°F (260°C) may cause formation of potentially toxic substances.

Appearance white translucent

Physical state Liquid

Odor Sweet ester odor

Precautionary Statements - Prevention

P201: Obtain special instructions before use
P202: Do not handle until all safety precautions have been read and understood
P210: Keep away from heat/sparks/open flames/hot surfaces — No smoking
P211: Do not spray on an open flame or other ignition source
P251: Pressurized container: Do not pierce or burn, even after use
P261: Avoid breathing dust/fume/gas/mist/vapors/spray.
P264: Wash skin thoroughly after handling
P270: Do not eat, drink or smoke when using this product
P271: Use only outdoors or in a well-ventilated area
P280: Wear protective gloves and eye / face protection

Precautionary Statements - Response

P304 + P340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
P305 + P351 + P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do so. Continue rinsing
P312: Call a POISON CENTER or doctor/ physician if you feel unwell
P332 + P313: If skin irritation occurs: Get medical advice/ attention
P337 + P313: If eye irritation persists: Get medical advice/attention

Precautionary Statements - Storage

P410 + P412: Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F
P405: Store locked up

Precautionary Statements - Disposal

P501: Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

None

Other Information

Prolonged exposure may cause chronic effects. May be irritating to eyes, respiratory system and skin. Prolonged skin contact may defat skin and produce dermatitis. May cause central nervous system depression with nausea, headache, dizziness, vomiting, and incoordination. Do not smoke. Do not contaminate tobacco products. The thermal decomposition vapours of fluorinated polymers may cause polymer fume fever with flu-like symptoms in humans, especially when smoking contaminated tobacco. Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal Do not puncture or burn aerosol can, even after use When operating continuously for long periods, the aerosol container can become very cold. Care should be taken to avoid skin burns.

3. COMPOSITION/INFORMATION ON INGREDIENTS**Substance**

Not applicable

Mixture**Synonyms**

Mixture.

Chemical nature

Fluoropolymer dispersion, Aerosol

Component Information:

Chemical Name	CAS No.	Weight-%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Heptane (n-)	142-82-5	40.0-50.0	Skin Irrit. 2; (H315) STOT SE 3; (H336) Asp. Tox. 1; (H304) Aquatic Acute 1; (H400) Aquatic Chronic 1; (H410) Flam. Liq. 2; (H225)
n-Butyl acetate	123-86-4	10.0-20.0	(EUH066) STOT SE 3 (H336) Flam. Liq. 3 (H226)
Ethanol	64-17-5	10.0-20.0	Flam. Liq. 2 (H225)
Dimethyl ether	115-10-6	10.0-20.0	Flam. Gas 1 (H220) Press. Gas (H280)
Carbon dioxide	124-28-9	5.0-10.0	
Propan-2-ol	67-63-0	1.0-5.0	Eye Irrit. 2, (H319) STOT SE 3, (H336) Flam. Liq. 2, (H225) [Asp. Tox. 2, (H305)]
Toluene	108-88-3	0.1-0.5	Skin Irrit. 2 (H315) Repr. 2 (H361d) STOT SE 3 (H336) STOT RE 2 (H373) Asp. Tox. 1 (H304) Flam. Liq. 2 (H225)

The exact percentage (concentration) of composition has been withheld as a trade secret.

For the full text of the Classifications and Hazard Statements mentioned in this Section, see Section 16

Amounts listed are typical and do not represent a specification. Remaining components are proprietary, nonhazardous, and/or present at amounts below reportable limits.

4. FIRST AID MEASURES**Description of first aid measures****General advice**

Use first aid treatment according to the nature of the injury. Never give anything by mouth to an unconscious person. When symptoms persist or in all cases of doubt, seek medical advice.

Eye contact

Rinse thoroughly with plenty of water for at least 15 minutes, lifting lower and upper eyelids.

	Consult a physician.
Skin contact	Wash skin with soap and water. Get medical attention if irritation develops and persists. Wash contaminated clothing before reuse.
Inhalation	Remove from exposure, lie down. Artificial respiration and/or oxygen may be necessary. If symptoms persist, call a physician.
Ingestion	Never give anything by mouth to an unconscious person. Clean mouth with water. Do NOT induce vomiting without medical advice. Potential for aspiration if swallowed. Call a physician.
Self-protection of the first aider	First aider: Pay attention to self-protection. Remove all sources of ignition. Use personal protection recommended in Section 8.

Most important symptoms and effects, both acute and delayed

Symptoms Drowsiness. Dizziness.

Indication of any immediate medical attention and special treatment needed

Note to physicians Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Water spray (fog). Carbon dioxide (CO₂). Foam. Dry chemical. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing media

Do not use a solid water stream as it may scatter and spread fire.

Specific hazards arising from the chemical

May be ignited by heat, sparks or flames. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Flash back possible over considerable distance. Thermal decomposition can lead to release of irritating and toxic gases and vapors.

Hazardous combustion products

Carbon oxides. Fluorinated compounds.

Explosion data**Sensitivity to Mechanical Impact
Sensitivity to Static Discharge**

None.

May be ignited by heat, sparks or flames. All equipment used when handling must be grounded. Use spark-resistant tools.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures**Personal precautions**

Use personal protection recommended in Section 8. Evacuate personnel to safe areas. Remove all sources of ignition. Take precautionary measures against static discharges. Extremely slippery when spilled.

Environmental precautions**Environmental precautions**

Prevent further leakage or spillage if safe to do so. Prevent entry into waterways, sewers, basements or confined areas.

Methods and material for containment and cleaning up

Methods for containment	Prevent further leakage or spillage if safe to do so. Dike far ahead of liquid spill for later disposal.
Methods for cleaning up	Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Sweep up and shovel into suitable containers for disposal. Clean contaminated surface thoroughly.

7. HANDLING AND STORAGE**Precautions for safe handling**

Advice on safe handling	Contents under pressure. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Take precautionary measures against static discharges. Use spark-proof tools and explosion-proof equipment. Do not smoke. Avoid contact with skin and eyes. Avoid breathing vapors or mists. Use personal protection recommended in Section 8.
--------------------------------	--

Conditions for safe storage, including any incompatibilities

Storage Conditions	Protect from sunlight. Store at temperatures not exceeding 50 °C/ 122 °F. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity).
Incompatible materials	Strong oxidizing agents.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION**Control parameters****Exposure Guidelines****Components with Workplace Control Parameters:**

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Heptane (n-) 142-82-5	STEL: 500 ppm TWA: 400 ppm	TWA: 500 ppm TWA: 2000 mg/m ³ (vacated) TWA: 400 ppm (vacated) TWA: 1600 mg/m ³ (vacated) STEL: 500 ppm (vacated) STEL: 2000 mg/m ³	IDLH: 750 ppm Ceiling: 440 ppm 15 min Ceiling: 1800 mg/m ³ 15 min TWA: 85 ppm TWA: 350 mg/m ³
n-Butyl acetate 123-86-4	STEL: 200 ppm TWA: 150 ppm	TWA: 150 ppm TWA: 710 mg/m ³ (vacated) TWA: 150 ppm (vacated) TWA: 710 mg/m ³ (vacated) STEL: 200 ppm (vacated) STEL: 950 mg/m ³	IDLH: 1700 ppm TWA: 150 ppm TWA: 710 mg/m ³ STEL: 200 ppm STEL: 950 mg/m ³
Ethanol 64-17-5	STEL: 1000 ppm	TWA: 1000 ppm TWA: 1900 mg/m ³ (vacated) TWA: 1000 ppm (vacated) TWA: 1900 mg/m ³	IDLH: 3300 ppm TWA: 1000 ppm TWA: 1900 mg/m ³
Propan-2-ol 67-63-0	STEL: 400 ppm TWA: 200 ppm	TWA: 400 ppm TWA: 980 mg/m ³ (vacated) TWA: 400 ppm (vacated) TWA: 980 mg/m ³ (vacated) STEL: 500 ppm (vacated) STEL: 1225 mg/m ³	IDLH: 2000 ppm TWA: 400 ppm TWA: 980 mg/m ³ STEL: 500 ppm STEL: 1225 mg/m ³
Toluene 108-88-3	TWA: 20 ppm	TWA: 200 ppm (vacated) TWA: 100 ppm (vacated) TWA: 375 mg/m ³ (vacated) STEL: 150 ppm (vacated) STEL: 560 mg/m ³ Ceiling: 300 ppm	IDLH: 500 ppm TWA: 100 ppm TWA: 375 mg/m ³ STEL: 150 ppm STEL: 560 mg/m ³

Appropriate engineering controls

Engineering Controls	Ensure adequate ventilation, especially in confined areas. As a general rule, at least 10 air
-----------------------------	---

changes per hour are recommended at the workplace.
 Explosion-proof equipment (for example fans, switches, and grounded ducts) should be used in mechanical ventilation systems.
 Showers. Eyewash stations.

Individual protection measures, such as personal protective equipment

Eye/face protection	Avoid contact with eyes. Wear safety glasses with side shields (or goggles).
Skin and body protection	Avoid skin contact. Wear protective gloves and protective clothing.
Respiratory protection	Ensure adequate ventilation, especially in confined areas. In case of insufficient ventilation, wear suitable respiratory equipment. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators.
General Hygiene Considerations	Handle in accordance with good industrial hygiene and safety practice. Do not eat, drink or smoke when using this product.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties: Physical and chemical properties apply to liquid (less propellant)

Physical state	Liquid
Appearance	white translucent
Color	white
Odor	Sweet ester odor
Odor threshold	No data available

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
pH	No data available	
Melting point / Freezing point	No data available	
Boiling point / boiling range	78 - 149 °C / 173 - 301 °F	
Flash point	- 4 °C / 24 °F	Tag Closed Cup
Evaporation rate	< 1	(Butyl Acetate = 1)
Flammability (solid, gas)	No data available	
Flammability Limit in Air		
Upper flammability limit:	10.7	(Vol % @ 100°F (38°C))
Lower flammability limit:	2.02	(Vol % @ 100°F (38°C))
Vapor pressure	2.0	@ 20 °C (kPa)
Vapor density	3.5	(Air = 1)
Specific Gravity	0.76	g/ml @ 20°C
Water solubility	< 10%	
Solubility in other solvents	No data available	
Partition coefficient	No data available	
Autoignition temperature	No data available	
Decomposition temperature	325 - 400 °C / 600 - 750 °F	
Kinematic viscosity	No data available	
Dynamic viscosity	No data available	
Explosive properties	Not applicable	
Oxidizing properties	No data available	

Other Information

Softening point	No data available	
Molecular weight	No data available	
VOC Content (%)	<= 98.0	Wt %
Density	6.33	lbs./gal.
Bulk density	No data available	

10. STABILITY AND REACTIVITY

Reactivity Stable

Chemical stability

Stability Stable

Possibility of Hazardous Reactions None under normal processing

Hazardous polymerization Hazardous polymerization does not occur.

Conditions to avoid Heat, flames and sparks. Take precautionary measures against static discharges.
Decomposition temperature: 325-400°C / 600-750°F.

Incompatible materials Strong oxidizing agents.

Hazardous Decomposition Products Carbon oxides. Fluorinated compounds.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information	The product itself has not been tested
Inhalation	May cause irritation. Aspiration into lungs can produce severe lung damage.
Eye contact	May cause irritation.
Skin contact	May cause irritation.
Ingestion	Not an expected route of exposure. May be harmful if swallowed. Potential for aspiration if swallowed.

Component Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Heptane (n-) 142-82-5	> 5000 mg/kg (Rat)	= 3000 mg/kg (Rabbit)	= 103 g/m ³ (Rat) 4 h
n-Butyl acetate 123-86-4	= 12789 mg/kg (Rat)	> 17600 mg/kg (Rabbit)	= 390 ppm (Rat) 4 h
Ethanol 64-17-5	= 15010 mg/kg (Rat)	= 20000 mg/kg (Rabbit)	= 124.7 mg/L (Rat) 4 h
Dimethyl ether 115-10-6	-	-	= 308.5 mg/L (Rat) 4 h
Propan-2-ol 67-63-0	= 4396 mg/kg (Rat)	= 12800 mg/kg (Rabbit)	= 16000 ppm (Rat) 8 h
Toluene 108-88-3	= 636 mg/kg (Rat)	= 14100 uL/kg (Rabbit)	= 49 gm/m ³ (Rat) 4 h > 26700 ppm (Rat) 1 h

Information on toxicological effects

Symptoms Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization No information available.

Germ cell mutagenicity No information available.

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
Ethanol	A3	Group 1	Known	X

64-17-5				
Propan-2-ol 67-63-0	-	Group 1 Group 3	-	X
Toluene 108-88-3	-	Group 3	-	-

Reproductive toxicity No information available.

STOT - single exposure No information available.

STOT - repeated exposure No information available.

Chronic toxicity Prolonged exposure may cause chronic effects. Prolonged skin contact may defat the skin and produce dermatitis. Repeated or prolonged exposure may cause central nervous system damage. Aspiration may cause pulmonary edema and pneumonitis.

Aspiration hazard Risk of serious damage to the lungs by aspiration.

Numerical measures of toxicity - Product Information

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral) > 5000 mg/kg
 ATEmix (dermal) 4164 mg/kg
 ATEmix (inhalation-gas) > 20000
 ATEmix (inhalation-dust/mist) > 5 mg/l
 ATEmix (inhalation-vapor) > 20 mg/l

12. ECOLOGICAL INFORMATION

Marine pollutant Yes.

Ecotoxicity The environmental impact of this product has not been fully investigated

Component Information:

Chemical Name	Algae/aquatic plants	Fish	Crustacea
Heptane (n-) 142-82-5	4,338: 72 h Pseudokirchneriella subcapitata mg/L EL50	375.0: 96 h Cichlid fish mg/L LC50	10: 24 h Daphnia magna mg/L EC50
n-Butyl acetate 123-86-4	674.7: 72 h Desmodesmus subspicatus mg/L EC50	17 - 19: 96 h Pimephales promelas mg/L LC50 flow-through 100: 96 h Lepomis macrochirus mg/L LC50 static 62: 96 h Leuciscus idus mg/L LC50 static	72.8: 24 h Daphnia magna mg/L EC50
Ethanol 64-17-5	1000: 96 h Chlorella vulgaris mg/L EC50	12.0 - 16.0: 96 h Oncorhynchus mykiss mL/L LC50 static 100: 96 h Pimephales promelas mg/L LC50 static 13400 - 15100: 96 h Pimephales promelas mg/L LC50 flow-through	9268 - 14221: 48 h Daphnia magna mg/L LC50 10800: 24 h Daphnia magna mg/L EC50 2: 48 h Daphnia magna mg/L EC50 Static
Propan-2-ol 67-63-0	1000: 96 h Desmodesmus subspicatus mg/L EC50 1000: 72 h Desmodesmus subspicatus mg/L EC50	9640: 96 h Pimephales promelas mg/L LC50 flow-through 11130: 96 h Pimephales promelas mg/L LC50 static 1400000: 96 h Lepomis macrochirus µg/L LC50	13299: 48 h Daphnia magna mg/L EC50
Toluene 108-88-3	433: 96 h Pseudokirchneriella subcapitata mg/L EC50 12.5: 72 h Pseudokirchneriella subcapitata mg/L EC50 static	15.22 - 19.05: 96 h Pimephales promelas mg/L LC50 flow-through 12.6: 96 h Pimephales promelas mg/L LC50 static 5.89 - 7.81: 96 h Oncorhynchus mykiss mg/L LC50 flow-through 14.1 - 17.16: 96 h Oncorhynchus mykiss mg/L LC50 static 5.8: 96 h Oncorhynchus mykiss mg/L LC50 semi-static	5.46 - 9.83: 48 h Daphnia magna mg/L EC50 Static 11.5: 48 h Daphnia magna mg/L EC50

		11.0 - 15.0: 96 h <i>Lepomis macrochirus</i> mg/L LC50 static 54: 96 h <i>Oryzias latipes</i> mg/L LC50 static 28.2: 96 h <i>Poecilia reticulata</i> mg/L LC50 semi-static 50.87 - 70.34: 96 h <i>Poecilia reticulata</i> mg/L LC50 static	
--	--	---	--

Persistence and degradability No information available.

Bioaccumulation No information available.

Mobility No information available.

Component Information:

Chemical Name	Partition coefficient
Heptane (n-) 142-82-5	4.66
n-Butyl acetate 123-86-4	1.81
Ethanol 64-17-5	-0.32
Dimethyl ether 115-10-6	-0.18
Propan-2-ol 67-63-0	0.05
Toluene 108-88-3	2.65

Other adverse effects No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal of wastes Disposal should be in accordance with applicable regional, national and local laws and regulations.

Contaminated packaging Pressurized container: Do not pierce or burn, even after use. Disposal should be in accordance with applicable regional, national and local laws and regulations.

Chemical Name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
Toluene 108-88-3	U220	Included in waste streams: F005, F024, F025, F039, K015, K036, K037, K149, K151	-	U220

Chemical Name	RCRA - Halogenated Organic Compounds	RCRA - P Series Wastes	RCRA - F Series Wastes	RCRA - K Series Wastes
Toluene 108-88-3	-	-	Toxic waste waste number F025 Waste description: Condensed light ends, spent filters and filter aids, and spent desiccant wastes from the production of certain chlorinated aliphatic hydrocarbons, by free radical catalyzed processes. These chlorinated aliphatic hydrocarbons are those having carbon chain lengths	-

			ranging from one to and including five, with varying amounts and positions of chlorine substitution.	
--	--	--	--	--

Chemical Name	California Hazardous Waste Status
Heptane (n-) 142-82-5	Toxic Ignitable
n-Butyl acetate 123-86-4	Toxic
Ethanol 64-17-5	Toxic Ignitable
Propan-2-ol 67-63-0	Toxic Ignitable
Toluene 108-88-3	Toxic Ignitable

14. TRANSPORT INFORMATION

DOT

Proper shipping name Consumer Commodity
Hazard Class LIMITED QUANTITY

ICAO (air)

Proper shipping name Consumer Commodity, 9, ID8000

IATA

Proper shipping name Consumer Commodity, 9, ID8000

IMDG

Proper shipping name Aerosols, 2.1, UN1950, Limited Quantity
Marine pollutant Yes

15. REGULATORY INFORMATION

International Inventories

TSCA	Complies
DSL/NDL	Complies
EINECS/ELINCS	Complies
ENCS	Complies
IECSC	Complies
KECL	Complies
PICCS	Complies
AICS	Complies

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
 DSL/NDL - Canadian Domestic Substances List/Non-Domestic Substances List
 EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances
 ENCS - Japan Existing and New Chemical Substances
 IECSC - China Inventory of Existing Chemical Substances
 KECL - Korean Existing and Evaluated Chemical Substances
 PICCS - Philippines Inventory of Chemicals and Chemical Substances
 AICS - Australian Inventory of Chemical Substances

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	SARA 313 - Threshold Values %
Toluene - 108-88-3	1.0%

SARA 311/312 Hazard Categories

Acute health hazard	Yes
Chronic Health Hazard	Yes
Fire hazard	Yes
Sudden release of pressure hazard	No
Reactive Hazard	No

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
n-Butyl acetate 123-86-4	5000 lb	-	-	X
Toluene 108-88-3	1000 lb	X	X	X

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
n-Butyl acetate 123-86-4	5000 lb	-	RQ 5000 lb final RQ RQ 2270 kg final RQ
Toluene 108-88-3	1000 lb	-	RQ 1000 lb final RQ RQ 454 kg final RQ

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals:

(Note: Ethyl alcohol is only considered a Proposition 65 developmental hazard when it is ingested as an alcoholic beverage)

Chemical Name	California Proposition 65
Ethanol - 64-17-5	Carcinogen Developmental
Toluene - 108-88-3	Developmental Female Reproductive

U.S. State Right-to-Know Regulations

This product contains substances regulated by state right-to-know regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
Heptane (n-) 142-82-5	X	X	X
n-Butyl acetate 123-86-4	X	X	X
Ethanol 64-17-5	X	X	X
Dimethyl ether 115-10-6	X	X	X
Propan-2-ol 67-63-0	X	X	X
Toluene 108-88-3	X	X	X

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OF THE LAST REVISION
--

NFPA	Health hazards 2	Flammability 3	Instability 0	Physical and Chemical Properties -
HMIS	Health hazards 2	Flammability 3	Physical hazards 0	Personal protection X

Key to Classifications and Hazard Statements contained in Sections 2 and 3

Flam. Aerosol 1 (H222): Extremely flammable aerosol; Flammable Aerosols, Cat 1
H229 - Pressurized gas; May burst if heated
Asp. Tox. 1 (H304): May be fatal if swallowed and enters airways; Aspiration, Cat 1
Skin Irrit. 2 (H316): Causes mild skin irritation; Skin Corr/Irritation, Cat 2
STOT SE 3 (H336): May cause drowsiness or dizziness; Target Organ Single, Narcotic, Cat 3
Aquatic Chronic 1 (H410): Very toxic to aquatic life with long lasting effects; Chronic Env. Tox., Cat 1
Skin Irrit. 2 (H315): Causes skin irritation; Skin Corr/Irritation, Cat 2
Aquatic Acute 1 (H400): Very toxic to aquatic life; Acute Env. Tox., Cat 1
Flam. Liq. 2 (H225): Highly flammable liquid and vapor; Flammable Liquid, Cat 2
EUH066: Repeated exposure may cause skin dryness or cracking
Flam. Liq. 3 (H226): Flammable liquid and vapor; Flammable Liquid Cat 3
Flam. Gas 1 (H220): Extremely flammable gas; Flammable gases, Cat 1
Press. Gas (H280): Contains gas under pressure; Pressurized Gas, Compressed Gas
Eye Irrit. 2 (H319): Causes serious eye irritation; Eye Dam Irrit., Cat 2
[Asp. Tox. 2 (H305)]: May be harmful if swallowed and enters airways; Aspiration, Cat 2
Repr. 2 (H361d): Suspected of damaging the unborn child; Reproductive Toxicity, Cat 2
STOT RE 2 (H373): May cause damage to organs through prolonged or repeated exposure; Target Organ Repeat, Cat 2

Issue Date 2003 07 01

Revision Date 2015 07 09

Revision Note

2003 07 01: Initial release.
2006 03 28: Modified to conform to 16 part format of ANSI Standard Z400.1-2004.
2007 04 09: Modified to correct environmental and ecological hazards identifications.
2007 04 23: Modified to correct specific gravity.
2008 02 04: Modified to reflect new transportation information.
2010 09 27: Modified to update expiring issue date.
2013 03 16: Modified to update expiring issue date.
2013 09 09: Modified to update transportation information and handling and storage information.
2015 07 09: Modified to conform to 29 CFR 1910 (OSHA HCS).

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. We do not accept liability for any loss or damage that may occur from the use of this information nor do we offer warranty against patent infringement.

End of Safety Data Sheet