

Safety Data Sheet

Copyright, 2013, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document Group:32-6625-1Version Number:1.00Issue Date:10/03/13Supercedes Date:Initial Issue

SECTION 1: Identification

1.1. Product identifier

3M™ Process Color 880I Series Special Color CF0880I-218 Orange

Product Identification Numbers

75-0302-4259-0

1.2. Recommended use and restrictions on use

Recommended use

Ink

1.3. Supplier's details

MANUFACTURER: 3M

DIVISION: Traffic Safety and Security Division

ADDRESS: 3M Center, St. Paul, MN 55144-1000, USA **Telephone:** 1-888-3M HELPS (1-888-364-3577)

1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

SECTION 2: Hazard identification

2.1. Hazard classification

Carcinogenicity: Category 1A.

Serious Eye Damage/Irritation: Category 2A.

Flammable Liquid: Category 3. Reproductive Toxicity: Category 1B.

Skin Sensitizer: Category 1.

2.2. Label elements

Signal word

Danger

Symbols

Flame | Exclamation mark | Health Hazard |

Pictograms







Hazard Statements

Flammable liquid and vapor.

Causes serious eye irritation.

May cause an allergic skin reaction.

May damage fertility or the unborn child.

May cause cancer.

Precautionary Statements

Prevention:

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Ground/bond container and receiving equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Keep container tightly closed.

Use explosion-proof electrical/ventilating/lighting equipment.

Avoid breathing dust/fume/gas/mist/vapors/spray.

Wear protective gloves and eye/face protection.

Wash thoroughly after handling.

Contaminated work clothing must not be allowed out of the workplace.

Response:

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

If eye irritation persists: Get medical advice/attention.

IF ON SKIN: Wash with plenty of soap and water.

If skin irritation or rash occurs: Get medical advice/attention.

Wash contaminated clothing before reuse.

IF exposed or concerned: Get medical advice/attention.

Specific treatment (see Notes to Physician on this label).

In case of fire: Use a fire fighting agent suitable for flammable liquids and solids such as dry chemical or carbon dioxide to extinguish.

Storage:

Store in a well-ventilated place. Keep cool.

Store locked up.

Disposal:

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

2.3. Hazards not otherwise classified

None.

84% of the mixture consists of ingredients of unknown acute inhalation toxicity.

SECTION 3: Composition/information on ingredients

Ingredient	C.A.S. No.	% by Wt
Dipropylene glycol methyl ether acetate	88917-22-0	30 - 60
Butyl methacrylate-methyl methacrylate polymer	25608-33-7	15 - 40
Cyclohexanone	108-94-1	3 - 7
1-Methoxy-2-propyl acetate	108-65-6	3 - 7
Organic pigment (NJ TSR # 04499600-5230P)	Trade Secret*	1 - 5
Vinyl polymer (NJ TSR # 04499600-5238P)	Trade Secret*	1 - 5
3-Dodecyl-1-(2,2,6,6-tetramethyl-4-piperidinyl) -2,5-	79720-19-7	< 0.6
pyrrolidinedione		
2,3,4,5-Tetrachloro-6-cyanobenzoic acid, meth ester,	106276-79-3	< 0.4
reaction products with 2-methyl-1,3-benzenediamine and		
sodium methoxide		
Toluene	108-88-3	< 0.3
Ethylbenzene	100-41-4	< 0.3
Nickel, 5,5'-azobis-2,4,5(1H,3H,5H)-pyrimidinetrione	68511-62-6	< 0.3
complexes		
n-Butyl methacrylate	97-88-1	< 0.2
2,3-Epoxypropyl neodecanoate	26761-45-5	< 0.2
Light aromatic solvent naphtha (petroleum)	64742-95-6	< 0.2

NJTS or NJTSRN: New Jersey Trade Secret Registry Number.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye Contact:

Immediately flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. Get medical attention.

If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1. Information on toxicological effects.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable.

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

^{*}The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

In case of fire: Use a fire fighting agent suitable for flammable liquids and solids such as dry chemical or carbon dioxide to extinguish.

5.2. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode.

Hazardous Decomposition or By-Products

Substance	<u>Condition</u>
Hydrocarbons	During Combustion
Carbon monoxide	During Combustion
Carbon dioxide	During Combustion

5.3. Special protective actions for fire-fighters

Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapors in the spill area to burn or explode. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

Contain spill. Cover spill area with a fire-extinguishing foam designed for use on solvents, such as alcohols and acetone, that can dissolve in water. An AR - AFFF type foam is recommended. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible using non-sparking tools. Place in a metal container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and SDS. Seal the container. Dispose of collected material as soon as possible.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

For industrial or professional use only. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Use explosion-proof electrical/ventilating/lighting equipment. Do not breathe dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.) Wear low static or properly grounded shoes. Use personal protective equipment (eg. gloves, respirators...) as required.

7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep cool. Keep container tightly closed. Protect from sunlight. Store away from heat. Store away from oxidizing agents.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
Ethylbenzene	100-41-4	Amer Conf of Gov. Indust.	TWA:20 ppm	
Ethylbenzene	100-41-4	Hyg. Chemical Manufacturer Rec Guid	TWA:25 ppm;STEL:75 ppm	
Ethylbenzene	100-41-4	US Dept of Labor - OSHA	TWA:435 mg/m3(100 ppm)	
1-Methoxy-2-propyl acetate	108-65-6	American Indust. Hygiene Assoc	TWA:50 ppm	
1-Methoxy-2-propyl acetate	108-65-6	Chemical Manufacturer Rec Guid	TWA:10 mg/m3;STEL:90 ppm	
Toluene	108-88-3	Amer Conf of Gov. Indust.	TWA:20 ppm	
Toluene	108-88-3	Hyg. Chemical Manufacturer Rec Guid	STEL:75 ppm	Skin Notation
Toluene	108-88-3	US Dept of Labor - OSHA	TWA:200 ppm;CEIL:300 ppm	
Cyclohexanone	108-94-1	Amer Conf of Gov. Indust. Hyg.	TWA:20 ppm;STEL:50 ppm	Skin Notation
Cyclohexanone	108-94-1	US Dept of Labor - OSHA	TWA:200 mg/m3(50 ppm)	
Light aromatic solvent naphtha (petroleum)	64742-95-6	Chemical Manufacturer Rec Guid	TWA:50 ppm(245 mg/m3)	
NICKEL, INSOLUBLE COMPOUNDS	68511-62-6	US Dept of Labor - OSHA	TWA(as Ni):1 mg/m3	
Dipropylene glycol methyl ether acetate	88917-22-0	Manufacturer determined	TWA:100 ppm;STEL:150 ppm	Skin Notation
n-Butyl methacrylate	97-88-1	Chemical Manufacturer Rec Guid	TWA:50 ppm;STEL:75 ppm	

Amer Conf of Gov. Indust. Hyg. : American Conference of Governmental Industrial Hygienists

American Indust. Hygiene Assoc : American Industrial Hygiene Association

Chemical Manufacturer Rec Guid : Chemical Manufacturer's Recommended Guidelines

 $US\ Dept\ of\ Labor\ -\ OSHA: United\ States\ Department\ of\ Labor\ -\ Occupational\ Safety\ and\ Health\ Administration$

TWA: Time-Weighted-Average STEL: Short Term Exposure Limit

CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment. Use explosion-proof ventilation equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Indirect Vented Goggles

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing.

Gloves made from the following material(s) are recommended: Nitrile Rubber

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

General Physical Form: Liquid

Odor, Color, Grade: Sweet solvent-like odor, orange, liquid

Odor thresholdNo Data AvailablepHNot ApplicableMelting pointNot ApplicableBoiling Point>=281 °F

Flash Point 108.00 °F [Test Method: Tagliabue Closed Cup]

Evaporation rate <=0.04 [*Ref Std:* BUOAC=1]

Flammability (solid, gas)

Flammable Limits(LEL)

Flammable Limits(UEL)

Not Applicable
1 % volume
8.6 % volume

Vapor Pressure <=5.1 mmHg [@ 20 °C]

Vapor Density No Data Available

Density 1.02 g/ml

Specific Gravity 1.02 [*Ref Std:* WATER=1]

Solubility In Water No Data Available

Solubility- non-water No Data Available

Partition coefficient: n-octanol/ waterNo Data AvailableAutoignition temperatureNo Data AvailableDecomposition temperatureNo Data AvailableViscosity1,000 - 2,000 centipoise

Volatile Organic Compounds Approximately 638 g/l [Details: CONDITIONS: As packaged]

Percent volatile VOC Less H2O & Exempt Solvents60 - 70 % weight
No Data Available

SECTION 10: Stability and reactivity

10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Sparks and/or flames

10.5. Incompatible materials

Strong acids

Strong oxidizing agents

10.6. Hazardous decomposition products

Substance Condition

None known.

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

May be harmful if inhaled.

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

Skin Contact:

Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye Contact:

Severe Eye Irritation: Signs/symptoms may include significant redness, swelling, pain, tearing, cloudy appearance of the cornea, and impaired vision.

Ingestion:

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

Reproductive/Developmental Toxicity:

Contains a chemical or chemicals which can cause birth defects or other reproductive harm.

Carcinogenicity:

Contains a chemical or chemicals which can cause cancer.

Ingredient	C.A.S. No.	Class Description	Regulation
Ethylbenzene	100-41-4	Grp. 2B: Possible human carc.	International Agency for Research on Cancer
NI CMPDS NOT ALLOYS	68511-62-6	Known human carcinogen	National Toxicology Program Carcinogens
NICKEL COMPOUNDS	68511-62-6	Grp. 1: Carcinogenic to humans	International Agency for Research on Cancer

Toxicological Data

Acute Toxicity

Name	Route	Species	Value
Overall product	Inhalation-		Data not available or insufficient for classification;
	Vapor(4 hr)		calculated ATE 27.1 mg/l
Overall product	Ingestion		Data not available or insufficient for classification;
			calculated ATE > 5,000 mg/kg
Dipropylene glycol methyl ether acetate	Dermal	Rat	LD50 > 2,000 mg/kg
Dipropylene glycol methyl ether acetate	Inhalation-	Rat	LC50 > 5.7 mg/l
	Dust/Mist		
	(4 hours)		
Dipropylene glycol methyl ether acetate	Ingestion	Rat	LD50 > 5,000 mg/kg
Butyl methacrylate-methyl methacrylate polymer	Dermal	Rabbit	LD50 > 3,000 mg/kg
Butyl methacrylate-methyl methacrylate polymer	Ingestion	Rat	LD50 > 5,000 mg/kg
1-Methoxy-2-propyl acetate	Dermal	Rabbit	LD50 > 5,000 mg/kg
1-Methoxy-2-propyl acetate	Inhalation-	Rat	LC50 > 28.8 mg/l
, 1 1,	Vapor (4		
	hours)		
1-Methoxy-2-propyl acetate	Ingestion	Rat	LD50 8,532 mg/kg
Cyclohexanone	Dermal	Rabbit	LD50 948 mg/kg
Cyclohexanone	Inhalation-	Rat	LC50 > 6.2 mg/l
	Vapor (4		8
	hours)		
Cyclohexanone	Ingestion	Rat	LD50 1,296 mg/kg
Vinyl polymer (NJ TSR # 04499600-5238P)	Dermal	Rabbit	LD50 > 8,000 mg/kg
Vinyl polymer (NJ TSR # 04499600-5238P)	Ingestion	Rat	LD50 > 8,000 mg/kg
Organic pigment (NJ TSR # 04499600-5230P)	Inhalation-	Rat	LC50 > 1 mg/l
	Dust/Mist		
	(4 hours)		
Organic pigment (NJ TSR # 04499600-5230P)	Ingestion	Rat	LD50 > 5,000 mg/kg
3-Dodecyl-1-(2,2,6,6-tetramethyl-4-piperidinyl) -2,5-	Ü		Data not available or insufficient for classification
pyrrolidinedione			
2,3,4,5-Tetrachloro-6-cyanobenzoic acid, meth ester, reaction			Data not available or insufficient for classification
products with 2-methyl-1,3-benzenediamine and sodium			
methoxide			
Ethylbenzene	Dermal	Rabbit	LD50 15,433 mg/kg
Ethylbenzene	Inhalation-	Rat	LC50 17.4 mg/l
•	Vapor (4		
	hours)		
Ethylbenzene	Ingestion	Rat	LD50 4,769 mg/kg
Toluene	Dermal	Rat	LD50 12,000 mg/kg

Toluene	Inhalation-	Rat	LC50 30 mg/l
	Vapor (4		
	hours)		
Toluene	Ingestion	Rat	LD50 2,600 mg/kg
Nickel, 5,5'-azobis-2,4,5(1H,3H,5H)-pyrimidinetrione complexes	Ingestion	Rat	LD50 5,000 mg/kg
n-Butyl methacrylate	Dermal	Rabbit	LD50 > 2,000 mg/kg
n-Butyl methacrylate	Inhalation-	Rat	LC50 > 27 mg/l
	Dust/Mist		
	(4 hours)		
n-Butyl methacrylate	Ingestion	Rat	LD50 > 2,000 mg/kg
Light aromatic solvent naphtha (petroleum)	Dermal	Rabbit	LD50 > 2,000 mg/kg
Light aromatic solvent naphtha (petroleum)	Inhalation-	Rat	LC50 > 5.2 mg/l
	Vapor (4		
	hours)		
Light aromatic solvent naphtha (petroleum)	Ingestion	Rat	LD50 > 5,000 mg/kg
2,3-Epoxypropyl neodecanoate			Data not available or insufficient for classification

 \overline{ATE} = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Dipropylene glycol methyl ether acetate	Rabbit	No significant irritation
Butyl methacrylate-methyl methacrylate polymer	Rabbit	Minimal irritation
1-Methoxy-2-propyl acetate	Rabbit	No significant irritation
Cyclohexanone	Rabbit	Mild irritant
Vinyl polymer (NJ TSR # 04499600-5238P)		No significant irritation
Organic pigment (NJ TSR # 04499600-5230P)	Rabbit	No significant irritation
3-Dodecyl-1-(2,2,6,6-tetramethyl-4-piperidinyl) -2,5-pyrrolidinedione		Data not available or insufficient for classification
2,3,4,5-Tetrachloro-6-cyanobenzoic acid, meth ester, reaction products with 2-		Data not available or insufficient for classification
methyl-1,3-benzenediamine and sodium methoxide		
Ethylbenzene	Rabbit	Mild irritant
Toluene	Rabbit	Irritant
Nickel, 5,5'-azobis-2,4,5(1H,3H,5H)-pyrimidinetrione complexes	Rabbit	No significant irritation
n-Butyl methacrylate	Rabbit	Irritant
Light aromatic solvent naphtha (petroleum)	Rabbit	Irritant
2,3-Epoxypropyl neodecanoate		Data not available or insufficient for classification

Serious Eve Damage/Irritation

Name	Species	Value
Dipropylene glycol methyl ether acetate	Rabbit	No significant irritation
Butyl methacrylate-methyl methacrylate polymer	Rabbit	Moderate irritant
1-Methoxy-2-propyl acetate	Rabbit	Mild irritant
Cyclohexanone	Rabbit	Severe irritant
Vinyl polymer (NJ TSR # 04499600-5238P)		No significant irritation
Organic pigment (NJ TSR # 04499600-5230P)	Rabbit	No significant irritation
3-Dodecyl-1-(2,2,6,6-tetramethyl-4-piperidinyl) -2,5-pyrrolidinedione		Data not available or insufficient for classification
2,3,4,5-Tetrachloro-6-cyanobenzoic acid, meth ester, reaction products with 2-		Data not available or insufficient for classification
methyl-1,3-benzenediamine and sodium methoxide		
Ethylbenzene	Rabbit	Moderate irritant
Toluene	Rabbit	Moderate irritant
Nickel, 5,5'-azobis-2,4,5(1H,3H,5H)-pyrimidinetrione complexes	Rabbit	No significant irritation
n-Butyl methacrylate	Rabbit	Mild irritant
Light aromatic solvent naphtha (petroleum)	Rabbit	Mild irritant
2,3-Epoxypropyl neodecanoate		Data not available or insufficient for classification

Skin Sensitization

Skiii Selisiuzation		
Name	Species	Value
Dipropylene glycol methyl ether acetate	Guinea	Not sensitizing
	pig	
Butyl methacrylate-methyl methacrylate polymer		Data not available or insufficient for classification
1-Methoxy-2-propyl acetate	Guinea	Not sensitizing
	pig	
Cyclohexanone	Guinea	Not sensitizing
	pig	
Vinyl polymer (NJ TSR # 04499600-5238P)		Data not available or insufficient for classification
Organic pigment (NJ TSR # 04499600-5230P)	Human	Not sensitizing

Page 9 of 17

3-Dodecyl-1-(2,2,6,6-tetramethyl-4-piperidinyl) -2,5-pyrrolidinedione		Data not available or insufficient for classification
2,3,4,5-Tetrachloro-6-cyanobenzoic acid, meth ester, reaction products with 2-		Data not available or insufficient for classification
methyl-1,3-benzenediamine and sodium methoxide		
Ethylbenzene	Human	Not sensitizing
Toluene	Guinea	Not sensitizing
	pig	
Nickel, 5,5'-azobis-2,4,5(1H,3H,5H)-pyrimidinetrione complexes	similar	Sensitizing
	compoun	
	ds	
n-Butyl methacrylate	Guinea	Sensitizing
	pig	
Light aromatic solvent naphtha (petroleum)	Guinea	Not sensitizing
	pig	
2,3-Epoxypropyl neodecanoate	Guinea	Sensitizing
	pig	

Respiratory Sensitization

respiratory sensitization		
Name	Species	Value
Dipropylene glycol methyl ether acetate		Data not available or insufficient for classification
Butyl methacrylate-methyl methacrylate polymer		Data not available or insufficient for classification
1-Methoxy-2-propyl acetate		Data not available or insufficient for classification
Cyclohexanone		Data not available or insufficient for classification
Vinyl polymer (NJ TSR # 04499600-5238P)		Data not available or insufficient for classification
Organic pigment (NJ TSR # 04499600-5230P)		Data not available or insufficient for classification
3-Dodecyl-1-(2,2,6,6-tetramethyl-4-piperidinyl) -2,5-pyrrolidinedione		Data not available or insufficient for classification
2,3,4,5-Tetrachloro-6-cyanobenzoic acid, meth ester, reaction products with 2-		Data not available or insufficient for classification
methyl-1,3-benzenediamine and sodium methoxide		
Ethylbenzene		Data not available or insufficient for classification
Toluene		Data not available or insufficient for classification
Nickel, 5,5'-azobis-2,4,5(1H,3H,5H)-pyrimidinetrione complexes		Data not available or insufficient for classification
n-Butyl methacrylate		Data not available or insufficient for classification
Light aromatic solvent naphtha (petroleum)		Data not available or insufficient for classification
2,3-Epoxypropyl neodecanoate		Data not available or insufficient for classification

Germ Cell Mutagenicity

Name	Route	Value
Dipropylene glycol methyl ether acetate	In Vitro	Not mutagenic
Dipropylene glycol methyl ether acetate	In vivo	Not mutagenic
Butyl methacrylate-methyl methacrylate polymer		Data not available or insufficient for classification
1-Methoxy-2-propyl acetate	In Vitro	Not mutagenic
Cyclohexanone	In vivo	Not mutagenic
Cyclohexanone	In Vitro	Some positive data exist, but the data are not sufficient for classification
Vinyl polymer (NJ TSR # 04499600-5238P)		Data not available or insufficient for classification
Organic pigment (NJ TSR # 04499600-5230P)	In Vitro	Not mutagenic
3-Dodecyl-1-(2,2,6,6-tetramethyl-4-piperidinyl) -2,5-pyrrolidinedione		Data not available or insufficient for classification
2,3,4,5-Tetrachloro-6-cyanobenzoic acid, meth ester, reaction products with 2-		Data not available or insufficient for classification
methyl-1,3-benzenediamine and sodium methoxide		
Ethylbenzene	In vivo	Not mutagenic
Ethylbenzene	In Vitro	Some positive data exist, but the data are not
		sufficient for classification
Toluene	In Vitro	Not mutagenic
Toluene	In vivo	Not mutagenic
Nickel, 5,5'-azobis-2,4,5(1H,3H,5H)-pyrimidinetrione complexes		Data not available or insufficient for classification
n-Butyl methacrylate	In Vitro	Not mutagenic
n-Butyl methacrylate	In vivo	Not mutagenic
Light aromatic solvent naphtha (petroleum)		Data not available or insufficient for classification
2,3-Epoxypropyl neodecanoate		Data not available or insufficient for classification

Carcinogenicity

eur emogemeny			
Name	Route	Species	Value
Dipropylene glycol methyl ether acetate			Data not available or insufficient for classification
Butyl methacrylate-methyl methacrylate polymer			Data not available or insufficient for classification
1-Methoxy-2-propyl acetate			Data not available or insufficient for classification
Cyclohexanone	Ingestion	Multiple	Some positive data exist, but the data are not

Page 10 of 17

		animal species	sufficient for classification
Vinyl polymer (NJ TSR # 04499600-5238P)			Data not available or insufficient for classification
Organic pigment (NJ TSR # 04499600-5230P)			Data not available or insufficient for classification
3-Dodecyl-1-(2,2,6,6-tetramethyl-4-piperidinyl) -2,5- pyrrolidinedione			Data not available or insufficient for classification
2,3,4,5-Tetrachloro-6-cyanobenzoic acid, meth ester, reaction products with 2-methyl-1,3-benzenediamine and sodium methoxide			Data not available or insufficient for classification
Ethylbenzene	Inhalation	Multiple animal species	Carcinogenic
Toluene	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
Toluene	Ingestion	Rat	Some positive data exist, but the data are not sufficient for classification
Toluene	Inhalation	Mouse	Some positive data exist, but the data are not sufficient for classification
Nickel, 5,5'-azobis-2,4,5(1H,3H,5H)-pyrimidinetrione complexes	Not Specified	similar compou nds	Carcinogenic
n-Butyl methacrylate			Data not available or insufficient for classification
Light aromatic solvent naphtha (petroleum)	Inhalation	Mouse	Some positive data exist, but the data are not sufficient for classification
2,3-Epoxypropyl neodecanoate			Data not available or insufficient for classification

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test Result	Exposure Duration
Dipropylene glycol methyl ether acetate	Ingestion	Not toxic to male reproduction	Rat	NOAEL 1,000 mg/kg/day	4 weeks
Butyl methacrylate-methyl methacrylate polymer		Data not available or insufficient for classification			
1-Methoxy-2-propyl acetate	Ingestion	Not toxic to female reproduction	Rat	NOAEL 1,000 mg/kg/day	premating & during gestation
1-Methoxy-2-propyl acetate	Ingestion	Not toxic to male reproduction	Rat	NOAEL 1,000 mg/kg/day	premating & during gestation
1-Methoxy-2-propyl acetate	Ingestion	Not toxic to development	Rat	NOAEL 1,000 mg/kg/day	premating & during gestation
1-Methoxy-2-propyl acetate	Inhalation	Not toxic to development	Rat	NOAEL 21.6 mg/l	during organogenesi s
Cyclohexanone	Inhalation	Not toxic to female reproduction	Rat	NOAEL 4 mg/l	2 generation
Cyclohexanone	Inhalation	Some positive male reproductive data exist, but the data are not sufficient for classification	Rat	NOAEL 2 mg/l	2 generation
Cyclohexanone	Ingestion	Some positive developmental data exist, but the data are not sufficient for classification	Mouse	LOAEL 1,100 mg/kg/day	during organogenesi s
Cyclohexanone	Inhalation	Some positive developmental data exist, but the data are not sufficient for classification	Rat	NOAEL 2 mg/l	2 generation
Vinyl polymer (NJ TSR # 04499600- 5238P)		Data not available or insufficient for classification			
Organic pigment (NJ TSR # 04499600-5230P)		Data not available or insufficient for classification			
3-Dodecyl-1-(2,2,6,6-tetramethyl-4-piperidinyl) -2,5-pyrrolidinedione		Data not available or insufficient for classification			
2,3,4,5-Tetrachloro-6-cyanobenzoic acid, meth ester, reaction products with 2-methyl- 1,3-benzenediamine and sodium methoxide		Data not available or insufficient for classification			

Ethylbenzene	Inhalation	Some positive developmental data exist, but the data are not sufficient for classification	Rat	NOAEL 4.3 mg/l	premating & during gestation
Toluene	Inhalation	Some positive female reproductive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	occupational exposure
Toluene	Inhalation	Some positive male reproductive data exist, but the data are not sufficient for classification	Rat	NOAEL 2.3 mg/l	1 generation
Toluene	Ingestion	Toxic to development	Rat	LOAEL 520 mg/kg/day	during gestation
Toluene	Inhalation	Toxic to development	Human	NOAEL Not available	poisoning and/or abuse
Nickel, 5,5'-azobis-2,4,5(1H,3H,5H)- pyrimidinetrione complexes		Data not available or insufficient for classification			
n-Butyl methacrylate	Inhalation	Not toxic to female reproduction	Rat	NOAEL 11 mg/l	28 days
n-Butyl methacrylate	Ingestion	Not toxic to male reproduction	Rat	NOAEL 1,000 mg/kg/day	44 days
n-Butyl methacrylate	Inhalation	Not toxic to male reproduction	Rat	NOAEL 11 mg/l	28 days
n-Butyl methacrylate	Ingestion	Some positive female reproductive data exist, but the data are not sufficient for classification	Rat	NOAEL 300 mg/kg/day	premating & during gestation
n-Butyl methacrylate	Ingestion	Some positive developmental data exist, but the data are not sufficient for classification	Rabbit	NOAEL 300 mg/kg/day	during gestation
n-Butyl methacrylate	Inhalation	Some positive developmental data exist, but the data are not sufficient for classification	Rat	NOAEL 1.8 mg/l	during gestation
Light aromatic solvent naphtha (petroleum)	Inhalation	Not toxic to female reproduction	Rat	NOAEL 1,500 ppm	2 generation
Light aromatic solvent naphtha (petroleum)	Inhalation	Not toxic to male reproduction	Rat	NOAEL 1,500 ppm	2 generation
Light aromatic solvent naphtha (petroleum)	Inhalation	Some positive developmental data exist, but the data are not sufficient for classification	Rat	NOAEL 500 ppm	2 generation
2,3-Epoxypropyl neodecanoate		Data not available or insufficient for classification			

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Dipropylene glycol methyl ether acetate			Data not available or insufficient for classification			
Butyl methacrylate-methyl methacrylate polymer			Data not available or insufficient for classification			
1-Methoxy-2-propyl acetate	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification		NOAEL Not available	
Cyclohexanone	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Guinea pig	LOAEL 16.1 mg/l	6 hours
Cyclohexanone	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
Vinyl polymer (NJ TSR # 04499600-5238P)			Data not available or insufficient for classification			
Organic pigment (NJ TSR # 04499600-5230P)			Data not available or insufficient for classification			
3-Dodecyl-1-(2,2,6,6- tetramethyl-4-piperidinyl) - 2,5-pyrrolidinedione			Data not available or insufficient for classification			
2,3,4,5-Tetrachloro-6- cyanobenzoic acid, meth			Data not available or insufficient for classification			

Page 12 of 17

ester, reaction products						
with 2-methyl-1,3-						
benzenediamine and						
sodium methoxide	T 1 1	. 1		**	NOAEL Not	
Ethylbenzene	Inhalation	central nervous	May cause drowsiness or	Human	11011221101	
T.4. 11	7.1.1.1	system depression	dizziness	**	available	
Ethylbenzene	Inhalation	respiratory irritation	Some positive data exist, but the	Human	NOAEL Not	
			data are not sufficient for classification	and animal	available	
Toluene	Inhalation	central nervous		Human	NOAEL Not	
Toluene	Innalation		May cause drowsiness or	Human		
T. 1	T 1 1 1	system depression	dizziness	**	available NOAEL Not	
Toluene	Inhalation	respiratory irritation	Some positive data exist, but the	Human		
			classification		available	
Toluene	Inhalation	immune system	Some positive data exist, but the	Mouse	NOAEL	3 hours
			data are not sufficient for		0.004 mg/l	
			classification			
Toluene	Ingestion	central nervous	May cause drowsiness or	Human	NOAEL Not	poisoning
		system depression	dizziness		available	and/or abuse
Nickel, 5,5'-azobis-			Data not available or insufficient			
2,4,5(1H,3H,5H)-			for classification			
pyrimidinetrione						
complexes						
n-Butyl methacrylate	Inhalation	respiratory irritation	May cause respiratory irritation		NOAEL Not	
					available	
Light aromatic solvent	Inhalation	central nervous	May cause drowsiness or		NOAEL Not	
naphtha (petroleum)		system depression	dizziness		available	
Light aromatic solvent	Inhalation	respiratory irritation	Some positive data exist, but the		NOAEL Not	
naphtha (petroleum)			data are not sufficient for		available	
			classification			
Light aromatic solvent	Ingestion	central nervous	May cause drowsiness or		NOAEL Not	
naphtha (petroleum)		system depression	dizziness		available	
2,3-Epoxypropyl			Data not available or insufficient			
neodecanoate			for classification			

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Dipropylene glycol methyl ether acetate	Ingestion	liver	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 1,000 mg/kg/day	4 weeks
Dipropylene glycol methyl ether acetate	Ingestion	heart endocrine system hematopoietic system kidney and/or bladder	All data are negative	Rat	NOAEL 1,000 mg/kg/day	4 weeks
Butyl methacrylate-methyl methacrylate polymer			Data not available or insufficient for classification			
1-Methoxy-2-propyl acetate	Inhalation	kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 16.2 mg/l	9 days
1-Methoxy-2-propyl acetate	Inhalation	olfactory system	Some positive data exist, but the data are not sufficient for classification		NOAEL Not available	
1-Methoxy-2-propyl acetate	Inhalation	blood	All data are negative	Multiple animal species	NOAEL 16.2 mg/l	9 days
1-Methoxy-2-propyl acetate	Ingestion	endocrine system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 1,000 mg/kg/day	44 days
Cyclohexanone	Inhalation	liver kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rabbit	NOAEL 0.76 mg/l	50 days
Cyclohexanone	Ingestion	liver	Some positive data exist, but the data are not sufficient for classification	Mouse	NOAEL 4,800 mg/kg/day	90 days
Vinyl polymer (NJ TSR #			Data not available or insufficient			

D 42 0 4

04499600-5238P)			for classification			
Organic pigment (NJ TSR			Data not available or insufficient			
# 04499600-5230P)			for classification			
3-Dodecyl-1-(2,2,6,6-			Data not available or insufficient			
tetramethyl-4-piperidinyl)			for classification			
-2,5-pyrrolidinedione			Data not available and CC 1	-		
2,3,4,5-Tetrachloro-6- cyanobenzoic acid, meth			Data not available or insufficient for classification			
ester, reaction products			101 Classification			
with 2-methyl-1,3-						
benzenediamine and						
sodium methoxide						
Ethylbenzene	Inhalation	kidney and/or	Some positive data exist, but the	Rat	NOAEL 1.1	2 years
		bladder	data are not sufficient for		mg/l	
	1		classification			
Ethylbenzene	Inhalation	liver	Some positive data exist, but the	Mouse	NOAEL 1.1	103 weeks
			data are not sufficient for classification		mg/l	
Ethylbenzene	Inhalation	hematopoietic	Some positive data exist, but the	Rat	NOAEL 3.4	28 days
Eurytoenzene	Illiaiation	system	data are not sufficient for	Kat	mg/l	26 days
	1	2,500	classification			
Ethylbenzene	Inhalation	auditory system	Some positive data exist, but the	Rat	NOAEL 2.4	5 days
•	1		data are not sufficient for		mg/l	_
	1		classification			
Ethylbenzene	Inhalation	endocrine system	Some positive data exist, but the	Mouse	NOAEL 3.3	103 weeks
	1		data are not sufficient for		mg/l	
Ethylbenzene	Inhalation	hone t	classification	M ₃₋₁₄ !. 1	NOAEL 4.2	00 4
Etnylbenzene	Innalation	bone, teeth, nails, and/or hair	All data are negative	Multiple animal	NOAEL 4.2	90 days
		muscles		species	mg/l	
Ethylbenzene	Inhalation	heart immune	All data are negative	Multiple	NOAEL 3.3	2 years
		system respiratory		animal	mg/l	
		system		species		
Ethylbenzene	Ingestion	liver kidney and/or	Some positive data exist, but the	Rat	NOAEL 680	6 months
		bladder	data are not sufficient for		mg/kg/day	
	<u> </u>		classification			
Toluene	Inhalation	auditory system	Causes damage to organs	Human	NOAEL Not	poisoning
		nervous system	through prolonged or repeated		available	and/or abuse
		eyes olfactory system	exposure			
Toluene	Inhalation	respiratory system	Some positive data exist, but the	Rat	LOAEL 2.3	15 months
Totache	Illialation	respiratory system	data are not sufficient for	Kat	mg/l	13 months
			classification		8	
Toluene	Inhalation	heart liver kidney	Some positive data exist, but the	Rat	NOAEL 11.3	15 weeks
		and/or bladder	data are not sufficient for		mg/l	
			classification			
Toluene	Inhalation	endocrine system	Some positive data exist, but the	Rat	NOAEL 1.1	4 weeks
			data are not sufficient for		mg/l	
Tolyona	Imb al-4:	immum a at	classification	Movee	NOAEL N-4	20 day
Toluene	Inhalation	immune system	Some positive data exist, but the data are not sufficient for	Mouse	NOAEL Not available	20 days
	1		classification		avanable	
Toluene	Inhalation	bone, teeth, nails,	Some positive data exist, but the	Mouse	NOAEL 1.1	8 weeks
Lordon	Immanation	and/or hair	data are not sufficient for	1,10050	mg/l	O WEEKS
	1		classification		5	
Toluene	Inhalation	hematopoietic	Some positive data exist, but the	Human	NOAEL Not	occupational
	1	system vascular	data are not sufficient for		available	exposure
	1	system	classification			
Toluene	Ingestion	nervous system	Some positive data exist, but the	Rat	NOAEL 625	13 weeks
	1		data are not sufficient for		mg/kg/day	
Tolyona	Inct	hoout	classification	Dot	NOAEI	121
Toluene	Ingestion	heart	Some positive data exist, but the	Rat	NOAEL	13 weeks
			data are not sufficient for classification		2,500 mg/kg/day	
			I CIASSILICATION	1	mg/kg/dav	1
Toluene	Ingestion	liver kidney and/or		Multiple		13 weeks
Toluene	Ingestion	liver kidney and/or bladder	Some positive data exist, but the	Multiple animal	NOAEL	13 weeks
Toluene	Ingestion	liver kidney and/or bladder		Multiple animal species		13 weeks

		system	data are not sufficient for classification		mg/kg/day	
Toluene	Ingestion	endocrine system	Some positive data exist, but the data are not sufficient for classification	Mouse	NOAEL 105 mg/kg/day	28 days
Toluene	Ingestion	immune system	Some positive data exist, but the data are not sufficient for classification	Mouse	NOAEL 105 mg/kg/day	4 weeks
Nickel, 5,5'-azobis- 2,4,5(1H,3H,5H)- pyrimidinetrione complexes			Data not available or insufficient for classification			
n-Butyl methacrylate	Inhalation	kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 11 mg/l	28 days
n-Butyl methacrylate	Inhalation	olfactory system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 1.8 mg/l	28 days
n-Butyl methacrylate	Inhalation	heart endocrine system hematopoietic system liver nervous system respiratory system	All data are negative	Rat	NOAEL 11 mg/l	28 days
n-Butyl methacrylate	Ingestion	olfactory system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 60 mg/kg/day	90 days
n-Butyl methacrylate	Ingestion	endocrine system hematopoietic system liver nervous system kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 360 mg/kg/day	90 days
n-Butyl methacrylate	Ingestion	heart immune system	All data are negative	Rat	NOAEL 360 mg/kg/day	90 days
Light aromatic solvent naphtha (petroleum)			Data not available or insufficient for classification			
2,3-Epoxypropyl neodecanoate			Data not available or insufficient for classification			

Aspiration Hazard

Name	Value
Dipropylene glycol methyl ether acetate	Not an aspiration hazard
Butyl methacrylate-methyl methacrylate polymer	Not an aspiration hazard
1-Methoxy-2-propyl acetate	Not an aspiration hazard
Cyclohexanone	Not an aspiration hazard
Vinyl polymer (NJ TSR # 04499600-5238P)	Not an aspiration hazard
Organic pigment (NJ TSR # 04499600-5230P)	Not an aspiration hazard
3-Dodecyl-1-(2,2,6,6-tetramethyl-4-piperidinyl) -2,5-pyrrolidinedione	Not an aspiration hazard
2,3,4,5-Tetrachloro-6-cyanobenzoic acid, meth ester, reaction products with 2-methyl-	Not an aspiration hazard
1,3-benzenediamine and sodium methoxide	
Ethylbenzene	Aspiration hazard
Toluene	Aspiration hazard
Nickel, 5,5'-azobis-2,4,5(1H,3H,5H)-pyrimidinetrione complexes	Not an aspiration hazard
n-Butyl methacrylate	Not an aspiration hazard
Light aromatic solvent naphtha (petroleum)	Aspiration hazard
2,3-Epoxypropyl neodecanoate	Not an aspiration hazard

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

Ecotoxicological information

Chemical fate information

SECTION 13: Disposal considerations

13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Incinerate in a permitted waste incineration facility. Combustion products will include halogen acid (HCl/HF/HBr). Facility must be capable of handling halogenated materials. As a disposal alternative, utilize an acceptable permitted waste disposal facility. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

EPA Hazardous Waste Number (RCRA): D001 (Ignitable)

SECTION 14: Transport Information

For Transport Information, please visit http://3M.com/Transportinfo or call 1-800-364-3577 or 651-737-6501.

SECTION 15: Regulatory information

15.1. US Federal Regulations

Contact 3M for more information.

311/312 Hazard Categories:

Fire Hazard - Yes Pressure Hazard - No Reactivity Hazard - No Immediate Hazard - Yes Delayed Hazard - Yes

Section 313 Toxic Chemicals subject to the reporting requirements of that section and 40 CFR part 372 (EPCRA):

<u>Ingredient</u>	<u>C.A.S. No</u>	% by Wt
Ethylbenzene	100-41-4	< 0.3
Nickel, 5,5'-azobis-2,4,5(1H,3H,5H)-	68511-62-6	< 0.3
pyrimidinetrione complexes (NICKEL		
COMPOUNDS)		

15.2. State Regulations

Contact 3M for more information.

This product does not require warnings under California Proposition 65.

15.3. Chemical Inventories

The components of this product are in compliance with the chemical notification requirements of TSCA.

Contact 3M for more information.

15.4. International Regulations

Contact 3M for more information.

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 16: Other information

NFPA Hazard Classification

Health: 2 Flammability: 2 Instability: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Document Group:32-6625-1Version Number:1.00Issue Date:10/03/13Supercedes Date:Initial Issue

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M

3M USA SDSs are available at www.3M.com