



Safety Data Sheet

Copyright, 2016, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document Group:	32-4070-2	Version Number:	3.00
Issue Date:	04/26/16	Supersedes Date:	09/22/14

SECTION 1: Identification

1.1. Product identifier

3M Scotchkote Epoxy Ceramic Surfacer CR 511 (N) Pt B

Product Identification Numbers

GR-2001-4398-4, GR-2001-4399-2

1.2. Recommended use and restrictions on use

Recommended use

Coating, Ceramic fluid flow coating.

1.3. Supplier's details

MANUFACTURER:	3M
DIVISION:	3M United Kingdom Electrical Markets Division
ADDRESS:	3M Center, St. Paul, MN 55144-1000, USA
Telephone:	1-888-3M HELPS (1-888-364-3577)

1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

SECTION 2: Hazard identification

2.1. Hazard classification

Acute Toxicity (oral): Category 4.
Acute Toxicity (inhalation): Category 4.
Serious Eye Damage/Irritation: Category 1.
Skin Corrosion/Irritation: Category 1B.
Skin Sensitizer: Category 1.
Reproductive Toxicity: Category 2.
Specific Target Organ Toxicity (central nervous system): Category 3.
Specific Target Organ Toxicity (repeated exposure): Category 2.

2.2. Label elements

Signal word

Danger

Symbols

Corrosion | Exclamation mark | Health Hazard |

Pictograms



Hazard Statements

Harmful if swallowed.
Causes severe skin burns and eye damage.
May cause an allergic skin reaction.
Harmful if inhaled.
May cause drowsiness or dizziness.
Suspected of damaging fertility or the unborn child.

May cause damage to organs through prolonged or repeated exposure:
liver |
musculoskeletal system |

Precautionary Statements

Prevention:

Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Do not breathe dust/fume/gas/mist/vapors/spray.
Use only outdoors or in a well-ventilated area.
Wear protective gloves, protective clothing, and eye/face protection.
Do not eat, drink or smoke when using this product.
Wash thoroughly after handling.
Contaminated work clothing must not be allowed out of the workplace.

Response:

IF INHALED: Remove person to fresh air and keep comfortable for breathing.
IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
Immediately call a POISON CENTER or doctor/physician.
If skin irritation or rash occurs: Get medical advice/attention.
Wash contaminated clothing before reuse.
IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
IF exposed or concerned: Get medical advice/attention.
Specific treatment (see Notes to Physician on this label).
Get medical advice/attention if you feel unwell.

Storage:

Store in a well-ventilated place. Keep container tightly closed.
Store locked up.

Disposal:

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

2.3. Hazards not otherwise classified

May cause chemical gastrointestinal burns. Persons previously sensitized to amines may develop a cross-sensitization

reaction to certain other amines.

71% of the mixture consists of ingredients of unknown acute dermal toxicity.

46% of the mixture consists of ingredients of unknown acute inhalation toxicity.

SECTION 3: Composition/information on ingredients

Ingredient	C.A.S. No.	% by Wt
BENZYL ALCOHOL	100-51-6	30 - 60 Trade Secret *
FORMALDEHYDE, POLYMER WITH BENZENEAMINE, HYDROGENATED	135108-88-2	20 - 30 Trade Secret *
FORMALDEHYDE-PHENOL-M-XYLYLENEDIAMINE COPOLYMER	57214-10-5	10 - 20 Trade Secret *
M-PHENYLENEBIS(METHYLAMINE)	1477-55-0	5 - 15 Trade Secret *
4,4-METHYLENEBIS(2-METHYLCYCLOHEXYLAMINE)	1761-71-3	1 - 5 Trade Secret *
SALICYLIC ACID	69-72-7	1 - 5 Trade Secret *

*The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:

Immediately flush with large amounts of water for at least 15 minutes. Remove contaminated clothing. Get immediate medical attention. Wash clothing before reuse.

Eye Contact:

Immediately flush with large amounts of water for at least 15 minutes. Remove contact lenses if easy to do. Continue rinsing. Immediately get medical attention.

If Swallowed:

Rinse mouth. Do not induce vomiting. Get immediate medical attention.

4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1. Information on toxicological effects.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable.

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products

Substance

Carbon monoxide
Carbon dioxide
Oxides of Nitrogen

Condition

During Combustion
During Combustion
During Combustion

5.3. Special protective actions for fire-fighters

No special protective actions for fire-fighters are anticipated.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and SDS. Seal the container. Dispose of collected material as soon as possible.

SECTION 7: Handling and storage**7.1. Precautions for safe handling**

For industrial or professional use only. Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.) Use personal protective equipment (gloves, respirators, etc.) as required.

7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep container tightly closed to prevent contamination with water or air. If contamination is suspected, do not reseal container. Store away from acids. Store away from strong bases. Store away from oxidizing agents. Store away from areas where product may come into contact with food or pharmaceuticals. Store away from amines.

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****Occupational exposure limits**

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
BENZYL ALCOHOL	100-51-6	AIHA	TWA:44.2 mg/m3(10 ppm)	
M-PHENYLENEBIS(METHYLAMINE)	1477-55-0	ACGIH	CEIL:0.1 mg/m3	Skin Notation

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines
OSHA : United States Department of Labor - Occupational Safety and Health Administration
TWA: Time-Weighted-Average
STEL: Short Term Exposure Limit
CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Full Face Shield
Indirect Vented Goggles

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity. Gloves made from the following material(s) are recommended: Butyl Rubber
Polymer laminate

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron – Butyl rubber
Apron - polymer laminate

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

General Physical Form:	Liquid
Odor, Color, Grade:	Ammonia Odor, Amber Color
Odor threshold	No Data Available
pH	> 8 [Details: Alkaline]
Melting point	Not Applicable
Boiling Point	107.22 - 222 °C
Flash Point	>=104 °C [Test Method: Closed Cup]
Evaporation rate	No Data Available
Flammability (solid, gas)	Not Applicable
Flammable Limits(LEL)	No Data Available

Flammable Limits(UEL)	No Data Available
Vapor Pressure	0.7 - 7.5 mmHg [@ 25 °C]
Vapor Density	No Data Available
Density	1.080 g/ml
Specific Gravity	1.080 [Ref Std: WATER=1]
Solubility In Water	0 %
Solubility- non-water	No Data Available
Partition coefficient: n-octanol/ water	No Data Available
Autoignition temperature	No Data Available
Decomposition temperature	No Data Available
Viscosity	No Data Available
Volatile Organic Compounds	70 g/l - 76 g/l [Test Method: tested per EPA method 24] [Details: (Parts A and B mixed)]

SECTION 10: Stability and reactivity

10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Avoid curing large quantities of material to prevent a premature reaction (exotherm) with production of intense heat and smoke.

10.5. Incompatible materials

Amines

Reaction with water, alcohols, and amines is not hazardous if container can vent to the atmosphere to prevent pressure buildup.

Strong acids

Strong bases

Strong oxidizing agents

10.6. Hazardous decomposition products

Substance

None known.

Condition

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

Harmful if inhaled. Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

May cause additional health effects (see below).

Skin Contact:

Corrosive (Skin Burns): Signs/symptoms may include localized redness, swelling, itching, intense pain, blistering, ulceration, and tissue destruction.

Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye Contact:

Corrosive (Eye Burns): Signs/symptoms may include cloudy appearance of the cornea, chemical burns, severe pain, tearing, ulcerations, significantly impaired vision or complete loss of vision.

Ingestion:

Harmful if swallowed. Gastrointestinal Corrosion: Signs/symptoms may include severe mouth, throat and abdominal pain; nausea; vomiting; and diarrhea; blood in the feces and/or vomitus may also be seen.

May cause additional health effects (see below).

Additional Health Effects:

Single exposure may cause target organ effects:

Central Nervous System (CNS) Depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness.

Prolonged or repeated exposure may cause target organ effects:

Liver Effects: Signs/symptoms may include loss of appetite, weight loss, fatigue, weakness, abdominal tenderness and jaundice.

Muscular Effects: Signs/symptoms may include generalized muscle weakness, paralysis and atrophy.

Reproductive/Developmental Toxicity:

Contains a chemical or chemicals which can cause birth defects or other reproductive harm.

Additional Information:

Persons previously sensitized to amines may develop a cross-sensitization reaction to certain other amines.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE > 5,000 mg/kg
Overall product	Inhalation-Dust/Mist(4 hr)		No data available; calculated ATE 1 - 5 mg/l
Overall product	Ingestion		No data available; calculated ATE 300 - 2,000 mg/kg
BENZYL ALCOHOL	Inhalation-Dust/Mist	Rat	LC50 8.8 mg/l

	(4 hours)		
BENZYL ALCOHOL	Ingestion	Rat	LD50 1,230 mg/kg
M-PHENYLENEBIS(METHYLAMINE)	Dermal	Rabbit	LD50 > 2,000 mg/kg
M-PHENYLENEBIS(METHYLAMINE)	Inhalation-Dust/Mist (4 hours)	Rat	LC50 1.2 mg/l
M-PHENYLENEBIS(METHYLAMINE)	Ingestion	Rat	LD50 980 mg/kg
4,4-METHYLENEBIS(2-METHYLCYCLOHEXYLAMINE)	Dermal	Rabbit	LD50 2,110 mg/kg
4,4-METHYLENEBIS(2-METHYLCYCLOHEXYLAMINE)	Ingestion	Rat	LD50 350 mg/kg
SALICYLIC ACID	Dermal	Rat	LD50 > 2,000 mg/kg
SALICYLIC ACID	Ingestion	Rat	LD50 891 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
BENZYL ALCOHOL	Multiple animal species	Mild irritant
M-PHENYLENEBIS(METHYLAMINE)	Rat	Corrosive
4,4-METHYLENEBIS(2-METHYLCYCLOHEXYLAMINE)	Rabbit	Corrosive
SALICYLIC ACID	Rabbit	No significant irritation

Serious Eye Damage/Irritation

Name	Species	Value
BENZYL ALCOHOL	Rabbit	Severe irritant
M-PHENYLENEBIS(METHYLAMINE)	Rabbit	Corrosive
4,4-METHYLENEBIS(2-METHYLCYCLOHEXYLAMINE)	Rabbit	Corrosive
SALICYLIC ACID	Rabbit	Corrosive

Skin Sensitization

Name	Species	Value
BENZYL ALCOHOL	Human and animal	Some positive data exist, but the data are not sufficient for classification
M-PHENYLENEBIS(METHYLAMINE)	Guinea pig	Sensitizing
4,4-METHYLENEBIS(2-METHYLCYCLOHEXYLAMINE)	Guinea pig	Sensitizing
SALICYLIC ACID	Mouse	Not sensitizing

Photosensitization

Name	Species	Value
SALICYLIC ACID	Mouse	Not sensitizing

Respiratory Sensitization

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
BENZYL ALCOHOL	In vivo	Not mutagenic
BENZYL ALCOHOL	In Vitro	Some positive data exist, but the data are not sufficient for classification
M-PHENYLENEBIS(METHYLAMINE)	In Vitro	Not mutagenic
M-PHENYLENEBIS(METHYLAMINE)	In vivo	Not mutagenic
SALICYLIC ACID	In Vitro	Not mutagenic
SALICYLIC ACID	In vivo	Not mutagenic

Carcinogenicity

Name	Route	Species	Value
BENZYL ALCOHOL	Ingestion	Multiple animal species	Not carcinogenic

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test Result	Exposure Duration
BENZYL ALCOHOL	Ingestion	Not toxic to development	Mouse	NOAEL 550 mg/kg/day	during organogenesis
M-PHENYLENEBIS(METHYLAMINE)	Ingestion	Not toxic to female reproduction	Rat	NOAEL 450 mg/kg/day	1 generation
M-PHENYLENEBIS(METHYLAMINE)	Ingestion	Not toxic to male reproduction	Rat	NOAEL 450 mg/kg	1 generation
M-PHENYLENEBIS(METHYLAMINE)	Ingestion	Not toxic to development	Rat	NOAEL 450 mg/kg/day	1 generation
SALICYLIC ACID	Ingestion	Toxic to development	Rat	NOAEL 75 mg/kg/day	during organogenesis

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
BENZYL ALCOHOL	Inhalation	central nervous system depression	May cause drowsiness or dizziness		NOAEL Not available	
BENZYL ALCOHOL	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification		NOAEL Not available	
BENZYL ALCOHOL	Ingestion	central nervous system depression	May cause drowsiness or dizziness		NOAEL Not available	
M-PHENYLENEBIS(METHYLAMINE)	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Not available	NOAEL Not available	
4,4-METHYLENEBIS(2-METHYLCYCLOHEXYLAMINE)	Inhalation	respiratory irritation	May cause respiratory irritation	similar health hazards	NOAEL Not available	

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
BENZYL ALCOHOL	Ingestion	endocrine system muscles kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 400 mg/kg/day	13 weeks
BENZYL ALCOHOL	Ingestion	nervous system respiratory system	Some positive data exist, but the data are not sufficient for classification	Mouse	NOAEL 645 mg/kg/day	8 days
M-PHENYLENEBIS(METHYLAMINE)	Ingestion	endocrine system blood bone marrow	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 600 mg/kg/day	28 days
4,4-METHYLENEBIS(2-METHYLCYCLOHEXYLAMINE)	Ingestion	liver muscles	May cause damage to organs though prolonged or repeated exposure	Rat	NOAEL 15 mg/kg/day	36 days
SALICYLIC ACID	Ingestion	liver	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 500 mg/kg/day	3 days

Aspiration Hazard

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

Ecotoxicological information

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

Chemical fate information

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

SECTION 13: Disposal considerations

13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of waste product in a permitted industrial waste facility. As a disposal alternative, incinerate in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

EPA Hazardous Waste Number (RCRA): Not regulated

SECTION 14: Transport Information

For Transport Information, please visit <http://3M.com/Transportinfo> or call 1-800-364-3577 or 651-737-6501.

SECTION 15: Regulatory information

15.1. US Federal Regulations

Contact 3M for more information.

311/312 Hazard Categories:

Fire Hazard - Yes Pressure Hazard - No Reactivity Hazard - No Immediate Hazard - Yes Delayed Hazard - Yes

15.2. State Regulations

Contact 3M for more information.

15.3. Chemical Inventories

The components of this material are in compliance with the provisions of Australia National Industrial Chemical Notification and Assessment Scheme (NICNAS). Certain restrictions may apply. Contact the selling division for additional information.

The components of this material are in compliance with the China "Measures on Environmental Management of New Chemical Substance". Certain restrictions may apply. Contact the selling division for additional information.

The components of this material are in compliance with the provisions of the Korean Toxic Chemical Control Law. Certain restrictions may apply. Contact the selling division for additional information.

The components of this product are in compliance with the chemical notification requirements of TSCA.

Contact 3M for more information.

15.4. International Regulations

Contact 3M for more information.

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 16: Other information

NFPA Hazard Classification

Health: 4 **Flammability:** 2 **Instability:** 0 **Special Hazards:** None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Document Group: 32-4070-2

Issue Date: 04/26/16

Version Number: 3.00

Supersedes Date:

3.00

09/22/14

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M

3M USA SDSs are available at www.3M.com