

Safety Data Sheet

Copyright, 2016, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

 Document Group:
 23-2914-2
 Version Number:
 6.00

 Issue Date:
 02/25/16
 Supercedes Date:
 06/01/15

SECTION 1: Identification

1.1. Product identifier

3MTM ESPETM ADPERTM EASY ONE VIAL

Product Identification Numbers

70 - 2011 - 3187 - 0, 70 - 2011 - 3188 - 8, 70 - 2011 - 3189 - 6, 70 - 2011 - 3193 - 8, 70 - 2011 - 3194 - 6, 70 - 2011 - 3195 - 3 - 2011 - 3195 - 2011 - 3195 - 2011 - 3195 - 2011 - 3195 - 2011 - 3195 - 2011 - 3195 - 2011 - 3195 - 2011 - 3195 - 2011 - 3195 - 201

1.2. Recommended use and restrictions on use

Recommended use

Dental Product, Dental Adhesive

Restrictions on use

For use only by dental professionals.

1.3. Supplier's details

MANUFACTURER: 3M

DIVISION: Oral Care Solutions Division

ADDRESS: 3M Center, St. Paul, MN 55144-1000, USA **Telephone:** 1-888-3M HELPS (1-888-364-3577)

1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

SECTION 2: Hazard identification

This document has been prepared in accordance with the U.S. OSHA Hazard Communication Standard, which requires the inclusion of all known hazards of the product or ingredients regardless of the potential risk. The risks of the hazards communicated in this document may vary depending on the potential for exposure.

2.1. Hazard classification

Flammable Liquid: Category 3.

Serious Eye Damage/Irritation: Category 2A.

Skin Corrosion/Irritation: Category 2.

Skin Sensitizer: Category 1B.

Reproductive Toxicity: Category 2.

Specific Target Organ Toxicity (repeated exposure): Category 2.

2.2. Label elements

Page 1 of 12

Signal word

Warning

Symbols

Flame | Exclamation mark | Health Hazard |





Hazard Statements

Flammable liquid and vapor.

Causes serious eye irritation.

Causes skin irritation.

May cause an allergic skin reaction.

Suspected of damaging fertility or the unborn child.

May cause damage to organs through prolonged or repeated exposure: respiratory system |

Precautionary Statements

Prevention:

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

 $Keep\ away\ from\ heat/sparks/open\ flames/hot\ surfaces.\ -\ No\ smoking.$

Keep container tightly closed.

Use explosion-proof electrical/ventilating/lighting equipment.

Do not breathe dust/fume/gas/mist/vapors/spray.

Wear protective gloves and eye/face protection.

Wear eye/face protection.

Wear protective gloves.

Wash thoroughly after handling.

Contaminated work clothing must not be allowed out of the workplace.

Response:

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

If eye irritation persists: Get medical advice/attention.

If skin irritation or rash occurs: Get medical advice/attention.

If skin irritation occurs: Get medical advice/attention.

Take off contaminated clothing and wash it before reuse.

IF exposed or concerned: Get medical advice/attention.

In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

Storage:

Store in a well-ventilated place. Keep cool.

Disposal:

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

Page 2 **of** 12

2.3. Hazards not otherwise classified

None.

11% of the mixture consists of ingredients of unknown acute oral toxicity.

11% of the mixture consists of ingredients of unknown acute dermal toxicity.

SECTION 3: Composition/information on ingredients

Ingredient	C.A.S. No.	% by Wt
2-HYDROXYETHYL METHACRYLATE	868-77-9	15 - 25 Trade Secret *
BISPHENOL A DIGLYCIDYL ETHER	1565-94-2	15 - 25 Trade Secret *
DIMETHACRYLATE (BISGMA)		
ETHANOL	64-17-5	10 - 15 Trade Secret *
WATER	7732-18-5	10 - 15 Trade Secret *
PHOSPHORIC ACIDS-6-METHACRYLOXY-	None	5 - 15 Trade Secret *
HEXYLESTERS		
1,6-HEXANEDIOL DIMETHACRYLATE	6606-59-3	5 - 10 Trade Secret *
METHACRYLOXYPROPYLTRIMETHOXYSILANE	2530-85-0	1 - 10 Trade Secret *
Synthetic amorphous silica, fumed, crystalline-free	112945-52-5	1 - 10 Trade Secret *
(DIMETHYLAMINO)ETHYL METHACRYLATE	2867-47-2	1 - 5 Trade Secret *
COPOLYMER OF ACRYLIC AND ITACONIC ACID	25948-33-8	1 - 5 Trade Secret *
2,4,6-	75980-60-8	1 - 3 Trade Secret *
TRIMETHYLBENZOYLDIPHENYLPHOSPHINE		
OXIDE		
CAMPHORQUINONE	10373-78-1	1 - 3 Trade Secret *

^{*}The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye Contact:

Immediately flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. Get medical attention.

If Swallowed:

Rinse mouth. Do not induce vomiting. Get immediate medical attention.

4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1. Information on toxicological effects.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

5.2. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode.

Hazardous Decomposition or By-Products

Condition Substance

Carbon monoxide **During Combustion** Carbon dioxide **During Combustion** Irritant Vapors or Gases **During Combustion**

5.3. Special protective actions for fire-fighters

Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapors in the spill area to burn or explode. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Contain spill. Collect as much of the spilled material as possible using non-sparking tools. Place in a metal container approved for transportation by appropriate authorities. Clean up residue with detergent and water. Seal the container. Dispose of collected material as soon as possible.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

A no-touch technique is recommended. If skin contact occurs, wash skin with soap and water. Acrylates may penetrate commonly-used gloves. If product contacts glove, remove and discard glove, wash hands immediately with soap and water and then re-glove. Do not breathe dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.) Use personal protective equipment (gloves, respirators, etc.) as required. To minimize the risk of ignition, determine applicable electrical classifications for the process using this product and select specific local exhaust ventilation equipment to avoid flammable vapor accumulation.

7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store away from heat. Store away from acids. Store away from oxidizing agents.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
SILICA, AMORPHOUS	112945-52-	OSHA	TWA concentration:0.8	
	5		mg/m3;TWA:20 millions of	
			particles/cu. ft.	
ETHANOL	64-17-5	ACGIH	STEL:1000 ppm	A3: Confirmed animal
				carcin.
ETHANOL	64-17-5	OSHA	TWA:1900 mg/m3(1000 ppm)	

ACGIH: American Conference of Governmental Industrial Hygienists

AIHA: American Industrial Hygiene Association

CMRG: Chemical Manufacturer's Recommended Guidelines

OSHA: United States Department of Labor - Occupational Safety and Health Administration

TWA: Time-Weighted-Average STEL: Short Term Exposure Limit

CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Use in a well-ventilated area.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Safety Glasses with side shields

Skin/hand protection

See Section 7.1 for additional information on skin protection.

Respiratory protection

None required.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

General Physical Form: Liquid

Specific Physical Form: Viscous Liquid

Odor, Color, Grade: Characteristic odor, yellow

Odor thresholdNo Data AvailablepHNot ApplicableMelting pointNo Data Available

Boiling Point >= 78 °C

Flash Point 34 °C [Test Method: Closed Cup]

Evaporation rateNo Data AvailableFlammability (solid, gas)Not ApplicableFlammable Limits(LEL)No Data AvailableFlammable Limits(UEL)No Data AvailableVapor Pressure<= 15 mmHg</th>Vapor DensityNo Data Available

Page 5 of 12

3MTM ESPETM ADPERTM EASY ONE VIAL 02/25/16

Density 1 - 1.2 g/cm3

1 - 1.2 [*Ref Std*: WATER=1] **Specific Gravity**

Solubility in Water Appreciable No Data Available Solubility- non-water Partition coefficient: n-octanol/ water No Data Available No Data Available **Autoignition temperature Decomposition temperature** No Data Available Molecular weight No Data Available

SECTION 10: Stability and reactivity

10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Heat

10.5. Incompatible materials

None known.

10.6. Hazardous decomposition products

Substance Condition

None known.

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

This document has been prepared in accordance with the U.S. OSHA Hazard Communication Standard, which requires the inclusion of all known hazards of the product or ingredients regardless of the potential risk. The risks of the hazards communicated in this document may vary depending on the potential for exposure.

The information below represents toxicological information associated with the individual components of the uncured product. Once properly mixed and/or cured, the product is safe for its intended use.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

Skin Contact:

Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, dryness, cracking, blistering, and pain. Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye Contact:

Severe Eye Irritation: Signs/symptoms may include significant redness, swelling, pain, tearing, cloudy appearance of the cornea, and impaired vision.

Ingestion:

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

May cause additional health effects (see below).

Additional Health Effects:

Prolonged or repeated exposure may cause target organ effects:

Respiratory Effects: Signs/symptoms may include cough, shortness of breath, chest tightness, wheezing, increased heart rate, bluish colored skin (cyanosis), sputum production, changes in lung function tests, and/or respiratory failure.

Reproductive/Developmental Toxicity:

Contains a chemical or chemicals which can cause birth defects or other reproductive harm.

Additional Information:

This product contains ethanol. Alcoholic beverages and ethanol in alcoholic beverages have been classified by the International Agency for Research on Cancer as carcinogenic to humans. There are also data associating human consumption of alcoholic beverages with developmental toxicity and liver toxicity. Exposure to ethanol during the foreseeable use of this product is not expected to cause cancer, developmental toxicity, or liver toxicity.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Acute Toxicity			T == -
Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE > 5,000 mg/kg
Overall product	Ingestion		No data available; calculated ATE > 5,000 mg/kg
2-HYDROXYETHYL METHACRYLATE	Dermal	Rabbit	LD50 > 5,000 mg/kg
2-HYDROXYETHYL METHACRYLATE	Ingestion	Rat	LD50 5,564 mg/kg
BISPHENOL A DIGLYCIDYL ETHER DIMETHACRYLATE	Ingestion		LD50 estimated to be 2,000 - 5,000 mg/kg
(BISGMA)			
BISPHENOL A DIGLYCIDYL ETHER DIMETHACRYLATE	Dermal	Professio	LD50 estimated to be 2,000 - 5,000 mg/kg
(BISGMA)		nal	
		judgeme	
		nt	
ETHANOL	Dermal	Rabbit	LD50 > 15,800 mg/kg
ETHANOL	Inhalation-	Rat	LC50 124.7 mg/l
	Vapor (4		
	hours)		
ETHANOL	Ingestion	Rat	LD50 17,800 mg/kg
Synthetic amorphous silica, fumed, crystalline-free	Dermal	Rabbit	LD50 > 5,000 mg/kg
Synthetic amorphous silica, fumed, crystalline-free	Inhalation-	Rat	LC50 > 0.691 mg/l
	Dust/Mist		
	(4 hours)		
Synthetic amorphous silica, fumed, crystalline-free	Ingestion	Rat	LD50 > 5,110 mg/kg
1,6-HEXANEDIOL DIMETHACRYLATE	Dermal	Professio	LD50 estimated to be 2,000 - 5,000 mg/kg
		nal	

		judgeme	
		nt	
1,6-HEXANEDIOL DIMETHACRYLATE	Ingestion	similar compoun ds	LD50 2000-5000 mg/kg
COPOLYMER OF ACRYLIC AND ITACONIC ACID	Dermal	Professio nal judgeme nt	LD50 estimated to be > 5,000 mg/kg
COPOLYMER OF ACRYLIC AND ITACONIC ACID	Ingestion	Rat	LD50 > 5,000 mg/kg
METHACRYLOXYPROPYLTRIMETHOXYSILANE	Dermal	Rabbit	LD50 > 20,900 mg/kg
METHACRYLOXYPROPYLTRIMETHOXYSILANE	Inhalation- Dust/Mist (4 hours)	Rat	LC50 > 2.28 mg/l
METHACRYLOXYPROPYLTRIMETHOXYSILANE	Ingestion	Rat	LD50 > 5,225 mg/kg
(DIMETHYLAMINO)ETHYL METHACRYLATE	Dermal	Rat	LD50 > 2,000 mg/kg
(DIMETHYLAMINO)ETHYL METHACRYLATE	Inhalation- Dust/Mist (4 hours)	Rat	LC50 > 0.436 mg/l
(DIMETHYLAMINO)ETHYL METHACRYLATE	Ingestion	Rat	LD50 > 2,000 mg/kg
2,4,6-TRIMETHYLBENZOYLDIPHENYLPHOSPHINE OXIDE	Dermal	Professio nal judgeme nt	LD50 estimated to be > 5,000 mg/kg
2,4,6-TRIMETHYLBENZOYLDIPHENYLPHOSPHINE OXIDE	Ingestion	Rat	LD50 > 5,000 mg/kg
CAMPHORQUINONE	Dermal	Professio nal judgeme nt	LD50 estimated to be 2,000 - 5,000 mg/kg
CAMPHORQUINONE	Ingestion	Rat	LD50 > 2,000 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
	•	
2-HYDROXYETHYL METHACRYLATE	Rabbit	Minimal irritation
BISPHENOL A DIGLYCIDYL ETHER DIMETHACRYLATE (BISGMA)	Not	Minimal irritation
	available	
ETHANOL	Rabbit	No significant irritation
Synthetic amorphous silica, fumed, crystalline-free	Rabbit	No significant irritation
METHACRYLOXYPROPYLTRIMETHOXYSILANE	Rabbit	No significant irritation
2,4,6-TRIMETHYLBENZOYLDIPHENYLPHOSPHINE OXIDE	Rabbit	No significant irritation

Serious Eye Damage/Irritation

Name	Species	Value
Overall product	Rabbit	Severe irritant
2-HYDROXYETHYL METHACRYLATE	Rabbit	Moderate irritant
BISPHENOL A DIGLYCIDYL ETHER DIMETHACRYLATE (BISGMA)	Not	Moderate irritant
	available	
ETHANOL	Rabbit	Moderate irritant
Synthetic amorphous silica, fumed, crystalline-free	Rabbit	No significant irritation
METHACRYLOXYPROPYLTRIMETHOXYSILANE	Rabbit	Mild irritant
2,4,6-TRIMETHYLBENZOYLDIPHENYLPHOSPHINE OXIDE	Rabbit	No significant irritation

Skin Sensitization

Skin Schsitzation		
Name	Species	Value
2-HYDROXYETHYL METHACRYLATE	Human	Sensitizing
	and	
	animal	
BISPHENOL A DIGLYCIDYL ETHER DIMETHACRYLATE (BISGMA)	Guinea	Sensitizing
	pig	
ETHANOL	Human	Some positive data exist, but the data are not
		sufficient for classification

Page 8 of 12

Synthetic amorphous silica, fumed, crystalline-free	Human	Not sensitizing
	and	
	animal	
METHACRYLOXYPROPYLTRIMETHOXYSILANE	Guinea	Not sensitizing
	pig	

Respiratory Sensitization

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
2-HYDROXYETHYL METHACRYLATE	In vivo	Not mutagenic
2-HYDROXYETHYL METHACRYLATE	In Vitro	Some positive data exist, but the data are not sufficient for classification
BISPHENOL A DIGLYCIDYL ETHER DIMETHACRYLATE (BISGMA)	In Vitro	Some positive data exist, but the data are not sufficient for classification
ETHANOL	In Vitro	Some positive data exist, but the data are not sufficient for classification
ETHANOL	In vivo	Some positive data exist, but the data are not sufficient for classification
Synthetic amorphous silica, fumed, crystalline-free	In Vitro	Not mutagenic
METHACRYLOXYPROPYLTRIMETHOXYSILANE	In Vitro	Not mutagenic
METHACRYLOXYPROPYLTRIMETHOXYSILANE	In vivo	Not mutagenic
2,4,6-TRIMETHYLBENZOYLDIPHENYLPHOSPHINE OXIDE	In Vitro	Not mutagenic

Carcinogenicity

Name	Route	Species	Value
ETHANOL	Ingestion	Multiple	Some positive data exist, but the data are not
		animal	sufficient for classification
		species	
Synthetic amorphous silica, fumed, crystalline-free	Not	Mouse	Some positive data exist, but the data are not
	Specified		sufficient for classification

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test Result	Exposure Duration
2-HYDROXYETHYL METHACRYLATE	Ingestion	Not toxic to female reproduction	Rat	NOAEL 1,000 mg/kg/day	premating & during gestation
2-HYDROXYETHYL METHACRYLATE	Ingestion	Not toxic to male reproduction	Rat	NOAEL 1,000 mg/kg/day	49 days
2-HYDROXYETHYL METHACRYLATE	Ingestion	Not toxic to development	Rat	NOAEL 1,000 mg/kg/day	premating & during gestation
BISPHENOL A DIGLYCIDYL ETHER DIMETHACRYLATE (BISGMA)	Ingestion	Not toxic to female reproduction	Mouse	NOAEL 0.8 mg/kg/day	premating & during gestation
BISPHENOL A DIGLYCIDYL ETHER DIMETHACRYLATE (BISGMA)	Ingestion	Not toxic to male reproduction	Mouse	NOAEL 0.8 mg/kg/day	premating & during gestation
BISPHENOL A DIGLYCIDYL ETHER DIMETHACRYLATE (BISGMA)	Ingestion	Not toxic to development	Mouse	NOAEL 0.8 mg/kg/day	premating & during gestation
ETHANOL	Inhalation	Not toxic to development	Rat	NOAEL 38 mg/l	during gestation
ETHANOL	Ingestion	Some positive developmental data exist, but the data are not sufficient for classification	Rat	NOAEL 5,200 mg/kg/day	premating & during gestation
Synthetic amorphous silica, fumed, crystalline-free	Ingestion	Not toxic to female reproduction	Rat	NOAEL 509 mg/kg/day	1 generation
Synthetic amorphous silica, fumed,	Ingestion	Not toxic to male reproduction	Rat	NOAEL 497	1 generation

crystalline-free				mg/kg/day	
Synthetic amorphous silica, fumed, crystalline-free	Ingestion	Not toxic to development	Rat	NOAEL 1,350 mg/kg/day	during organogenesi s
METHACRYLOXYPROPYLTRIMETHO XYSILANE	Ingestion	Some positive developmental data exist, but the data are not sufficient for classification	Rat	NOAEL 5,200 mg/kg/day	during organogenesi s
2,4,6- TRIMETHYLBENZOYLDIPHENYLPHO SPHINE OXIDE	Ingestion	Toxic to male reproduction	Rat	NOAEL 100 mg/kg/day	90 days

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Overall product	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	
ETHANOL	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	LOAEL 2.6 mg/l	30 minutes
ETHANOL	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	LOAEL 9.4 mg/l	not available
ETHANOL	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Multiple animal species	NOAEL not available	
ETHANOL	Ingestion	kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Dog	NOAEL 3,000 mg/kg	
COPOLYMER OF ACRYLIC AND ITACONIC ACID	Ingestion	nervous system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 5,000 mg/kg	

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
BISPHENOL A DIGLYCIDYL ETHER DIMETHACRYLATE (BISGMA)	Ingestion	endocrine system liver nervous system kidney and/or bladder	All data are negative	Mouse	NOAEL 0.8 mg/kg/day	premating & during gestation
ETHANOL	Inhalation	liver	Some positive data exist, but the data are not sufficient for classification	Rabbit	LOAEL 124 mg/l	365 days
ETHANOL	Inhalation	hematopoietic system immune system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 25 mg/l	14 days
ETHANOL	Ingestion	liver	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 8,000 mg/kg/day	4 months
ETHANOL	Ingestion	kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Dog	NOAEL 3,000 mg/kg/day	7 days
Synthetic amorphous silica, fumed, crystalline-free	Inhalation	respiratory system silicosis	All data are negative	Human	NOAEL Not available	occupational exposure
METHACRYLOXYPROP YLTRIMETHOXYSILAN E	Dermal	skin	Some positive data exist, but the data are not sufficient for classification	Rabbit	NOAEL 2,100 mg/kg/day	17 days
METHACRYLOXYPROP YLTRIMETHOXYSILAN E	Dermal	liver kidney and/or bladder	All data are negative	Rabbit	NOAEL 2,100 mg/kg/day	17 days
METHACRYLOXYPROP YLTRIMETHOXYSILAN E	Inhalation	respiratory system	May cause damage to organs though prolonged or repeated exposure	Rat	LOAEL 0.05 mg/l	14 weeks
METHACRYLOXYPROP	Inhalation	liver	Some positive data exist, but the	Rat	NOAEL	14 weeks

Page 10 of 12

3MTM ESPETM ADPERTM EASY ONE VIAL 02/25/16

YLTRIMETHOXYSILAN E			data are not sufficient for classification		0.244 mg/l	
METHACRYLOXYPROP YLTRIMETHOXYSILAN E	Inhalation	hematopoietic system eyes kidney and/or bladder	All data are negative	Rat	NOAEL 0.244 mg/l	14 weeks
2,4,6- TRIMETHYLBENZOYL DIPHENYLPHOSPHINE OXIDE	Ingestion	skin blood liver kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 1,000 mg/kg/day	90 days
2,4,6- TRIMETHYLBENZOYL DIPHENYLPHOSPHINE OXIDE	Ingestion	nervous system	All data are negative	Rat	NOAEL 1,000 mg/kg/day	90 days

Aspiration Hazard

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

Ecotoxicological information

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

Chemical fate information

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

SECTION 13: Disposal considerations

13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of completely cured (or polymerized) material in a permitted industrial waste facility. As a disposal alternative, incinerate uncured product in a permitted waste incineration facility.

EPA Hazardous Waste Number (RCRA): D001 (Ignitable), D035 (Methyl ethyl ketone)

SECTION 14: Transport Information

For Transport Information, please visit http://3M.com/Transportinfo or call 1-800-364-3577 or 651-737-6501.

SECTION 15: Regulatory information

15.1. US Federal Regulations

Contact 3M for more information.

311/312 Hazard Categories:

Fire Hazard - Yes Pressure Hazard - No Reactivity Hazard - No Immediate Hazard - Yes Delayed Hazard - Yes

Page 11 of 12

15.2. State Regulations

Contact 3M for more information.

15.3. Chemical Inventories

This material contains one or more substances not listed on the TSCA Inventory. Commercial use of this material is regulated by the FDA.

Contact 3M for more information.

15.4. International Regulations

Contact 3M for more information.

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 16: Other information

NFPA Hazard Classification

Health: 2 Flammability: 3 Instability: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

 Document Group:
 23-2914-2
 Version Number:
 6.00

 Issue Date:
 02/25/16
 Supercedes Date:
 06/01/15

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M

3M USA SDSs are available at www.3M.com

Page 12 **of** 12