



Safety Data Sheet

Copyright, 2016, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document Group:	26-6409-2	Version Number:	6.01
Issue Date:	11/07/16	Supersedes Date:	08/19/14

SECTION 1: Identification

1.1. Product identifier

3M(TM) Fire Barrier Sealant FD 150+, Limestone

Product Identification Numbers

98-0400-5641-2, 98-0400-5642-0, 98-0400-5643-8, 98-0400-5644-6

1.2. Recommended use and restrictions on use

Recommended use

Passive Fire Protection

1.3. Supplier's details

MANUFACTURER:	3M
DIVISION:	Industrial Adhesives and Tapes Division
ADDRESS:	3M Center, St. Paul, MN 55144-1000, USA
Telephone:	1-888-3M HELPS (1-888-364-3577)

1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

SECTION 2: Hazard identification

2.1. Hazard classification

Skin Corrosion/Irritation: Category 2.

Carcinogenicity: Category 1A.

Specific Target Organ Toxicity (single exposure): Category 1.

2.2. Label elements

Signal word

Danger

Symbols

Exclamation mark | Health Hazard |

Pictograms

**Hazard Statements**

Causes skin irritation.

May cause cancer.

Causes damage to organs:

cardiovascular system |

nervous system |

kidney/urinary tract |

respiratory system |

Precautionary Statements**General:**

Keep out of reach of children.

If medical advice is needed, have product container or label at hand.

Prevention:

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Do not breathe dust/fume/gas/mist/vapors/spray.

Wear protective gloves.

Do not eat, drink or smoke when using this product.

Wash thoroughly after handling.

Response:

IF ON SKIN: Wash with plenty of soap and water.

If skin irritation occurs: Get medical advice/attention.

Take off contaminated clothing and wash it before reuse.

IF exposed: Call a POISON CENTER or doctor/physician.

Specific treatment (see Notes to Physician on this label).

Storage:

Store locked up.

Disposal:

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

Notes to Physician:

This product contains ethylene glycol. If there is reasonable suspicion of ethylene glycol poisoning, intravenous (IV) administration with either fomepizole (preferred) or ethanol (if fomepizole is unavailable) should be considered as part of the medical management.

2.3. Hazards not otherwise classified

None.

11% of the mixture consists of ingredients of unknown acute oral toxicity.

11% of the mixture consists of ingredients of unknown acute dermal toxicity.

9% of the mixture consists of ingredients of unknown acute inhalation toxicity.

SECTION 3: Composition/information on ingredients

Ingredient	C.A.S. No.	% by Wt
Calcium Carbonate	1317-65-3	30 - 60 Trade Secret *
Polymer NJTS Reg. No. 04499600-7186	Trade Secret*	10 - 30 Trade Secret *
Acrylic Emulsion	70677-00-8	5 - 10 Trade Secret *
Mineral Spirits	64742-88-7	5 - 10 Trade Secret *
Water	7732-18-5	5 - 10 Trade Secret *
Ethylene Glycol	107-21-1	1 - 5 Trade Secret *
Plasticizer	27138-31-4	1 - 5 Trade Secret *
Titanium Dioxide	13463-67-7	1 - 5 Trade Secret *
Surfactant	Trade Secret*	< 2 Trade Secret *
Ethyl Hydroxyethyl Cellulose	9004-58-4	0.5 - 1.5 Trade Secret *
Quartz Silica	14808-60-7	< 0.2 Trade Secret *

NJTS or NJTSRN: New Jersey Trade Secret Registry Number.

*The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye Contact:

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1. Information on toxicological effects.

4.3. Indication of any immediate medical attention and special treatment required

This product contains ethylene glycol. If there is reasonable suspicion of ethylene glycol poisoning, intravenous (IV) administration with either fomepizole (preferred) or ethanol (if fomepizole is unavailable) should be considered as part of the medical management.

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

Use a fire fighting agent suitable for the surrounding fire.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products

Substance

Carbon monoxide
Carbon dioxide

Condition

During Combustion
During Combustion

5.3. Special protective actions for fire-fighters

No special protective actions for fire-fighters are anticipated.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue. Seal the container. Dispose of collected material as soon as possible.

SECTION 7: Handling and storage**7.1. Precautions for safe handling**

Keep out of reach of children. Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid release to the environment. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.) Use personal protective equipment (gloves, respirators, etc.) as required.

7.2. Conditions for safe storage including any incompatibilities

Keep cool. Store away from oxidizing agents. Store away from areas where product may come into contact with food or pharmaceuticals. Store in a dry place.

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****Occupational exposure limits**

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
Ethylene Glycol	107-21-1	ACGIH	CEIL(as aerosol):100 mg/m3	A4: Not class. as human carcin
Calcium Carbonate	1317-65-3	OSHA	TWA(as total dust):15 mg/m3;TWA(respirable fraction):5 mg/m3	
Titanium Dioxide	13463-67-7	ACGIH	TWA:10 mg/m3	A4: Not class. as human carcin
Titanium Dioxide	13463-67-7	OSHA	TWA(as total dust):15 mg/m3	
Quartz Silica	14808-60-7	ACGIH	TWA(respirable fraction):0.025 mg/m3	A2: Suspected human carcin.
Quartz Silica	14808-60-7	OSHA	TWA concentration(respirable):0.1	

			mg/m3(2.4 millions of particles/cu. ft.);TWA:0.05 mg/m3	
Kerosine (petroleum)	64742-88-7	ACGIH	TWA(as total hydrocarbon vapor, non-aerosol):200 mg/m3	A3: Confirmed animal carcin., SKIN

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines

OSHA : United States Department of Labor - Occupational Safety and Health Administration

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

None required.

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing.

Gloves made from the following material(s) are recommended: Nitrile Rubber

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

General Physical Form:	Solid
Specific Physical Form:	Paste
Odor, Color, Grade:	Gray paste with low odor
Odor threshold	No Data Available
Melting point	No Data Available
Flash Point	Flash point > 93 °C (200 °F)
Flammability (solid, gas)	Not Classified
Flammable Limits(LEL)	Not Applicable
Flammable Limits(UEL)	Not Applicable
Density	1.45 g/cm3
Specific Gravity	1.45 [Ref Std: WATER=1]
Solubility- non-water	No Data Available

Autoignition temperature	<i>Not Applicable</i>
Decomposition temperature	<i>No Data Available</i>
Molecular weight	<i>No Data Available</i>
Volatile Organic Compounds	< 15 % weight
VOC Less H2O & Exempt Solvents	< 250 g/l

SECTION 10: Stability and reactivity

10.1. Reactivity

This material is considered to be non reactive under normal use conditions.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

None known.

10.5. Incompatible materials

Strong oxidizing agents

10.6. Hazardous decomposition products

<u>Substance</u>	<u>Condition</u>
------------------	------------------

None known.	
-------------	--

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

May cause additional health effects (see below).

Skin Contact:

Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, dryness, cracking, blistering, and pain.

Eye Contact:

Contact with the eyes during product use is not expected to result in significant irritation.

Ingestion:

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

May cause additional health effects (see below).

Additional Health Effects:**Single exposure may cause target organ effects:**

Cardiac Effects: Signs/symptoms may include irregular heartbeat (arrhythmia), changes in heart rate, damage to heart muscle, heart attack, and may be fatal.

Neurological Effects: Signs/symptoms may include personality changes, lack of coordination, sensory loss, tingling or numbness of the extremities, weakness, tremors, and/or changes in blood pressure and heart rate.

Respiratory Effects: Signs/symptoms may include cough, shortness of breath, chest tightness, wheezing, increased heart rate, bluish colored skin (cyanosis), sputum production, changes in lung function tests, and/or respiratory failure.

Kidney/Bladder Effects: Signs/symptoms may include changes in urine production, abdominal or lower back pain, increased protein in urine, increased blood urea nitrogen (BUN), blood in urine, and painful urination.

Carcinogenicity:

Contains a chemical or chemicals which can cause cancer.

Ingredient	CAS No.	Class Description	Regulation
SILICA, CRYSTAL AIRRESP	14808-60-7	Known human carcinogen	National Toxicology Program Carcinogens
Quartz Silica	14808-60-7	Grp. 1: Carcinogenic to humans	International Agency for Research on Cancer
Titanium Dioxide	13463-67-7	Grp. 2B: Possible human carc.	International Agency for Research on Cancer

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE > 5,000 mg/kg
Overall product	Inhalation-Vapor(4 hr)		No data available; calculated ATE > 50 mg/l
Overall product	Ingestion		No data available; calculated ATE > 5,000 mg/kg
Calcium Carbonate	Dermal	Rat	LD50 > 2,000 mg/kg
Calcium Carbonate	Inhalation-Dust/Mist (4 hours)	Rat	LC50 3 mg/l
Calcium Carbonate	Ingestion	Rat	LD50 6,450 mg/kg
Polymer NJTS Reg. No. 04499600-7186	Dermal		LD50 estimated to be > 5,000 mg/kg
Polymer NJTS Reg. No. 04499600-7186	Ingestion	Rat	LD50 > 2,000 mg/kg
Mineral Spirits	Inhalation-Vapor		LC50 estimated to be 20 - 50 mg/l
Mineral Spirits	Dermal	Rabbit	LD50 > 3,000 mg/kg
Mineral Spirits	Ingestion	Rat	LD50 > 5,000 mg/kg
Plasticizer	Dermal	Rat	LD50 > 2,000 mg/kg
Plasticizer	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 200 mg/l
Plasticizer	Ingestion	Rat	LD50 3,295 mg/kg
Titanium Dioxide	Dermal	Rabbit	LD50 > 10,000 mg/kg
Titanium Dioxide	Inhalation-	Rat	LC50 > 6.82 mg/l

	Dust/Mist (4 hours)		
Titanium Dioxide	Ingestion	Rat	LD50 > 10,000 mg/kg
Ethylene Glycol	Ingestion	Human	LD50 1,600 mg/kg
Ethylene Glycol	Inhalation- Dust/Mist (4 hours)	Other	LC50 estimated to be 5 - 12.5 mg/l
Ethylene Glycol	Dermal	Rabbit	9,530 mg/kg
Ethyl Hydroxyethyl Cellulose	Dermal		LD50 estimated to be > 5,000 mg/kg
Ethyl Hydroxyethyl Cellulose	Ingestion	Rat	LD50 > 10,000 mg/kg
Quartz Silica	Dermal		LD50 estimated to be > 5,000 mg/kg
Quartz Silica	Ingestion		LD50 estimated to be > 5,000 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Calcium Carbonate	Rabbit	No significant irritation
Polymer NJTS Reg. No. 04499600-7186	Rabbit	Minimal irritation
Mineral Spirits	Rabbit	Irritant
Plasticizer	Rabbit	No significant irritation
Titanium Dioxide	Rabbit	No significant irritation
Ethylene Glycol	Rabbit	Minimal irritation
Ethyl Hydroxyethyl Cellulose	Professional judgement	Minimal irritation
Quartz Silica	Professional judgement	No significant irritation

Serious Eye Damage/Irritation

Name	Species	Value
Calcium Carbonate	Rabbit	No significant irritation
Polymer NJTS Reg. No. 04499600-7186	Professional judgement	Mild irritant
Mineral Spirits	Rabbit	No significant irritation
Plasticizer	Rabbit	No significant irritation
Titanium Dioxide	Rabbit	No significant irritation
Ethylene Glycol	Rabbit	Mild irritant
Ethyl Hydroxyethyl Cellulose	Professional judgement	Mild irritant

Skin Sensitization

Name	Species	Value
Mineral Spirits	Guinea pig	Not sensitizing
Plasticizer	Guinea pig	Not sensitizing
Titanium Dioxide	Human and animal	Not sensitizing
Ethylene Glycol	Human	Some positive data exist, but the data are not sufficient for classification

Respiratory Sensitization

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
Mineral Spirits	In vivo	Not mutagenic
Mineral Spirits	In Vitro	Some positive data exist, but the data are not sufficient for classification
Plasticizer	In Vitro	Not mutagenic
Titanium Dioxide	In Vitro	Not mutagenic
Titanium Dioxide	In vivo	Not mutagenic
Ethylene Glycol	In Vitro	Not mutagenic
Ethylene Glycol	In vivo	Not mutagenic
Quartz Silica	In Vitro	Some positive data exist, but the data are not sufficient for classification
Quartz Silica	In vivo	Some positive data exist, but the data are not sufficient for classification

Carcinogenicity

Name	Route	Species	Value
Mineral Spirits	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
Mineral Spirits	Inhalation	Human and animal	Some positive data exist, but the data are not sufficient for classification
Titanium Dioxide	Ingestion	Multiple animal species	Not carcinogenic
Titanium Dioxide	Inhalation	Rat	Carcinogenic
Ethylene Glycol	Ingestion	Multiple animal species	Not carcinogenic
Quartz Silica	Inhalation	Human and animal	Carcinogenic

Reproductive Toxicity**Reproductive and/or Developmental Effects**

Name	Route	Value	Species	Test Result	Exposure Duration
Calcium Carbonate	Ingestion	Not toxic to development	Rat	NOAEL 625 mg/kg/day	prematuring & during gestation
Mineral Spirits	Inhalation	Not toxic to development	Rat	NOAEL 2.4 mg/l	during organogenesis
Plasticizer	Ingestion	Not toxic to female reproduction	Rat	NOAEL 500 mg/kg/day	2 generation
Plasticizer	Ingestion	Not toxic to male reproduction	Rat	NOAEL 400 mg/kg/day	2 generation
Plasticizer	Ingestion	Some positive developmental data exist, but the data are not sufficient for classification	Rat	NOAEL 1,000 mg/kg/day	during gestation
Ethylene Glycol	Dermal	Some positive developmental data exist, but the data are not sufficient for classification	Mouse	NOAEL 3,549 mg/kg/day	during organogenesis
Ethylene Glycol	Ingestion	Some positive developmental data exist, but the data are not sufficient for classification	Mouse	LOAEL 750 mg/kg/day	during organogenesis
Ethylene Glycol	Inhalation	Some positive developmental data exist, but the data are not sufficient for classification	Mouse	NOAEL 1,000 mg/kg/day	during organogenesis

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Calcium Carbonate	Inhalation	respiratory system	All data are negative	Rat	NOAEL 0.812 mg/l	90 minutes
Mineral Spirits	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human and animal	NOAEL Not available	
Mineral Spirits	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification		NOAEL Not available	
Mineral Spirits	Inhalation	nervous system	Some positive data exist, but the data are not sufficient for classification	Dog	NOAEL 6.5 mg/l	4 hours
Mineral Spirits	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Professional judgement	NOAEL Not available	
Ethylene Glycol	Ingestion	heart nervous system kidney and/or bladder respiratory system	Causes damage to organs	Human	NOAEL Not available	poisoning and/or abuse
Ethylene Glycol	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	poisoning and/or abuse
Ethylene Glycol	Ingestion	liver	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	poisoning and/or abuse

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Calcium Carbonate	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	occupational exposure
Mineral Spirits	Inhalation	nervous system	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 4.6 mg/l	6 months
Mineral Spirits	Inhalation	kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 1.9 mg/l	13 weeks
Mineral Spirits	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Multiple animal species	NOAEL 0.6 mg/l	90 days
Mineral Spirits	Inhalation	bone, teeth, nails, and/or hair blood liver muscles	All data are negative	Rat	NOAEL 5.6 mg/l	12 weeks
Mineral Spirits	Inhalation	heart	All data are negative	Multiple animal species	NOAEL 1.3 mg/l	90 days
Plasticizer	Ingestion	hematopoietic system liver	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 2,500 mg/kg/day	90 days
Titanium Dioxide	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 0.01 mg/l	2 years
Titanium Dioxide	Inhalation	pulmonary fibrosis	All data are negative	Human	NOAEL Not available	occupational exposure
Ethylene Glycol	Ingestion	kidney and/or bladder vascular system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 200 mg/kg/day	2 years
Ethylene Glycol	Ingestion	heart hematopoietic system liver immune system muscles	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 1,000 mg/kg/day	2 years
Ethylene Glycol	Ingestion	respiratory system	Some positive data exist, but the	Mouse	NOAEL	2 years

			data are not sufficient for classification		12,000 mg/kg/day	
Ethylene Glycol	Ingestion	skin endocrine system bone, teeth, nails, and/or hair nervous system eyes	All data are negative	Multiple animal species	NOAEL 1,000 mg/kg/day	2 years
Quartz Silica	Inhalation	silicosis	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	occupational exposure

Aspiration Hazard

Name	Value
Mineral Spirits	Aspiration hazard

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information**Ecotoxicological information**

Test Organism	Test Type	Result
Water flea, Ceriodaphnia dubia	48 hours Effect Level 50%	96.5 mg/l

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

Chemical fate information

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

SECTION 13: Disposal considerations**13.1. Disposal methods**

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of completely cured (or polymerized) material in a permitted industrial waste facility. As a disposal alternative, incinerate uncured product in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

EPA Hazardous Waste Number (RCRA): Not regulated

SECTION 14: Transport Information

For Transport Information, please visit <http://3M.com/Transportinfo> or call 1-800-364-3577 or 651-737-6501.

SECTION 15: Regulatory information**15.1. US Federal Regulations**

Contact 3M for more information.

311/312 Hazard Categories:

Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No Immediate Hazard - Yes Delayed Hazard - Yes

Section 313 Toxic Chemicals subject to the reporting requirements of that section and 40 CFR part 372 (EPCRA):

<u>Ingredient</u>	<u>C.A.S. No</u>	<u>% by Wt</u>
Ethylene Glycol	107-21-1	Trade Secret 1 - 5

15.2. State Regulations

Contact 3M for more information.

California Proposition 65

<u>Ingredient</u>	<u>C.A.S. No.</u>	<u>Classification</u>
SILICA, CRYSTALLINE (AIRBORNE PARTICLES OF RESPIRABLE SIZE)	None	Carcinogen
Carbon Black	1333-86-4	Carcinogen
Ethylene Glycol	107-21-1	Developmental Toxin
Titanium Dioxide	13463-67-7	Carcinogen

WARNING: This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

WARNING: This product contains a chemical known to the State of California to cause cancer.

15.3. Chemical Inventories

The components of this product are in compliance with the new substance notification requirements of CEPA.

The components of this product are in compliance with the chemical notification requirements of TSCA.

Contact 3M for more information.

15.4. International Regulations

Contact 3M for more information.

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 16: Other information**NFPA Hazard Classification**

Health: 2 **Flammability:** 1 **Instability:** 0 **Special Hazards:** None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Document Group:	26-6409-2	Version Number:	6.01
Issue Date:	11/07/16	Supersedes Date:	08/19/14

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY

OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M

3M USA SDSs are available at www.3M.com