

Safety Data Sheet

Copyright, 2015, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

10-2470-2 **Document Group: Version Number:** 31.01 **Issue Date:** 07/10/15 **Supercedes Date:** 02/13/15

SECTION 1: Identification

1.1. Product identifier

3MTM Scotch-WeldTM Structural Adhesive Film AF 126, 0.03Wt and 0.06Wt

Product Identification Numbers

62-3126-0305-3, 62-3126-1200-5, 62-3126-3901-6, 62-3126-3902-4, 62-3126-4505-4, 62-3126-5301-7, 62-3126-5302-5, 62-3126-3902-4, 62-3126-3126-3002-4, 62-3126-3002-4, 62-3126-3002-4, 62-3126-3002-4, 62-3126-3002-4, 62-3126-3002-4, 62-3126-3002-4, 62-3126-3002-4, 62-3126-4, 62-3126-4, 62-3126-4, 62-3126-4, 62-3126-4, 62-3126-4, 62-3126-4, 62-3126-4, 62-3126-4, 62-3126 3126-5303-3, 62-3126-5305-8, 62-3126-5306-6, 62-3326-0305-9, 62-3326-0450-3, 62-3326-0452-9, 62-3326-0555-9, 62-306-6, 62-6, 62-6, 62-6, 62-6, 62-6, 62-6, 62-6, 62-6, 62-6, 62-6, 62-6, 62-6, 62-6, 62-6, 62-6 3326-0655-7, 62-3326-1205-0, 62-3326-1735-6, 62-3326-1752-1, 62-3326-2001-2, 62-3326-2006-1, 62-3326-2805-6, 62-326-2001-2, 62-3326-2001-2, 62-3326-2006-1, 62-3326-2805-6, 62-326-2001-2, 62-3001-2, 62-3001-2, 62-3001-2, 62-3001-2, 62-3001-2, 62-3001-2, 62-3001-2, 62-3001-2, 62-2001-2, 62-2001-2, 62-2001-2, 62-2001-2, 62-2001-2, 62-2001-2, 62-2001-2, 62-2001-2, 62-2001-2, 62-2001-2 3326-2806-4, 62-3326-3301-5, 62-3326-3305-6, 62-3326-3755-2, 62-3326-3901-2, 62-3326-3902-0, 62-3326-4505-0, 62-3326-3901-2, 62-3326-3902-0, 62-3326-3900-0, 62-3326-3900-0, 62-3326-3900-0, 62-3326-3900-0, 62-3326-3900-0, 62-3326-3900-0, 62-3326-3900-0, 62-3000-0, 62-3000-0, 62-3000-0, 62-3000-0, 62-3000-0, 62-3000-0, 62-3000-0, 62-3000-0, 62-3000-0, 62-3000-0, 62-6000-0, 62-600-0, 62-600-0, 62-600-0, 62-600-0, 62-600-0, 62-600-3326-4506-8, 62-3326-5301-3, 62-3326-5303-9, 62-3326-5307-0, 87-3300-0585-8

1.2. Recommended use and restrictions on use

Recommended use

Structural Adhesive Film

1.3. Supplier's details

MANUFACTURER: 3M

DIVISION: Aerospace and Commercial Transportation Division 3M Center, St. Paul, MN 55144-1000, USA **ADDRESS: Telephone:** 1-888-3M HELPS (1-888-364-3577)

1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

SECTION 2: Hazard identification

2.1. Hazard classification

Not classified as hazardous according to OSHA Hazard Communication Standard, 29 CFR 1910.1200.

2.2. Label elements

Signal word

Not applicable.

Symbols

Not applicable.

Pictograms

Not applicable.

Precautionary Statements

Response:

Call a POISON CENTER or doctor/physician if you feel unwell.

Disposal:

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

2.3. Hazards not otherwise classified

None.

95% of the mixture consists of ingredients of unknown acute oral toxicity.

95% of the mixture consists of ingredients of unknown acute dermal toxicity.

SECTION 3: Composition/information on ingredients

Ingredient	C.A.S. No.	% by Wt
Nitrile Rubber/Phenolic Epoxy Resins/Phenolic Resin	Trade Secret*	90 - 98
Dicyandiamide	461-58-5	1 - 5
para-Chlorophenol-Dimethylurea	150-68-5	1 - 3
Chromium Oxide	1308-38-9	0.1 - 0.5

^{*}The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:

Wash with soap and water. If signs/symptoms develop, get medical attention.

Eye Contact:

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1. Information on toxicological effects.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

3MTM Scotch-WeldTM Structural Adhesive Film AF 126, 0.03Wt and 0.06Wt 07/10/15

None inherent in this product.

Hazardous Decomposition or By-Products

Substance	<u>Condition</u>
Chlorine	During Combustion
Carbon monoxide	During Combustion
Carbon dioxide	During Combustion
Hydrogen Chloride	During Combustion
Hydrogen Cyanide	During Combustion
Ammonia	During Combustion
Oxides of Nitrogen	During Combustion

5.3. Special protective actions for fire-fighters

No special protective actions for fire-fighters are anticipated.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue. Seal the container. Dispose of collected material as soon as possible.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid breathing of vapors created during cure cycle. Avoid breathing of dust created by cutting, sanding, grinding or machining. For industrial or professional use only. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid release to the environment.

7.2. Conditions for safe storage including any incompatibilities

Store away from heat.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

ioi une componenti.				
Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
CHROMIUM (III)	1308-38-9	ACGIH	TWA(as Cr):0.5 mg/m3	
COMPOUNDS				
Chromium, insoluble salts	1308-38-9	OSHA	TWA(as Cr):1 mg/m3	
CHROMIUM (III)	1308-38-9	OSHA	TWA(as Cr):0.5 mg/m3	
COMPOUNDS				

ACGIH: American Conference of Governmental Industrial Hygienists

AIHA: American Industrial Hygiene Association

CMRG: Chemical Manufacturer's Recommended Guidelines

Page 3 of 9

3MTM Scotch-WeldTM Structural Adhesive Film AF 126, 0.03Wt and 0.06Wt 07/10/15

OSHA: United States Department of Labor - Occupational Safety and Health Administration

TWA: Time-Weighted-Average STEL: Short Term Exposure Limit

CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Provide ventilated enclosure for heat curing. Curing enclosures must be exhausted to outdoors or to a suitable emission control device. Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Safety Glasses with side shields

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing.

Gloves made from the following material(s) are recommended: Nitrile Rubber

Respiratory protection

Under normal use conditions, airborne exposures are not expected to be significant enough to require respiratory protection.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

General Physical Form:

Solid
Specific Physical Form:

Film

Odor, Color, Grade: essentially no odor, green

Odor threshold No Data Available pН Not Applicable **Melting point** No Data Available **Boiling Point** Not Applicable **Flash Point** No flash point **Evaporation rate** Not Applicable Flammability (solid, gas) Not Classified Not Applicable Flammable Limits(LEL) Flammable Limits(UEL) Not Applicable Not Applicable Vapor Pressure Not Applicable **Vapor Density Density** No Data Available **Specific Gravity** No Data Available

Solubility in Water Nil

Solubility- non-waterNo Data AvailablePartition coefficient: n-octanol/ waterNot ApplicableAutoignition temperatureNot Applicable

Page 4 of 9

3MTM Scotch-WeldTM Structural Adhesive Film AF 126, 0.03Wt and 0.06Wt 07/10/15

Decomposition temperature No Data Available Viscosity Not Applicable **Volatile Organic Compounds** Not Applicable Percent volatile Nil

VOC Less H2O & Exempt Solvents Not Applicable

SECTION 10: Stability and reactivity

10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Heat

10.5. Incompatible materials

Amines

10.6. Hazardous decomposition products

Substance Condition

None known.

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

No health effects are expected.

Skin Contact:

Contact with the skin during product use is not expected to result in significant irritation.

Eye Contact:

Contact with the eyes during product use is not expected to result in significant irritation.

Ingestion:

May be harmful if swallowed.

Physical Blockage: Signs/symptoms may include cramping, abdominal pain, and constipation.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

10400 101110103			
Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE > 5,000 mg/kg
Overall product	Ingestion		No data available; calculated ATE 2,000 - 5,000 mg/kg
Dicyandiamide	Dermal	Rabbit	LD50 > 10,000 mg/kg
Dicyandiamide	Ingestion	Rat	LD50 > 30,000 mg/kg
para-Chlorophenol-Dimethylurea	Dermal	Rabbit	LD50 > 2,500 mg/kg
para-Chlorophenol-Dimethylurea	Ingestion	Rat	LD50 1,480 mg/kg
Chromium Oxide	Ingestion	Rat	LD50 > 5,000 mg/kg

 $\overline{ATE} = \overline{acute\ toxicity\ estimate}$

Skin Corrosion/Irritation

Name	Species	Value
Dicyandiamide	Human	Minimal irritation
	and	
	animal	
para-Chlorophenol-Dimethylurea	similar	Mild irritant
	compoun	
	ds	

Serious Eye Damage/Irritation

circus Lyc Duning (Hilluston					
Name	Species	Value			
Dicyandiamide	Professio	Mild irritant			
	nal				
	judgeme				
	nt				
para-Chlorophenol-Dimethylurea	similar	Moderate irritant			
	compoun				
	ds				

Skin Sensitization

Name	Species	Value
Dicyandiamide	Guinea	Some positive data exist, but the data are not
	pig	sufficient for classification

Respiratory Sensitization

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
Dicyandiamide	In Vitro	Not mutagenic
para-Chlorophenol-Dimethylurea	In Vitro	Some positive data exist, but the data are not sufficient for classification
para-Chlorophenol-Dimethylurea	In vivo	Some positive data exist, but the data are not sufficient for classification

Carcinogenicity

Name	Route	Species	Value
Dicyandiamide	Ingestion	Rat	Not carcinogenic
para-Chlorophenol-Dimethylurea	Ingestion	Rat	Some positive data exist, but the data are not

3MTM Scotch-WeldTM Structural Adhesive Film AF 126, 0.03Wt and 0.06Wt 07/10/15

	sufficient for classification

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test Result	Exposure Duration
Dicyandiamide	Ingestion	Not toxic to female reproduction	Rat	NOAEL 1,000 mg/kg/day	premating & during gestation
Dicyandiamide	Ingestion	Not toxic to male reproduction	Rat	NOAEL 1,000 mg/kg/day	44 days
Dicyandiamide	Ingestion	Not toxic to development	Rat	NOAEL 1,000 mg/kg/day	premating & during gestation
para-Chlorophenol-Dimethylurea	Ingestion	Some positive developmental data exist, but the data are not sufficient for classification	Mouse	LOAEL 215 mg/kg/day	during gestation

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
para-Chlorophenol- Dimethylurea	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar compoun ds	NOAEL Not available	
para-Chlorophenol- Dimethylurea	Ingestion	methemoglobinemi a	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL Not available	not applicable

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Dicyandiamide	Ingestion	kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 6,822 mg/kg/day	13 weeks
para-Chlorophenol- Dimethylurea	Ingestion	liver	Some positive data exist, but the data are not sufficient for classification	Mouse	LOAEL 800 mg/kg/day	103 weeks
para-Chlorophenol- Dimethylurea	Ingestion	kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 65 mg/kg/day	103 weeks
para-Chlorophenol- Dimethylurea	Ingestion	immune system	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 520 mg/kg/day	13 weeks

Aspiration Hazard

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

Ecotoxicological information

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

Chemical fate information

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material

Page 7 of 9

and/or its components.

SECTION 13: Disposal considerations

13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of completely cured (or polymerized) material in a permitted industrial waste facility. As a disposal alternative, incinerate uncured product in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Combustion products will include halogen acid (HCl/HF/HBr). Facility must be capable of handling halogenated materials. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

EPA Hazardous Waste Number (RCRA): Not regulated

SECTION 14: Transport Information

For Transport Information, please visit http://3M.com/Transportinfo or call 1-800-364-3577 or 651-737-6501.

SECTION 15: Regulatory information

15.1. US Federal Regulations

Contact 3M for more information.

311/312 Hazard Categories:

Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No Immediate Hazard - Yes Delayed Hazard - No

Section 313 Toxic Chemicals subject to the reporting requirements of that section and 40 CFR part 372 (EPCRA):

<u>Ingredient</u>	C.A.S. No	% by Wt
para-Chlorophenol-Dimethylurea	150-68-5	1 - 3

15.2. State Regulations

Contact 3M for more information.

15.3. Chemical Inventories

The components of this product are in compliance with the chemical notification requirements of TSCA.

Contact 3M for more information.

15.4. International Regulations

Contact 3M for more information.

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 16: Other information

NFPA Hazard Classification

Deep 0 of 0

3MTM Scotch-WeldTM Structural Adhesive Film AF 126, 0.03Wt and 0.06Wt 07/10/15

Health: 1 Flammability: 1 Instability: 1 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

 Document Group:
 10-2470-2
 Version Number:
 31.01

 Issue Date:
 07/10/15
 Supercedes Date:
 02/13/15

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M

3M USA SDSs are available at www.3M.com

Page 9 of 9