

Safety Data Sheet

Copyright, 2016, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

 Document Group:
 19-3785-3
 Version Number:
 8.00

 Issue Date:
 12/20/16
 Supercedes Date:
 09/22/14

SECTION 1: Identification

1.1. Product identifier

3M Brand Roofing Granules - 4100L, 4600L & 4950L (Little Rock, AR)

Product Identification Numbers

98-0111-1330-9, 98-0111-1331-7, 98-0111-1342-4, 98-0111-1732-6, 98-0111-1734-2, 98-0111-1738-3

1.2. Recommended use and restrictions on use

Recommended use

Granules for coating roofing shingles.

1.3. Supplier's details

MANUFACTURER: 3M

DIVISION: Industrial Mineral Products

ADDRESS: 3M Center, St. Paul, MN 55144-1000, USA **Telephone:** 1-888-3M HELPS (1-888-364-3577)

1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

SECTION 2: Hazard identification

2.1. Hazard classification

Carcinogenicity: Category 1A.

2.2. Label elements

Signal word

Danger

Symbols

Health Hazard

Pictograms



12/20/16

Hazard Statements

May cause cancer.

Precautionary Statements

Prevention:

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Response:

IF exposed or concerned: Get medical advice/attention.

Storage:

Store locked up.

Disposal:

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

2.3. Hazards not otherwise classified

None.

97% of the mixture consists of ingredients of unknown acute oral toxicity.

SECTION 3: Composition/information on ingredients

Ingredient	C.A.S. No.	% by Wt
Pulaskite	Mixture	90 - 98
Quartz (a component of Pulaskite)	14808-60-7	< 1
Ceramic	66402-68-4	1 - 4
Oil	64742-52-5	< 0.2

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact

Wash with soap and water. If signs/symptoms develop, get medical attention.

Eye Contact:

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1. Information on toxicological effects.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

Non-combustible. Use a fire fighting agent suitable for surrounding fire.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

5.3. Special protective actions for fire-fighters

No special protective actions for fire-fighters are anticipated.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Collect as much of the spilled material as possible. Use wet sweeping compound or water to avoid dusting. Sweep up. Place in a closed container approved for transportation by appropriate authorities. Clean up residue. Seal the container. Dispose of collected material as soon as possible.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

For industrial or professional use only. Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Use personal protective equipment (gloves, respirators, etc.) as required. Granules are not respirable. Dust generated during handling may contain respirable material. 3M does not recommend material handling methods that could damage the coating or base mineral. In particular, roofing granules should not be conveyed pneumatically, via screw conveyors, or used as a sand blasting media. These uses can cause coating and base mineral attrition which may lead to increased levels of dust generation.

7.2. Conditions for safe storage including any incompatibilities

No special storage requirements.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
Quartz (a component of	14808-60-7	ACGIH	TWA(respirable	A2: Suspected human
Pulaskite)			fraction):0.025 mg/m3	carcin.
Quartz (a component of	14808-60-7	OSHA	TWA Table Z-	
Pulaskite)			1(respirable):0.05	
			mg/m3;TWA Table Z-	
			3(respirable):0.1 mg/m3	

3M Brand Roofing Granules - 4100L, 4600L & 4950L (Little Rock, AR) 12/20/16

Paraffin oil	64742-52-5	OSHA	TWA(as mist):5 mg/m3	
PETROLEUM DISTILLATES	64742-52-5	OSHA	TWA:2000 mg/m3(500 ppm)	

ACGIH: American Conference of Governmental Industrial Hygienists

AIHA: American Industrial Hygiene Association

CMRG: Chemical Manufacturer's Recommended Guidelines

OSHA: United States Department of Labor - Occupational Safety and Health Administration

TWA: Time-Weighted-Average STEL: Short Term Exposure Limit

CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Provide local exhaust ventilation at transfer points. Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Safety Glasses with side shields

Skin/hand protection

No chemical protective gloves are required.

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

General Physical Form:Solid **Specific Physical Form:**Granules

Odor, Color, Grade: Brown colors, slightly oily odor, typical particle size 0.84-2.0 mm

Melting pointNot ApplicableFlash PointNo flash pointFlammability (solid, gas)Not ClassifiedFlammable Limits(LEL)Not ApplicableFlammable Limits(UEL)Not Applicable

Specific Gravity 2.55 - 2.70 [Ref Std: WATER=1]

Solubility In WaterNot ApplicableSolubility- non-waterNot ApplicableAutoignition temperatureNot ApplicableDecomposition temperatureNot Applicable

Percent volatile Nil

SECTION 10: Stability and reactivity

10.1. Reactivity

Page 4 of 9

This material is considered to be non reactive under normal use conditions.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

None known.

10.5. Incompatible materials

None known.

10.6. Hazardous decomposition products

Substance

Condition

None known.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

May cause additional health effects (see below).

Skin Contact:

Mechanical Skin irritation: Signs/symptoms may include abrasion, redness, pain, and itching.

Eve Contact:

Mechanical eye irritation: Signs/symptoms may include pain, redness, tearing and corneal abrasion.

Ingestion:

May be harmful if swallowed.

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

Additional Health Effects:

Carcinogenicity:

Contains a chemical or chemicals which can cause cancer.

Ingredient	CAS No.	Class Description	Regulation
SILICA, CRYS AIRRESP	14808-60-7	Known human carcinogen	National Toxicology Program Carcinogens

Page 5 of 9

Quartz (a component of Pulaskite)	14808-60-7	Grp. 1: Carcinogenic to humans	International Agency for Research on Cancer
-----------------------------------	------------	--------------------------------	---

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Ingestion		No data available; calculated ATE 2,000 - 5,000
			mg/kg
Ceramic	Dermal		LD50 estimated to be > 5,000 mg/kg
Ceramic	Ingestion		LD50 estimated to be 2,000 - 5,000 mg/kg
Quartz (a component of Pulaskite)	Dermal		LD50 estimated to be > 5,000 mg/kg
Quartz (a component of Pulaskite)	Ingestion		LD50 estimated to be > 5,000 mg/kg
Oil	Dermal	Rabbit	LD50 > 2,000 mg/kg
Oil	Ingestion	Rat	LD50 > 5,000 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Kill Coll onto Il litteron				
Name	Species	Value		
	1			
Ceramic	Rabbit	No significant irritation		
Quartz (a component of Pulaskite)	Professio	No significant irritation		
	nal			
	judgeme			
	nt			
Oil	Rabbit	Minimal irritation		

Serious Eve Damage/Irritation

Strious Lyt Duminger Irritation		
Name	Species	Value
Ceramic	Rabbit	Mild irritant
Oil	Rabbit	Mild irritant

Skin Sensitization

Name	Species	Value	
Oil	Guinea	Not sensitizing	
	nia		

Respiratory Sensitization

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
Ceramic	In Vitro	Some positive data exist, but the data are not sufficient for classification
Quartz (a component of Pulaskite)	In Vitro	Some positive data exist, but the data are not sufficient for classification
Quartz (a component of Pulaskite)	In vivo	Some positive data exist, but the data are not sufficient for classification

Carcinogenicity

~ ··· · · · · · · · · · · · · · · · · ·			
Name	Route	Species	Value
Ceramic	Inhalation	Multiple animal species	Some positive data exist, but the data are not sufficient for classification
Quartz (a component of Pulaskite)	Inhalation	Human	Carcinogenic

3M Brand Roofing Granules - 4100L, 4600L & 4950L	(Little Rock, AR)	12/20/16	

		and animal	
Oil	Ingestion	Rat	Not carcinogenic
Oil	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification

Reproductive Toxicity

Reproductive and/or Developmental Effects

For the component/components, either no data are currently available or the data are not sufficient for classification.

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Specific Target Organ Toxicity - single exposure						
Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure
						Duration
Oil	Inhalation	respiratory irritation	Some positive data exist, but the		NOAEL Not	
			data are not sufficient for		available	
			classification			

Specific Target Organ Toxicity - repeated exposure

Specific ranger Organ	1 OAICIC	cpeated exposure				
Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure
						Duration
Ceramic	Inhalation	pulmonary fibrosis	Some positive data exist, but the	Multiple	NOAEL not	
			data are not sufficient for	animal	available	
			classification	species		
Ceramic	Inhalation	respiratory system	Some positive data exist, but the	Human	NOAEL not	occupational
			data are not sufficient for		available	exposure
			classification			
Quartz (a component of	Inhalation	silicosis	Causes damage to organs through	Human	NOAEL Not	occupational
Pulaskite)			prolonged or repeated exposure		available	exposure

Aspiration Hazard

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

Ecotoxicological information

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

Chemical fate information

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

SECTION 13: Disposal considerations

13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of waste product in a permitted industrial waste facility.

EPA Hazardous Waste Number (RCRA): Not regulated

Page 7 of 9

SECTION 14: Transport Information

For Transport Information, please visit http://3M.com/Transportinfo or call 1-800-364-3577 or 651-737-6501

SECTION 15: Regulatory information

15.1. US Federal Regulations

Contact 3M for more information.

311/312 Hazard Categories:

Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No Immediate Hazard - Yes Delayed Hazard - Yes

15.2. State Regulations

Contact 3M for more information.

California Proposition 65

<u>Ingredient</u>	<u>C.A.S. No.</u>	Classification
SILICA, CRYSTALLINE (AIRBORNE	None	Carcinogen
PARTICLES OF RESPIRABLE SIZE)		
Titanium Dioxide	13463-67-7	Carcinogen
Carbon Black	1333-86-4	Carcinogen

WARNING: This product contains a chemical known to the State of California to cause cancer.

15.3. Chemical Inventories

The components of this product are in compliance with the chemical notification requirements of TSCA.

Contact 3M for more information.

15.4. International Regulations

Contact 3M for more information.

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 16: Other information

NFPA Hazard Classification

Health: 1 Flammability: 0 Instability: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

 Document Group:
 19-3785-3
 Version Number:
 8.00

 Issue Date:
 12/20/16
 Supercedes Date:
 09/22/14

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY

Page 8 of 9

OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M

3M USA SDSs are available at www.3M.com