SSS Metal Cleaner & Polish

Section 1: PRODUCT AND COMPANY IDENTIFICATION

Product Name: SSS Metal Cleaner & Polish

Product Number: 05013

Product Use: Cleaner.

Manufacturer/Supplier: Triple S

2 Executive Park Dr. Billerica, MA 01862

Phone Number: (978) 667-7900 **D.O.T. Emergency Phone:** 1-(888) 779-1339

Date of Preparation: November 11, 2010 **Revision #**: 2.0

Section 2: HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

DANGER

EXTREMELY FLAMMABLE. HARMFUL BY INHALATION. MAY CAUSE EYE IRRITATION. MAY CAUSE SKIN IRRITATION. CONTENTS UNDER PRESSURE. CONTAINER MAY EXPLODE IF HEATED.

Potential Health Effects: See Section 11 for more information.

Likely Routes of Exposure: Skin contact, eye contact, inhalation, and ingestion.

Eye: May cause eye irritation.

Skin: May cause skin irritation.

Ingestion: Not a normal route of exposure. Harmful: may cause lung damage if swallowed.Inhalation: Harmful by inhalation. May cause respiratory tract irritation. Vapours may

cause drowsiness and dizziness. This product may be aspirated into the

HMIS: See Section 15

lungs and cause chemical pneumonitis.

Chronic Effects: Prolonged or repeated contact may dry skin and cause irritation.

Signs and Symptoms: Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva. Handling can cause dry skin.

Medical Conditions Aggravated By Exposure: Asthma. Allergies.

Target Organs: Skin, eyes, gastrointestinal tract, respiratory system.

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

Potential Environmental Effects: May cause long-term adverse effects in the aquatic environment. See Section 12 for more information.

Section 3: COMPOSITION / INFORMATION ON INGREDIENTS

Ingredient	CAS#	Wt. %
Distillates, (petroleum), hydrotreated light naphthenic	64742-53-6	30 - 60
Distillates (petroleum), hydrotreated light	64742-47-8	10 - 30
Isobutane	75-28-5	3 - 7
Propane	74-98-6	1 - 5

SSS Metal Cleaner & Polish

Section 4: FIRST AID MEASURES

Eye Contact: In case of contact, immediately flush eyes with plenty of water. If easy to do,

remove contact lenses, if worn.

Skin Contact: In case of contact, immediately flush skin with plenty of water. Remove

contaminated clothing and shoes. Wash clothing before reuse. Call a physician

if irritation develops and persists.

Inhalation: If inhaled, remove to fresh air. If not breathing, give artificial respiration. If

breathing is difficult, give oxygen.

Ingestion: If swallowed, do NOT induce vomiting unless directed to do so by medical

personnel. Never give anything by mouth to an unconscious person.

General Advice: In case of accident or if you feel unwell, seek medical advice immediately

(show the label or MSDS where possible).

Note to Physicians: Symptoms may not appear immediately.

Section 5: FIRE FIGHTING MEASURES

Flammability: Extremely flammable by OSHA criteria.

Means of Extinction:

Suitable Extinguishing Media: Powder, water spray, foam, carbon dioxide.

Unsuitable Extinguishing Media: Not available.

Products of Combustion: May include, and are not limited to: oxides of carbon.

Explosion Data:

Sensitivity to Mechanical Impact: Not available.

Sensitivity to Static Discharge: Not available.

Protection of Firefighters: Containers may explode when heated. Spills of this material are a slipping hazard. Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA).

Section 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions: Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel. Eliminate sources of ignition. Ruptured cylinders may rocket.

Environmental Precautions: Many gases are heavier than air and will spread along ground and collect in low or confined areas (sewers, basements, tanks). This material is a water pollutant. Keep out of drains, sewers, ditches, and waterways. Minimize use of water to prevent environmental contamination.

Methods for Containment: Contain and/or absorb spill with inert material (e.g. sand, vermiculite), then place in a suitable container. Do not flush to sewer or allow to enter waterways. Use appropriate Personal Protective Equipment (PPE).

Methods for Clean-Up: Vacuum or sweep material and place in a disposal container. Allow gas to dissipate harmlessly into the atmosphere.

Other Information: Not available.

SSS Metal Cleaner & Polish

Section 7: HANDLING AND STORAGE

Handling:

Keep away from sources of ignition. No smoking. Avoid contact with skin and eyes. Do not swallow. Do not breathe gas/fumes/vapor/spray. Use only in well-ventilated areas. Handle and open container with care. When using, do not eat or drink. Wash hands before eating, drinking, or smokina.

Storage:

Keep out of the reach of children. Keep container in a well-ventilated place. Do not store at temperatures above 49°C / 120°F.

Section 8: EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Guidelines

Exposure Limits Ingredient OSHA-PEL **ACGIH-TLV** Distillates, (petroleum), hydrotreated light naphthenic 5 mg/m³ (mist) 5 mg/m³ (mist) 100 ppm 200 mg/m³ Distillates (petroleum), hydrotreated light Not available. 1000 ppm Isobutane Propane 1000 ppm 1000 ppm

Engineering Controls: Use ventilation adequate to keep exposures (airborne levels of dust, fume, vapor, etc.) below recommended exposure limits.

Personal Protective Equipment: HMIS: See Section 15

Eye/Face Protection: Wear eye/face protection.

Hand Protection: Wear suitable gloves.

Skin and Body Protection: Wear suitable protective clothing.

Respiratory Protection: In case of insufficient ventilation, wear suitable respiratory equipment.

General Hygiene Considerations: Handle according to established industrial hygiene and

safety practices.

Section 9: PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Clear. Color: Yellow. Odour: Citrus.

Odour Threshold: Not available.

Physical State: Gas/Pressurized Liquid.

pH: Not applicable. Viscosity: Not available. Freezing Point: Not available. **Boiling Point:** Not available. Flash Point: Not available. **Evaporation Rate:** Not available. **Lower Flammability Limit:** Not available. **Upper Flammability Limit:** Not available.

SSS Metal Cleaner & Polish

Vapor Pressure: Not available.
Vapor Density: Not available.

Specific Gravity: 0.856 (Concentrate only)

Solubility in Water: Insoluble.

Coefficient of Water/Oil Distribution: Not available.

Auto-ignition Temperature: Not available.

Percent Volatile, wt. %: Not available.

VOC content, wt. %: 15% (US federal/CARB/OTC/LADCO)

VOC content, g/L:Not available.

Section 10: STABILITY AND REACTIVITY

Stability: Stable under normal storage conditions. Contents under pressure. Container may explode if heated. Do not puncture. Do not burn. Keep in a cool place.

Conditions of Reactivity: Heat. Incompatible materials.

Incompatible Materials: Oxidizers.

Hazardous Decomposition Products: May include, and are not limited to: oxides of carbon. **Possibility of Hazardous Reactions:** No dangerous reaction known under conditions of normal use.

Section 11: TOXICOLOGY INFORMATION

EFFECTS OF ACUTE EXPOSURE

Component Analysis

Eye: May cause eye irritation. Symptoms may include discomfort or pain, excess

blinking and tear production, with marked redness and swelling of the conjunctiva.

Skin: May cause skin irritation. Handling can cause dry skin.

Ingestion: Not a normal route of exposure. Harmful: may cause lung damage if swallowed. **Inhalation:** Harmful by inhalation. May cause respiratory tract irritation. Vapours may cause

drowsiness and dizziness. This product may be aspirated into the lungs and

cause chemical pneumonitis.

EFFECTS OF CHRONIC EXPOSURE

Target Organs: Not available.

Chronic Effects: Not hazardous by OSHA criteria. **Carcinogenicity:** Not hazardous by OSHA criteria.

SSS Metal Cleaner & Polish

Ingredient

Chemical Listed as Carcinogen or Potential Carcinogen *

Not listed. I -3, G-A3 Not listed. Not listed.

Distillates, (petroleum), hydrotreated light naphthenic Distillates (petroleum), hydrotreated light Isobutane

Propane

* See Section 15 for more information.

Mutagenicity: Not hazardous by OSHA criteria.

Reproductive Effects: Not hazardous by OSHA criteria.

Developmental Effects:

Teratogenicity: Not hazardous by OSHA criteria.

Embryotoxicity: Not hazardous by OSHA criteria.

Respiratory Sensitization: Not hazardous by OSHA criteria.

Skin Sensitization: Not hazardous by OSHA criteria. **Toxicologically Synergistic Materials:** Not available.

Section 12: ECOLOGICAL INFORMATION

Ecotoxicity: May cause long-term adverse effects in the aquatic environment

Persistence / Degradability: Not available.

Bioaccumulation / Accumulation: Not available.

Mobility in Environment: Not available.

Section 13: DISPOSAL CONSIDERATIONS

Disposal Instructions:

This material must be disposed of in accordance with all local, state, provincial, and federal regulations.

Section 14: TRANSPORTATION INFORMATION

DOT Classification

ORM-D

Section 15: REGULATORY INFORMATION

Federal Regulations

US: MSDS prepared pursuant to the Hazard Communication Standard (29 CFR 1910.1200).

SARA Title III

Section 302 (EHS) TPQ (lbs.)	Section 304 EHS RQ (lbs.)	CERCLA RQ (lbs.)	Section 313
Not listed.	Not listed.	Not listed.	Not listed.
Not listed.	Not listed.	Not listed.	Not listed.
Not listed.	Not listed.	Not listed.	Not listed.
Not listed.	Not listed.	Not listed.	Not listed.
	Not listed. Not listed. Not listed. Not listed.	(EHS) TPQ (lbs.) EHS RQ (lbs.) Not listed. Not listed. Not listed. Not listed. Not listed. Not listed.	(EHS) TPQ (lbs.) EHS RQ (lbs.) RQ (lbs.) Not listed. Not listed. Not listed. Not listed. Not listed. Not listed. Not listed. Not listed. Not listed.

SSS Metal Cleaner & Polish

State Regulations

California Proposition 65:

This product does not contain a chemical known to the State of California to cause cancer, birth defects or other reproductive harm.

Global Inventories

Ingredient	USA
	TSCA
Distillates, (petroleum), hydrotreated light naphthenic	Yes.
Distillates (petroleum), hydrotreated light	Yes.
Isobutane	Yes.
Propane	Yes.

HMIS - Hazardous Materials Identification System

Health - 2 Flammability - 3 Physical Hazard - 0 PPE - B

NFPA - National Fire Protection Association:

Health - 2 Fire - 3 Reactivity - 0

Hazard Rating: 0 = minimal, 1 = slight, 2 = moderate, 3 = severe, 4 = extreme

SOURCE AGENCY CARCINOGEN CLASSIFICATIONS:

OSHA (O) Occupational Safety and Health Administration.

ACGIH (G) American Conference of Governmental Industrial Hygienists.

A1 - Confirmed human carcinogen. A2 - Suspected human carcinogen.

A3 - Animal carcinogen.

A4 - Not classifiable as a human carcinogen.

A5 - Not suspected as a human carcinogen.

IARC (I) International Agency for Research on Cancer.

1 - The agent (mixture) is carcinogenic to humans.

2A - The agent (mixture) is probably carcinogenic to humans; there is limited evidence of carcinogenicity in humans and sufficient evidence of carcinogenicity in experimental animals.

2B - The agent (mixture) is possibly carcinogenic to humans; there is limited evidence of carcinogenicity in humans in the absence of sufficient evidence of carcinogenicity in experimental animals.

3 - The agent (mixture, exposure circumstance) is not classifiable as to its carcinogenicity to humans.

4 - The agent (mixture, exposure circumstance) is probably not carcinogenic to humans.

NTP (N) National Toxicology Program.

- 1 Known to be carcinogens.
- 2 Reasonably anticipated to be carcinogens.

Section 16: OTHER INFORMATION

Disclaimer:

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.

Prepared by: Nexreg Compliance Inc.

Prepared for: Triple S

Phone: (978) 667-7900