SAFETY DATA SHEET

SECTION I -PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: Mineral Oil

PRODUCT TYPE:Liquid Metal Protector

SECTION II - INGREDIENTS

INGREDIENT

Light Mineral Oil U.S.P.

wearing.

C.A.S. NUMBER

8042-47-5

SECTION III - HAZARDS IDENTIFICATION

ROUTE(S) OF ENTRY:	Ingestion. Not likely to be inhaled in dangerous
amounts.	
LISTED CARCINOGEN:	Not listed by IARC, NTP or OSHA.
MEDICAL CONDITION AGGRAVATED	:.May aggravate pre-existing dermatitis.
INHALATION:	Not likely to be inhaled in hazardous amounts.
Maintain adequate ventilation in the	e work area.
INGESTION:	Large amounts can be irritating if ingested.
EYES:	May cause eye irritation.
SKIN (DERMAL):	Not likely to irritate. Prolonged exposure to
undiluted product may cause irritation	on.

SECTION IV - FIRST AID

SWALLOWING (INGESTION):	DO NOT INDUCE VOMITING! Drink a large quantity			
of water or milk. Do not attempt to give liquids to an unconscious person. Get				
immediate medical attention!				
EYES:	Flush eyes with a large quantity of fresh water for at			
least 15 minutes. If irritation persists, consult a physician.				
SKIN (DERMAL):	Flush from skin and clothing with large amounts of			
fresh water. If irritation persists, cons	sult physician. Wash contaminated clothing before			

SECTION V - FIRE AND EXPLOSION DATA

	OLO II OI	TIME THE EXILECTION DITIN		
	FLASHPOINT:	355 degrees F. (ASTM D-92)		
	EXTINGUISHING MEDIA:	Carbon dioxide, foam and/or dry chemical may		
	be used.			
	SPECIAL FIRE FIGHTING PROCEDURES:	:.Firefighters working in areas where this product is		
	present should be equipped with an	approved, fully enclosed SCBA.		
	UNUSUAL FIRE AND EXPLOSION HAZA	ARDS:None known.		
SECTION VI – RELEASE MEASURES				

SPILL:Dike to prevent spillage into streams or sewer systems. Consult local, state and federal authorities.

SECTION VII - HANDLING & STORAGE

HANDLING & STORAGE PRECAUTIONS:Store in a cool, well ventilated area. Avoid overheating or freezing.

SECTION VIII - EMPLOYEE PROTECTION

RESPIRATORY PROTECTION: Not usually needed in well-ventilated areas. If needed, use a NIOSH approved respirator.

PROTECTIVE CLOTHING:.....Special protection not usually needed. Wear eye protection if product is likely to splash.

SECTION IX - PHYSICAL DATA

APPEARANCE: Slightly viscous transparent liquid. No significant odor.

VAPOR PRESSURE:N/A **VAPOR DENSITY (AIR=1):** Greater than 1.

SPECIFIC GRAVITY:0.83 pH:N/A

BOILING POINT:550 degrees F. **SOLUBILITY IN WATER:** Insoluble.

SECTION X - REACTIVITY DATA

STABILITY:	Stable under normal conditions.
HAZARDOUS POLYMERIZATION:	This product not known to polymerize.
INCOMPATIBILITY:	Do not mix with other chemicals.
HAZARDOUS BYPRODUCTS	Carbon monoxide, carbon dioxide.

SECTION XI - TOXICOLOGICAL INFORMATION

INGREDIENT	C.A.S. NUMBER	PEL
Light Mineral Oil U.S.P.	8042-47-5	5 mg/m3 (mist)

SECTION XII - ECOLOGICAL INFORMATION

This information is not available

SECTION XIII - DISPOSAL PROCEDURES

WASTE DISPOSAL:As recommended by local, state and federal authorities.

SECTION XIV - TRANSPORTATION INFORMATION

PROPER SHIPPING NAME: Not D.O.T.

regulated.

SECTION XV - REGULATORY INFORMATION

WARNING: The information contained in this MSDS is based on

the data available to us from sources we believe to be reliable. No warranty or guaranty expressed or implied is made regarding the accuracy of this data or the results obtained from the reliance on this data. The manufacturer assumes no responsibility for injury from the use of this product. Be safe- read this product safety information and pass it on to all persons who may be exposed to this product. Federal law requires it. This product and/or all of its components are either included on or exempt from the TSCA Inventory of Chemical Substances.

SECTION XVI - OTHER INFORMATION

NFPA HEALTH: 1

NFPA FLAMMABILITY: 1
NFPA REACTIVITY: 0
NFPA OTHER: None

This product meets the requirements of the US FDA as per 21 CFR 172.878 and 21 CFR 178.3620(a)