

MATERIAL SAFETY DATA SHEET

Product Trade Name: 10% WEIGHTED HYDROCHLORIC ACID

Revision Date: 21-Dec-2012

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Trade Name: 10% WEIGHTED HYDROCHLORIC ACID
Synonyms: None
Chemical Family: Inorganic acid
Application: Solvent

Manufacturer/Supplier Halliburton Energy Services
P.O. Box 1431
Duncan, Oklahoma 73536-0431
Emergency Telephone: (281) 575-5000

Prepared By Chemical Compliance
Telephone: 1-580-251-4335
e-mail: fdunexchem@halliburton.com

2. COMPOSITION/INFORMATION ON INGREDIENTS

Substances	CAS Number	PERCENT	ACGIH TLV-TWA	OSHA PEL-TWA
Calcium chloride	10043-52-4	10 - 30%	Not applicable	Not applicable
Ethylene glycol monobutyl ether	111-76-2	10 - 30%	20 ppm	50 ppm
Hydrochloric acid	7647-01-0	10 - 30%	2 ppm	5 ppm

3. HAZARDS IDENTIFICATION

Hazard Overview May cause eye, skin, and respiratory burns. May cause headache, dizziness, and other central nervous system effects. May be absorbed through the skin. May be harmful if swallowed.

4. FIRST AID MEASURES

Inhalation If inhaled, remove to fresh air. If not breathing give artificial respiration, preferably mouth-to-mouth. If breathing is difficult give oxygen. Get medical attention.

Skin In case of contact, immediately flush skin with plenty of soap and water for at least 15 minutes. Get medical attention. Remove contaminated clothing and launder before reuse.

Eyes In case of contact, or suspected contact, immediately flush eyes with plenty of water for at least 15 minutes and get medical attention immediately after flushing.

Ingestion Do not induce vomiting. Slowly dilute with 1-2 glasses of water or milk and seek medical attention. Never give anything by mouth to an unconscious person.

Notes to Physician Not Applicable

5. FIRE FIGHTING MEASURES

Flash Point/Range (F):	> 150
Flash Point/Range (C):	> 66
Flash Point Method:	PMCC
Autoignition Temperature (F):	Not Determined
Autoignition Temperature (C):	PMCC
Flammability Limits in Air - Lower (%):	Not Determined
Flammability Limits in Air - Upper (%):	Not Determined

Fire Extinguishing Media Water fog, carbon dioxide, foam, dry chemical.

Special Exposure Hazards May form explosive mixtures with strong alkalis. Decomposition in fire may produce toxic gases. Reaction with steel and certain other metals generates flammable hydrogen gas. Do not allow runoff to enter waterways.

Special Protective Equipment for Fire-Fighters Full protective clothing and approved self-contained breathing apparatus required for fire fighting personnel.

NFPA Ratings: Health 3, Flammability 2, Reactivity 1
HMS Ratings: Health 3, Flammability 2, Reactivity 1

6. ACCIDENTAL RELEASE MEASURES

Personal Precautionary Measures Use appropriate protective equipment.

Environmental Precautionary Measures Prevent from entering sewers, waterways, or low areas.

Procedure for Cleaning / Absorption Isolate spill and stop leak where safe. Contain spill with sand or other inert materials. Neutralize to pH of 6-8. Scoop up and remove.

7. HANDLING AND STORAGE

Handling Precautions Avoid contact with eyes, skin, or clothing. Avoid breathing vapors. Wash hands after use. Launder contaminated clothing before reuse.

Storage Information Store away from alkalis. Store away from oxidizers. Store in a cool well ventilated area. Keep container closed when not in use.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Controls Use in a well ventilated area. Local exhaust ventilation should be used in areas without good cross ventilation.

Respiratory Protection Acid gas respirator.

Hand Protection Impervious rubber gloves.

Skin Protection Rubber boots. Full protective chemical resistant clothing.

Eye Protection Chemical goggles; also wear a face shield if splashing hazard exists.

Other Precautions Eyewash fountains and safety showers must be easily accessible.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State: Liquid

9. PHYSICAL AND CHEMICAL PROPERTIES

Color:	Clear colorless
Odor:	Pungent acrid
pH:	0.8
Specific Gravity @ 20 C (Water=1):	Not Determined
Density @ 20 C (lbs./gallon):	Not Determined
Bulk Density @ 20 C (lbs/ft3):	Not Determined
Boiling Point/Range (F):	Not Determined
Boiling Point/Range (C):	Not Determined
Freezing Point/Range (F):	Not Determined
Freezing Point/Range (C):	Not Determined
Vapor Pressure @ 20 C (mmHg):	Not Determined
Vapor Density (Air=1):	Not Determined
Percent Volatiles:	Not Determined
Evaporation Rate (Butyl Acetate=1):	Not Determined
Solubility in Water (g/100ml):	Soluble
Solubility in Solvents (g/100ml):	Not Determined
VOCs (lbs./gallon):	Not Determined
Viscosity, Dynamic @ 20 C (centipoise):	Not Determined
Viscosity, Kinematic @ 20 C (centistokes):	Not Determined
Partition Coefficient/n-Octanol/Water:	Not Determined
Molecular Weight (g/mole):	Not Determined

10. STABILITY AND REACTIVITY

Stability Data:	Stable
Hazardous Polymerization:	Will Not Occur
Conditions to Avoid	None anticipated
Incompatibility (Materials to Avoid)	Strong alkalis. Strong oxidizers.
Hazardous Decomposition Products	Chlorine. Hydrogen sulfide. Flammable hydrogen gas. Carbon monoxide and carbon dioxide.
Additional Guidelines	Not Applicable

11. TOXICOLOGICAL INFORMATION

Principle Route of Exposure	Eye or skin contact, inhalation.
Inhalation	Causes severe respiratory irritation. May cause central nervous system depression including headache, dizziness, drowsiness, incoordination, slowed reaction time, slurred speech, giddiness and unconsciousness.
Skin Contact	May cause skin burns. May be absorbed through the skin and produce effects similar to those caused by inhalation and/or ingestion.
Eye Contact	May cause eye burns.
Ingestion	Causes burns of the mouth, throat and stomach. May produce nervous system effects such as feeling of weakness, unsteady walk, and dilation of blood vessels.
Aggravated Medical Conditions	Skin disorders.
Chronic Effects/Carcinogenicity	Prolonged, excessive exposure may cause erosion of the teeth. Prolonged or repeated exposure may cause fetal damage and testicular effects.

Other Information None known.

Toxicity Tests

Oral Toxicity:	Not determined
Dermal Toxicity:	Not determined
Inhalation Toxicity:	LC50: 3124 ppm/1 hr. (Rat)
Primary Irritation Effect:	Not determined
Carcinogenicity	Not determined
Genotoxicity:	Not determined
Reproductive / Developmental Toxicity:	Not determined

12. ECOLOGICAL INFORMATION

Mobility (Water/Soil/Air) Not determined

Persistence/Degradability Not determined

Bio-accumulation Not determined

Ecotoxicological Information

Acute Fish Toxicity:	Not determined
Acute Crustaceans Toxicity:	Not determined
Acute Algae Toxicity:	Not determined

Chemical Fate Information Not determined

Other Information Not applicable

13. DISPOSAL CONSIDERATIONS

Disposal Method Disposal should be made in accordance with federal, state, and local regulations.

Contaminated Packaging Follow all applicable national or local regulations.

14. TRANSPORT INFORMATION

Land Transportation

DOT

UN1789, Hydrochloric Acid Solution, 8, II
RQ (Hydrochloric Acid - 22730 kg.)
NAERG 157

Canadian TDG

Hydrochloric Acid Solution, 8, UN1789, II

ADR

UN1789,Hydrochloric Acid Solution, 8, II

Air Transportation

ICAO/IATA

UN1789,Hydrochloric Acid Solution, 8, II
RQ (Hydrochloric Acid - 22730 kg.)

Sea Transportation

IMDG

UN1789,Hydrochloric Acid Solution, 8, II
RQ (Hydrochloric Acid - 22730 kg.)
EmS F-A, S-B

Other Transportation Information

Labels: Corrosive

15. REGULATORY INFORMATION

US Regulations

US TSCA Inventory All components listed on inventory or are exempt.

EPA SARA Title III Extremely Hazardous Substances Not applicable

EPA SARA (311,312) Hazard Class Acute Health Hazard
Chronic Health Hazard
Fire Hazard

EPA SARA (313) Chemicals This product does not contain a toxic chemical for routine annual "Toxic Chemical Release Reporting" under Section 313 (40 CFR 372).

EPA CERCLA/Superfund Reportable Spill Quantity EPA Reportable Spill Quantity is 1592 Gallons based on Hydrochloric acid (CAS: 7647-01-0).

EPA RCRA Hazardous Waste Classification If product becomes a waste, it does meet the criteria of a hazardous waste as defined by the US EPA, because of:

Corrosivity D002

California Proposition 65 All components listed do not apply to the California Proposition 65 Regulation.

MA Right-to-Know Law One or more components listed.

NJ Right-to-Know Law One or more components listed.

PA Right-to-Know Law One or more components listed.

Canadian Regulations

Canadian DSL Inventory All components listed on inventory or are exempt.

16. OTHER INFORMATION

The following sections have been revised since the last issue of this MSDS

Not applicable

Additional Information

For additional information on the use of this product, contact your local Halliburton representative.

For questions about the Material Safety Data Sheet for this or other Halliburton products, contact Chemical Compliance at 1-580-251-4335.

Disclaimer Statement

This information is furnished without warranty, expressed or implied, as to accuracy or completeness. The information is obtained from various sources including the manufacturer and other third party sources. The information may not be valid under all conditions nor if this material is used in combination with other materials or in any process. Final determination of suitability of any material is the sole responsibility of the user.

*****END OF MSDS*****