PART I

What is the material and what do I need to know in an emergency?

1. PRODUCT IDENTIFICATION

TRADE NAME (AS LABELED): NITE WHITE ACP, Unflavored/Cherry/Mint, 10 -22%

<u>CHEMICAL NAME/CLASS:</u> Tooth Whitener/Bleach <u>PRODUCT USE:</u> Dental Care Product

SUPPLIER/MANUFACTURER'S NAME: DISCUS DENTAL Incorporated

ADDRESS: 8550 Higuera Street, Culver City, CA 90232

 MSDS MESSAGE LINE:
 (310) 845 - 8450

 BUSINESS PHONE:
 (310) 845 - 8200

 DATE OF PREPARATION:
 April 25, 2005

This product is sold for commercial use. This MSDS has been developed to address safety concerns of those individuals working with bulk quantities of this material, as well as those of potential users of this product in industrial /occupational settings. All pertinent health, safety and environmental information has been presented based on ANSI Z400.1-2003, the US Federal OSHA Hazard Communication Standard (29 CFR 1910.1200) and Canadian Workplace Hazardous Materials Information System (WHMIS) and Controlled Products Regulations (CPR).

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

PHYSICAL DESCRIPTION: This product is a gel with a characteristic odor, depending on gel flavor.

WARNINGS (per ANSI Z129.1

CAUTION! OXIDIZER. HARMFUL IF SWALLOWED. EYE, SKIN, AND RESPIRATORY TRACT IRRITANT.

PRECAUTIONS (per ANSI Z129.1):

Do not breathe fumes, dusts, vapors or mist. Do not swallow or take internally. Do not get in eyes or on clothing. Wash thoroughly after handling. Keep container closed. Use only in a well-ventilated area. Do not expose to heat or store at temperatures above 120°F.

HAZARD SYMBOLS:

HMIS HAZARDOUS MATERIALS IDENTIFICATION SYSTEM (HMIS)

Health	1
Flammability	1
Physical Hazard	0
Protective Equipment	В

HMIS PERSONAL PROTECTIVE EQUIPMENT RATING: Industrial Use situations: B; Safety Glasses, Gloves.

CANADIAN WHMIS SYMBOLS:

C - Oxidizing Materials

D2B - Poisonous and infectious material - Other effects - Toxic


F - Dangerously Reactive Material







This product has been classified in accordance with the hazard criteria of the Canadian Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR.



NFPA RATING

OSHA REGULATORY STATUS

This material is classified as hazardous under OSHA regulations.

POTENTIAL HEALTH EFFECTS

The most significant routes of occupational overexposure are ingestion and contact with skin and eyes. The symptoms of overexposure to this product are as follows:

<u>CONTACT WITH SKIN or EYES</u>: Contact can cause eye or skin irritation. Prolonged skin contact can result in dermatitis. Prolonged eye exposure may include redness, pain, and tearing. This product can irritate the eyes. If this product contaminates the eyes, eye injury can occur. Prolonged skin contact can result in redness, pain, ulceration and scarring.

SKIN ABSORPTION: No component of this product is reported to be absorbed through intact skin.

<u>INGESTION</u>: If the product is swallowed, irritation of the mouth, throat, and other tissues of the gastro-intestinal system can occur. Ingestion of large amounts can cause irritation, pain, vomiting, and diarrhea. If vomiting results in aspiration, chemical pneumonia could follow.

INHALATION: Overexposure to vapors, mists, sprays, or dusts of this product can cause irritation to the respiratory tract.

<u>INJECTION</u>: Accidental injection of this product can cause burning, reddening, and swelling in addition to the wound. Symptoms of such exposure can include those described under "Inhalation", "Contact with Skin or Eyes," and "Ingestion".

<u>CHRONIC EFFECTS:</u> Long-term skin or eye contact can result in dermatitis or eye irritation.

<u>SIGNS AND SYMPTOMS OF OVEREXPOSURE:</u> Eye and skin irritation (redness or swelling). See Section 11: TOXICOLOGICAL INFORMATION.

POTENTIAL ENVIRONMENTAL EFFECTS

This product does not normally present a significant hazard to aquatic or terrestrial life in small quantities. Do not discharge effluent containing this product into streams, ponds, estuaries, oceans or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance, contact your State Water Board or Regional Office of the EPA. See Section 12: ECOLOGICAL INFORMATION.

3. HAZARD IDENTIFICATION

CHEMICAL NAME	% w/w
Water Conditioners	55-67
Supporting matrix	7-17
Whitening agents	7-16
Water and ingredients present in concentrations of less than 1%	Balance

(or less than 0.1% if carcinogens)

The ingredients in the balance of this product do not contribute significant hazards beyond those described in this document.

PART II

What should I do if a hazardous situation occurs?

4. FIRST-AID MEASURES

Victims of chemical exposure must be taken for medical attention if any adverse effects occur. Take a copy of label and MSDS to physician or health professional with victim.

FIRST AID PROCEDURES

<u>SKIN EXPOSURE</u>: If this product contaminates the skin, decontaminate with running water. Remove exposed or contaminated clothing, taking care not to contaminate eyes. Victim must seek immediate medical attention if any adverse exposure symptoms develop.

EYE EXPOSURE: If this product enters the eyes, open victim's eyes while under gently running water. Use sufficient force to open eyelids. Have victim "roll" eyes. Minimum flushing is for 15 minutes. Victim must seek medical attention.

<u>INHALATION</u>: If vapors, mists, or sprays of this product are inhaled, remove victim to fresh air. Victim must seek immediate medical attention if any adverse exposure symptoms develop. If necessary, use artificial respiration to support vital functions.

<u>INGESTION</u>: If a quantity of this product is swallowed in excess of amount normally swallowed during routine dental treatment, CALL PHYSICIAN OR POISON CONTROL CENTER FOR MOST CURRENT INFORMATION. DO NOT INDUCE VOMITING, unless directed by medical personnel. Have victim rinse mouth with water, if conscious. Never induce vomiting or give a diluent (e.g., water) to someone who is <u>unconscious</u>, <u>having convulsions</u>, <u>or unable to swallow</u>. If contaminated individual is convulsing, maintain an open airway and obtain immediate medical attention.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE: Persons with pre-existing skin disorders, eye problems, or impaired respiratory function can be more susceptible to health effects associated with overexposures to this product.

NOTE TO PHYSICIANS

Treat symptoms and eliminate overexposure.

5. FIRE-FIGHTING MEASURES

FLAMMABLE PROPERTIES

This product requires considerable pre-heating before ignition and combustion will occur. This material will not significantly contribute to the intensity of a fire. Use extinguishing material suitable to the surrounding fire. Not sensitive to mechanical impact under normal conditions. Not sensitive to static discharge under normal conditions.

EXTINGUISHING MEDIA

SUITABLE EXTINGUISHING MEDIA:

Water Spray: OK <u>Carbon Dioxide:</u> OK Foam: OK <u>Dry Chemical:</u> OK

Halon: OK Other Any "ABC" Class

UNSUITABLE EXTINGUISHING MEDIA:

None

PROTECTION OF FIREFIGHTERS

SPECIFIC HAZARDS ARISING FROM THE CHEMICAL:

When involved in a fire, this material can decompose and produce irritating fumes and toxic gases (e.g., Carbon monoxide, Carbon dioxide, Oxides of Nitrogen). Exposure to heat may cause containers to rupture due to thermal expansion of compressed gases and liquids.

PROTECTIVE EQUIPMENT AND PRECAUTIONS FOR FIREFIGHTERS:

Incipient fire responders should wear eye protection. Structural firefighters must wear Self-Contained Breathing Apparatus and full protective equipment. Move containers from fire area if it can be done without risk to personnel. If possible, prevent runoff water from entering storm drains, bodies of water, or other environmentally sensitive areas. Isolate from incompatible chemicals (see Section 10, Stability and Reactivity), heat, sparks, electrical equipment, and open flame.

6. ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS

Responders should wear the level of protection appropriate to the type of chemical released, the volume or amount of the material spilled, and the location where the incident has occurred. Level D Protective Equipment (gloves, chemical resistant apron, boots, and eye protection) should be adequate for this product under most circumstances.

ENVIRONMENTAL PRECAUTIONS

Minimize use of water to prevent environmental contamination. Prevent spill or rinsate from contamination of storm drains, sewers, soil or groundwater. Place all spill residues in a suitable container and seal. Dispose of in accordance with applicable U.S. Federal, State, or local procedures or appropriate standards of Canada (see Section 13, Disposal Considerations)

METHODS FOR CONTAINMENT

<u>SPILL AND LEAK RESPONSE</u>: Trained personnel using pre-planned procedures should respond to uncontrolled releases. Proper protective equipment should be used. In case of a spill, clear the affected area and protect people.

<u>RESPONSE TO INCIDENTAL RELEASES</u>: Personnel who have received basic chemical safety training can generally handle small-scale releases, such as 1 container of this product. Respond to incidental chemical releases by wearing gloves, goggles, and appropriate body protection.

<u>RESPONSE TO NON-INCIDENTAL RELEASES</u>: Respond to non-incidental chemical releases of this product, such as the simultaneous puncturing of several containers, by clearing the impacted area and contacting appropriate emergency personnel. Clean up should only be done by qualified personnel.

METHODS FOR CLEAN-UP

Prevent spill or rinsate from contaminating storm drains, sewers, soil or groundwater. Absorb spilled liquid with polypads or other suitable absorbent materials. Vacuum or sweep material and place in a disposal container. Decontaminate the area thoroughly.

OTHER INFORMATION

US regulations require reporting spills of this material that could reach any surface waters. The toll-free phone number for the US Coast Guard National Response Center is 1-800-424-8802.

7. HANDLING and STORAGE

HANDLING

As with all chemicals, avoid getting this product ON YOU or IN YOU. Wash thoroughly after using this product. Do not eat or drink while using this material. Avoid generating dusts, mists or sprays of this product. Remove contaminated clothing immediately. Do not breathe (dust, vapor, mist, gas). Avoid contact with eyes or clothing. In the event of a spill, follow practices indicated in Section 6 (Accidental Release Measures). Collect any rinsates and dispose of according to applicable U.S. Federal, State, or local procedures or appropriate Canadian standards. All employees who handle this material should be trained to use it safely. Open containers carefully on a stable surface. Empty containers can contain residual material; therefore, empty containers should be handled with care.

STORAGE

This product is stable under ordinary conditions of handling, use and storage. Store containers in a cool, dry location, away from direct sunlight, sources of intense heat, or where freezing is possible. Store away from incompatible materials (see Section 10, Stability and Reactivity). Keep container tightly closed when not in use. Inspect all incoming containers before storage, to ensure containers are properly labeled and not damaged.

8. EXPOSURE CONTROLS - PERSONAL PROTECTION

EXPOSURE GUIDELINES:

CHEMICAL NAME	<u>Guideline</u>	<u>Value</u>
Water Conditioners	TLV-TWA (ACGIH)	10 ppm
	PEL- TWA (OSHA)	15 mg/m ³ (total dust)
		5 mg/m ³ (respirable fraction)
Supporting Matrix	TLV-TWA (ACGIH)	10 mg/m^3
		(For CAS# 112926- 00-8)
	PEL- TWA (OSHA)	20 mppcf or
	, ,	80/(%SiO ₂)
REL-TWA (NIOSH)		6 mg/m ³
	IDLH (NIOSH)	3,000 mg/m ³
Whitening Agents	TLV-TWA (ACGIH)	1.4 mg/m^3
	PEL- TWA (OSHA)	1.4 mg/m^3
	REL-TWA (NIOSH)	1.4 mg/m^3
	IDLH (NIOSH)	75 ppm

NE = Not Established. See Section 16 for Definitions of Terms Used.

ENGINEERING CONTROLS

Use with adequate ventilation to ensure exposure levels are maintained below the limits provided above. Ensure eyewash/safety shower stations are available near areas where this product is used.

PERSONAL PROTECTIVE EQUIPMENT (PPE)

EYE/FACE PROTECTION

For specific industrial applications, enhanced eye protection can be necessary. Use approved safety goggles or safety glasses, as described in OSHA 29 CFR 1910.133. If necessary, refer to U.S. OSHA 29 CFR 1910.133, or appropriate Canadian standards.

SKIN PROTECTION

For specific industrial applications, wear chemical impervious gloves (e.g., Neoprene or Nitrile). If necessary, refer to U.S. OSHA 29 CFR 1910.138 or the appropriate standards of Canada. For consumer use, no specific body protection is normally needed.

BODY PROTECTION

For general industrial applications, chemically protective clothing is not normally needed. Use chemically protective clothing appropriate for task (e.g., Tyvek suit, rubber apron).

RESPIRATORY PROTECTION

None needed under normal conditions of use or handling. Use NIOSH approved respirators if ventilation is inadequate to control dusts, mists, fumes or vapors. Maintain airborne contaminate concentrations below guidelines listed above. Oxygen levels below 19.5% are considered IDLH by OSHA. In such atmospheres use of a full-face-piece pressure/demand SCBA or a full face-piece, supplied air respirator with auxiliary self-contained air supply is required under OSHA's Respiratory Protection Standard (29 CFR 1910.134).

9. PHYSICAL and CHEMICAL PROPERTIES

PHYSICAL PROPERTIES

RELATIVE VAPOR DENSITY (air = 1):Not AvailableEVAPORATION RATE (BuAc = 1):Not AvailableSPECIFIC GRAVITY:> 1MELTING/FREEZING POINT:Not AvailableSOLUBILITY IN WATER:MiscibleBOILING POINT:Not Available

<u>VAPOR PRESSURE, mm Hg @ 20°C</u>: Not Available <u>pH</u>: ~6.5

COEFFICIENT OF OIL/WATER DISTRIBUTION (PARTITION COEFFICIENT)

Not Available

PHYSICAL STATE, APPEARANCE AND Translucent to waxy gel with odor characteristic of flavoring ingredients. COLOR

<u>HOW TO DETECT THIS SUBSTANCE (warning properties)</u>: The appearance and odor of this product can act as warning properties in the event of an accidental release

CHEMICAL PROPERTIES

ODOR THRESHOLD: Not Available

FLASH POINT: Not determined <u>AUTOIGNITION TEMPERATURE</u>: Not determined

FLAMMABLE LIMITS (in air by volume, %):

<u>Lower</u>: Not determined <u>Upper</u>: Not determined

10. STABILITY and REACTIVITY

CHEMICAL STABILITY

Stable under normal circumstances of use and handling.

CONDITIONS TO AVOID

Avoid contact with incompatible chemicals and exposure to extreme temperatures.

INCOMPATIBLE MATERIALS

This product is not compatible with strong bases and strong acids.

HAZARDOUS DECOMPOSITION PRODUCTS

Thermal decomposition of this product can generate dusts, irritating fumes, and toxic gases (e.g., Carbon monoxide, Carbon dioxide, Oxides of Nitrogen).

POSSIBILITY OF HAZARDOUS REACTIONS

This product is not expected to undergo hazardous polymerization, decomposition, condensation or self-reactivity.

PART IV Is there any other

Is there any other useful information about this material?

11. TOXICOLOGICAL INFORMATION

TOXICITY DATA: The following toxicity data are available for this product. This data was obtained using the MTT Tetrazolium Assay. L929 fibroblasts, comparable to human gingival fibroblasts, were evaluated on exposure to 15, 30, 50, 60, 85, 100, and 150 μg/ml Nite White ACP (10 - 22% Carbamide peroxide equivalent). The 50% inhibitory doses (ID₅₀) are estimated at 92 μg/ml Nite White ACP (10%) (24 hours) and 71 μg/ml Nite White ACP (10%) (48 hours). These are much higher than the ID₅₀ of eugenol (35 μg/ml), a commonly used dental agent. The ID₅₀ values for 16 & 22% Nite White ACP were comparable to the values for 10% Nite White ACP. The conclusion of the investigators is that the observed cytotoxicity of Nite White ACP, 10 -22% should not constitute a significant clinical risk when used under the supervision of dental professionals.

SUSPECTED CANCER AGENT: The following table summarizes the carcinogenicity listing for the components of this product. "NO" indicates that the substance is not considered to be, or suspected to be, a carcinogen by the listed agency, see section 16 for definition of other ratings.

CHEMICAL	IARC	NTP	NIOSH	ACGIH	OSHA	CA PROP 65
Water Conditioners	No	No	No	No	No	No
Supporting Matrix	3	No	No	No	No	No
Whitening Agents	3	No	No	A3	No	No

<u>IRRITANCY OF PRODUCT</u>: This product can be mildly irritating to contaminated tissue. Prolonged exposure can lead to tissue damage. Degree of irritancy observations were made incidental to performing the Maximum Sensitization Test on NITE WHITE ACP, and the conclusion of the investigators is that NITE WHITE ACP has negligible irritating effects on tissue.

<u>SENSITIZATION TO THE PRODUCT</u>: NITE WHITE ACP, 10 - 22%, has been tested for sensitization potential and is reported not to be a skin sensitizer following the procedures specified in the ISO 10993-10 (1995) (Maximum Sensitization Test).

TOXICOLOGICAL SYNERGISTIC PRODUCTS: None.

<u>REPRODUCTIVE TOXICITY INFORMATION</u>: Listed below is information concerning the effects of this product and its components on the human reproductive system.

<u>Mutagenicity</u>: When used as directed, this product is not expected to produce mutagenic effects in humans. Nite White ACP, 10 - 22%, has been specifically tested for mutagenicity using the Ames Salmonella/Microsome test. The conclusion of the investigators is that there were no numbers of revertants colonies above normal in plates treated with microsome S9 preparation.

Embryotoxicity: When used as directed, this product is not expected to produce embryotoxic effects in humans.

<u>Teratogenicity</u>: When used as directed, this product is not expected to produce teratogenic effects in humans.

Reproductive Toxicity: When used as directed, this product is not expected to produce reproductive toxicity in humans.

A <u>mutagen</u> is a chemical that causes permanent changes to genetic material (DNA) such that the changes will propagate through generational lines. An <u>embryotoxin</u> is a chemical that causes damage to a developing embryo (i.e. within the first eight weeks of pregnancy in humans), but the damage does not propagate across generational lines. A <u>teratogen</u> is a chemical that causes damage to a developing fetus, but the damage does not propagate across generational lines. A <u>reproductive toxin</u> is any substance that interferes in any way with the reproductive process.

BIOLOGICAL EXPOSURES INDICES (BEIs): There are no BEI's established for any component of this product at this time.

12. ECOLOGICAL INFORMATION

ALL WORK PRACTICES MUST BE AIMED AT ELIMINATING ENVIRONMENTAL CONTAMINATION. ECOTOXICITY:

This product can be harmful to terrestrial plant and animal life if large volumes of it are released into the environment. Refer to Section 11, "Toxicological Information", for specific animal data. This product can be harmful to animal life if large volumes of it are released into an aquatic environment. The following aquatic toxicity data is available for components of this product:

The following data are available a for Water Conditioner component:

Water flea Daphnia: $EC_{50} > 10000 \text{ mg/L}$ (48 hour, unspecified ria) Phytobacterium phosphoreum: $EC_{50} = 710 \text{ mg/L}$ (30 minutes)

Microtox test Goldfish: $LC_{50} > 5000 \text{ mg/L}$ (24 hour)

Unspecified Guppy: $LC_{50} > 1000 \text{ mg/L}$ (48 hour, unspecified conditions)

The following data are available for a second Water Conditioner component:

LC50 (96 Hr.) rainbow trout = 50-67 mg/L; 12 degrees

C LC50 (96 Hr.) goldfish = >5000 mg/L

PERSISTENCE/DEGRADABILITY:

There is no environmental stability data for any component of this product at this time.

BIOACCUMULATION/ACCUMULATION:

There is no accumulation data for any component of this product at this time

13. DISPOSAL CONSIDERATIONS

<u>PREPARING WASTES FOR DISPOSAL</u>: Recover or recycle if possible. **Consumer Waste:** Dispose of according to pertinent state and local household waste and requirements. **Industrial Use:** Waste disposal must be in accordance with appropriate U.S. Federal, State, and local regulations or with regulations of Canada.

EPA WASTE NUMBER: The specific RCRA codes depend on the exact nature of the discarded material.

14. TRANSPORTATION INFORMATION

BASIC SHIPPING DESCRIPTION

This product is not hazardous per 49 CFR 172.101, the U.S. Department of Transportation.

PROPER SHIPPING NAME:

HAZARD CLASS NUMBER and DESCRIPTION:

UN IDENTIFICATION NUMBER:

DOT LABEL(S) REQUIRED:

PACKAGING GROUP:

Not Regulated

Not Regulated

Not Regulated

MARINE POLLUTANT: No component is designated as a DOT Marine Pollutant.

Not Regulated

ADDITIONAL INFORMATION

TRANSPORT CANADA TRANSPORTATION OF DANGEROUS GOODS REGULATIONS: This product is not considered as dangerous goods, per Transport Canada regulations.

INTERNATIONAL AIR TRANSPORT ASSOCIATION (IATA) REGULATIONS

NORTH AMERICAN RESPONSE GUIDEBOOK NUMBER (2000):

This product is not hazardous per IATA regulations.

PROPER SHIPPING NAME:
HAZARD CLASS NUMBER and DESCRIPTION:
UN IDENTIFICATION NUMBER:
DOT LABEL(S) REQUIRED:
PACKAGING GROUP:
Not Regulated
North American Response Guidebook Number (2000):
Not Regulated
North American Response Guidebook Number (2000):
Not Regulated

MARINE POLLUTANT: No component is designated as a Marine Pollutant.

INTERNATIONAL MARITIME ORGANIZATION REGULATIONS (IMO)];

This product is not hazardous per IMO regulations.

PROPER SHIPPING NAME:
HAZARD CLASS NUMBER and DESCRIPTION:
UN IDENTIFICATION NUMBER:
DOT LABEL(S) REQUIRED:
PACKAGING GROUP:
Not Regulated
North American Response Guidebook Number (2000):
Not Regulated
North American Response Guidebook Number (2000):
Not Regulated

MARINE POLLUTANT: No component is designated as a Marine Pollutant.

INTERNATIONAL CIVIL AVIATION ORGANIZATION (ICAO

This product is not hazardous per ICAO regulations.

PROPER SHIPPING NAME:
HAZARD CLASS NUMBER and DESCRIPTION:
Not Regulated
UN IDENTIFICATION NUMBER:
Not Regulated
DOT LABEL(S) REQUIRED:
Not Regulated
PACKAGING GROUP:
Not Regulated
NORTH AMERICAN RESPONSE GUIDEBOOK NUMBER (2000):
Not Regulated

MARINE POLLUTANT: No component is designated as a Marine Pollutant.

15. REGULATORY INFORMATION

ADDITIONAL U.S. REGULATIONS - EPA REPORTING REQUIREMENTS:

The following reporting requirements are applicable to components of this product:

<u>CHEMICAL</u>	SECTION 302 EHS (TPQ)	SECTION 304 RQ	SECTION 313 TRI (threshold)
	(40 CFR 355, Appendix A)	(40 CFR Table 302.4)	(40 CFR 372.65)
Water Conditioners	No	NA	No
Supporting Matrix	No	NA	No
Whitening Agents	Yes (1,000 lbs)	NA	No

U.S. SARA SECTION 311/312 FOR PRODUCT: Acute health effects.

<u>U.S. TSCA INVENTORY STATUS</u>: The components of this product are listed on the TSCA Inventory.

OTHER U.S. FEDERAL REGULATIONS: Not applicable.

CALIFORNIA SAFE DRINKING WATER AND TOXIC ENFORCEMENT ACT (PROPOSITION 65):

No component of this material is found on either the Proposition 65 Carcinogen List or the Adverse Reproductive Effects List. **ADDITIONAL CANADIAN REGULATIONS:**

<u>CANADIAN DSL/NDSL INVENTORY STATUS</u>: The components of this product are listed on the DSL Inventory.

16. OTHER INFORMATION

DATE OF PRINTING

August 25, 2005

DEFINITIONS OF TERMS

A large number of abbreviations and acronyms appear on a MSDS. Some of these, which are commonly used, include the following:

CAS #: This is the Chemical Abstract Service Number that uniquely identifies each compound.

ACGIH - American Conference of Governmental Industrial Hygienists, a professional association which establishes exposure limits.

TLV - Threshold Limit Value - an airborne concentration of a substance that represents conditions under which it is generally believed that nearly all workers can be repeatedly exposed without adverse effect. The duration must be considered, including the 8-hour Time Weighted Average (TWA), the 15-minute Short Term Exposure Limit, and the instantaneous Ceiling Level (C). Skin absorption effects must also be considered.

OSHA - U.S. Occupational Safety and Health Administration.

PEL - Permissible Exposure Limit - This exposure value means exactly the same as a TLV, except that it is enforceable by OSHA. The OSHA Permissible Exposure Limits are based in the 1989 PELs and the June, 1993 Air Contaminants Rule (<u>Federal Register</u>: 58: 35338-35351 and 58: 40191). Both the current PELs and the vacated PELs are indicated. The phrase, "Vacated 1989 PEL," is placed next to the PEL that was vacated by Court Order.

IDLH - Immediately Dangerous to Life and Health - This level represents a concentration from which one can escape within 30-minutes without suffering escape-preventing or permanent injury. The DFG - MAK is the Republic of Germany's Maximum Exposure Level, similar to the U.S. PEL. NIOSH is the National Institute of Occupational Safety and Health, which is the research arm of the U.S. Occupational Safety and Health Administration (OSHA). NIOSH issues exposure guidelines called Recommended Exposure Levels (RELs). When no exposure guidelines are established, an entry of NE is made for reference.

OEL – Occupational Exposure Level – In some cases, specific exposure guidelines have been assigned by industry. These are referred to as "Occupational Exposure Levels."

HAZARD RATINGS:

HAZARDOUS MATERIALS IDENTIFICATION SYSTEM: Hea

Hazard: 0 (minimal acute or chronic exposure hazard); 1 (slight acute or chronic exposure hazard); 2 (moderate acute or significant chronic exposure hazard); 3 (severe acute exposure hazard; onetime overexposure can be fatal); 4 (extreme acute exposure hazard; onetime overexposure can be fatal). An "*" indicates that the health hazard is chronic. Flammability Hazard: 0 (minimal hazard); 1 (materials that require substantial pre-heating before burning); 2 (combustible liquid or solids; liquids with a flash point of 38-93°C [100-200°F]); 3 (Class IB and IC flammable liquids with flash points below 23°C [100°F]); 4 (Class IA flammable liquids with flash points below 23°C [100°F]); 1 (material that can become unstable at elevated temperatures or which can react slightly with water); 2 (materials that are unstable but do not detonate or which can react violently with water); 3 (materials that can detonate when initiated or which can react explosively with water); 4 (materials that can detonate at normal temperatures or pressures).

NATIONAL FIRE PROTECTION ASSOCIATION: Health Hazard: 0 (material that on exposure under fire conditions would offer no hazard beyond that of ordinary combustible materials); 1 (materials that on exposure under fire conditions could cause irritation or minor residual injury); 2 (materials that on intense or continued exposure under fire conditions could cause temporary incapacitation or possible residual injury); 3 (materials that can on short exposure could cause serious temporary or residual injury); 4 (materials that under very short exposure could cause death or major residual injury). Flammability Hazard and Reactivity Hazard: Refer to definitions for "Hazardous Materials Identification System".

FLAMMABILITY LIMITS IN AIR:

Much of the information related to fire and explosion is derived from the National Fire Protection Association (NFPA). Flash Point - Minimum temperature at which a liquid gives off sufficient vapors to form an ignitable mixture with air. Autoignition Temperature: The minimum temperature required to initiate combustion in air with no other source of ignition. LEL - the lowest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source. UEL - the highest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source.

TOXICOLOGICAL INFORMATION:

Possible health hazards as derived from human data, animal studies, or from the results of studies with similar compounds are presented. Definitions of some terms used in this section are: LD50 - Lethal Dose (solids & liquids) which kills 50% of the exposed animals; LC_{50} - Lethal Concentration (gases) which kills 50% of the exposed animals; **ppm** concentration expressed in parts of material per million parts of air or water; mg/m³ concentration expressed in weight of substance per volume of air; mg/kg quantity of material, by weight, administered to a test subject, based on their body weight in kg. Other measures of toxicity include TDLo, the lowest dose to cause a symptom and TCLo the lowest concentration to cause a symptom; TDo, LDLo, LDo, TC, TCo, LCLo, and LCo, the lowest dose (or concentration) to cause lethal or toxic effects. BEI - Biological Exposure Indices, represent the levels of determinants which are most likely to be observed in specimens collected from a healthy worker who has been exposed to chemicals to the same extent as a worker with inhalation exposure to the TLV. Ecological Information: EC is the effect concentration in water.

Data from several sources are used to evaluate the cancer-causing potential of the material. The sources and ratings are: IARC - the International Agency for Research on Cancer; 1 = Carcinogenic to humans, 2A, 2B = Probably carcinogenic to humans, 3 = Unclassifiable as to carcinogenicity in humans, and 4 = Probably not carcinogenic to humans. NTP - the National Toxicology Program; K =Known to be a human carcinogen, and R = Reasonably anticipated to be a human carcinogen. RTECS - the Registry of Toxic Effects of Chemical Substances. OSHA - Occupational Safety and Health Administration and CAL/OSHA - California's subunit of the Occupational Safety and Health Administration; Ca = Carcinogen defined with no further categorization. ACGIH - American Conference of Governmental Industrial Hygienists; A1 = Confirmed human carcinogen, A2 = Suspected human carcinogen, A3 = Confirmed animal carcinogen with unknown relevance to humans, A4 = Not classifiable as a human carcinogen, and A5 = Not suspected as a human carcinogen. NIOSH - U.S. National Institute for Occupational Safety and Health; Ca = Potential occupational carcinogen, with no further categorization. **EPA** – U.S. Environmental Protection; A = Human carcinogen, B = Probable human carcinogen, C = Possible human carcinogen, D = Not classifiable as to human carcinogenicity, E = Evidence of Noncarcinogenicity for humans, K = Known human carcinogen, L = Likely to produce cancer in humans, CBD = Cannot be determined, NL = Not likely to be carcinogenic in humans, and I = Data are inadequate for an assessment of human carcinogenic potential.

REGULATORY INFORMATION:

This section explains the impact of various laws and regulations on the material. **EPA** is the U.S. Environmental Protection Agency. **WHMIS** is the Canadian Workplace Hazardous Materials Information System. **DOT** and **TC** are the U.S. Department of Transportation and the Transport Canada, respectively. Superfund Amendments and Reauthorization Act (**SARA**); the Canadian Domestic/Non-Domestic Substances List (**DSL/NDSL**); the U.S. Toxic Substance Control Act (**TSCA**); Marine Pollutant status according to the **DOT**; the Comprehensive Environmental Response, Compensation, and Liability Act (**CERCLA or Superfund**); and various state regulations. This section also includes information on the precautionary warnings that appear on a material's industrial package label.