

Neo-Form CPF=35^A

Special Purpose Arterial Fluid with Entrone and AD-P

Neo-Form is a formaldehyde arterial fluid suitable for use in extreme situations requiring thorough preservation and definite firmness of tissues with minimum dehydration effects. Difficult cases such as serious diseases, delayed embalming or advanced decomposition respond well to Neo-Form. Special buffers and penetrating agents make it possible to obtain maximum tissue fixation and fluid distribution, with enhanced drainage. Neo-Form is not recommended for normal cases.

PH-A¹	DI-SAN²	NEO-FORM ^B DEFINITE ³ FIRMNESS	DI-SAN⁴ ADD FOR EXTRA FIRMNESS
3-4	1-2	8-10	1-3
\rightarrow MIX IN THIS ORDER \rightarrow \rightarrow			

Notes:

- A A value assigned to all Champion fluids ranking them on the basis of preservative ability using recommended dilutions in normal cases. The Champion Preservative Factor is not index but can equal it in certain fluids. It is derived from the total chemical composition of each fluid and results of extensive field research. The Champion Preservative Factor can be used by the embalmer to predict the reactivity, preservative value and firming action of Champion fluids.
- B Add Champion Coloro Dyes as needed to achieve desired cosmetic effect.
- 1 For proper water conditioning and pH balance to maximize fluid efficiency (if using soft water reduce amount to 2-3 ozs.)
- 2 For sanitizing action in solution and improved fluid action in all non-glutaraldehyde based fluids.
- 3 Embalmer should adjust quantity used according to severity of case and fluid action required. For tissue gas use at maximum rate of 16 oz.
- 4 For increased aldehyde action with improved preservation and sanitation. In cases of tissue gas use at rate of 8 oz. Di-San per gallon.

BEFORE USING, READ MATERIAL SAFETY DATA SHEET. FOR PROFESSIONAL EMBALMING USE ONLY.

MATERIAL SAFETY DATA SHEET

THE CHAMPION COMPANY

400 Harrison Street Springfield, Ohio 45505

EMERGENCY TELEPHONE NO. (937) 324-5681

CHEMTREC: (800) 424-9300 (Spill, Leak, Fire, Exposure or Accident)

HAZARD RATING Health 2

2 Fire Reactivity 0 Special 0

I. PRODUCT INFORMATION

General Type:

Embalming Fluid

Trade Name:

Neo-Form

II. HAZARDOUS INGREDIENTS

OSHA PEL ACGIH TLV MATERIAL (CAS) TWA/STEL (15) <u>%</u> TWA/STEL (15) Formaldehyde (50-00-0) 35 .75ppm/2ppm .3ppm (ceiling)

Possible Carcinogen: NTP, IARC

Methanol (67-56-1)

200ppm/NONE

200ppm/250ppm

III. PHYSICAL DATA

Boiling Point 205°F+ Freezing Point N/A Specific Gravity 1.083 Vapor Pressure UNKNOWN Vapor Density Solubility in Water COMPLETE 1

21

Percent Volatiles 21

Evaporation Rate (Butyl Acetate = 1)

Appearance and Odor

Reddish, clear liquid with pungent odor.

IV. FIRE AND EXPLOSION HAZARD DATA

163° F (COC) Combustible Liquid Flash Point

Flammable Limits In Air Lower 6.7 Upper 72

Extinguishing Media Foam, Dry Chemical, Carbon Dioxide, Water Spray

Special Fire Fighting Wear self-contained breathing apparatus, cool container with water

Procedures Unusual Fire and Explosion Hazard

spray.

V. HEALTH HAZARD DATA

Threshold Limit Value

See Part II

Effects of Overexposure

If swallowed may cause burns, nausea, vomiting, diarrhea, blindness or death. Skin contact may cause burns, dermatitis or serious skin injury. Eye contact may cause burns, inflammation, eye injury or blindness. Inhalation may cause burning of throat and lungs, difficult breathing and collapse, liver damage, nerve damage or blindness. Can be absorbed through skin.

1

Emergency and First Aid

Procedures

Contact physician immediately. If swallowed give milk or water and induce vomiting by sticking finger down throat and get medical attention. If unconscious - give nothing. If eye or skin contact - flush with water for 15 minutes. Remove contaminated clothing, get medical attention. If inhaled remove to fresh air, give artificial respiration if not breathing, get medical

attention.

VI. REACTIVITY DATA

Stability

Product is stable

Conditions to Avoid Incompatibilities

Sparks, heat and open flames

Strong acids and alkalis

Hazardous Decomposition Products

At high temperatures may release carbon monoxide or carbon dioxide

Hazardous Polymerization

Will not occur

VII. SPILL OR LEAK PROCEDURES

If Material is Spilled

Neutralize with sodium sulfite solution and flush to sewer with large quantity of water - if allowed. Mop up with dry, non-reactive absorbent and dispose of as solid waste as allowed.

Waste Disposal Method

Flush to chemical sewer, incinerate, dispose in sanitary landfill - if allowed or flush to waste treatment system - if allowed.

VIII. SPECIAL PROTECTION INFORMATION

Respiratory Protection

Unnecessary if area is adequately ventilated - use organic vapor mask

if necessary.

Local Ventilation

Preferred

Mechanical Ventilation Special Ventilation

Acceptable if necessary Not normally required Not normally required

Other Ventilation **Protective Gloves Eye Protection**

Impervious vinyl or rubber type Coverall goggles or full face shield

Other Protective Equipment

Safety shower, eye wash and full protective clothing is required.

IX. SPECIAL PRECAUTIONS

Maintain adequate ventilation and engineering controls to insure exposure levels below OSHA limits. prolonged inhalation or contact with skin or eyes.

Keep bottles tightly capped. Keep away from heat and flames. Store in cool, dry, well-ventilated area.

The information herein given is in good faith but no warranty, expressed or implied, is made, except that to the best of the Company's knowledge it is accurate. The Champion Company does not assume any legal responsibilities for use or dependence upon same. Customers may wish to conduct tests of their own. The user is urged to read the information provided on the label before using product.

Date August 1, 2010 Neo-Form