

Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

Date of issue: 05/27/2015

Version: 1.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name : New Era Gel

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Embalming Gel

Use of the substance/mixture : For professional use only

1.3. Details of the supplier of the safety data sheet

THE CHAMPION COMPANY 400 Harrison Street Springfield, Ohio 45505

Telephone No. (937) 324-5681

1.4. Emergency telephone number

Emergency number : CHEMTREC (800) 424-9300 (Spill, Leak, Fire, Exposure or Accident)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GHS-US classification

Flam. Liq. 3 H226 Acute Tox. 4 (Oral) H302 Acute Tox. 4 (Inhalation:dust,mist) H332 Skin Corr. 1B H314 Eye Dam. 1 H318 Resp. Sens. 1 H334 Skin Sens. 1 H317 Muta. 2 H341 STOT SE 3 H336 STOT SE 3 H335 STOT RE 2 H373

2.2. Label elements

GHS-US labelling

Hazard pictograms (GHS-US)







GHS02 GHS05

GHS07 GH

Signal word (GHS-US) : Danger

Hazard statements (GHS-US) : H226 - Flammable liquid and vapor

H302+H332 - Harmful if swallowed or if inhaled H314 - Causes severe skin burns and eye damage H317 - May cause an allergic skin reaction

H318 - Causes serious eye damage

H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled

H335 - May cause respiratory irritation H336 - May cause drowsiness or dizziness

H341 - Suspected of causing genetic defects (inhalation, oral)

H373 - May cause damage to organs through prolonged or repeated exposure

Precautionary statements (GHS-US) : P201 - Obtain special instructions before use

P202 - Do not handle until all safety precautions have been read and understood P210 - Keep away from heat, sparks, open flames, hot surfaces. - No smoking

P233 - Keep container tightly closed

P240 - Ground container and receiving equipment

P241 - Use explosion-proof electrical, ventilating, lighting, and equipment

P242 - Use only non-sparking tools

P243 - Take precautionary measures against static discharge P260 - Do not breathe dust, fume, mist, spray, vapors

05/27/2015 EN (English) Page 1

Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

P261 - Avoid breathing dust, fume, mist, spray, vapors

P264 - Wash hands thoroughly after handling

P270 - Do not eat, drink or smoke when using this product

P271 - Use only in a well-ventilated area

P272 - Contaminated work clothing must not be allowed out of the workplace

P280 - Wear protective clothing, protective gloves, eye protection, face protection

P285 - In case of inadequate ventilation wear respiratory protection

P301+P312 - If swallowed: Call a POISON CENTER

P301+P330+P331 - If swallowed: rinse mouth. Do NOT induce vomiting

P302+P352 - If on skin: Wash with plenty of soap and water

P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse

P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing

P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing

P308+P313 - If exposed or concerned: Get medical attention

P310 - Immediately call a POISON CENTER

P312 - Call a POISON CENTERel

P314 - Get medical attention if you feel unwell

P330 - Rinse mouth

P333+P313 - If skin irritation or rash occurs: Get medical attention

P342+P311 - If experiencing respiratory symptoms: Call a doctor

P362 - Take off contaminated clothing and wash before reuse

P363 - Wash contaminated clothing before reuse

P370+P378 - In case of fire: Use alcohol resistant foam, dry powder, carbon dioxide (CO2) to extinguish

P403+P233 - Store in a well-ventilated place. Keep container tightly closed

P403+P235 - Store in a well-ventilated place. Keep cool

P405 - Store locked up

P501 - Dispose of contents and container to comply with applicable local, state, national and international regulation

Other hazards 2.3.

No additional information available

Unknown acute toxicity (GHS-US) 2.4.

No data available

SECTION 3: Composition/information on ingredients

Substance

Not applicable

3.2. **Mixture**

Name	Product identifier	%	GHS-US classification
Isopropyl alcohol	(CAS No) 67-63-0	<25	Flam. Liq. 2, H225 Eye Irrit. 2A, H319 STOT SE 3, H336
Phenol	(CAS No) 108-95-2	<15	Acute Tox. 3 (Oral), H301 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Inhalation), H331 Skin Corr. 1B, H314 Muta. 2, H341 STOT RE 2, H373
Tetrahydrofurfuryl alcohol	(CAS No) 97-99-4	<5	Flam. Liq. 4, H227 Eye Irrit. 2A, H319
Glutaraldehyde	(CAS No) 111-30-8	<3	Flam. Liq. 4, H227 Acute Tox. 3 (Oral), H301 Acute Tox. 2 (Inhalation:dust,mist), H330 Skin Corr. 1B, H314 Eye Dam. 1, H318 Resp. Sens. 1, H334 Skin Sens. 1, H317 STOT SE 3, H335

SECTION 4: First aid measures

Description of first aid measures

First-aid measures general : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible). Call a doctor.

05/27/2015 EN (English) 2/10

Safety Data Sheet

First-aid measures after ingestion

Symptoms/injuries after skin contact

Symptoms/injuries after eye contact

Symptoms/injuries after ingestion

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

First-aid measures after inhalation	: F	Remove	vict	tim to f	esh ai	r and kee	ep at rest i	n a position	comf	ortable for b	oreathin	g. Ke	ep victim
	٧	varm a	nd	rested.	Seek	medica	l attention	immediate	ly. If	breathing	stops,	give	artificial
	r	espiration	on. ⁻	Transfe	r to hos	spital rap	idlv.						

First-aid measures after skin contact : Wash immediately with lots of wate at least 15 minutes. Remove all contaminated clothing and footwear. Seek medical attention immediately.

First-aid measures after eye contact : In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist. Removal of contact lenses after an eye injury should only be undertaken by skilled personnel. Seek medical attention immediately.

: Immediately call a POISON CENTER. If swallowed, rinse mouth with water (only if the person is conscious). Seek medical advice (show the label where possible). Give water or milk if the person is fully conscious.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries : Causes severe skin burns and eye damage. Suspected of causing genetic defects (- Inhalation).

May cause damage to organs through prolonged or repeated exposure.

Symptoms/injuries after inhalation : Harmful if inhaled. May cause drowsiness or dizziness. May cause allergy or asthma symptoms or breathing difficulties if inhaled. Danger of serious damage to health by prolonged exposure through inhalation. Difficulty breathing and tightness in the chest. Burning in the nasal passage.

: Causes severe skin burns and eye damage. May cause an allergic skin reaction. Repeated exposure to this material can result in absorption through skin causing significant health hazard. Contains phenol. Strong skin absorption as main danger of phenol poisoning at the workplace with paralysis of th central nervous system (with lethal consiquences in severe cases) as well as liver and kidney damage. Phenol destroys the nerve endings in the skin. Therefore absence of pain does not necessarily mean the skin has been properly decontaminated.

Causes serious eye damage. Inflammation. Can cause blindness.
Harmful if swallowed. Swallowing a small quantity of this material will result in serious health hazard. Ingestion may cause immediate pain and severe burns of the mucous membranes. Ingestion may cause nausea, vomiting and diarrhea. Swallowing can cause severe injury leading to death.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Alcohol resistant foam. Dry powder. Carbon dioxide. Water spray. Unsuitable extinguishing media : Do not use a water jet since it may cause the fire to spread.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Flammable liquid and vapor.

Explosion hazard : May form flammable/explosive vapor-air mixture. Vapor heavier than air may travel considerable distance to a source of ignition and flash back. Heating will cause pressure rise with risk of bursting and subsequent explosion.

5.3. Advice for firefighters

Other information

Firefighting instructions

: Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering environment. Prevent runoff from entering drains, sewers or waterways.

uranis, sewers or waterways

Protective equipment for firefighters : Do not enter fire area without proper protective equipment, including respiratory protection.

: Combustible liquid. Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of burns and injuries. Use water spray to cool unopened containers. Move undamaged containers from immediate hazard area if it can be done safely. In presence of intense heat may generate acrid fumes. On burning: release of toxic/corrosive/combustible gases/vapors. Formaldehyde. unburned hydrocarbons. carbon oxides (CO and CO2). Vapors are heavier than air and may travel considerable distance to an ignition source and flash back to source of vapors.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Eliminate all ignition sources if safe to do so. Use special care to avoid static electric charges. No open flames. No smoking. Stop leak if safe to do so. Avoid breathing dust, fume, mist, spray,

vapors. Avoid contact with skin, eyes and clothing.

05/27/2015 EN (English) 3/10

Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

6.1.1. For non-emergency personnel

Protective equipment : Wear suitable protective clothing. For further information refer to section 8: "Exposure

controls/personal protection".

Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment : Equip cleanup crew with proper protection. Avoid breathing dust, fume, mist, spray, vapors.

: Ventilate area. **Emergency procedures**

Environmental precautions 6.2.

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

Methods and material for containment and cleaning up

Methods for cleaning up

: Keep upwind of the spilled material and isolate exposure . Wear proper protective equipment. Do Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Gather the product and place it in a spare container that has been suitably labelled. Store away from other materials. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Eliminate all sources of ignition, avoid sparks, flames and do not smoke in risk area. Consult the appropriate authorities about waste disposal. Incinerate, dispose in sanitary landfill - if permitted. Small spills may be flushed to a sanitary sewer with copious amounts of water, if in accordance with local, state or national legislation.

Ensure all local, state, national and international regulations are observed.

Reference to other sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

Precautions for safe handling

Additional hazards when processed

: Handle empty containers with care because residual vapors are flammable.

Precautions for safe handling

: Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Provide good ventilation in process area to prevent formation of vapor. No open flames. No smoking. Take precautionary measures against static discharge. Use only non-sparking tools. Work in a well-ventilated area. Use personal protective equipment as required. Avoid breathing dust, fume, mist, spray, vapors. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Before entering storage tanks and commencing any operation in a confined area check the atmosphere for oxygen content and flammability. Keep away from clothing as well as other incompatible

materials. Avoid contact with skin, eyes and clothing.

Do not eat, drink or smoke when using this product. Handle in accordance with good industrial Hygiene measures hygiene and safety practices. Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace. Discard contaminated leather articles.

Conditions for safe storage, including any incompatibilities

Technical measures

: A washing facility for eye and skin cleaning purposes should be present. Ensure adequate ventilation. Proper grounding procedures to avoid static electricity should be followed. Ground container and receiving equipment. Use explosion-proof electrical, ventilating, lighting, and equipment. Comply with applicable regulations.

Storage conditions

Protect containers against physical damage. Keep container tightly closed. Keep only in the original container in a cool, well ventilated place. Store away from direct sunlight or other heat sources.

Strong acids, bases. Oxidizing agents. Incompatible materials

Specific end use(s) 7.3.

No additional information available

SECTION 8: Exposure controls/personal protection

Control parameters

Glutaraldehyde (111-30-8)				
USA ACGIH	ACGIH Ceiling (ppm)	0.05 ppm (activated and inactivated)		
Phenol (108-95-2)				
USA ACGIH	ACGIH TWA (ppm)	5 ppm		
USA OSHA	OSHA PEL (TWA) (mg/m³)	19 mg/m³		
USA OSHA	OSHA PEL (TWA) (ppm)	5 ppm		

05/27/2015 EN (English) 4/10

Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

Isopropyl alcohol (67-63-0)				
USA ACGIH	ACGIH TWA (ppm)	200 ppm		
USA ACGIH	ACGIH STEL (ppm)	400 ppm		
USA OSHA	OSHA PEL (TWA) (mg/m³)	980 mg/m³		
USA OSHA	OSHA PEL (TWA) (ppm)	400 ppm		

8.2. **Exposure controls**

: Emergency eye wash fountains and safety showers should be available in the immediate vicinity Appropriate engineering controls

of any potential exposure. Provide adequate ventilation. Monitoring the effectiveness of

engineering control is recommended.

Personal protective equipment : Avoid all unnecessary exposure. Wear protective clothing, protective gloves, eye

protection/goggles, face protection. For certain operations, additional Personal Protection

Equipment (PPE) may be required.

Hand protection Wear impermeable protective nitrile gloves. The quality of the protective gloves resistant to

chemicals must be chosen as a function of the specific working place concentration and quantity

of hazardous substances.

Contact lenses should not be worn. Chemical goggles and face shields are required to prevent Eye protection

potential eye contact, irritation or injury.

Skin and body protection Long sleeved protective clothing. Overall. Rubber apron, boots, safety foot-wear.

In case of insufficient ventilation. Wear suitable respiratory equipment. Approved organic vapor Respiratory protection

respirator.

Environmental exposure controls Avoid discharge to the environment.

Other information : Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

Information on basic physical and chemical properties

Physical state : Liquid Appearance : Gel Pink Color

Odor Slight pungent odor Odor threshold : No data available Ha No data available

Relative evaporation rate (butyl acetate=1)

Melting point No data available Freezing point : No data available Boiling point : No data available

Flash point 46.11 °C (115 °F) (TTC)

Auto-ignition temperature : No data available Decomposition temperature No data available Flammability (solid, gas) No data available : No data available Vapor pressure

Relative vapor density at 20 °C

Relative density : No data available Density > 1 Specific Gravity Water: completely soluble Solubility

Log Pow : No data available Log Kow No data available Viscosity, kinematic : No data available : No data available Viscosity, dynamic No data available Explosive properties Oxidising properties : No data available Explosive limits : No data available

Other information

VOC content (Percent volatiles with heat)

05/27/2015 EN (English) 5/10

Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

Stable under normal conditions. Unstable on exposure to heat. Flammable liquid and vapor. May form flammable/explosive vapor-air mixture.

10.3. Possibility of hazardous reactions

Not established.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures. Open flame. Overheating. Heat. Sparks.

10.5. Incompatible materials

Strong acids. strong bases. Oxidizing agents.

10.6. Hazardous decomposition products

Thermal decomposition generates: May release flammable gases. Fume. Corrosive vapors. Carbon monoxide. Carbon dioxide.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Harmful if swallowed. Harmful if inhaled.

New Era Gel	
ATE US (oral)	500.0000000 mg/kg bodyweight
ATE US (dust,mist)	1.50000000 mg/l/4h

Glutaraldehyde (111-30-8)	
LD50 oral rat	252 mg/kg
LD50 dermal rabbit	560 μl/kg
LC50 inhalation rat (mg/l)	0.1 mg/l/4h
ATE US (oral)	252.00000000 mg/kg bodyweight
ATE US (vapors)	0.10000000 mg/l/4h
ATE US (dust,mist)	0.10000000 mg/l/4h

Phenol (108-95-2)	
LD50 dermal rat	525
LD50 dermal rabbit	630 mg/kg
ATE US (oral)	100.0000000 mg/kg bodyweight
ATE US (dermal)	630.0000000 mg/kg bodyweight
ATE US (gases)	700.0000000 ppmv/4h
ATE US (vapors)	3.00000000 mg/l/4h
ATE US (dust,mist)	0.50000000 mg/l/4h

Isopropyl alcohol (67-63-0)	
LD50 oral rat	1870 mg/kg
LD50 dermal rabbit	4059 mg/kg
LC50 inhalation rat (mg/l)	72600 mg/m³ (Exposure time: 4 h)
ATE US (oral)	4396.00000000 mg/kg bodyweight
ATE US (dermal)	12800.0000000 mg/kg bodyweight

Skin corrosion/irritation : Causes severe skin burns and eye damage.

Serious eye damage/irritation : Causes serious eye damage.

Respiratory or skin sensitisation : May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic

skin reaction.

Germ cell mutagenicity : Suspected of causing genetic defects (Inhalation, oral).

Carcinogenicity : Not classified

(Based on available data, the classification criteria are not met)

Phenol (108-95-2)	
IARC group	3 - Not classifiable

05/27/2015 EN (English) 6/10

Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

Isopropyl alcohol (67-63-0)	
IARC group	3 - Not classifiable
Reproductive toxicity	: Not classified
	(Based on available data, the classification criteria are not met)
Specific target organ toxicity (single exposure)	: May cause drowsiness or dizziness. May cause respiratory irritation.
Specific target organ toxicity (repeated exposure)	: May cause damage to organs through prolonged or repeated exposure.
Aspiration hazard	: Not classified
	(Based on available data, the classification criteria are not met)
Potential Adverse human health effects and symptoms	: Harmful if inhaled. Toxic if swallowed. Toxic in contact with skin.
Symptoms/injuries after inhalation	: Harmful if inhaled. May cause drowsiness or dizziness. May cause allergy or asthma symptor or breathing difficulties if inhaled. Danger of serious damage to health by prolonged exposuthrough inhalation. Difficulty breathing and tightness in the chest. Burning in the nasal passage
Symptoms/injuries after skin contact	: Causes severe skin burns and eye damage. May cause an allergic skin reaction. Repeat exposure to this material can result in absorption through skin causing significant health hazar Contains phenol. Strong skin absorption as main danger of phenol poisoning at the workpla with paralysis of th central nervous system (with lethal consiquences in severe cases) as well liver and kidney damage. Phenol destroys the nerve endings in the skin. Therefore absence pain does not necessarily mean the skin has been properly decontaminated.
Symptoms/injuries after eye contact	: Causes serious eye damage. Inflammation. Can cause blindness.
Symptoms/injuries after ingestion	: Harmful if swallowed. Swallowing a small quantity of this material will result in serious hea hazard. Ingestion may cause immediate pain and severe burns of the mucous membrane Ingestion may cause nausea, vomiting and diarrhea. Swallowing can cause severe injury leading to death.

SECTION 12: Ecological information

12.1. Toxicity

LC50 fishes 1

Glutaraldehyde (111-30-8)

EC50 Daphnia 1	14 mg/l (Exposure time: 48 h - Species: Daphnia magna)
LC50 fish 2	2.6 - 4.8 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [flow-through])
EC50 Daphnia 2	0.56 - 1.0 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])
Phenol (108-95-2)	
LC50 fishes 1	11.9 - 50.5 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
EC50 Daphnia 1	4.24 - 10.7 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])
LC50 fish 2	20.5 - 25.6 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
EC50 Daphnia 2	10.2 - 15.5 mg/l (Exposure time: 48 h - Species: Daphnia magna)
Isopropyl alcohol (67-63-0)	
LC50 fishes 1	9640 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
EC50 Daphnia 1	13299 mg/l (Exposure time: 48 h - Species: Daphnia magna)
LC50 fish 2	11130 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
2.2. Persistence and degradability	
New Era Gel	
New Era Gel Persistence and degradability	Not established.
Persistence and degradability	Not established.
Persistence and degradability	Not established.
Persistence and degradability 2.3. Bioaccumulative potential	Not established. Not established.
Persistence and degradability 12.3. Bioaccumulative potential New Era Gel	
Persistence and degradability 12.3. Bioaccumulative potential New Era Gel Bioaccumulative potential	
Persistence and degradability 12.3. Bioaccumulative potential New Era Gel Bioaccumulative potential Glutaraldehyde (111-30-8)	Not established.
Persistence and degradability 12.3. Bioaccumulative potential New Era Gel Bioaccumulative potential Glutaraldehyde (111-30-8) Log Pow	Not established.

7.8 - 22 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static])

05/27/2015 EN (English) 7/10

Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

Isopropyl alcohol (67-63-0)	
Log Pow	0.05 (at 25 °C)

Mobility in soil 12.4.

No additional information available

12.5. Other adverse effects

Effect on ozone layer : No additional information available Effect on the global warming : No additional information available

Other information : Avoid release to the environment.

SECTION 13: Disposal considerations

Waste treatment methods

Waste disposal recommendations

: Dispose in a safe manner in accordance with local, state, national and international regulations. Dispose of contents and container to comply with applicable local, state, national and international regulation. Consult the appropriate authorities about waste disposal. Ensure all local, state, national and international regulations are observed. It is the responsibility of the user to determine if disposal material is hazardous according to federal, state and local regulations. Do not pressurize, cut, weld, braze solder, drill, grind, or expose containers to flames, sparks, heat, or other potential ignition sources. Do not re-use empty containers.

Additional information : Handle empty containers with care because residual vapors are flammable.

Ecology - waste materials Avoid release to the environment. Hazardous waste due to toxicity.

SECTION 14: Transport information

In accordance with DOT

: UN2924, Flammable liquids, corrosive, n.o.s. (Isopropanol, Glutaraldehyde), 3, PGIII, ltd. qty. Transport document description

Hazard labels (DOT) : 3 - Flammable liquid

8 - Corrosive





: III - Minor Danger Packing group (DOT)

DOT Packaging Exceptions (49 CFR 173.xxx) 150 : 203 DOT Packaging Non Bulk (49 CFR 173.xxx) DOT Packaging Bulk (49 CFR 173.xxx) : 241 DOT Quantity Limitations Passenger aircraft/rail : 5 L (49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : 60 L

CFR 175.75)

DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a

passenger vessel.

DOT Vessel Stowage Other : 40 - Stow "clear of living guarters"

Additional information

Other information : No supplementary information available.

Transport by sea

No additional information available

Air transport

No additional information available

SECTION 15: Regulatory information

15.1. US Federal regulations

New Era Gel	
RQ (Reportable quantity, section 304 of EPA's List of List	s) 7117 lb

05/27/2015 EN (English) 8/10

Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

Phenol (108-95-2)		
Listed on the United States TSCA (Toxic Substances Control Act) inventory Listed on the United States SARA Section 302 Listed on United States SARA Section 313		
EPA TSCA Regulatory Flag	T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA.	
RQ (Reportable quantity, section 304 of EPA's List of Lists)	1000 lb	
SARA Section 302 Threshold Planning Quantity (TPQ)	500 - 10000	
SARA Section 313 - Emission Reporting	1.0 %	

Isopropyl alcohol (67-63-0)		
Listed on the United States TSCA (Toxic Substances Control Act) inventory Listed on United States SARA Section 313		
EPA TSCA Regulatory Flag	T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA.	
SARA Section 313 - Emission Reporting	1.0 % (only if manufactured by the strong acid process, no supplier notification)	

15.2. International regulations

CANADA

OANADA	
Glutaraldehyde (111-30-8)	
Listed on the Canadian DSL (Domestic	Sustances List)
WHMIS Classification	Class D Division 1 Subdivision B - Toxic material causing immediate and serious toxic effects Class D Division 2 Subdivision B - Toxic material causing other toxic effects Class E - Corrosive Material
Phenol (108-95-2)	
Listed on the Canadian DSL (Domestic	Sustances List)
WHMIS Classification	Class D Division 1 Subdivision A - Very toxic material causing immediate and serious toxic effects Class E - Corrosive Material
Isopropyl alcohol (67-63-0)	

Isopropyl alcohol (67-63-0)		
Listed on the Canadian DSL (Domestic Sustances List)		
WHMIS Classification	Class B Division 2 - Flammable Liquid	
	Class D Division 2 Subdivision B - Toxic material causing other toxic effects	

EU-Regulations

Phenol (108-95-2)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

Isopropyl alcohol (67-63-0)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

Classification according to Regulation (EC) No. 1272/2008 [CLP]

No additional information available

Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

No additional information available

15.2.2. National regulations

Phenol (108-95-2)

Listed on the AICS (Australian Inventory of Chemical Substances)

Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)

Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory

Listed on the Japanese ISHL (Industrial Safety and Health Law)

Listed on the Korean ECL (Existing Chemicals List)

Listed on NZIoC (New Zealand Inventory of Chemicals)

Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)

Japanese Poisonous and Deleterious Substances Control Law

Japanese Pollutant Release and Transfer Register Law (PRTR Law)

Listed on the Canadian IDL (Ingredient Disclosure List)

05/27/2015 EN (English) 9/10

Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

Isopropyl alcohol (67-63-0)

Listed on the AICS (Australian Inventory of Chemical Substances)

Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)

Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory

Listed on the Japanese ISHL (Industrial Safety and Health Law)

Listed on the Korean ECL (Existing Chemicals List)

Listed on NZIoC (New Zealand Inventory of Chemicals)

Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)

Listed on the Canadian IDL (Ingredient Disclosure List)

15.3. US State regulations

No additional information available

SECTION 16: Other information

Other information : None.

Full text of H-phrases: see section 16:

Acute Tox. 2 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 2
Acute Tox. 3 (Dermal)	Acute toxicity (dermal) Category 3
Acute Tox. 3 (Inhalation)	Acute toxicity (inhalation) Category 3
Acute Tox. 3 (Oral)	Acute toxicity (oral), Category 3
Acute Tox. 4 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Eye Irrit. 2A	Serious eye damage/eye irritation, Category 2A
Flam. Liq. 2	Flammable liquids Category 2
Flam. Liq. 3	Flammable liquids Category 3
Flam. Liq. 4	Flammable liquids Category 4
Muta. 2	Flammable liquids Category 1 flammable liquids Category 4
Resp. Sens. 1	Sensitisation — Respiratory, category 1
Skin Corr. 1B	Skin corrosion/irritation Category 1B
Skin Sens. 1	Sensitisation — Skin, category 1
STOT RE 2	Specific target organ toxicity (repeated exposure) Category 2
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H225	Highly flammable liquid and vapor
H226	Flammable liquid and vapor
H227	Combustible liquid
H301	Toxic if swallowed
H302	Harmful if swallowed
H311	Toxic in contact with skin
H314	Causes severe skin burns and eye damage
H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H319	Causes serious eye irritation
H330	Fatal if inhaled
H331	Toxic if inhaled
H332	Harmful if inhaled
H334	May cause allergy or asthma symptoms or breathing difficulties if
	inhaled
H335	May cause respiratory irritation
H336	May cause drowsiness or dizziness
H341	
	Suspected of causing genetic defects
H373	Suspected of causing genetic defects May cause damage to organs through prolonged or repeated exposure

HMIS III Rating

Health : 2 Moderate Hazard - Temporary or minor injury may occur

Flammability : 2 Moderate Hazard Physical : 0 Minimal Hazard

SDS US (GHS HazCom 2012)

The information herein given is in good faith but no warranty, expressed or implied, is made, except that to the best of the Company's knowledge it is accurate. The Champion Company does not assume any legal responsibilities for use or dependence upon same. Customers may wish to conduct tests of their own. The user is urged to read the information provided on the label before using product.

05/27/2015 EN (English) 10/10