

MATERIAL SAFETY DATA SHEET

Product Trade Name: OPTIFLO-III DELAYED RELEASE BREAKER

Revision Date: 22-May-2013

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Statement of Hazardous Nature Hazardous according to the criteria of NOHSC, Dangerous Goods according to the criteria of ADG.

Manufacturer/Supplier Halliburton Australia Pty. Ltd.
15 Marriott Road
Jandakot
WA 6164
Australia

ACN Number: 009 000 775
Telephone Number: 61 (08) 9455 8300
Fax Number: 61 (08) 9455 5300

Product Emergency Telephone

Australia: 08-64244950
Papua New Guinea: 05 1 281 575 5000
New Zealand: 06-7559274

Fire, Police & Ambulance - Emergency Telephone

Australia: 000
Papua New Guinea: 000
New Zealand: 111

Identification of Substances or Preparation

Product Trade Name: OPTIFLO-III DELAYED RELEASE BREAKER
Synonyms: None
Chemical Family: Sulfate
UN Number: , UN1444
Dangerous Goods Class: 5.1
Subsidiary Risk: None
Hazchem Code: 2W
Poisons Schedule: None Allocated
Application: Breaker

Prepared By Chemical Compliance
Telephone: 1-580-251-4335
e-mail: fdunexchem@halliburton.com

2. COMPOSITION/INFORMATION ON INGREDIENTS

Substances	CAS Number	PERCENT	Australia NOHSC	New Zealand WES	ACGIH TLV-TWA
Ammonium persulfate	7727-54-0	60 - 100%	0.01 mg/m ³	Not applicable	0.1 mg/m ³
Crystalline silica, quartz	14808-60-7	10 - 30%	TWA: 0.1 mg/m ³	TWA: 0.2 mg/m ³	TWA: 0.025 mg/m ³

Non-Hazardous Substance to Total of 100%

3. HAZARDS IDENTIFICATION

Hazard Overview

CAUTION! - ACUTE HEALTH HAZARD

May cause eye, skin, and respiratory irritation. May cause allergic skin and respiratory reaction. May be harmful if swallowed. Oxidizer.

DANGER! - CHRONIC HEALTH HAZARD

Breathing crystalline silica can cause lung disease, including silicosis and lung cancer. Crystalline silica has also been associated with scleroderma and kidney disease.

This product contains quartz, cristobalite, and/or tridymite which may become airborne without a visible cloud. Avoid breathing dust. Avoid creating dusty conditions. Use only with adequate ventilation to keep exposures below recommended exposure limits. Wear a NIOSH certified, European Standard EN 149, or equivalent respirator when using this product. Review the Material Safety Data Sheet (MSDS) for this product, which has been provided to your employer.

Risk Phrases

R8 Contact with combustible material may cause fire.

R22 Harmful if swallowed.

R49 May cause cancer by inhalation.

R36/37/38 Irritating to eyes, respiratory system and skin.

R42/43 May cause sensitization by inhalation and skin contact.

R48/20 Harmful: danger of serious damage to health by prolonged exposure through inhalation.

HSNO Classification

Not Determined

4. FIRST AID MEASURES

Inhalation

If inhaled, remove to fresh air. If not breathing give artificial respiration, preferably mouth-to-mouth. If breathing is difficult give oxygen. Get medical attention.

Skin

In case of contact, immediately flush skin with plenty of soap and water for at least 15 minutes. Get medical attention. Remove contaminated clothing and launder before reuse.

Eyes

In case of contact, or suspected contact, immediately flush eyes with plenty of water for at least 15 minutes and get medical attention immediately after flushing.

Ingestion

Do not induce vomiting. Slowly dilute with 1-2 glasses of water or milk and seek medical attention. Never give anything by mouth to an unconscious person.

Notes to Physician

Not Applicable

5. FIRE FIGHTING MEASURES

Suitable Extinguishing Media

Water fog, carbon dioxide, foam, dry chemical.

Extinguishing media which must not be used for safety reasons

None known.

Special Exposure Hazards

Oxidizer. May ignite combustibles. Decomposition in fire may produce toxic gases.

Special Protective Equipment for Fire-Fighters Full protective clothing and approved self-contained breathing apparatus required for fire fighting personnel.

6. ACCIDENTAL RELEASE MEASURES

Personal Precautionary Measures Use appropriate protective equipment. Avoid creating and breathing dust.

Environmental Precautionary Measures Prevent from entering sewers, waterways, or low areas.

Procedure for Cleaning / Absorption Collect using dustless method and hold for appropriate disposal. Consider possible toxic or fire hazards associated with contaminating substances and use appropriate methods for collection, storage and disposal. Flush area with water.

7. HANDLING AND STORAGE

Handling Precautions Avoid contact with eyes, skin, or clothing. This product contains quartz, cristobalite, and/or tridymite which may become airborne without a visible cloud. Avoid breathing dust. Avoid creating dusty conditions. Use only with adequate ventilation to keep exposure below recommended exposure limits. Wear a NIOSH certified, European Standard En 149, or equivalent respirator when using this product. Material is slippery when wet. Wash hands after use. Launder contaminated clothing before reuse.

Storage Information Store away from reducing agents. Store in a cool, dry location. Store between 20 F (-6 C) and 100 F (38 C). Product has a shelf life of 12 months.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Controls Use approved industrial ventilation and local exhaust as required to maintain exposures below applicable exposure limits.

Respiratory Protection Wear a NIOSH certified, European Standard EN 149 (FFP2/FFP3), or equivalent respirator when using this product.

Hand Protection Impervious rubber gloves. Neoprene gloves. Nitrile gloves.

Skin Protection Rubber apron. Wear clothing appropriate for the work environment. Dusty clothing should be laundered before reuse. Use precautionary measures to avoid creating dust when removing or laundering clothing.

Eye Protection Chemical goggles; also wear a face shield if splashing hazard exists.

Other Precautions Eyewash fountains and safety showers must be easily accessible.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State:	Solid
Color:	Off white to tan
Odor:	Mild acrid
pH:	5
Specific Gravity @ 20 C (Water=1):	1.76
Density @ 20 C (kg/l):	Not Determined
Bulk Density @ 20 C (kg/m³):	Not Determined
Boiling Point/Range (C):	Not Determined
Freezing Point/Range (C):	Not Determined
Pour Point/Range (C):	Not Determined
Flash Point/Range (C):	Not Determined

9. PHYSICAL AND CHEMICAL PROPERTIES

Flash Point Method:	Not Determined
Autoignition Temperature (C):	Not Determined
Flammability Limits in Air - Lower (g/m ³):	Not Determined
Flammability Limits in Air - Lower (%):	Not Determined
Flammability Limits in Air - Upper (g/m ³):	Not Determined
Flammability Limits in Air - Upper (%):	Not Determined
Vapor Pressure @ 20 C (mmHg):	Not Determined
Vapor Density (Air=1):	Not Determined
Percent Volatiles:	7.9
Evaporation Rate (Butyl Acetate=1):	Not Determined
Solubility in Water (g/100ml):	Not Determined
Solubility in Solvents (g/100ml):	Not Determined
VOCs (g/l):	Not Determined
Viscosity, Dynamic @ 20 C (centipoise):	Not Determined
Viscosity, Kinematic @ 20 C (centistokes):	Not Determined
Partition Coefficient/n-Octanol/Water:	Not Determined
Molecular Weight (g/mole):	228.22
Decomposition Temperature (C):	Not Determined

10. STABILITY AND REACTIVITY

Stability Data:	Stable
Hazardous Polymerization:	Will Not Occur
Conditions to Avoid	Avoid contact with readily oxidizable materials.
Incompatibility (Materials to Avoid)	Avoid halogens. Contact with acids. Organic matter. All flammables, especially petroleum products, asphalt & other volatile flammables. Amphoteric metals such as aluminum, magnesium, lead, tin, or zinc.
Hazardous Decomposition Products	Toxic fumes. Ammonia. Sulfuric acid. Amorphous silica may transform at elevated temperatures to tridymite (870 C) or cristobalite (1470 C).
Additional Guidelines	Not Applicable

11. TOXICOLOGICAL INFORMATION

Principle Route of Exposure Eye or skin contact, inhalation.

Symptoms related to exposure **Inhalation**

May cause allergic respiratory reaction. May cause respiratory irritation. Inhaled crystalline silica in the form of quartz or cristobalite from occupational sources is carcinogenic to humans (IARC, Group 1). There is sufficient evidence in experimental animals for the carcinogenicity of tridymite (IARC, Group 2A).

Breathing silica dust may cause irritation of the nose, throat, and respiratory passages. Breathing silica dust may not cause noticeable injury or illness even though permanent lung damage may be occurring. Inhalation of dust may also have serious chronic health effects (See "Chronic Effects/Carcinogenicity" subsection below).

Skin Contact May cause skin irritation. May cause an allergic skin reaction.

Eye Contact May cause eye irritation.

Ingestion Causes burns of the mouth, throat and stomach.

Aggravated Medical Conditions	Individuals with respiratory disease, including but not limited to asthma and bronchitis, or subject to eye irritation, should not be exposed to quartz dust.
Chronic Effects/Carcinogenicity	Silicosis: Excessive inhalation of respirable crystalline silica dust may cause a progressive, disabling, and sometimes-fatal lung disease called silicosis. Symptoms include cough, shortness of breath, wheezing, non-specific chest illness, and reduced pulmonary function. This disease is exacerbated by smoking. Individuals with silicosis are predisposed to develop tuberculosis. Cancer Status: The International Agency for Research on Cancer (IARC) has determined that crystalline silica inhaled in the form of quartz or cristobalite from occupational sources can cause lung cancer in humans (Group 1 - carcinogenic to humans) and has determined that there is sufficient evidence in experimental animals for the carcinogenicity of tridymite (Group 2A - possible carcinogen to humans). Refer to <u>IARC Monograph 68, Silica, Some Silicates and Organic Fibres</u> (June 1997) in conjunction with the use of these minerals. The National Toxicology Program classifies respirable crystalline silica as "Known to be a human carcinogen". Refer to the 9th Report on Carcinogens (2000). The American Conference of Governmental Industrial Hygienists (ACGIH) classifies crystalline silica, quartz, as a suspected human carcinogen (A2). There is some evidence that breathing respirable crystalline silica or the disease silicosis is associated with an increased incidence of significant disease endpoints such as scleroderma (an immune system disorder manifested by scarring of the lungs, skin, and other internal organs) and kidney disease.
Other Information	For further information consult "Adverse Effects of Crystalline Silica Exposure" published by the American Thoracic Society Medical Section of the American Lung Association, American Journal of Respiratory and Critical Care Medicine, Volume 155, pages 761-768 (1997).
Toxicity Tests	
Oral Toxicity:	Not determined
Dermal Toxicity:	Not determined
Inhalation Toxicity:	Not determined
Primary Irritation Effect:	Not determined
Carcinogenicity	Refer to <u>IARC Monograph 68, Silica, Some Silicates and Organic Fibres</u> (June 1997).
Genotoxicity:	Not determined
Reproductive / Developmental Toxicity:	Not determined

12. ECOLOGICAL INFORMATION

Mobility (Water/Soil/Air)	Not determined
Persistence/Degradability	Readily biodegradable
Bio-accumulation	Not determined

Ecotoxicological Information

Acute Fish Toxicity:	Not determined
Acute Crustaceans Toxicity:	Not determined
Acute Algae Toxicity:	Not determined

Chemical Fate Information	Not determined
---------------------------	----------------

Other Information	Not applicable
-------------------	----------------

13. DISPOSAL CONSIDERATIONS

Disposal Method	Disposal should be made in accordance with federal, state, and local regulations.
-----------------	---

Contaminated Packaging	This bag may contain residue of a hazardous material. Some authorities may regulate such containers as hazardous waste. Dispose of container according to national or local regulations.
------------------------	--

14. TRANSPORT INFORMATION

Land Transportation

ADR

UN1444, Ammonium Persulfate, 5.1, III

Air Transportation

ICAO/IATA

UN1444, Ammonium Persulfate, 5.1, III

Sea Transportation

IMDG

UN1444, Ammonium Persulfate, 5.1, III
EmS F-A, S-Q

Other Transportation Information

Labels:	Oxidizer
---------	----------

15. REGULATORY INFORMATION

Chemical Inventories

Australian AICS Inventory	Product contains one or more components not listed on inventory.
New Zealand Inventory of Chemicals	This product does not comply with NZIOC

US TSCA Inventory	All components listed on inventory or are exempt.
EINECS Inventory	This product, and all its components, complies with EINECS

Classification	O - Oxidizing. T - Toxic.
----------------	------------------------------

Risk Phrases

R8 Contact with combustible material may cause fire.
R22 Harmful if swallowed.
R49 May cause cancer by inhalation.
R36/37/38 Irritating to eyes, respiratory system and skin.
R42/43 May cause sensitization by inhalation and skin contact.
R48/20 Harmful: danger of serious damage to health by prolonged exposure through inhalation.

Safety Phrases

S2 Keep out of reach of children.
S22 Do not breathe dust.
S24 Avoid contact with skin.
S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
S37 Wear suitable gloves.

16. OTHER INFORMATION

The following sections have been revised since the last issue of this SDS

Not applicable

Contact**Australian Poisons Information Centre**

24 Hour Service: - 13 11 26

Police or Fire Brigade: - 000 (exchange): - 1100

New Zealand National Poisons Centre

0800 764 766

Additional Information

For additional information on the use of this product, contact your local Halliburton representative.

For questions about the Safety Data Sheet for this or other Halliburton products, contact Chemical Compliance at 1-580-251-4335.

Disclaimer Statement

This information is furnished without warranty, expressed or implied, as to accuracy or completeness. The information is obtained from various sources including the manufacturer and other third party sources. The information may not be valid under all conditions nor if this material is used in combination with other materials or in any process. Final determination of suitability of any material is the sole responsibility of the user.

*****END OF MSDS*****