

MATERIAL SAFETY DATA SHEET

SECTION 1

PRODUCT AND COMPANY IDENTIFICATION

Trade Name: OATEY #5 PASTE FLUX
Product Use: Flux for soldering.
Formula: See Section 2
Synonyms: Flux for Soldering Copper Pipe
Firm Name & Mailing Address: OATEY CO. 4700 West 160th Street P.O. Box 35906 Cleveland, Ohio 44135, U.S.A. <http://www.oatey.com>
Oatey Phone Number: (216) 267-7100 or (800) 321-9532
Emergency Phone Numbers: For Emergency First Aid call 1-303-623-5716 COLLECT. For chemical transportation emergencies ONLY, call Chemtrec at 1-800-424-9300. Outside the U.S. 1-703-527-3887.
Prepared By: Corporate Director - Safety and Environmental Compliance
Preparation Date: November 2, 2006

SECTION 2

COMPOSITION/INFORMATION ON INGREDIENTS

<u>INGREDIENTS:</u>	<u>% wt/wt:</u>	<u>CAS NUMBER:</u>	<u>ACGIH TLV TWA:</u>	<u>OSHA PEL TWA:</u>
Petrolatum	60 - 100%	8009-03-8	5 mg/m3 (oil mist)	5 mg/m3 (oil mist)
Zinc Chloride	10 - 30%	7646-85-7	1 mg/m3(fume) 2 mg/m3 STEL	1 mg/m3(fume)
Ammonium Chloride	1 - 5%	12125-02-9	10 mg/m3 (fume) 20 mg/m3 STEL	None Established

SECTION 3

HAZARDS IDENTIFICATION

Emergency Overview:

Yellow paste with a slight odor. May cause burns to the eye and skin. Inhalation of fumes may cause respiratory irritation, metal fume fever, chills, nausea and vomiting. Swallowing may cause burns to the mouth or throat, vomiting, diarrhea and kidney or liver disorders. May be harmful if swallowed. Symptoms may be delayed.

OSHA Hazard Classification: Corrosive, target organ effects

SECTION 4

FIRST AID MEASURES

CALL 1-303-623-5716 COLLECT

Skin: Remove contaminated clothing. Wash thoroughly with soap and water. Call a physician or poison control center if irritation persists.
Eyes: Remove contact lenses if any. Rinse eyes with water for 15 minutes. Get immediate medical attention.
Inhalation: Move to fresh air. If breathing is difficult, give oxygen. If not breathing, give artificial respiration. Keep victim quiet and warm. Call a poison control center or physician immediately.
Ingestion: **DO NOT INDUCE VOMITING.** Rinse mouth with water. Never give anything by mouth to a person who is unconscious or drowsy. Get immediate medical attention by calling a Poison Control Center, or hospital emergency room. If medical advice cannot be obtained, then take the person and product to the nearest medical emergency treatment center or hospital.

SECTION 5 FIRE FIGHTING MEASURES

Flashpoint / Method: 540 Degrees F (282 Degrees C)
Flammability: LEL = Not determined, UEL = Not determined
Extinguishing Small Fires: Use dry chemical, CO2, water, or foam extinguisher
Media: Large Fires: Evacuate area and call Fire Department immediately
Special Fire Firefighters should wear positive pressure self-contained
Fighting breathing apparatus and full protective clothing for fires in
Procedure: areas where chemicals are used or stored
Unusual Fire and None known.
Explosion
Hazards:
Hazardous Hydrocarbons, hydrogen chloride, zinc fumes, ammonia, smoke,
Decomposition carbon monoxide, carbon dioxide and nitrogen oxides.
Products:

SECTION 6 ACCIDENTAL RELEASE MEASURES

Spill or Ventilate area. Stop leak if it can be done without risk. Personnel
Leak cleaning up the spill should wear appropriate personal protective
Procedures: equipment. Take up spill with sand, earth or other absorbent material
and place into a clean, dry leak-proof container.

SECTION 7 HANDLING AND STORAGE

Handling: Do not get in eyes. Do not get on skin or clothing. Do not take
internally. Avoid breathing vapors or fumes. Use only with adequate
ventilation. Wash thoroughly after handling. Keep container closed when
not in use. Handle with care. Keep out of reach of children.
Storage: Store in original, labeled container.
Other: Containers, even empty will retain residue and may be harmful.

SECTION 8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Ventilation: Good general ventilation (equivalent to outdoors) should be adequate
for normal use. For operations where the TLV may be exceeded,
mechanical ventilation such as local exhaust may be needed to maintain
exposure levels below applicable limits.
Respiratory For operations where the TLV may be exceeded, a NIOSH approved
Protection: particulate respirator or supplied air respirator is recommended.
Equipment selection depends on contaminant type and concentration,
select in accordance with 29 CFR 1910.134 and good industrial hygiene
practice. For firefighting, use self-contained breathing apparatus.
Skin Wear rubber gloves.
Protection:
Eye Safety glasses with sideshields or safety goggles.
Protection:
Other: Eye wash and safety shower should be available.

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Boiling Point: 638 Degrees F (337 Degrees C)
Melting Point: Not determined
Vapor Pressure: Not determined
Vapor Density: (Air = 1) Greater than 1
Volatile Components: 7-10%
Solubility In Water: Negligible
pH: Not applicable
Specific Gravity: 1.1
Evaporation Rate: Not applicable
Appearance: Yellow Paste
Odor: Very little odor
Will Dissolve In: Methylene Chloride
Material Is: Paste

SECTION 10 STABILITY AND REACTIVITY

Stability: Stable.
Conditions To Avoid: None.
Hazardous Decomposition: Hydrocarbons, hydrogen chloride, zinc fumes, ammonia, smoke, smoke, carbon monoxide, carbon dioxide and nitrogen oxides.
Products:
Incompatibility/ Materials To Avoid: Strong oxidizing agents, potassium, cyanides and sulfides.
Hazardous Polymerization: Will not occur.

SECTION 11 TOXICOLOGICAL INFORMATION

Inhalation: Fumes from heated product may be corrosive to mucous membranes and the respiratory system. Fumes may cause burning sensation, coughing, wheezing, shortness of breath, cyanosis, fever, chills, muscular pain, anemia, metallic taste in the mouth, headache, nausea, vomiting, sweating, diarrhea and pulmonary edema. Fumes may cause stannosis, a mild benign pneumoconiosis. Repeated inhalation of fumes may cause occupational asthma. Symptoms may be delayed.
Skin: Contact may cause irritation, ulcerations, burns or dermatitis. Symptoms may be delayed.
Eye: Vapors or fumes may cause redness, pain, blurred vision and corneal damage. Direct contact may cause burns and eye damage with possible blindness. Symptoms may be delayed.
Ingestion: May cause irritation or burns to the mouth and throat, nausea, vomiting or diarrhea. Death may occur from strictures of the esophagus and pylorus. Symptoms may be delayed.
Toxicity Data: Petrolatum: No data available
Zinc Chloride: Oral rat LD50: 350 mg/kg
Ammonium Chloride: Oral rat LD50: 1,650 mg/kg
Sensitization: None of the components are known to cause sensitization.
Carcinogenicity: None of the components are listed as a carcinogen or suspect carcinogen by NTP, IARC or OSHA.
Mutagenicity: None of the components have been found to be mutagenic.
Reproductive Toxicity: None of the components are known to cause adverse reproductive effects.
Medical Conditions Aggravated By Exposure: Persons with pre-existing skin, lung, kidney or liver disorders may be at increased risk from exposure to this product.

SECTION 12 ECOLOGICAL INFORMATION

No data available.

SECTION 13 DISPOSAL CONSIDERATIONS

Waste Disposal: Dispose of in accordance with federal, state, and local regulations. It is the responsibility of the end-user to determine at the time of disposal of the product.

RCRA Hazardous Waste Number: None
EPA Hazardous Waste ID Number: None
EPA Hazard Waste Class: None

SECTION 14 TRANSPORT INFORMATION

DOT

Proper Shipping Name: Not regulated
Hazard Class/Packing Group: None
UN/NA Number: None
Hazard Labels: None

IMDG

Proper Shipping Name: Not regulated
Hazard Class/Packing Group: None
UN Number: None
Label: None

2004 North American Emergency Response Guidebook Number: None

SECTION 15 REGULATORY INFORMATION

Hazard Category for Section 311/312: Acute Health, Chronic Health

Section 302 Extremely Hazardous Substances (TPQ): This product does not contain chemicals regulated under SARA Section 302.

Section 313 Toxic Chemicals: This product contains the following chemicals subject to SARA Title III Section 313 Reporting requirements:

<u>Chemical</u>	<u>CAS #</u>	<u>% wt</u>
Zinc Chloride	7646-85-7	10-30%

CERCLA 103 Reportable Quantity: Spills of this product over the RQ (reportable quantity) must be reported to the National Response Center. The RQ for the product, based on the RQ for Zinc Chloride (30% max) of 1,000 lbs, is 3,300 lbs.

<u>Chemical</u>	<u>CAS #</u>	<u>RQ, lbs.</u>
Zinc Chloride	7646-85-7	1,000
Ammonium Chloride	12125-02-6	5,000

Many states have more stringent release reporting requirements. Report spills required under federal, state and local regulations.

California Proposition 65: This product does not contain chemicals regulated under California Proposition 65.

TSCA Inventory: All of the components of this product are listed on the TSCA inventory.

Canadian WHMIS Classification: Class E; Class D, Division 2, Subdivision B
This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR.

SECTION 16 OTHER INFORMATION

NFPA and HMIS:

NFPA Hazard Signal: Health: 3 Flammability: 1 Reactivity: 0 Special: None

HMIS Hazard Signal: Health: 3* Flammability: 1 Reactivity: 0 PPE: B

Disclaimer:

The information herein has been compiled from sources believed to be reliable, up-to-date, and is accurate to the best of our knowledge. However, Oatey cannot give any guarantees regarding information from other sources, and expressly does not make warranties, nor assumes any liability for its use.