Valvoline.	Page: 1
SAFETY DATA SHEET	Revision Date: 05/22/2017
	Print Date: 6/2/2017
	SDS Number: R0382102
Zerex [™] DEX-COOL® Orange OAT Formula RTU Antifreeze Coolant	Version: 1.3
ZXELRU1	

29 CFR 1910.1200 (OSHA HazCom 2012)

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product identifier

Trade name : Zerex™ DEX-COOL® Orange OAT Formula RTU

Antifreeze Coolant

Relevant identified uses of the substance or mixture and uses advised against

Recommended use : Industrial chemical

Details of the supplier of the safety data sheet

Valvoline LLC 100 Valvoline Way Lexington, KY 40509

United States of America (USA)

1-800-TEAMVAL

Emergency telephone number

1-800-VALVOLINE (1-800-825-8654)

Regulatory Information Number

1-800-TEAMVAL

Product Information

1-800-TEAMVAL

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Acute toxicity (Oral) : Category 4

Reproductive toxicity : Category 2

Specific target organ

systemic toxicity - repeated

exposure (Oral)

: Category 2 (Kidney, Liver)

GHS label elements

Hazard pictograms





Signal Word : Warning

Hazard Statements : Harmful if swallowed.

Suspected of damaging the unborn child.

May cause damage to organs (Kidney, Liver) through

prolonged or repeated exposure if swallowed.

Valvoline	Page: 2
SAFETY DATA SHEET	Revision Date: 05/22/2017
	Print Date: 6/2/2017
	SDS Number: R0382102
Zerex [™] DEX-COOL® Orange OAT Formula RTU Antifreeze	Version: 1.3
Coolant	
ZXELRU1	

Precautionary Statements : **Prevention:**

Obtain special instructions before use.

Do not handle until all safety precautions have been read and

understood.

Do not breathe dust/ fume/ gas/ mist/ vapors/ spray.

Wash skin thoroughly after handling.

Do not eat, drink or smoke when using this product.

Wear protective gloves/ protective clothing/ eye protection/ face

protection. Response:

IF SWALLOWED: Call a POISON CENTER/doctor if you feel

unwell. Rinse mouth.

IF exposed or concerned: Get medical advice/ attention.

Storage:

Store locked up.

Disposal:

Dispose of contents/ container to an approved waste disposal

plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

Chemical name	CAS-No.	Classification	Concentration (%)
ETHYLENE GLYCOL	107-21-1	Acute Tox. 4; H302	47.725
		STOT RE 2; H373	
DIETHYLENE GLYCOL	111-46-6	Acute Tox. 4; H302	2.3855
		STOT RE 2; H373	
POTASSIUM 2-	3164-85-0	Skin Irrit. 2; H315	1.91
ETHYLHEXANOATE		David O HOOA I	
		Repr. 2; H361d	

SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.

Valvoline.	Page: 3
SAFETY DATA SHEET	Revision Date: 05/22/2017
	Print Date: 6/2/2017
	SDS Number: R0382102
Zerex [™] DEX-COOL® Orange OAT Formula RTU Antifreeze Coolant	Version: 1.3
ZXELRU1	

Call a POISON CENTRE or doctor/physician if exposed or

you feel unwell.

Show this safety data sheet to the doctor in attendance.

Do not leave the victim unattended.

If inhaled If breathed in, move person into fresh air.

If unconscious, place in recovery position and seek medical

advice.

If symptoms persist, call a physician.

In case of skin contact : Remove contaminated clothing. If irritation develops, get

medical attention.

If on skin, rinse well with water.

Wash contaminated clothing before re-use.

: Flush eyes with water as a precaution. In case of eye contact

> Remove contact lenses. Protect unharmed eye.

If eye irritation persists, consult a specialist.

If swallowed : Obtain medical attention.

Rinse mouth with water.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician.

Most important symptoms and effects, both acute and delayed

Effects of acute ethylene glycol poisoning appear in three fairly distinct stages. The initial stage occurs shortly after exposure, lasts 6-12 hours, and is characterized by central nervous system effects (transient exhilaration, nausea, vomiting, and in severe cases, coma, convulsions, and possible death). The second stage lasts from 12-36 hours after exposure and is initiated by the onset of coma. This phase is characterized by tachypnia, tachycardia, mild hypotension, cyanosis, and in severe cases, pulmonary edema, bronchopneumonia, cardiac enlargement, and congestive failure. The final stage occurs 24-72 postexposure and is characterized by renal failure, ranging from a mild increase in blood urea nitrogen and creatinine followed by recovery, to complete anuria with acute tubular necrosis that can lead to death. Oxaluria is found in most cases. The

most significant laboratory finding in ethylene glycol

intoxication is severe metabolic acidosis.

Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include:

stomach or intestinal upset (nausea, vomiting, diarrhea)

irritation (nose, throat, airways)

Cough

Valvoline.	Page: 4
SAFETY DATA SHEET	Revision Date: 05/22/2017
	Print Date: 6/2/2017
	SDS Number: R0382102
Zerex [™] DEX-COOL® Orange OAT Formula RTU Antifreeze Coolant	Version: 1.3
ZXELRU1	

pain in the abdomen and lower back

cyanosis (causes blue coloring of the skin and nails from lack

of oxygen)

lung edema (fluid buildup in the lung tissue)

acute kidney failure (sudden slowing or stopping of urine

production) Convulsions

Harmful if swallowed.

Suspected of damaging the unborn child.

Notes to physician

: This product contains ethylene glycol. Ethanol decreases the metabolism of ethylene glycol to toxic metabolites. Ethanol should be administered as soon as possible in cases of severe poisoning since the elimination half-life of ethylene glycol is 3 hours. If medical care will be delayed several hours, give the patient three to four 1-ounce oral "shots" of 86-proof or higher whiskey before or during transport to the hospital. Fomepizole (4-methylpyrazole) is an effective antagonist of alcohol dehydrogenase, and as such, may be used as an antidote in the treatment of ethylene glycol poisoning. Hemodialysis effectively removes ethylene glycol and its metabolites from the body.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Water spray Foam

Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

: High volume water jet

Specific hazards during

firefighting

: Do not allow run-off from fire fighting to enter drains or water

courses.

Hazardous combustion

products

: Alcohols Aldehydes

carbon dioxide and carbon monoxide

ethers
toxic fumes
Hydrocarbons
acetaldehyde
formaldehyde-like
potassium oxide

Valvoline.	Page: 5
SAFETY DATA SHEET	Revision Date: 05/22/2017
	Print Date: 6/2/2017
	SDS Number: R0382102
Zerex [™] DEX-COOL® Orange OAT Formula RTU Antifreeze Coolant	Version: 1.3
ZXELRU1	

Specific extinguishing

methods

: Product is compatible with standard fire-fighting agents.

Further information : Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

for firefighters

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

: Use personal protective equipment.

Ensure adequate ventilation.

Persons not wearing protective equipment should be excluded

from area of spill until clean-up has been completed.

: Prevent product from entering drains. Environmental precautions

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

Other information : Comply with all applicable federal, state, and local regulations.

SECTION 7. HANDLING AND STORAGE

Advice on safe handling : Do not breathe vapours/dust.

Do not smoke.

Container hazardous when empty. Avoid contact with skin and eyes.

Smoking, eating and drinking should be prohibited in the

application area.

For personal protection see section 8.

Dispose of rinse water in accordance with local and national

regulations.

Conditions for safe storage Keep container tightly closed in a dry and well-ventilated

place.

Observe label precautions.

Valvoline.	Page: 6
SAFETY DATA SHEET	Revision Date: 05/22/2017
	Print Date: 6/2/2017
	SDS Number: R0382102
Zerex [™] DEX-COOL® Orange OAT Formula RTU Antifreeze Coolant	Version: 1.3
ZXELRU1	

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type	Control	Basis
·		(Form of	parameters /	
		exposure)	Permissible	
			concentration	
ETHYLENE GLYCOL	107-21-1	С	100 mg/m3	ACGIH
			Aerosol only	
		С	50 ppm	OSHA P0
			125 mg/m3	
		С	40 ppm	CAL PEL
			100 mg/m3	
			Vapour	
DIETHYLENE GLYCOL	111-46-6	TWA	10 mg/m3	US WEEL

Hazardous components without workplace control parameters

Components	CAS-No.

Engineering measures : Provide sufficient mechanical (general and/or local exhaust)

ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or

apparent adverse effects.

Personal protective equipment

Respiratory protection : A NIOSH-approved air-purifying respirator with an appropriate

cartridge and/or filter may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits (if applicable) or if overexposure has otherwise been determined. Protection provided by airpurifying respirators is limited. Use a positive pressure, airsupplied respirator if there is any potential for uncontrolled release, exposure levels are not known or any other circumstances where an air-purifying respirator may not

provide adequate protection.

Hand protection

Remarks : The suitability for a specific workplace should be discussed

with the producers of the protective gloves.

Eye protection : Not required under normal conditions of use. Wear splash-

proof safety goggles if material could be misted or splashed

into eyes.

Skin and body protection : Wear resistant gloves (consult your safety equipment

supplier).

Wear as appropriate: Impervious clothing Safety shoes

Valvoline	Page: 7
SAFETY DATA SHEET	Revision Date: 05/22/2017
	Print Date: 6/2/2017
	SDS Number: R0382102
Zerex [™] DEX-COOL® Orange OAT Formula RTU Antifreeze Coolant	Version: 1.3
ZXELRU1	

Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Hygiene measures : Wash hands before breaks and at the end of workday.

When using do not eat or drink. When using do not smoke.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state : liquid

Colour : orange

Odour : No data available

Odour Threshold : No data available

pH : Average 10.5

Melting point/freezing point : -34 °F / -37 °C

Boiling point/boiling range : 226 °F / 108 °C

(1013.33 hPa)

Flash point : $> 250.00 \, ^{\circ}\text{F} \, / > 121.11 \, ^{\circ}\text{C}$

Evaporation rate : No data available

Flammability (solid, gas) : No data available

Upper explosion limit : 15.3 %(V)

Calculated Explosive Limit

Lower explosion limit : 1.2 %(V)

Calculated Explosive Limit 23.33333333 hPa (20 °C)

Calculated Vapor Pressure

Relative vapour density : No data available

Relative density : 1.0700 (60.00 °F)

Density : 1.0700 g/cm3 (60.00 °F)

Solubility(ies)

Vapour pressure

Water solubility : No data available

Valvoline	Page: 8
SAFETY DATA SHEET	Revision Date: 05/22/2017
	Print Date: 6/2/2017
	SDS Number: R0382102
Zerex [™] DEX-COOL® Orange OAT Formula RTU Antifreeze Coolant	Version: 1.3
ZXELRU1	

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

: No data available

Thermal decomposition : No data available

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : No data available

Oxidizing properties : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : Stable under recommended storage conditions.

Possibility of hazardous

reactions.

: Product will not undergo hazardous polymerization.

Conditions to avoid : excessive heat

Incompatible materials : Acids

Aldehydes Alkali metals

Alkaline earth metals

Bases strong alkalis

Strong oxidizing agents Sulphur compounds

Hazardous decomposition

products

Alcohols

Aldehydes

carbon dioxide and carbon monoxide

ethers

Hydrocarbons Organic acids potassium oxide

ketones

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of : Inhalation

Valvoline.	Page: 9
SAFETY DATA SHEET	Revision Date: 05/22/2017
	Print Date: 6/2/2017
	SDS Number: R0382102
Zerex [™] DEX-COOL® Orange OAT Formula RTU Antifreeze	Version: 1.3
Coolant	
ZXELRU1	

exposure Skin contact

Eye Contact Ingestion

Acute toxicity

Harmful if swallowed.

Product:

Acute oral toxicity

Remarks: Ingestion of medications contaminated with diethylene glycol has caused kidney failure and death in humans. Products containing diethylene glycol should be

considered toxic by ingestion.

Acute dermal toxicity : Remarks: Skin absorption of this material (or a component)

may be increased through injured skin.

Components:

ETHYLENE GLYCOL:

Acute oral toxicity : LD0 (Human): Estimated 1.56 g/kg

Assessment: The component/mixture is classified as acute

oral toxicity, category 4.

Acute inhalation toxicity : LC50 (Rat): 10.9 mg/l

Exposure time: 1 h

Test atmosphere: dust/mist

Assessment: No adverse effect has been observed in acute

inhalation toxicity tests.

Acute dermal toxicity : LD50 (Rabbit): 9,530 mg/kg

DIETHYLENE GLYCOL:

Acute oral toxicity : LD50 (Human): Expected 1,120 mg/kg

Target Organs: Kidney

Acute inhalation toxicity : LC50 (Rat): > 4.6 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Assessment: No adverse effect has been observed in acute

inhalation toxicity tests.

Acute dermal toxicity : LD50 (Rabbit): 13,300 mg/kg

POTASSIUM 2-ETHYLHEXANOATE:

Acute oral toxicity : LD50 (Rat): 3,640 mg/kg

Remarks: Information given is based on data obtained from

similar substances.

Valvoline.	Page: 10
SAFETY DATA SHEET	Revision Date: 05/22/2017
	Print Date: 6/2/2017
	SDS Number: R0382102
Zerex [™] DEX-COOL® Orange OAT Formula RTU Antifreeze	Version: 1.3
Coolant	
ZXELRU1	

Acute inhalation toxicity : LC50 (Rat): > 0.11 mg/l

Exposure time: 8 h

Test atmosphere: dust/mist

Assessment: Not classified as acutely toxic by inhalation

under GHS.

Remarks: No mortality observed at this dose.

Information given is based on data obtained from similar

substances.

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg

Assessment: Not classified as acutely toxic by dermal

absorption under GHS.

Remarks: Information given is based on data obtained from

similar substances.

Skin corrosion/irritation

Not classified based on available information.

Components:

ETHYLENE GLYCOL:

Species: Rabbit

Result: No skin irritation

DIETHYLENE GLYCOL:

Species: Human

Result: Slight, transient irritation

POTASSIUM 2-ETHYLHEXANOATE:

Species: Rabbit

Method: OECD Test Guideline 404

Result: Irritating to skin.

GLP: yes

Serious eye damage/eye irritation

Not classified based on available information.

Product:

Remarks: Vapours may cause irritation to the eyes, respiratory system and the skin.

Components:

ETHYLENE GLYCOL:

Result: Slight, transient irritation

DIETHYLENE GLYCOL:

Species: Rabbit

Result: Slight, transient irritation

POTASSIUM 2-ETHYLHEXANOATE:

Result: Slight, transient irritation

Respiratory or skin sensitisation

Valvoline	Page: 11
SAFETY DATA SHEET	Revision Date: 05/22/2017
	Print Date: 6/2/2017
	SDS Number: R0382102
Zerex [™] DEX-COOL® Orange OAT Formula RTU Antifreeze Coolant	Version: 1.3
ZXELRU1	

Skin sensitisation: Not classified based on available information. Respiratory sensitisation: Not classified based on available information.

Components:

ETHYLENE GLYCOL:

Test Type: Maximisation Test

Species: Guinea pig

Assessment: Does not cause skin sensitisation.

DIETHYLENE GLYCOL:
Test Type: Maximisation Test

Species: Guinea pig

Method: Directive 67/548/EEC, Annex V, B.6.

Result: Did not cause sensitisation on laboratory animals.

Germ cell mutagenicity

Not classified based on available information.

Components:

ETHYLENE GLYCOL:

Genotoxicity in vitro : Test Type: Ames test

Test species: Salmonella typhimurium

Metabolic activation: with and without metabolic activation

Result: negative

DIETHYLENE GLYCOL:

Genotoxicity in vitro : Test Type: Ames test

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 471

Result: negative

GLP: yes

: Test species: Chinese hamster ovary cells

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 479

Result: negative

GLP: yes

Genotoxicity in vivo : Test Type: In vivo micronucleus test

Test species: Mouse

Method: OECD Test Guideline 474

Result: negative

GLP: yes

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Suspected of damaging the unborn child.

Components:

POTASSIUM 2-ETHYLHEXANOATE:

Reproductive toxicity - : Some evidence of adverse effects on development, based on

Valvoline.	Page: 12
SAFETY DATA SHEET	Revision Date: 05/22/2017
	Print Date: 6/2/2017
	SDS Number: R0382102
Zerex [™] DEX-COOL® Orange OAT Formula RTU Antifreeze	Version: 1.3
Coolant	
ZXELRU1	

Assessment animal experiments.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Components:

ETHYLENE GLYCOL: Exposure routes: Ingestion Target Organs: Kidney, Liver

Assessment: May cause damage to organs through prolonged or repeated exposure.

DIETHYLENE GLYCOL: Exposure routes: Ingestion Target Organs: Kidney

Assessment: May cause damage to organs through prolonged or repeated exposure.

Aspiration toxicity

Not classified based on available information.

Product:

No aspiration toxicity classification

Experience with human exposure

Components:

DIETHYLENE GLYCOL:

Liver

Further information

Product:

Remarks: No data available

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Ecotoxicology Assessment

Acute aquatic toxicity : Not classified based on available information.

Chronic aquatic toxicity : Not classified based on available information.

Components:

ETHYLENE GLYCOL:

Toxicity to fish : LC50 (Lepomis macrochirus (Bluegill sunfish)): 27,540 mg/l

Exposure time: 96 h Test Type: static test

LC50 (Pimephales promelas (fathead minnow)): 8,050 mg/l

Exposure time: 96 h

Toxicity to daphnia and other : LC50 (Daphnia magna (Water flea)): > 10,000 mg/l

Valvoline.	Page: 13
SAFETY DATA SHEET	Revision Date: 05/22/2017
	Print Date: 6/2/2017
	SDS Number: R0382102
Zerex [™] DEX-COOL® Orange OAT Formula RTU Antifreeze	Version: 1.3
Coolant	
TVEL DUA	
ZXELRU1	

aquatic invertebrates Exposure time: 48 h

Test Type: static test

Toxicity to algae : EC50 (Pseudokirchneriella subcapitata (green algae)): 6,500 -

13,000 mg/l

End point: Growth inhibition Exposure time: 7 Days

Toxicity to fish (Chronic

toxicity)

: NOEC (Pimephales promelas (fathead minnow)): 32,000 mg/l

Exposure time: 7 d

Toxicity to daphnia and other

aquatic invertebrates (Chronic toxicity)

: NOEC (Daphnia magna (Water flea)): 24,000 mg/l

Exposure time: 7 d

DIETHYLENE GLYCOL:

Toxicity to fish : LC50 (Fathead minnow (Pimephales promelas)): 75,210 mg/l

Exposure time: 96 h

Test Type: flow-through test

Toxicity to daphnia and other

aquatic invertebrates

: LC50 (Water flea (Daphnia magna)): > 10,000 mg/l

Exposure time: 24 h Test Type: static test Method: DIN 38412

POTASSIUM 2-ETHYLHEXANOATE:

Toxicity to fish : LC50 (Fish): > 100 mg/l

Exposure time: 96 h

Remarks: Information given is based on data obtained from

similar substances.

Toxicity to daphnia and other

aquatic invertebrates

: EC50 (Daphnia magna (Water flea)): 106 mg/l

Exposure time: 48 h Test Type: static test

Remarks: Information given is based on data obtained from

similar substances.

Toxicity to algae : EC50 (Desmodesmus subspicatus (green algae)): 49.3 mg/l

End point: Growth inhibition

Exposure time: 72 h
Test Type: static test

Remarks: Information given is based on data obtained from

similar substances.

Toxicity to daphnia and other

aquatic invertebrates (Chronic toxicity)

: NOEC (Daphnia magna (Water flea)): 25 mg/l

Exposure time: 21 d Test Type: static test

Remarks: Information given is based on data obtained from

similar substances.

Valvoline.	Page: 14
SAFETY DATA SHEET	Revision Date: 05/22/2017
	Print Date: 6/2/2017
	SDS Number: R0382102
Zerex [™] DEX-COOL® Orange OAT Formula RTU Antifreeze	Version: 1.3
Coolant	
ZXELRU1	

Persistence and degradability

Components:

ETHYLENE GLYCOL:

Biodegradability : Result: Readily biodegradable.

Biodegradation: 90 - 100 %

Exposure time: 10 d

Method: OECD Test Guideline 301

DIETHYLENE GLYCOL:

Biodegradability : Result: Readily biodegradable.

Biodegradation: 70 - 80 % Exposure time: 28 d

Method: OECD Test Guideline 301B

POTASSIUM 2-ETHYLHEXANOATE:

Biodegradability : Result: Readily biodegradable.

Biodegradation: 99 % Exposure time: 28 d

Remarks: Information given is based on data obtained from

similar substances.

No data available

Bioaccumulative potential

Components:

ETHYLENE GLYCOL:

Bioaccumulation : Species: Crayfish (Procambarus)

Bioconcentration factor (BCF): 0.27

Exposure time: 61 d Concentration: 1000 mg/l Method: Flow through

Partition coefficient: n-

octanol/water

: log Pow: -1.36

DIETHYLENE GLYCOL:

Bioaccumulation : Species: Leuciscus idus (Golden orfe)

Bioconcentration factor (BCF): 100

Partition coefficient: n-

octanol/water

: log Pow: -1.47

No data available

Mobility in soil

Components:

No data available

Other adverse effects

No data available

Product:

Additional ecological

information

: No data available

Valvoline.	Page: 15
SAFETY DATA SHEET	Revision Date: 05/22/2017
	Print Date: 6/2/2017
	SDS Number: R0382102
Zerex [™] DEX-COOL® Orange OAT Formula RTU Antifreeze	Version: 1.3
Coolant	
ZXELRU1	

Components:

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

General advice : Dispose of in accordance with all applicable local, state and

federal regulations.

Do not dispose of waste into sewer.

Do not contaminate ponds, waterways or ditches with

chemical or used container.

Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product.

Empty containers should be taken to an approved waste

handling site for recycling or disposal. Do not re-use empty containers.

SECTION 14. TRANSPORT INFORMATION

International transport regulations

REGULATION

ID NUMBER	PROPER SHIPPING NAME	*HAZARD	SUBSIDIARY	PACKING	MARINE
		CLASS	HAZARDS	GROUP	POLLUTANT /
					LTD. QTY.

U.S. DOT - ROAD

Not dangerous goods

CFR_RAIL_C

Not dangerous goods	

U.S. DOT - INLAND WATERWAYS

Not dangerous goods	

TDG ROAD C

Not dangerous goods

TDG RAIL C

Not dangerous goods

Valvoline	Page: 16
SAFETY DATA SHEET	Revision Date: 05/22/2017
	Print Date: 6/2/2017
	SDS Number: R0382102
Zerex [™] DEX-COOL® Orange OAT Formula RTU Antifreeze	Version: 1.3
Coolant	
ZXELRU1	

TDG	INWT	C

Not dangerous goods

INTERNATIONAL MARITIME DANGEROUS GOODS

Not dangerous goods

INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO

Not dangerous goods

INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER

Not dangerous goods

MX DG

Not dangerous goods	
gerete gerete	

*ORM = ORM-D, CBL = COMBUSTIBLE LIQUID

Marine pollutant	no	

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ	Calculated product RQ
		(lbs)	(lbs)
ETHYLENE GLYCOL	107-21-1	5000	10477

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards : Chronic Health Hazard

Acute Health Hazard

SARA 313

ETHYLENE GLYCOL 107-21-1 47.72 %

Valvoline.	Page: 17
SAFETY DATA SHEET	Revision Date: 05/22/2017
	Print Date: 6/2/2017
	SDS Number: R0382102
Zerex [™] DEX-COOL® Orange OAT Formula RTU Antifreeze Coolant	Version: 1.3
ZXELRU1	

California Prop 65 : This product does not contain any chemicals known to State

of California to cause cancer, birth defects, or any other

reproductive harm.

The components of this product are reported in the following inventories:

DSL : This product contains one or several components that are not

on the Canadian DSL and have annual quantity limits.

AICS : Not in compliance with the inventory

ENCS : Not in compliance with the inventory

KECI : Not in compliance with the inventory

PICCS : Not in compliance with the inventory

IECSC : On the inventory, or in compliance with the inventory

TSCA : On TSCA Inventory


Inventories

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (USA)

SECTION 16. OTHER INFORMATION

Further information

Revision Date: 05/22/2017



NFPA Flammable and Combustible Liquids Classification

Combustible Liquid Class IIIB

Full text of H-Statements

Valvoline.	Page: 18
SAFETY DATA SHEET	Revision Date: 05/22/2017
	Print Date: 6/2/2017
	SDS Number: R0382102
Zerex [™] DEX-COOL® Orange OAT Formula RTU Antifreeze	Version: 1.3
Coolant	
ZVELDIJA	
ZXELRU1	

H302 Harmful if swallowed. H315 Causes skin irritation.

H361d Suspected of damaging the unborn child.

H373 May cause damage to organs through prolonged or repeated exposure

if swallowed.

Sources of key data used to compile the Safety Data Sheet Valvoline internal data including own and sponsored test reports The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Valvoline's Environmental Health and Safety Department (1-800-VALVOLINE).

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet:

ACGIH: American Conference of Industrial Hygienists

BEI: Biological Exposure Index

CAS: Chemical Abstracts Service (Division of the American Chemical Society).

CMR: Carcinogenic, Mutagenic or Toxic for Reproduction

FG: Food grade

GHS: Globally Harmonized System of Classification and Labeling of Chemicals.

H-statement : Hazard Statement

IATA: International Air Transport Association.

IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO: International Civil Aviation Organization

ICAO-TI (ICAO): Technical Instructions by the "International Civil Aviation Organization"

IMDG: International Maritime Code for Dangerous Goods

ISO: International Organization for Standardization

logPow: octanol-water partition coefficient

LCxx: Lethal Concentration, for xx percent of test population

LDxx: Lethal Dose, for xx percent of test population. ICxx: Inhibitory Concentration for xx of a substance

Ecxx: Effective Concentration of xx N.O.S.: Not Otherwise Specified

OECD: Organization for Economic Co-operation and Development

OEL : Occupational Exposure Limit
P-Statement : Precautionary Statement
PBT : Persistent , Bioaccumulative and Toxic

PPE: Personal Protective Equipment STEL: Short-term exposure limit

Valvoline.	Page: 19
SAFETY DATA SHEET	Revision Date: 05/22/2017
	Print Date: 6/2/2017
	SDS Number: R0382102
Zerex [™] DEX-COOL® Orange OAT Formula RTU Antifreeze	Version: 1.3
Coolant	
ZXELRU1	

STOT: Specific Target Organ Toxicity

TLV : Threshold Limit Value TWA : Time-weighted average

vPvB: Very Persistent and Very Bioaccumulative

WEL: Workplace Exposure Level

CERCLA: Comprehensive Environmental Response, Compensation, and Liability Act

DOT: Department of Transportation

FIFRA: Federal Insecticide, Fungicide, and Rodenticide Act HMIRC: Hazardous Materials Information Review Commission

HMIS: Hazardous Materials Identification System NFPA: National Fire Protection Association

NIOSH: National Institute for Occupational Safety and Health

OSHA: Occupational Safety and Health Administration

PMRA: Health Canada Pest Management Regulatory Agency

RTK: Right to Know

WHMIS: Workplace Hazardous Materials Information System