

# Oxygen, refrigerated liquid

## Safety Data Sheet P-4637

This SDS conforms to U.S. Code of Federal Regulations 29 CFR 1910.1200, Hazard Communication.

Date of issue: 01/01/1979

Revision date: 10/21/2016

Supersedes: 09/02/2016

### SECTION: 1. Product and company identification

#### 1.1. Product identifier

Product form : Substance  
Name : Oxygen, refrigerated liquid  
CAS No : 7782-44-7  
Formula : O<sub>2</sub>  
Other means of identification : Oxygen (cryogenic liquid), Liquid Oxygen, Medipure Liquid Oxygen

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Industrial use  
Medical applications

#### 1.3. Details of the supplier of the safety data sheet

Praxair, Inc.  
10 Riverview Drive  
Danbury, CT 06810-6268 - USA  
T 1-800-772-9247 (1-800-PRAXAIR) - F 1-716-879-2146  
[www.praxair.com](http://www.praxair.com)

#### 1.4. Emergency telephone number

Emergency number : Onsite Emergency: 1-800-645-4633

CHEMTREC, 24hr/day 7days/week  
— Within USA: 1-800-424-9300, Outside USA: 001-703-527-3887  
(collect calls accepted, Contract 17729)

### SECTION 2: Hazard identification

#### 2.1. Classification of the substance or mixture

##### GHS-US classification

Ox. Gas 1 H270  
Refrigerated liquefied gas H281

#### 2.2. Label elements

##### GHS-US labeling

Hazard pictograms (GHS-US) :



GHS03

GHS04

Signal word (GHS-US) : DANGER

Hazard statements (GHS-US) : H270 - MAY CAUSE OR INTENSIFY FIRE; OXIDIZER  
H281 - CONTAINS REFRIGERATED GAS; MAY CAUSE CRYOGENIC BURNS OR INJURY  
CGA-HG13 - COMBUSTIBLES IN CONTACT WITH LIQUID OXYGEN MAY EXPLODE ON IGNITION OR IMPACT

Precautionary statements (GHS-US) : P202 - Do not handle until all safety precautions have been read and understood  
P220 - Keep/Store away from clothing, combustible materials  
P244 - Keep reduction valves/valves and fittings free from oil and grease  
P271+P403 - Use and store only outdoors or in a well-ventilated place  
P282 - Wear cold insulating gloves/face shield/eye protection. cold insulating gloves, face shield, eye protection  
P370+P376 - In case of fire: Stop leak if safe to do so  
CGA-PG05 - Use a back flow preventive device in the piping  
CGA-PG20+CGA-PG10 - Use only with equipment of compatible materials of construction and rated for cylinder pressure

# Oxygen, refrigerated liquid

## Safety Data Sheet P-4637

This SDS conforms to U.S. Code of Federal Regulations 29 CFR 1910.1200, Hazard Communication.

Date of issue: 01/01/1979 Revision date: 10/21/2016 Supersedes: 09/02/2016

CGA-PG22 - Use only with equipment cleaned for oxygen service  
CGA-PG24 - DO NOT change or force fit connections  
CGA-PG28 - Avoid spills. Do not walk on or roll equipment over spills  
CGA-PG06 - Close valve after each use and when empty  
CGA-PG23 - Always keep container in upright position

### 2.3. Other hazards

Other hazards not contributing to the classification : Breathing 80 percent or more oxygen at atmospheric pressure for more than a few hours may cause nasal stuffiness, cough, sore throat, chest pain, and breathing difficulty. Breathing oxygen at higher pressure increases the likelihood of adverse effects within a shorter time period. Breathing pure oxygen under pressure may cause lung damage and central nervous system (CNS) effects, resulting in dizziness, poor coordination, tingling sensation, visual and hearing disturbances, muscular twitching, unconsciousness, and convulsions. Breathing oxygen under pressure may cause prolongation of adaptation to darkness and reduced peripheral vision

Contact with liquid may cause cold burns/frostbite.

### 2.4. Unknown acute toxicity (GHS US)

No data available

## SECTION 3: Composition/Information on ingredients

### 3.1. Substance

| Name                                              | Product identifier | %   |
|---------------------------------------------------|--------------------|-----|
| Oxygen, refrigerated liquid<br>(Main constituent) | (CAS No) 7782-44-7 | 100 |

### 3.2. Mixture

Not applicable

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

First-aid measures after inhalation : Remove victim to uncontaminated area. Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep victim warm and rested. Call a doctor. Apply artificial respiration if breathing stopped.

First-aid measures after skin contact : The liquid may cause frostbite. For exposure to liquid, immediately warm frostbite area with warm water not to exceed 105°F (41°C). Water temperature should be tolerable to normal skin. Maintain skin warming for at least 15 minutes or until normal coloring and sensation have returned to the affected area. In case of massive exposure, remove clothing while showering with warm water. Seek medical evaluation and treatment as soon as possible.

First-aid measures after eye contact : Immediately flush eyes thoroughly with water for at least 15 minutes. Hold the eyelids open and away from the eyeballs to ensure that all surfaces are flushed thoroughly. Contact an ophthalmologist immediately.. Get immediate medical attention.

First-aid measures after ingestion : Ingestion is not considered a potential route of exposure.

### 4.2. Most important symptoms and effects, both acute and delayed

No additional information available

### 4.3. Indication of any immediate medical attention and special treatment needed

None.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Suitable extinguishing media : Vigorously accelerates combustion. Use media appropriate for surrounding fire. Water (e.g, safety shower) is the preferred extinguishing media for clothing fires.

### 5.2. Special hazards arising from the substance or mixture

Fire hazard : Oxidizing agent; vigorously accelerates combustion. Contact with flammable materials may cause fire or explosion.

Reactivity : No reactivity hazard other than the effects described in sub-sections below.

# Oxygen, refrigerated liquid

## Safety Data Sheet P-4637

This SDS conforms to U.S. Code of Federal Regulations 29 CFR 1910.1200, Hazard Communication.

Date of issue: 01/01/1979    Revision date: 10/21/2016    Supersedes: 09/02/2016

### 5.3. Advice for firefighters

- Firefighting instructions** : DANGER! Extremely cold liquid and gas under pressure. Take care not to direct spray onto vents on top of container. Do not discharge sprays directly into liquid; cryogenic liquid can freeze water rapidly
- Evacuate all personnel from the danger area. Use self-contained breathing apparatus (SCBA) and protective clothing. Immediately cool containers with water from maximum distance. Stop flow of gas if safe to do so, while continuing cooling water spray. Remove ignition sources if safe to do so. Remove containers from area of fire if safe to do so. On-site fire brigades must comply with OSHA 29 CFR 1910.156 and applicable standards under 29 CFR 1910 Subpart L—Fire Protection.
- Protection during firefighting** : Do not enter fire area without proper protective equipment, including respiratory protection.
- Special protective equipment for fire fighters** : Standard protective clothing and equipment (Self Contained Breathing Apparatus) for fire fighters.
- Specific methods** : Use fire control measures appropriate for the surrounding fire. Exposure to fire and heat radiation may cause gas containers to rupture. Cool endangered containers with water spray jet from a protected position. Prevent water used in emergency cases from entering sewers and drainage systems
- Exposure to fire may cause containers to rupture/explode
- Stop flow of product if safe to do so
- Use water spray or fog to knock down fire fumes if possible
- If leaking do not spray water onto container. Water surrounding area (from protected position) to contain fire.
- Other information** : Do not walk on or roll equipment over a spill; any impact could cause an explosion. Smoking, flames, and electric sparks are potential explosion hazards in oxygen-enriched atmospheres
- Containers are equipped with a pressure relief device. (Exceptions may exist where authorized by DOT.)
- Cryogenic liquid causes severe frostbite, a burn-like injury. Heat of fire can build pressure in a closed container and cause it to rupture. Venting vapors may obscure visibility. Air will condense on surfaces such as vaporizers or piping exposed to liquid or cold gas. Nitrogen, which has a lower boiling point than oxygen, evaporates first, leaving an oxygen-enriched condensate.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

- General measures** : Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous. Ensure adequate air ventilation. Eliminate ignition sources. Evacuate area. Try to stop release. Monitor concentration of released product. Wear self-contained breathing apparatus when entering area unless atmosphere is proven to be safe. Stop leak if safe to do so.

#### 6.1.1. For non-emergency personnel

No additional information available

#### 6.1.2. For emergency responders

No additional information available

### 6.2. Environmental precautions

Try to stop release.

### 6.3. Methods and material for containment and cleaning up

No additional information available

### 6.4. Reference to other sections

See also sections 8 and 13.

# Oxygen, refrigerated liquid

## Safety Data Sheet P-4637

This SDS conforms to U.S. Code of Federal Regulations 29 CFR 1910.1200, Hazard Communication.

Date of issue: 01/01/1979 Revision date: 10/21/2016 Supersedes: 09/02/2016

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

##### Precautions for safe handling

: Never use oxygen as a substitute for compressed air. Never use an oxygen jet for any type of cleaning, especially for cleaning clothing. Oxygen-saturated clothing may burst into flame at the slightest spark and be quickly consumed in an engulfing fire. Do not get liquid in eyes, on skin, or on clothing. Persons exposed to high concentrations of liquid oxygen should stay in a well-ventilated or open area for 30 minutes before entering a confined space or going near any source of ignition. Immediately remove clothing exposed to oxygen and air it out to reduce the likelihood of an engulfing fire. Prevent ignition sources, such as static electricity generated in clothing while walking

Wear leather safety gloves and safety shoes when handling cylinders. Protect cylinders from physical damage; do not drag, roll, slide or drop. While moving cylinder, always keep in place removable valve cover. Never attempt to lift a cylinder by its cap; the cap is intended solely to protect the valve. When moving cylinders, even for short distances, use a cart (trolley, hand truck, etc.) designed to transport cylinders. Never insert an object (e.g. wrench, screwdriver, pry bar) into cap openings; doing so may damage the valve and cause a leak. Use an adjustable strap wrench to remove over-tight or rusted caps. Slowly open the valve. If the valve is hard to open, discontinue use and contact your supplier. Close the container valve after each use; keep closed even when empty. Never apply flame or localized heat directly to any part of the container. High temperatures may damage the container and could cause the pressure relief device to fail prematurely, venting the container contents. For other precautions in using this product, see section 16.

#### 7.2. Conditions for safe storage, including any incompatibilities

##### Storage conditions

: Store only where temperature will not exceed 125°F (52°C). Post "No Smoking/No Open Flames" signs in storage and use areas. There must be no sources of ignition. Separate packages and protect against potential fire and/or explosion damage following appropriate codes and requirements (e.g. NFPA 30, NFPA 55, NFPA 70, and/or NFPA 221 in the U.S.) or according to requirements determined by the Authority Having Jurisdiction (AHJ). Always secure containers upright to keep them from falling or being knocked over. Install valve protection cap, if provided, firmly in place by hand when the container is not in use. Store full and empty containers separately. Use a first-in, first-out inventory system to prevent storing full containers for long periods. For other precautions in using this product, see section 16

**OTHER PRECAUTIONS FOR HANDLING, STORAGE, AND USE:** When handling product under pressure, use piping and equipment adequately designed to withstand the pressures to be encountered. Never work on a pressurized system. Use a back flow preventive device in the piping. Store and use with adequate ventilation. If a leak occurs, close the container valve and blow down the system in a safe and environmentally correct manner in compliance with all international, federal/national, state/provincial, and local laws; then repair the leak. Never place a container where it may become part of an electrical circuit

When working with cryogenic/cold liquid or gaseous oxygen under pressure, avoid using materials that are incompatible with oxygen use

When working with cryogenic/cold liquid or gas under pressure, avoid using materials that are incompatible with cryogenic use. Some metals, such as carbon steel, may fracture easily at low temperature. Use only transfer lines designed for cryogenic liquids. Prevent liquid or cold gas from being trapped in piping between valves. Equip the piping with pressure relief devices. Praxair recommends piping all vents to the exterior of the building.

#### 7.3. Specific end use(s)

None.

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

| Oxygen, refrigerated liquid (7782-44-7) |                 |
|-----------------------------------------|-----------------|
| ACGIH                                   | Not established |
| USA OSHA                                | Not established |

# Oxygen, refrigerated liquid

## Safety Data Sheet P-4637

This SDS conforms to U.S. Code of Federal Regulations 29 CFR 1910.1200, Hazard Communication.

Date of issue: 01/01/1979    Revision date: 10/21/2016    Supersedes: 09/02/2016

### 8.2. Exposure controls

|                                  |                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
|----------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Appropriate engineering controls | : Avoid oxygen rich (>23.5%) atmospheres. Systems under pressure should be regularly checked for leakages. Ensure exposure is below occupational exposure limits (where available). Gas detectors should be used when oxidizing gases may be released. Oxygen detectors should be used when asphyxiating gases may be released. Provide adequate general and local exhaust ventilation. Consider work permit system e.g. for maintenance activities. |
| Hand protection                  | : Wear working gloves when handling gas containers.                                                                                                                                                                                                                                                                                                                                                                                                  |
| Eye protection                   | : Wear safety glasses with side shields. Wear goggles and a face shield when transfilling or breaking transfer connections.                                                                                                                                                                                                                                                                                                                          |
| Skin and body protection         | : Wear loose-fitting, cryogenic gloves, metatarsal shoes for container handling, and protective clothing where needed. Cuffless trousers should be worn outside the shoes. Gloves must be free of oil and grease. Select in accordance with OSHA 29 CFR 1910.132, 1910.136, and 1910.138.                                                                                                                                                            |
| Respiratory protection           | : None required under normal use. An air-supplied respirator must be used while working with this product in confined spaces. The respiratory protection used must conform with OSHA rules as specified in 29 CFR 1910.134. Select per OSHA 29 CFR 1910.134 and ANSI Z88.2.                                                                                                                                                                          |
| Thermal hazard protection        | : Wear cold insulating gloves. Wear cold insulating gloves when transfilling or breaking transfer connections.                                                                                                                                                                                                                                                                                                                                       |
| Environmental exposure controls  | : None necessary.                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| Other information                | : Consider the use of flame resistant safety clothing. Wear safety shoes while handling containers.                                                                                                                                                                                                                                                                                                                                                  |

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

|                                             |                                         |
|---------------------------------------------|-----------------------------------------|
| Physical state                              | : Gas                                   |
| Appearance                                  | : Colorless gas.                        |
| Molecular mass                              | : 32 g/mol                              |
| Color                                       | : Bluish liquid.                        |
| Odor                                        | : Odorless.                             |
| Odor threshold                              | : No data available                     |
| pH                                          | : Not applicable.                       |
| Relative evaporation rate (butyl acetate=1) | : No data available                     |
| Relative evaporation rate (ether=1)         | : Not applicable.                       |
| Melting point                               | : -219 °C (-362°F)                      |
| Freezing point                              | : -218.4 °C (-361°F)                    |
| Boiling point                               | : -183 °C (-297°F)                      |
| Flash point                                 | : No data available                     |
| Critical temperature                        | : -118.6 °C (-181°F)                    |
| Auto-ignition temperature                   | : Not applicable.                       |
| Decomposition temperature                   | : No data available                     |
| Flammability (solid, gas)                   | : No data available                     |
| Vapor pressure                              | : Not applicable.                       |
| Critical pressure                           | : 50.4 bar (731.4 psia)                 |
| Relative vapor density at 20 °C             | : No data available                     |
| Relative density                            | : 1.1                                   |
| Density                                     | : 1.4289 kg/m <sup>3</sup> (at 21.1 °C) |
| Relative gas density                        | : 1.1                                   |
| Solubility                                  | : Water: 39 mg/l                        |
| Log Pow                                     | : Not applicable.                       |
| Log Kow                                     | : Not applicable.                       |
| Viscosity, kinematic                        | : Not applicable.                       |
| Viscosity, dynamic                          | : Not applicable.                       |

# Oxygen, refrigerated liquid

## Safety Data Sheet P-4637

This SDS conforms to U.S. Code of Federal Regulations 29 CFR 1910.1200, Hazard Communication.

Date of issue: 01/01/1979

Revision date: 10/21/2016

Supersedes: 09/02/2016

|                      |                     |
|----------------------|---------------------|
| Explosive properties | : Not applicable.   |
| Oxidizing properties | : Oxidizer.         |
| Explosion limits     | : No data available |

### 9.2. Other information

|                        |                                                                                                        |
|------------------------|--------------------------------------------------------------------------------------------------------|
| Gas group              | : Refrigerated liquefied gas                                                                           |
| Additional information | : Gas/vapor heavier than air. May accumulate in confined spaces, particularly at or below ground level |

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No reactivity hazard other than the effects described in sub-sections below.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

Risk of explosion if spilt on organic structural materials (e.g. wood or asphalt). Violently oxidizes organic material.

### 10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

### 10.5. Incompatible materials

Consult supplier for specific recommendations. Consider the potential toxicity hazard due to the presence of chlorinated or fluorinated polymers in high pressure (> 30 bar) oxygen lines in case of combustion. Keep equipment free from oil and grease. May react violently with combustible materials. May react violently with reducing agents.

### 10.6. Hazardous decomposition products

None.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

|                                                    |                     |
|----------------------------------------------------|---------------------|
| Acute toxicity                                     | : Not classified    |
| Skin corrosion/irritation                          | : Not classified    |
|                                                    | pH: Not applicable. |
| Serious eye damage/irritation                      | : Not classified    |
|                                                    | pH: Not applicable. |
| Respiratory or skin sensitization                  | : Not classified    |
| Germ cell mutagenicity                             | : Not classified    |
| Carcinogenicity                                    | : Not classified    |
| Reproductive toxicity                              | : Not classified    |
| Specific target organ toxicity (single exposure)   | : Not classified    |
| Specific target organ toxicity (repeated exposure) | : Not classified    |
| Aspiration hazard                                  | : Not classified    |

## SECTION 12: Ecological information

### 12.1. Toxicity

|                   |                                                |
|-------------------|------------------------------------------------|
| Ecology - general | : No ecological damage caused by this product. |
|-------------------|------------------------------------------------|

### 12.2. Persistence and degradability

#### Oxygen, refrigerated liquid (7782-44-7)

|                               |                                              |
|-------------------------------|----------------------------------------------|
| Persistence and degradability | No ecological damage caused by this product. |
|-------------------------------|----------------------------------------------|

# Oxygen, refrigerated liquid

## Safety Data Sheet P-4637

This SDS conforms to U.S. Code of Federal Regulations 29 CFR 1910.1200, Hazard Communication.

Date of issue: 01/01/1979

Revision date: 10/21/2016

Supersedes: 09/02/2016

### 12.3. Bioaccumulative potential

| Oxygen, refrigerated liquid (7782-44-7) |                                              |
|-----------------------------------------|----------------------------------------------|
| Log Pow                                 | Not applicable.                              |
| Log Kow                                 | Not applicable.                              |
| Bioaccumulative potential               | No ecological damage caused by this product. |

### 12.4. Mobility in soil

| Oxygen, refrigerated liquid (7782-44-7) |                                              |
|-----------------------------------------|----------------------------------------------|
| Mobility in soil                        | No data available.                           |
| Ecology - soil                          | No ecological damage caused by this product. |

### 12.5. Other adverse effects

|                              |                                         |
|------------------------------|-----------------------------------------|
| Other adverse effects        | : Can cause frost damage to vegetation. |
| Effect on ozone layer        | : None                                  |
| Effect on the global warming | : No known effects from this product    |

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

|                                |                                                                                                                                                      |
|--------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------|
| Waste treatment methods        | : Do not discharge into any place where its accumulation could be dangerous.                                                                         |
| Waste disposal recommendations | : Dispose of contents/container in accordance with local/regional/national/international regulations. Contact supplier for any special requirements. |

## SECTION 14: Transport information

|                                |                                                                 |
|--------------------------------|-----------------------------------------------------------------|
| In accordance with DOT         |                                                                 |
| Transport document description | : UN1073 Oxygen, refrigerated liquid (cryogenic liquid), 2.2    |
| UN-No.(DOT)                    | : UN1073                                                        |
| Proper Shipping Name (DOT)     | : Oxygen, refrigerated liquid<br>(cryogenic liquid)             |
| Class (DOT)                    | : 2.2 - Class 2.2 - Non-flammable compressed gas 49 CFR 173.115 |
| Hazard labels (DOT)            | : 2.2 - Non-flammable gas<br>5.1 - Oxidizer                     |



|                                         |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
|-----------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| DOT Special Provisions (49 CFR 172.102) | : T75 - When portable tank instruction T75 is referenced in Column (7) of the 172.101 Table, the applicable refrigerated liquefied gases are authorized to be transported in portable tanks in accordance with the requirements of 178.277 of this subchapter<br>TP5 - For a portable tank used for the transport of flammable refrigerated liquefied gases or refrigerated liquefied oxygen, the maximum rate at which the portable tank may be filled must not exceed the liquid flow capacity of the primary pressure relief system rated at a pressure not exceeding 120 percent of the portable tank's design pressure. For portable tanks used for the transport of refrigerated liquefied helium and refrigerated liquefied atmospheric gas (except oxygen), the maximum rate at which the tank is filled must not exceed the liquid flow capacity of the pressure relief device rated at 130 percent of the portable tank's design pressure. Except for a portable tank containing refrigerated liquefied helium, a portable tank shall have an outage of at least two percent below the inlet of the pressure relief device or pressure control valve, under conditions of incipient opening, with the portable tank in a level attitude. No outage is required for helium<br>TP22 - Lubricants for portable tank fittings (for example, gaskets, shut-off valves, flanges) must be oxygen compatible |
|-----------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

### Additional information

|                                       |                                           |
|---------------------------------------|-------------------------------------------|
| Emergency Response Guide (ERG) Number | : 122 (UN1072)                            |
| Other information                     | : No supplementary information available. |

# Oxygen, refrigerated liquid

## Safety Data Sheet P-4637

This SDS conforms to U.S. Code of Federal Regulations 29 CFR 1910.1200, Hazard Communication.

Date of issue: 01/01/1979    Revision date: 10/21/2016    Supersedes: 09/02/2016

Special transport precautions : Avoid transport on vehicles where the load space is not separated from the driver's compartment. Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency. Before transporting product containers:

- Ensure there is adequate ventilation.
- Ensure that containers are firmly secured.
- Ensure cylinder valve is closed and not leaking.
- Ensure valve outlet cap nut or plug (where provided) is correctly fitted.
- Ensure valve protection device (where provided) is correctly fitted.

### Transport by sea

UN-No. (IMDG) : 1073  
 Proper Shipping Name (IMDG) : OXYGEN, REFRIGERATED LIQUID  
 Class (IMDG) : 2 - Gases  
 MFAG-No : 122

### Air transport

UN-No. (IATA) : 1073  
 Proper Shipping Name (IATA) : Oxygen, refrigerated liquid  
 Class (IATA) : 2  
 Civil Aeronautics Law : Gases under pressure/Gases nonflammable nontoxic under pressure

## SECTION 15: Regulatory information

### 15.1. US Federal regulations

| Oxygen, refrigerated liquid (7782-44-7)                                   |                                                                                     |
|---------------------------------------------------------------------------|-------------------------------------------------------------------------------------|
| Listed on the United States TSCA (Toxic Substances Control Act) inventory |                                                                                     |
| SARA Section 311/312 Hazard Classes                                       | Fire hazard<br>Immediate (acute) health hazard<br>Sudden release of pressure hazard |

All components of this product are listed on the Toxic Substances Control Act (TSCA) inventory.

This product or mixture does not contain a toxic chemical or chemicals in excess of the applicable de minimis concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

### 15.2. International regulations

#### CANADA

| Oxygen, refrigerated liquid (7782-44-7)               |
|-------------------------------------------------------|
| Listed on the Canadian DSL (Domestic Substances List) |

#### EU-Regulations

| Oxygen, refrigerated liquid (7782-44-7)                                                            |
|----------------------------------------------------------------------------------------------------|
| Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances) |

### 15.2.2. National regulations

| Oxygen, refrigerated liquid (7782-44-7)                                                                                                                                                                                                                                                                                                                                                                                           |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Listed on the AICS (Australian Inventory of Chemical Substances)<br>Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)<br>Listed on the Korean ECL (Existing Chemicals List)<br>Listed on NZIoC (New Zealand Inventory of Chemicals)<br>Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)<br>Listed on INSQ (Mexican National Inventory of Chemical Substances) |

# Oxygen, refrigerated liquid

## Safety Data Sheet P-4637

This SDS conforms to U.S. Code of Federal Regulations 29 CFR 1910.1200, Hazard Communication.

Date of issue: 01/01/1979 Revision date: 10/21/2016 Supersedes: 09/02/2016

### 15.3. US State regulations

| Oxygen, refrigerated liquid(7782-44-7)                              |                                                                                                                                                           |
|---------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------|
| U.S. - California - Proposition 65 - Carcinogens List               | No                                                                                                                                                        |
| U.S. - California - Proposition 65 - Developmental Toxicity         | No                                                                                                                                                        |
| U.S. - California - Proposition 65 - Reproductive Toxicity - Female | No                                                                                                                                                        |
| U.S. - California - Proposition 65 - Reproductive Toxicity - Male   | No                                                                                                                                                        |
| State or local regulations                                          | U.S. - Massachusetts - Right To Know List<br>U.S. - New Jersey - Right to Know Hazardous Substance List<br>U.S. - Pennsylvania - RTK (Right to Know) List |

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

## SECTION 16: Other information

### Other information

: When you mix two or more chemicals, you can create additional, unexpected hazards. Obtain and evaluate the safety information for each component before you produce the mixture. Consult an industrial hygienist or other trained person when you evaluate the end product. Before using any plastics, confirm their compatibility with this product

Praxair asks users of this product to study this SDS and become aware of the product hazards and safety information. To promote safe use of this product, a user should (1) notify employees, agents, and contractors of the information in this SDS and of any other known product hazards and safety information, (2) furnish this information to each purchaser of the product, and (3) ask each purchaser to notify its employees and customers of the product hazards and safety information

The opinions expressed herein are those of qualified experts within Praxair, Inc. We believe that the information contained herein is current as of the date of this Safety Data Sheet. Since the use of this information and the conditions of use are not within the control of Praxair, Inc, it is the user's obligation to determine the conditions of safe use of the product

Praxair SDSs are furnished on sale or delivery by Praxair or the independent distributors and suppliers who package and sell our products. To obtain current SDSs for these products, contact your Praxair sales representative, local distributor, or supplier, or download from [www.praxair.com](http://www.praxair.com). If you have questions regarding Praxair SDSs, would like the document number and date of the latest SDS, or would like the names of the Praxair suppliers in your area, phone or write the Praxair Call Center (Phone: 1-800-PRAXAIR/1-800-772-9247; Address: Praxair Call Center, Praxair, Inc, P.O. Box 44, Tonawanda, NY 14151-0044)

PRAXAIR and the Flowing Airstream design are trademarks or registered trademarks of Praxair Technology, Inc. in the United States and/or other countries.

### NFPA health hazard

: 3 - Short exposure could cause serious temporary or residual injury even though prompt medical attention was given.

### NFPA fire hazard


: 0 - Materials that will not burn.

### NFPA reactivity

: 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.

### NFPA specific hazard

: OX - This denotes an oxidizer, a chemical which can greatly increase the rate of combustion/fire.



# Oxygen, refrigerated liquid

## Safety Data Sheet P-4637

This SDS conforms to U.S. Code of Federal Regulations 29 CFR 1910.1200, Hazard Communication.

Date of issue: 01/01/1979    Revision date: 10/21/2016    Supersedes: 09/02/2016

### HMIS III Rating

|              |                                                                                                       |
|--------------|-------------------------------------------------------------------------------------------------------|
| Health       | : 3 Serious Hazard - Major injury likely unless prompt action is taken and medical treatment is given |
| Flammability | : 0 Minimal Hazard                                                                                    |
| Physical     | : 2 Moderate Hazard                                                                                   |

SDS US (GHS HazCom 2012) - Praxair

*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.*