REVISION DATE 15/01/2013

# MATERIAL SAFETY DATA SHEET PALFIQUE ESTELITE LV High-Flow

# 1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

PRODUCT NAME PALFIQUE ESTELITE LV High-Flow

PRODUCT USE Resin-based Dental Restorative Material. For dental professionals only.

SUPPLIER Tokuyama Dental America Inc. MANUFACTURER

Tel: (877) 378 3548 (Toll-Free)

Tokuyama Dental Corporation

38-9, Taitou 1-chome, Taitou-ku, Tokyo, Japan

TEL: +81-3-3835-7201

CONTACT PERSON http://www.tokuyama-dental.com/contact.htm

EMERGENCY TELEPHONE Washington

National Capital Poison Center

3201 New Mexico Avenue, Suite 310 Washington, DC 20016

Telephone: +1 202 362 3867

Emergency telephone: 1 800 222 1222

Fax: +1 202 362 8377 E-mail: pc@poison.org Web site: http://www.poison.org

San Francisco

California Poison Control System at San Francisco General Hospital

University of California San Francisco, Box 1369

1001 Potrero Avenue, Bldg 5 Rm 2A21 San Francisco, California 94143-1369

Telephone: +1 415 643 3200

Emergency telephone: 1 800 222 1222

Fax: +1 415 502 6010

E-mail: coadmin@calpoison.org Web site: http://www.calpoison.org

http://www.who.int/ipcs/poisons/centre/en/

# 2 HAZARDS IDENTIFICATION

# POTENTIAL HEALTH EFFECTS

INGESTION

Slightly irritating. DIGESTIVE SYSTEM.

SKIN CONTACT

Slightly irritating. May cause sensitization by skin contact.

EYE CONTACT Slightly irritating.

# 3 COMPOSITION/INFORMATION ON INGREDIENTS

Name	EC No.	CAS-No.	Content %
bisphenol A di(2-hydroxy propoxy) dimethacrylate	216-367-7	1565-94-2	10-30%
camphorquinone	233-814-1	10373-78-1	< 1%
dibutyl hydroxy toluene	204-881-4	128-37-0	< 1%
MEQUINOL	205-769-8	150-76-5	< 1%
N,N-DIMETHYL-PARA-TOLUIDINE	202-805-4	99-97-8	< 1%
triethylene glycol dimethacrylate	203-652-6	109-16-0	10-30%

## **4 FIRST-AID MEASURES**

# PALFIQUE ESTELITE LV High-Flow

#### **GENERAL INFORMATION**

Move the exposed person to fresh air at once. Get medical attention if any discomfort continues.

**INHALATION** 

Move the exposed person to fresh air at once.

INGESTION

Try to induce vomiting. Get medical attention if any discomfort continues.

SKIN CONTACT

Wash the skin immediately with soap and water.

**EYE CONTACT** 

Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes. Contact physician if irritation persists.

#### **5 FIRE-FIGHTING MEASURES**

## **EXTINGUISHING MEDIA**

Fire can be extinguished using: Foam. Carbon dioxide or dry powder.

SPECIAL FIRE FIGHTING PROCEDURES

Avoid breathing fire vapors.

SPECIFIC HAZARDS

When heated and in case of fire, irritating vapours/gases may be formed.

PROTECTIVE MEASURES IN FIRE

Wear full protective clothing.

## **6 ACCIDENTAL RELEASE MEASURES**

#### PERSONAL PRECAUTIONS

Wear protective clothing as described in Section 8 of this material safety data sheet.

SPILL CLEAN UP METHODS

Absorb in vermiculite, dry sand or earth and place into containers. Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate.

## **7 HANDLING AND STORAGE**

**HANDLING** 

All handling to take place in well-ventilated area.

STORAGE

Store in a cool, dark place (0-25°C, 32-77°F). Keep away from heat, direct sunlight, sparks and open flames.

STORAGE CLASS

Chemical storage.

# **8 EXPOSURE CONTROLS/PERSONAL PROTECTION**

#### PROTECTIVE EQUIPMENT





# **ENGINEERING MEASURES**

Provide adequate general and local exhaust ventilation.

HAND PROTECTION

Wear protective gloves.

**EYE PROTECTION** 

Wear approved safety goggles.

OTHER PROTECTION

Wear appropriate clothing to prevent any possibility of skin contact.

# PALFIQUE ESTELITE LV High-Flow

#### HYGIENE MEASURES

DO NOT SMOKE IN WORK AREA! Wash at the end of each work shift and before eating, smoking and using the toilet. Wash promptly with soap & water if skin becomes contaminated. Promptly remove any clothing that becomes contaminated. Use appropriate skin cream to prevent drying of skin. When using do not eat, drink or smoke.

# 9 PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE Paste

COLOR Yellow white

pH-VALUE, CONC. SOLUTION 7

## 10 STABILITY AND REACTIVITY

#### **STABILITY**

Stable under normal temperature conditions and recommended use.

CONDITIONS TO AVOID

Keep away from heat, sparks and open flame. Protect against direct sunlight.

MATERIALS TO AVOID

Strong oxidizing agents.

HAZARDOUS DECOMPOSITION PRODUCTS

Toxic gases are generated when heated.

# 11 TOXICOLOGICAL INFORMATION

## TOXICOLOGICAL INFORMATION

No data on possible toxic effects have been found.

## 12 ECOLOGICAL INFORMATION

# **ECOTOXICITY**

No data on possible environmental effects have been found.

# 13 DISPOSAL CONSIDERATIONS

**DISPOSAL METHODS** 

Dispose of waste and residues in accordance with local authority requirements.

# 14 TRANSPORT INFORMATION

TRANSPORT NOTES Not regulated.

## 15 REGULATORY INFORMATION

# **INVENTORIES**

COMPONENT	CAN	US	EU	AUS	JAP	KOR	CHN	PHLP
MEQUINOL	No.	No.	EINECS					

COMPONENT	TSCA 12(b) Export Notification
MEQUINOL	No.

# US FEDERAL REGULATIONS

COMPONENT	SARA 302-TPQ	CERCLA-RQ	SARA 313
MEQUINOL	Not Listed	Not Listed	No.

# CLEAN AIR ACT

COMPONENT	CAA Accidental Release Prevention
MEQUINOL	Not Listed

# PALFIQUE ESTELITE LV High-Flow

# **US STATE REGULATIONS**

COMPONENT	CAS	CA	FL	MA	MN	NJ	PA	RI
MEQUINOL	150-76-5	Not Listed	Not Listed	Not Listed		Not Listed	Not Listed	Not Listed

**REGULATORY REFERENCES** 

29 CFR 1910. 1200(g) Federal Regulations (OSHA Standard).

46 OTHE	D INIEC		
16 OTHE	RIIVEL	JRIVIAI	וו אוו

**REVISION DATE** 

15/01/2013