MATERIAL SAFETY DATA SHEET

SECTION 1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

LUBRIPLATE® Lubricants Co.

129 Lockwood St. Newark, NJ 07105 Emergency Telephone Number: 1-800-255-3924-CHEM-TEL (24 hour) Telephone Number for information: 1-973-589-9150

SUBSTANCE: LUBRIPLATE PB Gun Oil

TRADE NAMES/SYNONYMS:

PRODUCT USE: Petroleum lubricating oil

CREATION DATE: 11/01/2007 **REVISION DATE:** 03/05/2009

SECTION 2 COMPOSITION/INFORMATION ON INGREDIENTS

COMPONENT: White mineral oil

CAS NUMBER: 8042-47-5

EC NUMBER (EINECS): 232-455-8

PERCENTAGE: 95-100

COMPONENT: Alkylated diphenylamine

CAS NUMBER: 68411-46-1

EC NUMBER (EINECS): 270-128-1

PERCENTAGE: 0-1

COMPONENT: Amines CAS NUMBER: 80939-62-4

EC NUMBER (EINECS): 279-632-6

PERCENTAGE: 0-1

COMPONENT: Triphenyl phosphorothionate

CAS NUMBER: 597-82-0

EC NUMBER (EINECS): 209-909-9

PERCENTAGE: 0-1

COMPONENT: Propyl paraben

CAS NUMBER: 94-13-3

EC NUMBER (EINECS): 202-307-7

PERCENTAGE: 0-1

COMPONENT: Dimethylpolysiloxane

CAS NUMBER: 63149-62-9

EC NUMBER (EINECS): not assigned

PERCENTAGE: 0-1

NOTE: The IP 346 value of the mineral oil is less than 3%

SECTION 3 HAZARDS IDENTIFICATION

POTENTIAL HEALTH EFFECTS:

INHALATION:

SHORT TERM EXPOSURE: Irritation **LONG TERM EXPOSURE:** Lung damage

SKIN CONTACT:

SHORT TERM EXPOSURE: Irritation

LONG TERM EXPOSURE: Irritation, skin disorders

EYE CONTACT:

SHORT TERM EXPOSURE: Irritation

LONG TERM EXPOSURE: No information available

INGESTION:

SHORT TERM EXPOSURE: Diarrhea, difficulty breathing

LONG TERM EXPOSURE: no information on significant adverse effects

HAZARDOUS MATERIAL IDENTIFICATION SYSTEM (HMIS):

Health – 1

Flammability – 1

Reactivity -0

Not a Controlled Product under (WHMIS) – Canada

Special Protection: See Section 8

SECTION 4 FIRST AID MEASURES

INHALATION: Vapor pressure is very low and inhalation at room temperature is not a problem. If overcome by vapor from hot product, immediately remove from exposure and call a physician. If over-exposed to oil mist, remove from further exposure until excessive oil mist conditions subside.

SKIN CONTACT: Remove any contaminated clothing and wash with soap and warm water. If injected by high pressure under skin, regardless of the appearance or its size, contact a physician IMMEDIATELY. Delay may cause loss of affected part of the body.

EYE CONTACT: Flush with clear water for 15 minutes or until irritations subsides. If irritation persists, consult a physician.

INGESTION: If ingested, call a physician immediately. Do not induce vomiting.

SECTION 5 FIRE FIGHTING MEASURES

FIRE AND EXPLOSION HAZARDS: Intense heat may cause drums to rupture.

EXTINGUISHING MEDIA: Foam, Dry Chemical, Carbon Dioxide or Water Spray (Fog)

SPECIAL FIRE FIGHTING PROCEDURES: After water evaporates and fire starts, treat as an oil fire.

UNUSUAL FIRE AND EXPLOSION HAZARDS: None

SECTION 6 ACCIDENTAL RELEASE MEASURES

OCCUPATIONAL RELEASE: Recover liquid, wash remainder with suitable petroleum solvent or add absorbent. Keep petroleum products out of sewers and water courses. Advise authorities if product has entered or may enter sewers and water courses.

WASTE DISPOSAL METHOD: Assure conformity with applicable disposal regulations. Dispose of absorbed material at an approved waste disposal facility or site.

SECTION 7 HANDLING AND STORAGE

STORAGE: Keep containers closed when not in use. Do not handle of store near heat, sparks, flame, or strong oxidants.

SECTION 8 EXPOSURE CONTROLS/PERSONAL PROTECTION

EXPOSURE LIMITS:

OIL MIST IN AIR (Not Encountered in Normal Usage):

5 mg/m³ UK OES TWA 10mg/m³ UK OES STEL

VENTILATION: Provide local exhaust ventilation system. Ensure compliance with applicable exposure limits.

EYE PROTECTION: Wear splash resistant safety goggles. Provide an emergency eye wash fountain and quick drench shower in the immediate work area.

CLOTHING: Wear appropriate chemical resistant clothing.

GLOVES: Wear appropriate chemical resistant (nitrile) gloves.

RESPIRATOR: Normally not needed.

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE: liquid APPEARANCE: transparent

COLOUR: amber

PHYSICAL FORM: oil ODOR: mineral oil odor BOILING POINT: >288 C

FREEZING POINT: Not available **FLASH POINT:** 198 C (COC)

LOWER FLAMMABLE LIMIT: 0.9% UPPER FLAMMABLE LIMIT: 7.0% AUTO IGNITION: 215 C (COC) VAPOUR PRESSURE: <0.01 mm Hg

VAPOR DENSITY (air=1): >5

SPECIFIC GRAVITY (water=1): 0.95

DENSITY: not available

WATER SOLUBILITY: Negligible

pH: not available

VOLATILITY: not available

ODOR THRESHOLD: not available

EVAPORATION RATE (butyl acetate=1): <0.01

VISCOSITY: $6.2 \text{ mm}^2/\text{s}$ at 100 C

COEFFICIENT OF WATER/OIL DISTRIBUTION: not available

SECTION 10 STABILITY AND REACTIVITY

REACTIVITY: Stable at normal temperatures and pressures

CONDITIONS TO AVOID: Avoid heat, flames, sparks and other sources of ignition. Avoid contact with incompatible materials.

INCOMPATIBLES: Strong oxidants like liquid chlorine, concentrated oxygen

HAZARDOUS DECOMPOSITION:

Thermal decomposition products or combustion: oxides of carbon, oxides of sulfur

POLYMERISATION: Will not polymerise.

SECTION 11 TOXICOLOGICAL INFORMATION

White mineral oil:

TOXICITY DATA:

No data available

Alkylated diphenylamine:

TOXICITY DATA:

Greater than 5,000 mg/kg oral-rat LD50

Amines:

TOXICITY DATA:

Greater than 5,000 mg/kg oral-rat LD50

Triphenyl phosphorothionate:

TOXICITY DATA:

Greater than 10,000 mg/kg oral-rat LD50

Propyl paraben: TOXICITY DATA:

Greater than 8,000 mg/kg oral-rat LD50

Dimethylpolysiloxane: TOXICITY DATA:

Greater than 34,600 mg/kg oral-rat LD50

SECTION 12 ECOLOGICAL INFORMATION

Not available

SECTION 13 DISPOSAL CONSIDERATIONS

Dispose in accordance with all applicable regulations

SECTION 14 TRANSPORT INFORMATION

LAND TRANSPORT ADR: No classification assigned.

LAND TRANSPORT RID: No classification assigned.

AIR TRANSPORT IATA: No classification assigned.

AIR TRANSPORT ICAO: No classification assigned.

MARITIME TRANSPORT IMDG: No classification assigned.

SECTION 15 REGULATORY INFORMATION

EUROPEAN REGULATIONS:

EC CLASSIFICATION (CALCULATED): Not classified as dangerous.

SECTION 16 OTHER INFORMATION

The above information is furnished without warranty, expressed or implied, except that it is accurate to the best knowledge of LUBRIPLATE Lubricants Company. The data on these sheets relates only to the specific material designated herein. LUBRIPLATE Lubricants Company assumes no legal responsibility for use or reliance upon this data.