



Revision Date 20-Mar-2019

SAFETY DATA SHEET

Version 3

1. IDENTIFICATION

Product identifier

Product Name PC GASKET REMOVER 340 G AE

Other means of identification

Product Code 80579

Recommended use of the chemical and restrictions on use

Recommended Use Adhesive Remover
Uses advised against No information available

Details of the supplier of the safety data sheet

Manufacturer Address

ITW Permatex
6875 Parkland Blvd.
Solon, Ohio 44139 USA
Telephone: 1-87-Permatex
(866) 732-9502

24-hour emergency phone number

Chem-Tel: 800-255-3924
International Emergency:
00+1+ 813-248-0585
Contract Number: MIS0003453

May Also Be Distributed by:

ITW Permatex Canada
101-2360 Bristol Circle
Oakville, ON Canada L6H 6M5
Telephone: (800) 924-6994

E-mail address: mail@permatex.com

2. HAZARDS IDENTIFICATION

Classification

OSHA Regulatory Status

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Carcinogenicity	Category 2
Reproductive toxicity	Category 2
Specific target organ toxicity (repeated exposure)	Category 2
Flammable aerosols	Category 1
Gases under pressure	Liquefied gas

Label elements

Emergency Overview

Signal word

Danger

Suspected of causing cancer
Suspected of damaging fertility or the unborn child
May cause damage to organs through prolonged or repeated exposure
Extremely flammable aerosol
Contains gas under pressure; may explode if heated

**Appearance** Clear**Physical state** Liquid Flammable Aerosol**Odor** Ether**Precautionary Statements - Prevention**

Obtain special instructions before use
 Do not handle until all safety precautions have been read and understood
 Use personal protective equipment as required
 Do not breathe dust/fume/gas/mist/vapors/spray
 Keep away from heat/sparks/open flames/hot surfaces. - No smoking
 Do not spray on an open flame or other ignition source
 Pressurized container: Do not pierce or burn, even after use

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention

Precautionary Statements - Storage

Store locked up
 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Not applicable

Other Information

Not applicable

Unknown acute toxicity

1.134 % of the mixture consists of ingredient(s) of unknown toxicity

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No	Weight-%
DICHLOROMETHANE	75-09-2	30 - 60
ISOBUTANE	75-28-5	7 - 13
PROPANE	74-98-6	5 - 10
ETHANOL	64-17-5	5 - 10
TOLUENE	108-88-3	5 - 10
PETROLEUM WAX, UNFINISHED	8002-74-2	0.5-2.0

4. FIRST AID MEASURES

Description of first aid measures**General advice**

Get medical advice/attention if you feel unwell.

Eye contact

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

Skin contact	IF ON SKIN: Wash skin with soap and water. If skin irritation persists, call a physician. Take off contaminated clothing and wash before reuse.
Inhalation	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If symptoms persist, call a physician.
Ingestion	IF SWALLOWED: Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Call a physician.
Self-protection of the first aider	Ensure that medical personnel are aware of the material(s) involved and take precautions to protect themselves.

Most important symptoms and effects, both acute and delayed

Symptoms See section 2 for more information.

Indication of any immediate medical attention and special treatment needed

Note to physicians Treat symptomatically.

5. FIRE-FIGHTING MEASURES**Suitable extinguishing media**

Carbon dioxide (CO₂), Dry chemical, Foam

Unsuitable extinguishing media

None

Specific hazards arising from the chemical

Extremely flammable. Contains gas under pressure; may explode if heated. Thermal decomposition can lead to release of irritating and toxic gases and vapors.

Explosion data

Sensitivity to Mechanical Impact None.

Sensitivity to Static Discharge None.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES**Personal precautions, protective equipment and emergency procedures**

Personal precautions Ensure adequate ventilation, especially in confined areas. Avoid contact with eyes and skin. Use personal protective equipment as required. Remove all sources of ignition. Take precautionary measures against static discharges. Contents under pressure. Do not puncture or incinerate cans.

Environmental precautions

Environmental precautions See section 12 for additional ecological information.

Methods and material for containment and cleaning up

Methods for containment Prevent further leakage or spillage if safe to do so.

Methods for cleaning up Eliminate all ignition sources if safe to do so. Ensure adequate ventilation. Soak up with inert absorbent material. Sweep up and shovel into suitable containers for disposal.

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling

Handle in accordance with good industrial hygiene and safety practice. Avoid breathing vapors or mists. Avoid contact with skin, eyes or clothing. Wash thoroughly after handling. Wash contaminated clothing before reuse. Use personal protective equipment as required. Contents under pressure. Do not puncture or incinerate cans. Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Conditions for safe storage, including any incompatibilities

Storage Conditions

Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Incompatible materials

Strong oxidizing agents, Nitrates, Fluorine, Chlorine

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
DICHLOROMETHANE 75-09-2	TWA: 50 ppm	TWA: 25 ppm (vacated) TWA: 500 ppm (vacated) STEL: 2000 ppm 5 min in any 3 h (vacated) Ceiling: 1000 ppm STEL: 125 ppm see 29 CFR 1910.1052	IDLH: 2300 ppm
ISOBUTANE 75-28-5	STEL: 1000 ppm	-	TWA: 800 ppm TWA: 1900 mg/m ³
PROPANE 74-98-6	: See Appendix F: Minimal Oxygen Content	TWA: 1000 ppm TWA: 1800 mg/m ³ (vacated) TWA: 1000 ppm (vacated) TWA: 1800 mg/m ³	IDLH: 2100 ppm TWA: 1000 ppm TWA: 1800 mg/m ³
ETHANOL 64-17-5	STEL: 1000 ppm	TWA: 1000 ppm TWA: 1900 mg/m ³ (vacated) TWA: 1000 ppm (vacated) TWA: 1900 mg/m ³	IDLH: 3300 ppm TWA: 1000 ppm TWA: 1900 mg/m ³
TOLUENE 108-88-3	TWA: 20 ppm	TWA: 200 ppm (vacated) TWA: 100 ppm (vacated) TWA: 375 mg/m ³ (vacated) STEL: 150 ppm (vacated) STEL: 560 mg/m ³ Ceiling: 300 ppm	IDLH: 500 ppm TWA: 100 ppm TWA: 375 mg/m ³ STEL: 150 ppm STEL: 560 mg/m ³
PETROLEUM WAX, UNFINISHED 8002-74-2	TWA: 2 mg/m ³ fume	(vacated) TWA: 2 mg/m ³	TWA: 2 mg/m ³ fume

NIOSH IDLH Immediately Dangerous to Life or Health

Other Information

Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992).

Appropriate engineering controls

Engineering Controls

Showers
Eyewash stations
Ventilation systems

Individual protection measures, such as personal protective equipment

Eye/face protection

Wear safety glasses with side shields (or goggles).

Skin and body protection	Wear protective natural rubber, nitrile rubber, Neoprene™ or PVC gloves.
Respiratory protection	Use NIOSH-approved air-purifying respirator with organic vapor cartridge or canister, as appropriate.
General Hygiene Considerations	Handle in accordance with good industrial hygiene and safety practice. Regular cleaning of equipment, work area and clothing is recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Physical state	Liquid Flammable Aerosol
Appearance	Clear
Odor	Ether
Odor threshold	No information available

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
pH	No information available	
Melting point / freezing point	No information available	
Boiling point / boiling range	-42 °C / -44 °F	
Flash point	-104 °C / -156 °F	Gives a flame projection at full valve opening or flashback at any degree of valve opening
Evaporation rate	No information available	
Flammability (solid, gas)	No information available	
Flammability Limit in Air		
Upper flammability limit:	17.5%	
Lower flammability limit:	9.7%	
Vapor pressure	No information available	
Vapor density	No information available	
Relative density	1.15-1.19	
Water solubility	Negligible	
Solubility(ies)	No information available	
Partition coefficient	No information available	
Autoignition temperature	399-514 °C	
Decomposition temperature	No information available	
Kinematic viscosity	No information available	
Dynamic viscosity	No information available	
Explosive properties	No information available	
Oxidizing properties	No information available	

Other Information

Softening point	No information available
Molecular weight	No information available
VOC Content (%)	38.9%
Density	No information available
Bulk density	No information available
SADT (self-accelerating decomposition temperature)	No information available

10. STABILITY AND REACTIVITY

Reactivity

No information available

Chemical stability

Stable under normal conditions

Possibility of Hazardous Reactions

None under normal processing.

Conditions to avoid

Heat, flames and sparks.

Incompatible materials

Strong oxidizing agents, Nitrates, Fluorine, Chlorine

Hazardous Decomposition Products

Carbon oxides

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation	May cause damage to organs through prolonged or repeated exposure if inhaled.
Eye contact	Contact with eyes may cause irritation. May cause redness and tearing of the eyes.
Skin contact	May cause skin irritation and/or dermatitis.
Ingestion	Ingestion may cause irritation to mucous membranes.

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
DICHLOROMETHANE 75-09-2	= 1600 mg/kg (Rat)	-	= 53 mg/L (Rat) 6 h = 76000 mg/m ³ (Rat) 4 h
ISOBUTANE 75-28-5	-	-	= 658 mg/L (Rat) 4 h
PROPANE 74-98-6	-	-	= 658 mg/L (Rat) 4 h
ETHANOL 64-17-5	= 7060 mg/kg (Rat)	-	= 124.7 mg/L (Rat) 4 h
TOLUENE 108-88-3	= 2600 mg/kg (Rat)	= 12000 mg/kg (Rabbit)	= 12.5 mg/L (Rat) 4 h
PETROLEUM WAX, UNFINISHED 8002-74-2	> 3750 mg/kg (Rat)	> 3600 mg/kg (Rabbit)	-

Information on toxicological effects

Symptoms No information available.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization No information available.

Germ cell mutagenicity No information available.

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
DICHLOROMETHANE 75-09-2	A3	Group 2A	Reasonably Anticipated	X
ETHANOL 64-17-5	A3	-	Known	X
TOLUENE 108-88-3	-	Group 3	-	-

ACGIH (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen

IARC (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans

Group 2A - Probably Carcinogenic to Humans

Not classifiable as a human carcinogen

NTP (National Toxicology Program)

Known - Known Carcinogen

Reasonably Anticipated - Reasonably Anticipated to be a Human Carcinogen

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

Chronic toxicity

May cause adverse effects on the bone marrow and blood-forming system. May cause adverse liver effects. Contains a known or suspected reproductive toxin.

Target Organ Effects

Blood, Central nervous system, Central Vascular System (CVS), Eyes, kidney, Liver, Reproductive System, Respiratory system, Skin.

The following values are calculated based on chapter 3.1 of the GHS document .

ATEmix (oral)	2408 mg/kg
ATEmix (dermal)	97339 mg/kg
ATEmix (inhalation-gas)	1572729 mg/l
ATEmix (inhalation-dust/mist)	147 mg/l

12. ECOLOGICAL INFORMATION

Ecotoxicity

1.134 % of the mixture consists of component(s) of unknown hazards to the aquatic environment

Persistence and degradability

No information available.

Bioaccumulation

No information available.

Mobility

No information available.

Chemical Name	Partition coefficient
DICHLOROMETHANE 75-09-2	1.25
ISOBUTANE 75-28-5	2.88
PROPANE 74-98-6	2.3
ETHANOL 64-17-5	-0.32
TOLUENE 108-88-3	2.7

Other adverse effects

No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal of wastes

This material, as supplied, is a hazardous waste according to federal regulations (40 CFR 261).

Contaminated packaging

Do not reuse container.

US EPA Waste Number

D001

Chemical Name	RCRA - Halogenated Organic Compounds	RCRA - P Series Wastes	RCRA - F Series Wastes	RCRA - K Series Wastes
DICHLOROMETHANE 75-09-2	Category I - Volatiles	-	Toxic waste waste number F025 Waste description: Condensed light ends, spent filters and filter aids, and spent desiccant wastes from the production of certain chlorinated aliphatic hydrocarbons, by free radical catalyzed processes. These chlorinated aliphatic hydrocarbons are those having carbon chain lengths	-

			ranging from one to and including five, with varying amounts and positions of chlorine substitution.	
TOLUENE 108-88-3	-	-	Toxic waste waste number F025 Waste description: Condensed light ends, spent filters and filter aids, and spent desiccant wastes from the production of certain chlorinated aliphatic hydrocarbons, by free radical catalyzed processes. These chlorinated aliphatic hydrocarbons are those having carbon chain lengths ranging from one to and including five, with varying amounts and positions of chlorine substitution.	-

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste Status
DICHLOROMETHANE 75-09-2	Toxic
ETHANOL 64-17-5	Toxic Ignitable
TOLUENE 108-88-3	Toxic Ignitable

14. TRANSPORT INFORMATION

DOT

UN/ID No 1950
 Proper shipping name: Aerosols
 Hazard Class 2.1
 Emergency Response Guide Number 126

IATA

UN/ID No 1950
 Proper shipping name: Aerosols, flammable
 Hazard Class 2.1
 Subsidiary hazard class 6.1
 ERG Code 10P

IMDG

UN/ID No 1950
 Proper shipping name: Aerosols
 Hazard Class 2.1
 Subsidiary hazard class 6.1
 EmS-No F-D, S-U

15. REGULATORY INFORMATION

International Inventories

TSCA Complies
 DSL/NDL Complies
 EINECS/ELINCS Not determined
 ENCS Not determined
 IECSC Complies

KECL	Complies
PICCS	Complies
AICS	Complies

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
 DSL/NDL - Canadian Domestic Substances List/Non-Domestic Substances List
 EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances
 ENCS - Japan Existing and New Chemical Substances
 IECSC - China Inventory of Existing Chemical Substances
 KECL - Korean Existing and Evaluated Chemical Substances
 PICCS - Philippines Inventory of Chemicals and Chemical Substances
 AICS - Australian Inventory of Chemical Substances

US Federal Regulations**SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	SARA 313 - Threshold Values %
DICHLOROMETHANE - 75-09-2	0.1
TOLUENE - 108-88-3	1.0

SARA 311/312 Hazard Categories

Acute health hazard	Yes
Chronic Health Hazard	Yes
Fire hazard	Yes
Sudden release of pressure hazard	No
Reactive Hazard	No

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
DICHLOROMETHANE 75-09-2	-	X	X	-
TOLUENE 108-88-3	1000 lb	X	X	X

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
DICHLOROMETHANE 75-09-2	1000 lb 1 lb	-	RQ 1000 lb final RQ RQ 454 kg final RQ RQ 1 lb final RQ RQ 0.454 kg final RQ
TOLUENE 108-88-3	1000 lb 1 lb	-	RQ 1000 lb final RQ RQ 454 kg final RQ RQ 1 lb final RQ RQ 0.454 kg final RQ

US State Regulations**California Proposition 65**

This product contains the following Proposition 65 chemicals

Chemical Name	California Proposition 65
DICHLOROMETHANE - 75-09-2	Carcinogen
ETHANOL - 64-17-5	Carcinogen
	Developmental
TOLUENE - 108-88-3	Developmental

• Ethanol is only considered a Proposition 65 developmental hazard when it is ingested as an alcoholic beverage

• Ethanol has been shown to be carcinogenic in long-term studies only when consumed as alcoholic beverage

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
DICHLOROMETHANE 75-09-2	X	X	X
ISOBUTANE 75-28-5	X	X	X
PROPANE 74-98-6	X	X	X
ETHANOL 64-17-5	X	X	X
TOLUENE 108-88-3	X	X	X
PETROLEUM WAX, UNFINISHED 8002-74-2	X	X	X

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

WHMIS Hazard Class

A Compressed gases, B5 - Flammable aerosol, D2A - Very toxic materials

16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OF THE LAST REVISION

NFPA	Health hazards 2	Flammability 4	Instability 0	-
HMIS	Health hazards 2	Flammability 4	Physical hazards 0	Personal protection B

NFPA (National Fire Protection Association)
HMIS (Hazardous Material Information System)

Revision Date 20-Mar-2019

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet

valspar

Tractor and Implement Enamel



Product Description

A high gloss premium quality enamel designed to withstand tough wear and weathering on exterior metal or wood. **NOTE: INDUSTRIAL MAINTENANCE FINISH** – Some colors are formulated to match manufacturers' colors of farm equipment. Slight variations may be experienced due to weathering of the original coating or occasional change in manufacturers' standards.

Features

- Chip and Abrasion Resistant
- O.E.M. Color Matched
- Rust Resistant
- Fade Resistant
- High Gloss
- Non-Toxic

Recommended Uses

- Farm Equipment and Machinery
- Wood and Metal Trim
- Pipes and Railings
- Storage Tanks

Colors and Part Numbers

	Part Number
AC Orange	5339-03
New Equip. Yellow	5339-08
Frd Blue	5339-12
Frd Gray	5339-13
Frd Red	5339-20
New Holl Red	5339-05
New Holl Yellow	5339-09
IH Red	5339-01
IH White	5339-15
JD Green	5339-10
JD Yellow	5339-06
Kbota Orange	5339-24
MF Red	5339-02
MF Gray	5339-22
Oliver Green	5339-11
Trans Yellow	5339-07
Low Gloss Black	5339-19
Gloss Black	5339-16
Gloss White	5339-14

Typical Properties (18-4431 Series)

Vehicle Type: Urethane & Alkyd. Resins

Sheen: 80+ Units @ 60° angle

Solids by Volume: 47%

Solids by Weight: 65%

Weight per Gallon: 9.7 lbs./gal.

VOC: Less than 420 g/L

Viscosity: 76–80 Krebs Units

Dry Time: 77°F @ 50% Relative Humidity

To the touch: 4-6 hour(s)

Recoat: 24 hour(s)

Washing: Allow at least 7 days before washing. Use mild detergent and sponge.

Full Cure: 7 day(s)

Surface Coverage:

500 sq. ft./gal.

At: 4.0 mil Wet, 1.9 mil Dry

Storage and Disposal

- Do not freeze.
- Keep container closed when not in use.
- Do not transfer contents to other containers for storage or disposal.
- In case of spillage, absorb with inert material such as sand or kitty litter.
- Dispose of contaminated absorbent, container and/or unused contents in accordance with local, state and federal regulations.
- **DANGER:** Rags, steel wool or waste soaked with this product may spontaneously catch fire if improperly discarded. Immediately after each use, place rags, steel wool or waste in a sealed, water-filled metal container.

Shipping and Packaging

Freight Classification: Paint or Paint Related Material. Protect from freezing.

Packaging: Quart – 4 per carton
Gallon – 2 per carton

PDS 18-4431

Surface Preparation

Read the Lead Warning in Cautions section. The surface must be clean, free of dirt, chalk, grease, oil and other foreign matter. Remove residue by washing with a stiff brush using mild detergent and water. Rinse thoroughly. Remove all loose, peeling or cracked paint by scraping or wire brushing. Feather rough edges by sanding lightly to insure proper adhesion. Rusty metal should be sanded and spot primed with a rust inhibiting primer. **New Metal:** Wipe surface down with rag and paint thinner to remove factory oils. For best results, prime iron and steel with a rust inhibiting primer. Non-rusted galvanized and aluminum surfaces should be primed with galvanized and aluminum primer to insure maximum adhesion and flexibility. Spot prime rusted galvanized metal with rust inhibiting primer or zinc dust primer. Note: Oil paints may be applied over galvanized metal flashing, trim and railings, but are not recommended over continuous metal surfaces such as pole buildings. **New Wood:** Prime wood with oil-based primer or latex primer.

Application and Clean-up

Paint only when surface and air temperatures are 40–90 °F. Stir thoroughly using a circular, lifting motion. Purchase sufficient quantities to complete the job. When purchasing more than one container of the same color, intermix contents to ensure color uniformity. Use a premium quality polyester or pure bristle brush, roller or spray. Avoid painting in direct, hot sunlight or if rain is threatening. Brush out product uniformly and avoid over-brushing. If thinning is necessary, reduce with up to one half pint (8 fl. oz.) per gallon. For spray application, VM&P naphtha is recommended. For brush and roller application, mineral spirits is recommended. Clean up tools and spatters immediately with mineral spirits.

Cautions (18-4431 Series)

WARNING: CONTAINS PETROLEUM DISTILLATE AND CRYSTALLINE SILICA. May affect the brain or nervous system causing dizziness, headache or nausea. Causes eye, skin, nose and throat irritation. **USE ONLY WITH ADEQUATE VENTILATION.** Keep away from heat, sparks and flame. Avoid breathing vapors, spray mist or sanding dust. If painting indoors, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist levels above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's direction for respirator use. **AVOID CONTACT WITH EYES AND SKIN.** Wash thoroughly after use. Close container after each use.

Warning: This product contains chemicals known to the State of California to cause cancer.

FIRST AID: EYE CONTACT: Flush thoroughly with water for at least 15 minutes. If irritation persists, **get medical attention.** **IF INHALED:** If affected by vapor or spray mist, move to fresh air. If breathing difficulty continues, **get medical attention.** **IF SWALLOWED:** Drink 2 glasses of water. **Get medical attention immediately.**

Delayed effect from long-term exposure: Reports of commercial painters have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the vapors may be harmful or fatal. **Cancer Hazard.** Contains crystalline silica which can cause cancer. Risk depends upon duration and level of exposure to dust generated from sanding surfaces or spray mist.

DO NOT TAKE INTERNALLY.

KEEP OUT OF REACH OF CHILDREN.

For additional safety and chronic health hazard information, refer to the Material Safety Data Sheet for this product.

**EMERGENCY MEDICAL TELEPHONE:
1-888-345-5732**

This product contains less than 420 g/L VOC

WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean-up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

The data on this sheet represents typical values. Since application variables are a major factor in product performance, this information should serve only as a general guide. Valspar assumes no obligation or liability for use of this information. **UNLESS VALSPAR AGREES OTHERWISE IN WRITING, VALSPAR MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. VALSPAR WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES.** Your only remedy for any defect in this product, is the replacement of the defective product, or a refund of its purchase price, at our option.

valspar

1191 Wheeling Rd, Wheeling, IL 60090 800-845-9061
www.valspar.com

12/09

PDS 18-4431