

PLASTO-JOINT STIK®

LA-CO Industries, Inc.

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations
according to Canadian Hazardous Products Regulations (HPR)
Date of issue: 05/08/2012 Revision date: 03/06/2015 Supersedes: 05/08/2012
Version: 2.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product Identifier


Product form : Mixture
Trade name : PLASTO-JOINT STIK®

1.2. Relevant Identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Sealant.

1.3. Details of the supplier of the safety data sheet

LA-CO Industries, Inc.
1201 Pratt Boulevard
Elk Grove Village, IL. 60007-5746
Phone: (847) 956-7600
Fax: (847) 956-9885
E-mail: customer_service@laco.com



1.4. Emergency telephone number

Emergency number : 24-hour emergency: CHEMTREC- U.S. : 1-800-424-9300 International: +1-703-527-3887

SECTION 2: Hazards Identification

2.1. Classification of the substance or mixture

Classification in accordance with the Globally Harmonized Standard

Skin Irrit. 2 H315

Eye Irrit. 2A H319

Full text of H-phrases: see section 16

2.2. Label elements

GHS labelling

Hazard pictograms (GHS) :



GHS07

Signal word (GHS) :

Warning

Hazard statements (GHS) :

H315 - Causes skin irritation
H319 - Causes serious eye irritation

Precautionary statements (GHS) :

P264 - Wash hands thoroughly after handling
P280 - Wear eye protection, protective gloves
P302+P352 - If on skin: Wash with plenty of water
P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P321 - Specific treatment (see First aid measures on this label)
P332+P313 - If skin irritation occurs: Get medical advice/attention
P337+P313 - If eye irritation persists: Get medical advice/attention
P362 - Take off contaminated clothing and wash before reuse

2.3. Other hazards

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

PLASTO-JOINT STIK®

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations
according to Canadian Hazardous Products Regulations (HPR)

3.2. Mixture

Name	Product Identifier	% (w/w)	GHS classification
Polyisobutylene	(CAS No) 9003-27-4 or 9003-29-6	38.89	Skin Irrit. 2, H315 Eye Irrit. 2A, H319

Full text of H-phrases: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

- First-aid measures general : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
- First-aid measures after inhalation : If inhaled and if breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing.
- First-aid measures after skin contact : Wash with plenty of soap and water. Wash contaminated clothing before reuse. If skin irritation occurs: Get medical advice/attention.
- First-aid measures after eye contact : If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention if pain, blinking or redness persist.
- First-aid measures after ingestion : Do NOT induce vomiting. Get medical advice/attention if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/injuries after skin contact : Causes skin irritation.
- Symptoms/injuries after eye contact : Causes serious eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

All treatments should be based on observed signs and symptoms of distress in the patient.

SECTION 5: Firefighting measures

5.1. Extinguishing media

- Suitable extinguishing media : Dry powder. Carbon dioxide. Foam.
- Unsuitable extinguishing media : Do not use a solid water stream as it may scatter and spread fire.

5.2. Special hazards arising from the substance or mixture

- Fire hazard : No particular fire or explosion hazard.
- Reactivity : No dangerous reactions known.

5.3. Advice for firefighters

- Firefighting instructions : Exercise caution when fighting any chemical fire. Do not allow run-off from fire fighting to enter drains or water courses.
- Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection. Use self-contained breathing apparatus. Wear fire/flame resistant/retardant clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Avoid contact with skin and eyes.

6.1.1. For non-emergency personnel

- Protective equipment : Wear suitable gloves resistant to chemical penetration. Chemical goggles or safety glasses.
- Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

- Protective equipment : Wear suitable gloves. Chemical goggles or safety glasses.
- Emergency procedures : Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters.

6.3. Methods and material for containment and cleaning up

- For containment : Contain and collect as any solid.
- Methods for cleaning up : On land, sweep or shovel into suitable containers.

6.4. Reference to other sections

PLASTO-JOINT STIK®

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations
according to Canadian Hazardous Products Regulations (HPR)

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : Avoid contact with skin and eyes.
Hygiene measures : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

7.2. Conditions for safe storage, including any incompatibilities

- Storage conditions : Store in a dry, cool and well-ventilated place.
Incompatible products : Strong oxidizing agents.
Incompatible materials : Heat sources. Direct sunlight.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

PLASTO-JOINT STIK®	
ACGIH	Not applicable
OSHA	Not applicable
Polyisobutylene (9003-27-4 or 9003-29-6)	
ACGIH	Not applicable
OSHA	Not applicable

8.2. Exposure controls

- Appropriate engineering controls : Avoid dispersal of dust in the air (ie, clearing dust surfaces with compressed air). Either local exhaust or general room ventilation is usually required.
- Personal protective equipment : Avoid all unnecessary exposure.
- Hand protection : Wear dust impervious gloves.
- Eye protection : In case of dust production: protective goggles.
- Respiratory protection : In case of inadequate ventilation wear respiratory protection. Use air-purifying respirator equipped with particulate filtering cartridges.
- Other information : Do not eat, drink or smoke when using this product.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

- Physical state : Solid
- Appearance : waxy.
- Colour : Off-white.
- Odour : odourless.
- Odour threshold : No data available
- pH : No data available
- Relative evaporation rate (butyl acetate=1) : No data available
- Melting point : No data available
- Freezing point : No data available
- Boiling point : No data available
- Flash point : 185 °C (melted product)
- Auto-ignition temperature : No data available
- Decomposition temperature : > 138 °C
- Flammability (solid, gas) : No data available
- /apour pressure : No data available
- Relative vapour density at 20 °C : No data available
- Relative density : No data available
- Solubility : insoluble in water.
- Log Pow : > 1
- Log Kow : No data available
- Viscosity, kinematic : No data available

PLASTO-JOINT STIK®

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations
according to Canadian Hazardous Products Regulations (HPR)

Viscosity, dynamic : No data available
Explosive properties : No data available
Oxidising properties : No data available
Explosive limits : No data available

9.2. Other information

VOC content : 0 %

SECTION 10: Stability and reactivity

10.1. Reactivity

No dangerous reactions known.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Heat. Open flame.

10.5. Incompatible materials

Strong oxidizing agents.

10.6. Hazardous decomposition products

Burning produces irritating, toxic and noxious fumes. Carbon dioxide. Carbon monoxide.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

Polyisobutylene (9003-27-4 or 9003-29-6)	
LD50 oral rat	> 34600 mg/kg
LD50 dermal rabbit	> 10250 mg/kg
LC50 inhalation rat (mg/l)	> 17300 mg/m ³

Skin corrosion/irritation : Causes skin irritation.
Serious eye damage/irritation : Causes serious eye irritation.
Respiratory or skin sensitisation : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified.
Reproductive toxicity : Not classified
Specific target organ toxicity (single exposure) : Not classified
Specific target organ toxicity (repeated exposure) : Not classified
Aspiration hazard : Not classified
Potential adverse human health effects and symptoms
Symptoms/injuries after skin contact : Causes skin irritation.
Symptoms/injuries after eye contact : Causes serious eye irritation.
Likely routes of exposure : Skin and eye contact

SECTION 12: Ecological information

12.1 Toxicity

Polyisobutylene (9003-27-4 or 9003-29-6)	
LC50 fish 1	> 1000 mg/l
EC50 Daphnia 1	> 1000 mg/l

12.2. Persistence and degradability

Polyisobutylene (9003-27-4 or 9003-29-6)	
Persistence and degradability	This product is not expected to be biodegradable.

PLASTO-JOINT STIK®

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations
according to Canadian Hazardous Products Regulations (HPR)

12.3. Bioaccumulative potential

PLASTO-JOINT STIK®	
Log Pow	> 1

Polyisobutylene (9003-27-4 or 9003-29-6)	
Bioaccumulative potential	This product is not bioaccumulating.

12.4. Mobility in soil

Polyisobutylene (9003-27-4 or 9003-29-6)	
Ecology - soil	This material has low solubility and floats and is not expected to partition to water.

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

- Sewage disposal recommendations : Do not dispose of waste into sewer.
Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations.

SECTION 14: Transport information

In accordance with DOT and TDG

Not considered a dangerous good for transport regulations

Proper Shipping Name (ADR) : Not applicable

Transport by sea

No additional information available

Air transport

No additional information available

SECTION 15: Regulatory information

15.1. US Federal regulations

Polyisobutylene (9003-27-4 or 9003-29-6)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	

15.2. International regulations

CANADA

Polyisobutylene (9003-27-4 or 9003-29-6)	
Listed on the Canadian DSL (Domestic Substances List) inventory.	

EU-Regulations

Polyisobutylene (9003-27-4 or 9003-29-6)	
Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)	

National regulations

PLASTO-JOINT STIK®	
All components are listed on the EEC inventory European Inventory of Existing Commercial Chemical Substances (EINECS).	
All ingredients are listed in the Toxic Substances Control Act (TSCA).	
All ingredients are listed on the Canadian Domestic Substances List (DSL) or Non-Domestic Substances List (NDSL).	

15.3. US State regulations

No additional information available

SECTION 16: Other information


Indication of changes : GHS classification information. Revised format. Revised sections: 1 - 16.

PLASTO-JOINT STIK®

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations
according to Canadian Hazardous Products Regulations (HPR)

- Data sources** : ACGIH 2000.
Canadian Centre for Occupational Health and Safety. Accessed at:
http://www.ccohs.ca/oshanswers/legisl/whmis_classifi.html.
ESIS (European chemical Substances Information System; accessed at:
<http://esis.jrc.ec.europa.eu/index.php?PGM=cla>.
European Chemicals Agency (ECHA) Registered Substances list. Accessed at
<http://echa.europa.eu/>. Krister Forsberg and S.Z. Mansdorf, "Quick Selection Guide to
Chemical Protective Clothing", Fifth Edition.
National Fire Protection Association; Fire Protection Guide to Hazardous Materials; 10th
edition.
OSHA 29CFR 1910.1200 Hazard Communication Standard.
REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE
COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and
mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending
Regulation (EC) No 1907/2006.
TSCA Chemical Substance Inventory. Accessed at
<http://www.epa.gov/oppt/existingchemicals/pubs/tscainventory/howto.html>.
- Abbreviations and acronyms** : ACGIH (American Conference of Government Industrial Hygienists).
ATE: Acute Toxicity Estimate.
CAS (Chemical Abstracts Service) number.
CLP: Classification, Labelling, Packaging.
EC50: Environmental Concentration associated with a response by 50% of the test population.
GHS: Globally Harmonized System (of Classification and Labeling of Chemicals).
LD50: Lethal Dose for 50% of the test population.
OSHA: Occupational Safety & Health Administration.
PBT: Persistent, Bioaccumulative, Toxic.
STEL: Short Term Exposure Limits.
TSCA: Toxic Substances Control Act.
TWA: Time Weight Average.
- Other information** : None.
- NFPA health hazard** : 1 - Exposure could cause irritation but only minor residual
injury even if no treatment is given.
- NFPA fire hazard** : 1 - Must be preheated before ignition can occur.
- NFPA reactivity** : 0 - Normally stable, even under fire exposure conditions,
and not reactive with water.



Full text of H-phrases:

Eye Irrit. 2A	Serious eye damage/eye irritation, Category 2A
Skin Irrit. 2	Skin corrosion/irritation, Category 2
H315	Causes skin irritation
H319	Causes serious eye irritation

SDS Prepared by: The Redstone Group, LLC
6397 Emerald Pkwy.
Suite 200
Dublin, OH USA 43016
T 614-923-7472
www.redstonegrp.com

LACO NA GHS SDS

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product