SAFETY DATA SHEET

1. Identification

Product identifier H2O BLUE PEARL

Other means of identification

Product Code PLT-782-2

Recommended use Automotive Refinish Toner

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company name Pro-Spray Automotive Finishes Limited

Address Unit H, Normandy Lane, Stratton Business Park

Biggleswade, Bedfordshire SG18 8QB United Kingdom

United Kingdom

Telephone General Information +44 (0) 1767 314320

Website prosprayfinishes.com
E-mail colour@pro-spray.co.uk

Emergency phone number Office hours only +44 (0) 1767 314320

2. Hazard(s) identification

Physical hazardsFlammable liquidsCategory 4Health hazardsAcute toxicity, inhalationCategory 3Sensitization, skinCategory 1Germ cell mutagenicityCategory 1BCarcinogenicityCategory 1B

Environmental hazards Not classified.

OSHA defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement Combustible liquid. May cause an allergic skin reaction. Toxic if inhaled. May cause genetic

defects. May cause cancer.

Precautionary statement

Prevention Obtain special instructions before use. Do not handle until all safety precautions have been read

and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Avoid breathing mist or vapor. Use only outdoors or in a well-ventilated area. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves/protective clothing/eye

protection/face protection.

Response If on skin: Wash with plenty of water. If inhaled: Remove person to fresh air and keep comfortable

for breathing. Call a poison center/doctor. If skin irritation or rash occurs: Get medical

advice/attention. Wash contaminated clothing before reuse. In case of fire: Use appropriate media

to extinguish.

Storage Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place.

Keep cool. Store locked up.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise

classified (HNOC)

None known.

Supplemental information 22.99% of the mixture consists of component(s) of unknown acute inhalation toxicity.

Material name: H2O BLUE PEARL
PLT-782-2 Version #: 01 Issue date: 04-11-2015

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
2-Butoxyethanol		111-76-2	5 to <10
silicate : mica		12001-26-2	1 to <5
Titanium dioxide		13463-67-7	1 to <5
2-methyl-4-isothiazolin-3-one		2682-20-4	0.1 to <1
heavy alkylate naphtha		64741-65-7	0.1 to <1
Other components below reportable lev	els		80 to <90

^{*}Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. Oxygen or

artificial respiration if needed. Do not use mouth-to-mouth method if victim inhaled the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other

proper respiratory medical device. Call a POISON CENTER or doctor/physician.

Skin contact Remove contaminated clothing immediately and wash skin with soap and water. In case of eczema or other skin disorders: Seek medical attention and take along these instructions.

Rinse with water. Get medical attention if irritation develops and persists. Eye contact

Ingestion Rinse mouth. Get medical attention if symptoms occur.

Most important symptoms/effects, acute and

delayed

Direct contact with eyes may cause temporary irritation. May cause an allergic skin reaction. Dermatitis, Rash.

Indication of immediate medical attention and special Provide general supportive measures and treat symptomatically. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

treatment needed General information

IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing media

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from

the chemical

Special protective equipment and precautions for firefighters The product is combustible, and heating may generate vapors which may form explosive vapor/air mixtures. During fire, gases hazardous to health may be formed.

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting equipment/instructions

Specific methods

In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.

Use standard firefighting procedures and consider the hazards of other involved materials.

General fire hazards Combustible liquid.

6. Accidental release measures

Personal precautions. protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Avoid inhalation of vapors and spray mists. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.

Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Environmental precautions

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from open flames, hot surfaces and sources of ignition. When using do not smoke. Do not get in eyes, on skin, or on clothing. Avoid inhalation of vapors and spray mists. Avoid prolonged exposure. Should be handled in closed systems, if possible. Use only outdoors or in a well-ventilated area. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Store locked up. Keep away from heat, sparks and open flame. Store in a cool, dry place out of direct sunlight. Store in original tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Occupational exposure limits

Components	Type	Value	Form
2-Butoxyethanol (CAS 111-76-2)	PEL	240 mg/m3	
,		50 ppm	
heavy alkylate naphtha (CAS 64741-65-7)	PEL	400 mg/m3	
		100 ppm	
Titanium dioxide (CAS 13463-67-7)	PEL	15 mg/m3	Total dust.
US. OSHA Table Z-3 (29 CFR 19	10.1000)		
Components	Type	Value	
silicate : mica (CAS 12001-26-2)	TWA	20 mppcf	
US. ACGIH Threshold Limit Valu	ies		
Components	Туре	Value	Form
2-Butoxyethanol (CAS 111-76-2)	TWA	20 ppm	
silicate : mica (CAS 12001-26-2)	TWA	3 mg/m3	Respirable fraction.
Titanium dioxide (CAS 13463-67-7)	TWA	10 mg/m3	
US. NIOSH: Pocket Guide to Ch	emical Hazards		
Components	Туре	Value	Form
2-Butoxyethanol (CAS 111-76-2)	TWA	24 mg/m3	
,		5 ppm	
heavy alkylate naphtha (CAS 64741-65-7)	TWA	400 mg/m3	
•		100 ppm	
silicate : mica (CAS	TWA	3 mg/m3	Respirable.

Material name: H2O BLUE PEARL PLT-782-2 Version #: 01 Issue date: 04-11-2015

Biological limit values

ACGIH Biological Exposure Indices

Components	Value	Determinant	Specimen	Sampling Time	
2-Butoxyethanol (CAS 111-76-2)	200 mg/g	Butoxyacetic acid (BAA), with hydrolysis	Creatinine in urine	*	

^{* -} For sampling details, please see the source document.

Exposure guidelines

US - California OELs: Skin designation

2-Butoxyethanol (CAS 111-76-2)

Can be absorbed through the skin.

US - Minnesota Haz Subs: Skin designation applies

2-Butoxyethanol (CAS 111-76-2) Skin designation applies.

US - Tennessee OELs: Skin designation

2-Butoxyethanol (CAS 111-76-2) Can be absorbed through the skin.

US NIOSH Pocket Guide to Chemical Hazards: Skin designation

2-Butoxyethanol (CAS 111-76-2)

Can be absorbed through the skin.

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

2-Butoxyethanol (CAS 111-76-2)

Can be absorbed through the skin.

Appropriate engineering

controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin protection

Hand protection Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove

supplier.

Other Wear appropriate chemical resistant clothing.

Respiratory protection If engineering controls do not maintain airborne concentrations below recommended exposure

limits (where applicable) or to an acceptable level (in countries where exposure limits have not

been established), an approved respirator must be worn.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not

be allowed out of the workplace.

9. Physical and chemical properties

Appearance

Physical stateLiquid.FormLiquid.ColorBlue

Odor Slight. Solvent.
Odor threshold Not available.

PH Not available.

Melting point/freezing point Not available.

Initial boiling point and boiling

range

212 °F (100 °C) estimated

Flash point 143.0 °F (61.7 °C) estimated

Evaporation rate Not available.

Flammability (solid, gas) Not applicable.

Upper/lower flammability or explosive limits

Flammability limit - lower

Not available.

(%)

Flammability limit - upper

(%)

Not available.

Explosive limit - lower (%) Not available.

Explosive limit - upper (%) Not available.

Vapor pressure 0.11 hPa estimated

Vapor densityNot available.Relative densityNot available.

Solubility(ies)

Solubility (water) Not available.

Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperature 460.4 °F (238 °C) estimated

Decomposition temperature Not available. **Viscosity** Not available.

Other information

Density 8.72 lbs/gal

Flammability class Combustible IIIA estimated

Percent volatile 75.34 % estimated

Specific gravity 1.05

VOC 0.7 lbs/gal Material

2.9 lbs/gal Coating 82 g/l Material 352 g/l Coating

10. Stability and reactivity

ReactivityThe product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the

flash point. Contact with incompatible materials.

Incompatible materials Strong oxidizing agents.

Hazardous decomposition

products

No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation Toxic if inhaled.

Skin contact May cause an allergic skin reaction.

2-Butoxy ethanol may be absorbed through the skin in toxic amounts if contact is repeated and

prolonged. These effects have not been observed in humans.

Eye contact Direct contact with eyes may cause temporary irritation.

Ingestion Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics

May cause an allergic skin reaction. Dermatitis. Rash.

Information on toxicological effects

Acute toxicity Toxic if inhaled. May cause an allergic skin reaction.

Material name: H2O BLUE PEARL SDS US

Components Species Test Results

2-Butoxyethanol (CAS 111-76-2)

<u>Acute</u>

Dermal

LD50 Rabbit 400 mg/kg

Inhalation

LC50 Mouse 700 ppm, 7 Hours

Rat 450 ppm, 4 Hours

Oral

LD50 Guinea pig 1.2 g/kg

 Mouse
 1.2 g/kg

 Rabbit
 0.32 g/kg

 Rat
 560 mg/kg

heavy alkylate naphtha (CAS 64741-65-7)

Acute

Inhalation

LC50 Rat 61 mg/l, 4 Hours

Oral

LD50 Rat > 25 ml/kg

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation.

Serious eye damage/eye

irritation

Direct contact with eyes may cause temporary irritation.

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization May cause an allergic skin reaction.

Germ cell mutagenicity May cause genetic defects.

Carcinogenicity May cause cancer.

IARC Monographs. Overall Evaluation of Carcinogenicity

2-Butoxyethanol (CAS 111-76-2) 3 Not classifiable as to carcinogenicity to humans.

Titanium dioxide (CAS 13463-67-7) 2B Possibly carcinogenic to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Reproductive toxicityThis product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard Not an aspiration hazard.

Chronic effects May be harmful if absorbed through skin. Prolonged inhalation may be harmful.

2-Butoxy ethanol may be absorbed through the skin in toxic amounts if contact is repeated and

prolonged. These effects have not been observed in humans.

Prolonged exposure may cause chronic effects.

12. Ecological information

Ecotoxicity The product is not classified as environmentally hazardous. However, this does not exclude the

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Components Species Test Results

2-Butoxyethanol (CAS 111-76-2)

Aquatic

Fish LC50 Inland silverside (Menidia beryllina) 1250 mg/l, 96 hours

^{*} Estimates for product may be based on additional component data not shown.

Components		Species	Test Results	
heavy alkylate naphtha	a (CAS 64741-65-7	<u></u>		
Aquatic				
Crustacea	EC50	Water flea (Daphnia pulex)	2.7 - 5.1 mg/l, 48 hours	
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	8.8 mg/l, 96 hours	
			8.8 mg/l, 96 hours	
Titanium dioxide (CAS	3 13463-67-7)			
Aquatic				
Crustacea	EC50	Water flea (Daphnia magna)	> 1000 mg/l, 48 hours	
Fish	LC50	Mummichog (Fundulus heteroclitus)	> 1000 mg/l, 96 hours	

^{*} Estimates for product may be based on additional component data not shown.

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

2-Butoxyethanol 0.83

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructionsCollect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of

contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Not established.

Annex II of MARPOL 73/78 and

the IBC Code

15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

All components are on the U.S. EPA TSCA Inventory List.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

2-methyl-4-isothiazolin-3-one (CAS 2682-20-4) 1.0 % One-Time Export Notification only.

CERCLA Hazardous Substance List (40 CFR 302.4)

2-Butoxyethanol (CAS 111-76-2) Listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes

Delayed Hazard - Yes Fire Hazard - Yes Pressure Hazard - No Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous No

chemical

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.
2-Butoxyethanol	111-76-2	5 to <10

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

US state regulations

US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)

Not listed.

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd.

(a))

2-Butoxyethanol (CAS 111-76-2)

heavy alkylate naphtha (CAS 64741-65-7)

Titanium dioxide (CAS 13463-67-7)

US. Massachusetts RTK - Substance List

2-Butoxyethanol (CAS 111-76-2)

heavy alkylate naphtha (CAS 64741-65-7)

silicate: mica (CAS 12001-26-2) Titanium dioxide (CAS 13463-67-7)

US. New Jersey Worker and Community Right-to-Know Act

2-Butoxyethanol (CAS 111-76-2)

heavy alkylate naphtha (CAS 64741-65-7)

silicate: mica (CAS 12001-26-2) Titanium dioxide (CAS 13463-67-7)

US. Pennsylvania Worker and Community Right-to-Know Law

2-Butoxyethanol (CAS 111-76-2)

heavy alkylate naphtha (CAS 64741-65-7)

silicate: mica (CAS 12001-26-2) Titanium dioxide (CAS 13463-67-7)

US. Rhode Island RTK

2-Butoxyethanol (CAS 111-76-2)

US. California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause cancer.

US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

Titanium dioxide (CAS 13463-67-7) Listed: September 2, 2011

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Furope	Furopean List of Notified Chemical Substances (FLINCS)	Yes

Material name: H2O BLUE PEARL

Country(s) or region Inventory name On inventory (yes/no)*

United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

04-11-2015 Issue date

Version # 01

Health: 3* **HMIS®** ratings

> Flammability: 2 Physical hazard: 0

Health: 3 NFPA ratings

Flammability: 2 Instability: 0

The information in the sheet was written based on the best knowledge and experience currently Disclaimer

available. THE INFORMATION CONTAINED HEREIN IS BASED ON DATA BELIEVED TO BÉ RELIABLE AND THE MANUFACTURER DISCLAIMS ANY LIABILITY INCURRED FROM THE USE OR RELIANCE UPON THE SAME. THE INFORMATION GIVEN IS DESIGNED ONLY AS A GUIDANCE FOR SAFE HANDLING, USE, PROCESSING, STORAGE, TRANSPORTATION, DISPOSAL AND RELEASE AND IS NOT TO BE CONSIDERED A WARRANTY OR QUALITY SPECIFICATION. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. This safety information is not a license to use this material as claimed by any patents of third parties. The user alone must finally determine whether a contemplated use of this

material will infringe any such patents, and for obtaining any required licenses.

Material name: H2O BLUE PEARL SDS US