

1. PRODUCT AND COMPANY IDENTIFICATION**NAME: POLY SEALANT****USE: DRYING AGENT****LABEL BRAND: PROLINE****MSDS # 101381 CODE # 063484, 063485, 063486, 4966689**

U S CHEMICAL, 316 HART STREET, WATERTOWN, WI 53094 USA
MEDICAL EMERGENCY #: 1-866-923-4913 USA
SPILL EMERGENCY #: 1-800-424-9300 USA
PRODUCT INFORMATION #: 1-800-558-9566 (8 A.M. TO 5 P.M. CST MONDAY TO FRIDAY)
INTERNET ADDRESS: WWW.USCHEMICAL.COM
REVIEWED 1-5-12 REVISED 1-5-12 SECTION REVISED: 1

2. HAZARDS IDENTIFICATION**EMERGENCY OVERVIEW:****CAUTION! COMBUSTIBLE LIQUID. MAY BE MODERATELY IRRITATING TO EYES AND SKIN.****PRINCIPLE ROUTES OF EXPOSURE: EYES, SKIN, INGESTION, INHALATION.****POTENTIAL ACUTE HEALTH EFFECTS****EYES:** MAY BE MODERATELY IRRITATING TO EYES.**SKIN:** MAY BE MODERATELY IRRITATING TO SKIN.**INHALATION:** MAY BE IRRITATING TO NOSE, THROAT AND RESPIRATORY TRACT.**INGESTION:** MAY BE IRRITATING TO MOUTH, THROAT AND STOMACH. MAY CAUSE ABDOMINAL DISCOMFORT, NAUSEA, VOMITING AND DIARRHEA.**MEDICAL CONDITIONS AGGRAVATED:** PERSONS WITH PRE-EXISTING SKIN DISORDERS MAY BE MORE SUSCEPTABLE TO IRRITATING EFFECTS.**3. COMPOSITION / INFORMATION ON INGREDIENTS**

HAZARDOUS INGREDIENT	CAS #	% BY WT	LC50/LD50
QUATERNARY AMINE	68604-75-1	10.0 – 30.0	N.AV.
PETROLEUM DISTILLATES	64742-46-7	10.0 – 30.0	N.AV.
ISOPROPYL ALCOHOL	67-63-0	1.0 – 5.0	N.AV.
2-BUTOXYETHANOL	111-76-2	1.0 – 5.0	N.AV.

STATE RIGHT TO KNOW: THIS PRODUCT CONTAINS:
WATER/7732-18-5, PETROLEUM DISTILLATES/64742-46-7, QUATERNARY AMINE/68604-75-1,
2-BUTOXYETHANOL/111-76-2, ISOPROPYL ALCOHOL/67-63-0

4. FIRST AID MEASURES

Page 2 of 4

EYES: FLOOD WITH LUKEWARM (NOT HOT) WATER POURED FROM A LARGE GLASS 2 OR 3 INCHES FROM EYES. REMOVE CONTACTS. HAVE PATIENT BLINK AS MUCH AS POSSIBLE WHILE FLOODING THE EYES. CONTINUE FOR AT LEAST 15 MINUTES.

SKIN: REMOVE CONTAMINATED CLOTHES, THEN FLOOD WITH WATER.

INHALATION: MOVE VICTIM TO FRESH AIR. GIVE ARTIFICIAL RESPIRATION IF PATIENT IS NOT BREATHING.

INGESTION: DO NOT INDUCE VOMITING. IF PATIENT IS CONSCIOUS AND CAN SWALLOW, ADMINISTER MILK OR WATER.

ADMINISTER FIRST AID TREATMENT AS STATED ABOVE, THEN CALL 1-800-851-7145 EXT. 075 OR CONTACT PHYSICIAN FOR FURTHER MEDICAL INSTRUCTIONS.

NOTE TO PHYSICIAN: CALL 1-866-923-4913 FOR ASSISTANCE WITH THE MANAGEMENT OF EXPOSURES.

5. FIRE-FIGHTING MEASURES

FLAMMABILITY: COMBUSTIBLE

FLASH POINT: 130°F TCC

PRODUCTS OF COMBUSTION: SEE SECTION 10.

SUITABLE EXTINGUISHING MEDIA: FOR FIRES IN AREA, USE APPROPRIATE MEDIA.
USE DRY CHEMICAL OR ALCOHOL FOAM.

SPECIFIC HAZARDS: A VAPOR ACCUMULATION MAY FLASH IF IGNITED.

SPECIFIC METHODS: SOLVENT FIRE-FIGHTING PROCEDURES MAY BE USED.

6. ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS: SEE SECTION 8. PUT ON APPROPRIATE PPE.

SPILL RESPONSE: ELIMINATE ALL IGNITION SOURCES. EVACUATE UNPROTECTED PERSONNEL FROM AREA. WEAR PROPER PROTECTIVE EQUIPMENT INCLUDING RUBBER BOOTS. VENTILATE AREA IF NEEDED. STOP LEAK IF YOU CAN DO SO WITHOUT RISK. DIKE OR DAM LARGE SPILLS. AVOID DIRECT DISCHARGE TO SEWER AND SURFACE WATERS. PUMP TO CONTAINER OR SOAK UP WITH NON-COMBUSTIBLE INERT ABSORBENT MATERIALS. AFTER SPILL COLLECTION, FLUSH AREA WITH WATER AND FOLLOW WITH NORMAL CLEAN-UP PROCEDURES. WASH CONTAMINATED CLOTHING AND FOOTWEAR BEFORE RE-USE. BE CAREFUL AS SPILLS ARE SLIPPERY.

7. HANDLING AND STORAGE

HANDLING: FOLLOW ALL LABEL DIRECTIONS. INSTRUCT PERSONNEL ABOUT PROPER USE, HAZARDS, PRECAUTIONS, AND FIRST AID MEASURES.

USE IN WELL-VENTILATED AREAS. AVOID BREATHING VAPORS OR MISTS.

AVOID INGESTION AND CONTACT WITH EYES. DO NOT TASTE OR SWALLOW.

REMOVE AND WASH CONTAMINATED CLOTHING AND FOOTWEAR BEFORE RE-USE.

PRODUCT RESIDUE MAY REMAIN ON OR IN EMPTY CONTAINERS.

HANDLE CAREFULLY TO AVOID DAMAGING CONTAINER.

STORAGE: ROTATE STOCK REGULARLY. KEEP CONTAINER CLOSED WHEN NOT IN USE. AVOID TEMPERATURES BELOW 35°F OR ABOVE 120°F. KEEP AWAY FROM HEAT, SPARK AND FLAME. PROTECT FROM FREEZING. STORAGE AT AMBIENT TEMPERATURES IN A DRY AREA OUT OF DIRECT SUNLIGHT IS RECOMMENDED. KEEP AWAY FROM FOOD AND DRINK. KEEP OUT OF CHILDREN'S REACH.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Page 3 of 4

EXPOSURE LIMITS: 2-BUTOXYETHANOL = 20 PPM TWA (ACGIH), 50 PPM TWA-SKIN (OSHA)
ISOPROPYL ALCOHOL = 200 PPM TWA, 400 PPM STEL (ACGIH), 400 PPM TWA (OSHA)
ENGINEERING CONTROLS: NONE REQUIRED. GENERAL ROOM VENTILATION IS ADEQUATE.

PERSONAL PROTECTION

EYES: SAFETY GLASSES WITH SIDE SHIELDS RECOMMENDED IF SPRAYING.
HANDS: FOR PROLONGED OR REPEATED CONTACT WITH SKIN: RUBBER GLOVES.
RESPIRATORY: N.AP.
FEET: N.AP.
BODY: N.AP.

9. PHYSICAL AND CHEMICAL PROPERTIES

COLOR: GREEN	FLASH POINT: 130°F TCC
ODOR: SOLVENT	UEL: N.AV.
pH CONCENTRATE: 6.5	LEL: N.AV.
pH @ 2500 PPM SOLUTION: N.AP.	EVAPORATION RATE: N.AP.
pH @ USE DILUTION: N.AP.	ODOR THRESHOLD: N.AP.
PHYSICAL STATE: LIQUID	VAPOR PRESSURE: N.AP.
SPECIFIC GRAVITY: 0.935	VAPOR DENSITY: N. AP.
VISCOSITY: SLIGHTLY VISCOUS	COEFF. OIL/WATER: N.AP.
BOILING POINT: N.AP.	WATER SOLUBILITY: COMPLETE
MELTING POINT: N.AP.	OTHER: N.AP.

10. STABILITY AND REACTIVITY

STABLE: YES
CONDITIONS TO AVOID: AVOID TEMPERATURES BELOW 35°F.
AVOID HEAT, SPARKS AND FLAME.

MATERIALS TO AVOID: AVOID MIXING DIRECTLY WITH ANY OTHER CLEANING PRODUCT. AVOID OXIDIZING AGENTS. MIX ONLY WITH WATER.

DECOMPOSITION PRODUCTS: FIRE OR MIXING WITH INCOMPATIBLE MATERIALS MAY PRODUCE OXIDES OF CARBON AND OTHER TOXIC OR IRRITATING FUMES.

POSSIBILITY OF HAZARDOUS REACTIONS: N.AP.

11. TOXICOLOGICAL INFORMATION

ACUTE EFFECTS: SEE SECTION 2.
CHRONIC EFFECTS: NONE KNOWN. NO REPORTABLE CARCINOGENS, MUTAGENS, SENSITIZERS, SYNERGISTIC MATERIALS, TERATOGENS, OR REPRODUCTIVE TOXINS.
LC50/LD50: N.AV.
TARGET ORGANS: EYES, SKIN, RESPIRATORY SYSTEM.
OTHER TOXIC EFFECTS: NONE KNOWN.

12. ECOLOGICAL INFORMATION

Page 4 of 4

NOT AVAILABLE.

13. DISPOSAL CONSIDERATIONS

DISPOSAL METHOD: UNDILUTED PRODUCT WITH FLASH POINT BELOW 140 F IS REGULATED UNDER ENVIRONMENTAL AND TRANSPORTATION LAWS AS AN IGNITABLE WASTE (RCRA CLASS D001). COMPLY WITH ALL FEDERAL, STATE, PROVINCIAL AND LOCAL LAWS AND REGULATIONS. CONSULT STATE AND LOCAL AUTHORITIES FOR RESTRICTIONS ON DISPOSAL OF CHEMICAL WASTE. MANAGE CHEMICAL WASTES THROUGH AN APPROVED WASTE TREATMENT FACILITY. DO NOT REUSE EMPTY CONTAINER. RINSE EMPTY CONTAINER THOROUGHLY WITH WATER BEFORE DISCARDING CONTAINER IN ACCORDANCE WITH CURRENT LOCAL COMMUNITY CODES. PLEASE RECYCLE EMPTY CONTAINER WHENEVER POSSIBLE.

14. TRANSPORT INFORMATION

DOT/TDG: NOT REGULATED (COMBUSTIBLE EXCEPTION).

DOT RQ: N.AP.

DOT ERG #: N.AP.

15. REGULATORY INFORMATION

EPA CERCLA RQ: N.AP.

EPA REGISTERED: NO

OSHA HAZARDOUS: YES

PHOSPHORUS CONTENT: 0.00%

PROPOSITION 65: N.AP.

SARA 311/312 HAZARDS: ACUTE, FIRE

SARA 313 CHEMICALS: 2-BUTOXYETHANOL

STATE RIGHT TO KNOW: SEE SECTION 3 FOR STATE RTK CHEMICAL NAMES.

TSCA INVENTORY STATUS: ALL COMPONENTS ARE LISTED ON THE INVENTORY.

VOC: 5.80% CALCULATION METHOD USED IS BASED ON CALIFORNIA ARB STANDARD.

WHMIS CLASS: D-2B, B-3

16. OTHER INFORMATION

NFPA RATING: HEALTH-2/FLAMMABILITY-2/REACTIVITY-0/SPECIAL HAZARD-N.AP.

HMIS RATING: HEALTH-2/FLAMMABILITY-2/REACTIVITY-0/PERSONAL PROTECTION-SEE 8.0

N.AV. = NOT AVAILABLE N.AP. = NOT APPLICABLE

PREPARED BY: HEALTH AND SAFETY

NOTICE TO READER

THIS DOCUMENT HAS BEEN PREPARED USING DATA FROM SOURCES CONSIDERED TECHNICALLY RELIABLE. IT DOES NOT CONSTITUTE A WARRANTY, EXPRESS OR IMPLIED, AS TO THE ACCURACY OF THE INFORMATION CONTAINED WITHIN. ACTUAL CONDITIONS OF USE AND HANDLING ARE BEYOND SELLER'S CONTROL. USER IS RESPONSIBLE FOR EVALUATING ALL AVAILABLE INFORMATION WHEN USING PRODUCT FOR ANY PARTICULAR USE AND TO COMPLY WITH ALL FEDERAL, STATE, PROVINCIAL AND LOCAL LAWS AND REGULATIONS.