

SAFETY DATA SHEET

Revision Date 01/30/2015 REVISION NUMBER: 2

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product identifier

Product name POWER FOAM B2, Heavy Duty Chlorinated Caustic Cleaner

Other means of identification

 Product code
 118364

 UN/ID No.
 3266

 Synonyms
 NONE

Recommended use of the chemical and restrictions on use
Recommended Use
Uses advised against
No information available.
No information available

Details of the supplier of the safety data sheet

Manufacturer Address

Rochester Midland Corporation

155 Paragon Drive

Rochester, New York 14624 USA

Emergency telephone number

EMERGENCY TELEPHONE INFOTRAC: 1-800-535-5053

OUTSIDE U.S.: +1-352-323-3500

2. HAZARDS IDENTIFICATION

Classification

OSHA Regulatory Status

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Skin corrosion/irritation	Category 1
Serious eye damage/eye irritation	Category 1
Corrosive to metals	Category 1

Label elements

Emergency Overview

DANGER

Hazard statements

Causes severe skin burns and eye damage

May be corrosive to metals



Appearance Clear Light yellow liquid.

Physical state Liquid

Odor Chlorine

Revision Date 01/30/2015

Precautionary Statements - Prevention

Do not breathe dust/fume/gas/mist/vapors/spray

Wash face, hands and any exposed skin thoroughly after handling

Wear protective gloves/protective clothing/eye protection/face protection

Keep only in original container

Precautionary Statements - Response

Immediately call a POISON CENTER or doctor/physician

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing Immediately call a POISON CENTER or doctor/physician

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower

Wash contaminated clothing before reuse

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

Immediately call a POISON CENTER or doctor/physician IF SWALLOWED: Rinse mouth. DO NOT induce vomiting

Absorb spillage to prevent material damage

Precautionary Statements - Storage

Store locked up

Store in corrosive resistant container

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

No information available

Other Information

- Very toxic to aquatic life with long lasting effects
- · Very toxic to aquatic life

Unknown Acute Toxicity

4.63% of the mixture consists of ingredient(s) of unknown toxicity

3. COMPOSITION/INFORMATION ON INGREDIENTS

PRODUCT COMPOSITION CAS#	CAS No.	%	TRADE SECRET
POTASSIUM HYDROXIDE	1310-58-3	5.0-10.0	*
Sodium hypochlorite	7681-52-9	1.0 - 5.0	*

^{*}The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

First aid measures

General advice Immediately call a POISON CENTER or doctor/physician.

Eye contact IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. Immediately call a POISON CENTER or

doctor/physician.

Skin contact IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin

with water/shower. Wash contaminated clothing before reuse.

Inhalation IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for

breathing. Immediately call a POISON CENTER or doctor/physician.

Ingestion IF SWALLOWED: Rinse mouth. DO NOT induce vomiting.

118364 POWER FOAM B2, Heavy Duty Chlorinated Caustic Cleaner

Revision Date 01/30/2015

Most important symptoms and effects, both acute and delayed

Symptoms No information available.

Indication of any immediate medical attention and special treatment needed

Note to physicians Probable mucosal damage may contraindicate gastric lavage.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing media Caution: Use of water spray when fighting fire may be inefficient.

Specific hazards arising from the chemical

No information available.

Explosion data

Sensitivity to Mechanical Impact NONE. Sensitivity to Static Discharge NONE.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions Ensure adequate ventilation, especially in confined areas.

Environmental precautions

Environmental precautions See Section 12 for additional ecological information.

Methods and material for containment and cleaning up

Methods for containment Prevent further leakage or spillage if safe to do so.

Dike to contain. Pick up with absorbant material. Put in suitable container for disposal. Methods for cleaning up

7. HANDLING AND STORAGE

Precautions for safe handling

DANGER. CORROSIVE. Avoid contact with eyes, skin and clothing. Advice on safe handling

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep containers tightly closed in a dry, cool and well-ventilated place.

Incompatible materials Strong acids. Bases. Strong oxidizing agents. Reactive metals such as aluminum and

magnesium. Organic matter. Reducing agents.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

=======================================			
PRODUCT COMPOSITION	ACGIH TLV	OSHA PEL	NIOSH IDLH
CAS#			

118364 POWER FOAM B2, Heavy Duty Chlorinated Caustic Cleaner

Revision Date 01/30/2015

POTASSIUM HYDROXIDE	Ceiling: 2 mg/m ³	(vacated) Ceiling: 2 mg/m ³	=
1310-58-3			

Appropriate engineering controls

ENGINEERING CONTROLS Exhaust ventilation. Showers. Eyewash stations.

Individual protection measures, such as personal protective equipment

Eye/face protection Goggles and face shield are recommended to minimize eve contact.

Nitrile, neoprene, or other appropriate gloves are recommended to minimize hand skin Skin and body protection

contact. Appropriate protective clothing as needed to prevent skin contact. Eyewash fountains and safety showers must be easily accessible. It is the responsibility of the end user of this product to determine level of PPE required that is consistent with safe use of

this product.

RESPIRATORY PROTECTION Use approved NIOSH respiratory protection if TLV/PEL exceeded or if over exposure is

General Hygiene Considerations Handle in accordance with good industrial hygiene and safety practice.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state Liquid

Appearance Clear Light yellow liquid. Odor Chlorine

No information available Color No information available Odor threshold

Property Values Remarks • Method

(1% solution) pН 12.0

Melting point/freezing point No information available Boiling point / boiling range No information available

Flash point

None to boiling. **Evaporation rate** No information available

Flammability (solid, gas) No information available

Flammability Limit in Air Upper flammability limit: No information available

Lower flammability limit: No information available Vapor pressure No information available Vapor density 9.79 lb/gal, 9.66 lb/gal

Specific gravity 1.16

COMPLETE Water solubility

Solubility in other solvents No information available Partition coefficient No information available **Autoignition temperature** No information available **Decomposition temperature** No information available Kinematic viscosity No information available **Dynamic viscosity** No information available No information available **Explosive properties Oxidizing properties** No information available

Other Information

No information available Softening point VOC (EPA METH.24) (G/L): No information available

Density No information available No information available **Bulk density**

10. STABILITY AND REACTIVITY

REACTIVITY

No data available

Chemical stability

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

None under normal processing.

CONDITIONS TO AVOID

Extremes of temperature and direct sunlight.

Incompatible materials

Strong acids. Bases. Strong oxidizing agents. Reactive metals such as aluminum and magnesium. Organic matter. Reducing agents.

Hazardous Decomposition Products

Chlorine gas.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information Causes severe skin burns and eye damage

Inhalation Causes burns.

Eye contact Corrosive to the eyes and may cause severe damage including blindness.

Skin contact Causes burns.

Ingestion Causes burns.

PRODUCT COMPOSITION CAS#	Oral LD50	Dermal LD50	Inhalation LC50
POTASSIUM HYDROXIDE 1310-58-3	= 214 mg/kg (Rat)	-	-
Sodium hypochlorite 7681-52-9	= 8200 mg/kg (Rat)	> 10000 mg/kg (Rabbit)	-

Information on toxicological effects

Symptoms No information available.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

SensitizationNo information available.Germ cell mutagenicityNo information available.CarcinogenicityNo information available.

PRODUCT COMPOSITION CAS#	ACGIH	IARC	NTP	OSHA
Sodium hypochlorite 7681-52-9	-	Group 3	ı	-

Reproductive Toxicity
STOT - single exposure
STOT - repeated exposure
Aspiration hazard
No information available.
No information available.
No information available.

Numerical measures of toxicity - Product Information

Unknown Acute Toxicity 4.63% of the mixture consists of ingredient(s) of unknown toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral) 7298 mg/kg

12. ECOLOGICAL INFORMATION

Ecotoxicity

14.93% of the mixture consists of components(s) of unknown hazards to the aquatic environment

PRODUCT COMPOSITION CAS#	Algae/aquatic plants	Fish	Crustacea
Sodium hypochlorite 7681-52-9	-	4.5 - 7.6: 96 h Pimephales promelas mg/L LC50 static 0.06 - 0.11: 96 h Pimephales promelas mg/L LC50 flow-through 0.4 - 0.8: 96 h Lepomis macrochirus mg/L LC50 static 0.28 - 1: 96 h Lepomis macrochirus mg/L LC50 flow-through 0.05 - 0.771: 96 h Oncorhynchus mykiss mg/L LC50 flow-through 0.03 - 0.19: 96 h Oncorhynchus mykiss mg/L LC50 semi-static 0.18 - 0.22: 96 h Oncorhynchus mykiss mg/L LC50 static	

Persistence and degradability

No information available.

Bioaccumulation

No information available.

PRODUCT COMPOSITION CAS#	Partition coefficient
POTASSIUM HYDROXIDE	0.83
1310-58-3	

Other adverse effects No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal of wastes Disposal should be in accordance with applicable regional, national and local laws and

regulations.

Contaminated packaging Do not reuse container.

14. TRANSPORT INFORMATION

UN/ID No. 3266

Proper shipping name CORROSIVE LIQUID, BASIC, INORGANIC, N.O.S., (POTASSIUM HYDROXIDE, SODIUM

HYPOCHLORITE SOLUTION)

Hazard Class 8
Packing Group | |

Description 5 Liters (1.3 Gallons) and Less may be Classed as LTD. QTY.

15. REGULATORY INFORMATION

International Inventories

TSCA Complies
DSL/NDSL Complies
EINECS/ELINCS Complies
ENCS Does not Comply
IECSC Complies
KECL Does not Comply
PICCS Complies

Legend:

AICS

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

Complies

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

SARA 311/312 Hazard Categories

ACUTE HEALTH HAZARD
YES
CHRONIC HEALTH HAZARD
No
FIRE HAZARD
Sudden release of pressure hazard
No
REACTIVE HAZARD
YES

CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

CERCLA

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material

PRODUCT COMPOSITION CAS#	Hazardous Substances RQs (in LBS)	U.S CERCLA/SARA - Section 302 Extremely Hazardous Substances TPQs
POTASSIUM HYDROXIDE 1310-58-3	1000	
Sodium hypochlorite 7681-52-9	100	

US State Regulations

California Proposition 65

This product does not contain any Proposition 65 chemicals

U.S. State Right-to-Know Regulations

118364 POWER FOAM B2, Heavy Duty Chlorinated Caustic Cleaner

Revision Date 01/30/2015

PRODUCT COMPOSITION CAS#	NJRTK:	MARTK:	PARTK:
POTASSIUM HYDROXIDE 1310-58-3	1571	Listed	Listed
Sodium hypochlorite 7681-52-9	Listed	Listed	Listed

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

16. OTHER INFORMATION

NFPA

Health hazards 3 Flammability 0 Instability 1

Physical and Chemical Properties CORR

HMIS

Health hazards 3 Flammability 0 Physical hazards 1 Personal protection C

Prepared By EH&S DEPARTMENT

Revision Date 01/30/2015

Revision Note Disclaimer

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

*** END OF SDS ***