



MATERIAL SAFETY DATA SHEET

REVISION DATE: 10/28/2008 REVISION NUMBER: 2
DATE PRINTED: 11/11/2008 PREPARED BY: EH&S DEPARTMENT

1. CHEMICAL PRODUCT

PRODUCT NAME: **POWER FOAM NT**
PRODUCT CODE: 119037

NFPA/HMIS HAZARD CODES(minimal=0; slight=1; moderate=2; serious=3; severe=4)

Health: 3/3 Fire: 0/0
Reactivity: 1/1 Special/Protective Equipment: ALK/C

NAME OF THE MANUFACTURER: Rochester Midland Corporation
333 Hollenbeck Street
Rochester, New York 14621
Information: 585-336-2200
Emergency Phone:
INFOTRAC: 1-800-535-5053
OUTSIDE US: 1-352-323-3500

2. HAZARDS IDENTIFICATION

EFFECTS FROM ACUTE EXPOSURE:

INGESTION: Severe burns to mucous membranes of mouth, throat and digestive tract.
SKIN CONTACT: Prolonged contact causes severe burns which may not be immediately painful or visible.
INHALATION: Inhalation of mist will irritate mucous membranes. Can cause damage to mucous membranes of nose, throat, respiratory tract and lung tissue depending on severity of exposure.
EYE CONTACT: Causes severe eye burns. Corrosive to eye tissue and may cause severe damage and blindness.
CHRONIC EFFECTS: Dermatitis. Possible respiratory damage from inhalation of dust or mist.
EFFECTS/CARCINOGENICITY: None listed under OSHA, IARC, or NTP.
ROUTES OF ENTRY: Routes of entry for solids and liquids include eye and skin contact, ingestion and inhalation.

3. COMPOSITION/INFORMATION ON INGREDIENTS

PRODUCT COMPOSITION CAS#	%	ACGIH TLV	OSHA PELs
POTASSIUM HYDROXIDE 1310-58-3	9 max.	NA	NA
Diethylene glycol butyl ether 112-34-5	10	NA	NA

4. FIRST AID MEASURES

INGESTION: Do not induce vomiting. Slowly dilute with 1-2 glasses of water or milk and seek medical attention. Never give anything by mouth to an unconscious person.
SKIN: Flush with water for at least 15 minutes while removing all contaminated clothing and shoes. Continue rinsing until "slippery" feeling is gone. Get medical attention if irritation or burns develop.
INHALATION: Remove person to fresh air. If not breathing, give artificial respiration. If breathing is difficult, get immediate medical attention.
EYES: Immediately flush eyes with large amounts of water for at least 15 minutes. Get immediate medical attention.
NOTES TO PHYSICIAN: None.

POWER FOAM NT

5. FIRE AND EXPLOSION HAZARD DATA

FLASH POINT (F): None (C): NA
METHOD: TCC

FLAMMABLE LIMITS IN AIR

- LOWER (%): NA
- UPPER (%): NA

SENSITIVITY TO MECHANICAL IMPACT(Y/N):

SENSITIVITY TO STATIC DISCHARGE:

SUITABLE EXTINGUISHING MEDIA:

FIRE FIGHTING PROCEDURES:

NO

Sensitivity to static discharge is not expected.

Water fog, carbon dioxide, foam, dry chemical.

Corrosive material. Avoid exposure to mist and splashes. Fire-fighters should wear self-contained breathing apparatus and full protective clothing when fighting chemical fires.

6. ACCIDENTAL RELEASE MEASURES

SPILL PROCEDURES:

SMALL SPILLS:

Pick up with absorbant material. Flush residue with water.

LARGE SPILLS:

Dike to contain. Pick up with absorbant material. Put in suitable container for disposal. Flush remainder with water.

PERSONAL PRECAUTIONS:

NA

ENVIRONMENTAL PRECAUTIONS:

NA

METHODS FOR CLEANING UP:

NA

7. HANDLING AND STORAGE

PRECAUTIONS TO BE TAKEN
IN HANDLING AND STORAGE:

Danger: Corrosive. Avoid contact with eyes, skin and clothing. Store away from acids. Do not reuse container. Store in a cool, dry location away from incompatible materials. Keep container closed when not in use.

OTHER PRECAUTIONS:

Keep out of reach of children.

SPECIFIC USE(S):

NA

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

PROTECTIVE EQUIPMENT:



EXPOSURE CONTROLS:

Eyewash stations. Showers.

RESPIRATORY PROTECTION:

None normally required. Use NIOSH approved alkaline respirator with dust/mist filter as needed to meet exposure limits if product is used in a manner which creates dust or mist above recommended exposure limits.

PROTECTIVE GLOVES:

Neoprene. Rubber gloves. Nitrile gloves.

EYE PROTECTION:

Face shield. Goggles.

OTHER PERSONAL PROTECTION
EQUIPMENT:

Appropriate protective clothing as needed to prevent skin contact. Rubber boots. Rubber apron. Eyewash fountains and safety showers must be easily accessible.

VENTILATION:

General mechanical and/or local exhaust as needed to meet exposure limits if mist in air.

9. PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE AND ODOR:

Clear. Tan. Viscous liquid. Butyl odor

BOILING POINT (F):

As water

(C) NA

VAPOR PRESSURE:

As water

VAPOR DENSITY (AIR=1):

NA

SOLUBILITY IN WATER:

COMPLETELY SOLUBLE

SPECIFIC GRAVITY:

1.077 - 1.087

POWER FOAM NT

9. PHYSICAL AND CHEMICAL PROPERTIES

VOC Content (%): 10 (ARB Method 310)
VOV Content (%): NE
EVAPORATION RATE: As water
PH: 13.5 - 14.0

10. STABILITY AND REACTIVITY

STABILITY DATA: STABLE
POLYMERIZATION: Will Not Occur.
HAZARDOUS DECOMPOSITION: Exposure to fire or flame may generate: Organic vapors.
INCOMPATIBILITY (MATERIALS TO AVOID): Contact with acids. Avoid contact with aluminum, zinc, other soft metals or galvanized metals.
CONDITIONS/HAZARDS TO AVOID: None anticipated

11. TOXICOLOGICAL INFORMATION

ACUTE TOXICITY: NE
EFFECTS OF CHRONIC EXPOSURE: NE
OTHER TOXIC EFFECTS: NE

12. ECOLOGICAL INFORMATION

ECOTOXICOLOGICAL INFORMATION: No data at this time
CHEMICAL FATE INFORMATION: No data at this time.
MOBILITY: NA
PERSISTENCE/DEGRADABILITY: NA
BIOACCUMULATIVE POTENTIAL: NA
OTHER ADVERSE EFFECTS: NA

13. DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHODS: Dispose in accordance with Federal, State and Local regulations.

14. TRANSPORT INFORMATION

Please refer to the Bill of Lading/Receiving documents for up to date shipping information.

15. REGULATORY INFORMATION

PRODUCT COMPOSITION CAS#	%	TSCA:	EINECS:	Canada DSL:	CA PROP 65:
POTASSIUM HYDROXIDE 1310-58-3	9 max.	Listed	Listed	Listed	Not Listed
Diethylene glycol butyl ether 112-34-5	10	Listed	Listed	Listed	Not Listed

PRODUCT COMPOSITION CAS#	%	CERCLA:	SARA 302:	SARA 313:
POTASSIUM HYDROXIDE 1310-58-3	9 max.	1000 lb 454 kg	Not Listed	Not Listed
Diethylene glycol butyl ether 112-34-5	10	Not Listed	Not Listed	Listed

POWER FOAM NT

PRODUCT COMPOSITION CAS#	%	Canada WHMIS:
POTASSIUM HYDROXIDE 1310-58-3	9 max.	Listed
Diethylene glycol butyl ether 112-34-5	10	Listed

The following components of this material are included in the Massachusetts Substance List and are present at or above reportable levels.

PRODUCT COMPOSITION CAS#	%	MARTK:
POTASSIUM HYDROXIDE 1310-58-3	9 max.	Listed

The following components of this material are included in the New Jersey Substance List and are present at or above reportable levels.

PRODUCT COMPOSITION CAS#	%	NJRTK:
POTASSIUM HYDROXIDE 1310-58-3	9 max.	Listed
Diethylene glycol butyl ether 112-34-5	10	Listed

The following components of this material are included in the Pennsylvania Substance List and are present at or above reportable levels.

PRODUCT COMPOSITION CAS#	%	PARTK:
POTASSIUM HYDROXIDE 1310-58-3	9 max.	Listed
Diethylene glycol butyl ether 112-34-5	10	Listed

16. OTHER INFORMATION

This information was compiled from current, reliable sources and is believed to be correct. As data, and/or regulations change, and conditions of use and handling are beyond our control, no warranty, express or implied, is made as to completeness or continuing accuracy of this information.

*** END OF MSDS ***