

The Magic is the Media

A ISO 9001:2008 - ANSI-ISO-ASQ Q9001-2008 Company

SECTION I

PRODUCT NAME OR NUMBER (as it appears of Polyplus® Plastic Blast Abrasive (Type II)	on label)	
MANUFACTURER'S NAME	EMERGENCY TELEPHONE NO.	
U.S. Technology Media Inc.	(330) 455-1181	
ADDRESS (Number, Street, City and Zip Code)	DATE PREPARED/REVISED –	
509 Water ST., Bolivar OH. 44612	NO. September 10, 2015-9	
MATERIAL DESCRIPTION, PROPER SHIPPING	NAME	
Plastic Abrasive, Polyplus		
HAZARD CLASSES (as applicable): N.A.		
CHEMICAL FAMILY: Amino Thermoset Plastic	FORMULA: N.A.	

SECTION II – INGREDIENTS

(list all ingredients)

CAS REG ISTR Y NO.	Approx. %W	Chemical Name(s)	OSHA PEL	ACGIH TLV	Other Limits Recommended
9004-34-6 9011-05-6	98	Polymerized Urea/Melamine Formaldehyde Compound w/ Alpha Cellulose Filler			
2764-13-8	>1%	Anti-Static Agent – Cal Stat 600			
5280-80-8 13463-67-7 12769-96-9	<2%	Pigments and Additives			

SECTION III – PHYSICAL DATA

BOILING POINTºF ºC	SPECIFIC GRAVITY (H ₂ O=1):	BULK DENSITY
N.A.	1.47-1.52	58-60 lbs./ft ³
MELTING POINTºFºC	PERCENT VOLATILE BY	PERCENT SOLID BY WEIGHT
N.A.	VOLUME (%) N.A.	(%) 100
VAPOR DENSITY (AIR=1)	EVAPORATION RATE (=1)	
N.A.	N.A.	
SOLUBILITY IN WATER - Not	pH= 4-8	
APPEARANCE AND ODOR: Multi-colored granules with slight		MATERIAL FORM: Solid
plastic odor		

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT ºF ºC: N.A.	FLAMMABLE: N.A.	LEL: N.A.	UEL: N.A.
EXTINGUISHING MEDIA: Carbon dioxide, dry chemicals or water fog			
SPECIAL FIRE FIGHTING PROCEDURES: Do not use high-pressure water stream. Fog nozzles are preferable.			
UNUSUAL FIRE AND EXPLOSION HAZARDS: Maintain normal good housekeeping for control of dust.			

SECTION V - HEALTH HAZARD DATA

SECTION V HEALTH HALAND BATTA				
EFFECTS OF OV	EREXPOSI	JRE – Conditions to a	void:	THRESHOLD LIMIT VALUE:
Mechanical injury	to eyes and	l/or skin can occur. Exc	essive	PERMISSIBLE EXPOSURE LIMIT:
dust inhalation ma				
PRIMARY ROUTE	S OF ENT	RY: 🗹 Inhalation	☑ Sk	in Contact
			case of e	eye or skin irritation, flush with plenty of water for
15 minut	es. Inhalati	on – remove to fresh ai	r and co	ntact physician if necessary.
		SECTION VI – RI	EACTI	VITY DATA
STABILITY: 🗹		☐ UNSTABLE		ITIONS TO AVOID:
INCOMPATIBILIT	Y (Material	ls to avoid): No specifi	c incomp	patibility
				e, carbon dioxide, carbon monoxide,
		ogen cyanide at +500°F		
HAZARDOUS PO		_	COND	ITIONS TO AVOID:
✓ MAY NOT (OCCUR	☐ MAY OCCUR		
	SEC	TION VII - SPILL O	R LEA	K PROCEDURES
STEPS TO BE TA	KEN IN CA	ASE MATERIAL IS REI	EASED	OR SPILLED: Remove from open flame, sparks,
hot surfaces and oxidizing agents. Sweep up and place waste in disposal container.				
WASTE DISPOSAL METHOD: Sanitary landfill in accordance with Federal, State and Local regulations.				
CERCLA (Superfund) REPORTABLE QUANTITY (in lbs.): N.A.				
RCRA HAZARDOUS WASTE NO. (40 CFR 261.33): N.A.				
VOLATILE ORGA	NIC COMP	OUND (VOC) (as pack	caged, n	ninus water): N.A.
☐ Theoretica	al	lbs. /gal.	Analyti	cal lbs. /gal.
	SECTION	N VIII – SPECIAL P	ROTE	CTION INFORMATION
RESPIRATORY P	ROTECTIO	N (Specify Type): Wh	ere regu	ired, use NIOSH/MSHA approved respiratory
		ance with OSHA regula		
VENTILATION				re necessary to maintain exposure levels to
		OSHA permissible leve		The state of the s
MECHANICAL (General – Specify Rate): Acceptable				
SPECIAL: Explosion proof may be necessary if aerated and airveyed.				
	OTHER:			,

SECTION IX – SPECIAL PRECAUTIONS

EYE PROTECTION (Specify Type): Safety goggles

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: Store in closed, properly labeled containers in cool ventilated area. Keep away from heat, sparks, open flame and oxidizing agents. Do not transfer unmarked containers.

OTHER PRECAUTIONS: None

Prepared by:

Name (print): Casey Williams Title: Quality Assurance Manager Date Reviewed: September 10, 2015-9

PROTECTIVE GLOVES (Specify Type): Normal

OTHER PROTECTION EQUIPMENT: Respirator hood, if necessary.