

MATERIAL SAFETY DATA SHEET

NPVLA 6-70

(Approved by U.S. Department of Labor "Essentially Similar" to Form LSB-00S-4)

Section I

MANUFACTURER'S NAME

Precision Laboratories Inc.

STREET ADDRESS

333 Anthony Trail - P.O. Box 127

CITY, STATE, AND ZIP CODE

Northbrook, IL 60062

EMERGENCY TELEPHONE NO.

312-498-0800

CHEMICAL NAME AND SYNONYMS

TRADE NAME

POWER FOAM

CHEMICAL FAMILY

Foaming butyl cleaner

FORMULA

Section II — HAZARDOUS INGREDIENTS

PAINTS, PRESERVATIVES, & SOLVENTS

PIGMENTS	%	TLV (Units)	SOLVENTS	%	TLV (Units)
CATALYST			ADDITIVES	12.0	
VEHICLE	88.0		OTHERS		

HAZARDOUS MIXTURES OF OTHER LIQUIDS, SOLIDS, OR GASES

None

Section III — PHYSICAL DATA

BOILING POINT (°F.)	212°F	SPECIFIC GRAVITY (H ₂ O=1)	1.01
VAPOR PRESSURE (mm Hg.)	N/A	PERCENT VOLATILE BY VOLUME (%)	88
VAPOR DENSITY (AIR=1)	N/A	EVAPORATION RATE (.....=1)	N/A
SOLUBILITY IN WATER	100%		
APPEARANCE AND ODOR	Light green with mint odor		

Section IV — FIRE AND EXPLOSION HAZARD DATA

FLASH POINT (METHOD USED)	None	FLAMMABLE LIMITS	LeI	UeI
EXTINGUISHING MEDIA	None			
SPECIAL FIRE FIGHTING PROCEDURES	None			
UNUSUAL FIRE AND EXPLOSION HAZARDS	None			

Section V — HEALTH HAZARD DATA

THRESHOLD LIMIT VALUE

Exceeds 500 MAC

EFFECTS OF OVEREXPOSURE

Slight throat & nose irritation

EMERGENCY AND FIRST AID PROCEDURES

Provide air

Section VI — REACTIVITY DATA

STABILITY

UNSTABLE

CONDITIONS TO AVOID

STABLE

X

INCOMPATIBILITY (Materials to avoid)

Acids

HAZARDOUS DECOMPOSITION PRODUCTS

None

HAZARDOUS
POLYMERIZATION

MAY OCCUR

CONDITIONS TO AVOID

WILL NOT OCCUR

X

Section VII — SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

Wash with water

WASTE DISPOSAL METHOD

Land Fill

Section VIII — SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION (Specify type)

None

VENTILATION

LOCAL EXHAUST

SPECIAL

MECHANICAL (General)

OTHER

PROTECTIVE GLOVES

Neoprene

EYE PROTECTION

OTHER PROTECTIVE EQUIPMENT

N/A

Section IX — SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

Store between 32-110°F.

OTHER PRECAUTIONS

See label for full precautions