BEBBINGTON INDUSTRIES MATERIAL SAFETY DATA SHEET - POWER WASH 429

SECTION 1: PRODUCT INFORMATION

PRODUCT NAME: POWER WASH 429

INTENDED USE: INDUSTRIAL CLEANER/DEGREASER

TDG SHIPPING NAME: CORROSIVE LIOUIDS NOS (SODIUM HYDROXIDE)

TDG CLASSIFICATION: TDG CLASS 8, UN 1760, PG 11I

WHMIS CLASSIFICATION: CLASS E CORROSIVE

MANUFACTURER: BEBBINGTON INDUSTRIES

44 WRIGHT AVENUE

DARTMOUTH, NOVA SCOTIA B3B 1G6 TELEPHONE: 902 468-8180 FAX: 902 468-8559

EMERGENCY TELEPHONE : 613 996 6666

SECTION 2: HAZARDOUS INGREDIENTS.

NON IONIC SURFACTANTS, (ALKYL, POLYOXYETHYLENES)	1 - 10%
BLEND OF CAS NO'S 68551-13-3, 68439-46-3, 66455-14-9, TLV, LD\50, LC\50 N/A	
SODIUM SILICATE - CAS NO. 1344-09-08 LD 50 1280 MG/KG ORAL RAT	0.1 - 4 %
SODIUM PHOSPHATE - CAS NO. 7558-99-4 LD 50 ORAL RAT 7400 MG/KG	0.1 - 2 %
EDTA - CAS NO 19019-43-1 LD 50 ORAL RAT 681 MG/KG	0.1 - 2 %
GLYCOL ETHER - CAS NO 002807309 LD 50 ORAL RAT 1774 MG/KG	2 - 4 %
SODIUM ALKYL BENZENE SULPHONATE - CAS NO 68081-81-2 LD 50 NA 0.	1 -2 %

SECTION 3: PHYSICAL DATA.

A CLEAR COLOURLESS AQUEOUS SOLUTION WITH A PH BETWEEN 12.8 AND 13.5. PRODUCT IS MISCIBLE WITH WATER.

SECTION 4: FIRE AND EXPLOSION HAZARD DATA

NO FIRE OR EXPLOSION HAZARD. MAY REACT VIOLENTLY IF MIXED WITH CONCENTRATED ACIDS.

SECTION 5: HEALTH HAZARD DATA.

THIS PRODUCT IS CORROSIVE.

SWALLOWING - MAY CAUSE BURNS OF THE MOUTH, THROAT AND STOMACH. INHALATION - MISTS ARE IRRITANTS TO RESPIRATORY TRACT. SKIN CONTACT - CAN BE CORROSIVE TO SKIN. MAY CAUSE IRRITATION. EYE CONTACT - CORROSIVE TO EYE TISSUES, CAN CAUSE BURNS. PROLONGED CONTACT CAN DEHYDRATE AND REMOVE OILS FROM SKIN.

SECTION 6: FIRST AID PROCEDURES

INHALATION OF MIST - REMOVE TO FRESH AIR. OBTAIN MEDICAL ATTENTION

IMMEDIATELY.

SWALLOWING - IF SWALLOWED **DO NOT INDUCE VOMITING.** GIVE LARGE QUANTITIES OF WATER OR MILK IF AVAILABLE. CALL A PHYSICIAN IMMEDIATELY. NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON.

SKIN CONTACT - WASH SKIN WITH LARGE AMOUNTS OF WATER FOR AT LEAST 15 MINUTES AND REMOVE CONTAMINATED CLOTHING. WASH CLOTHES BEFORE REUSE. EYE CONTACT - RINSE EYES WITH LARGE AMOUNTS OF WATER FOR 15 MINUTES, AND LIFT LOWER AND UPPER EYE LIDS OCCASIONALLY. SEEK MEDICAL ATTENTION.

SECTION 7: REACTIVITY DATA

STABILITY - PRODUCT IS STABLE UNDER NORMAL CONDITIONS OF USE AND STORAGE. THIS PRODUCT IS INCOMPATIBLE WITH ACIDS. MAY PRODUCE A VIOLENT REACTION IF MIXED WITH CONCENTRATED ACID.

SECTION 8: SPILL OR LEAK PROCEDURES

VENTILATE AREA OF LEAK OR SPILL. CLEAN UP PERSONNEL REQUIRE PROTECTIVE CLOTHING. CONTAIN AND RECOVER LIQUID WHERE POSSIBLE - FOR SPILLS TO DRAINS OR SEWERS, FLUSH DRAIN WITH LARGE VOLUMES OF WATER.

SECTION 9: SPECIAL PROTECTION INFORMATION.

PROTECTIVE GLOVES –USE PROTECTIVE GLOVES SUCH AS VINYL OR NITRILE EYE PROTECTION - THE USE OF SAFETY GOGGLES OR GLASSES IS RECOMMENDED RESPIRATORY PROTECTION – NOT NORMALLY REQUIRED

SECTION 10: SPECIAL PRECAUTIONS.

AVOID CONTACT WITH SKIN, EYES AND CLOTHING. DO NOT INHALE MIST. WASH HANDS AFTER HANDLING.

SECTION 11: PREPARATION DATA.

PREPARED BY - BEBBINGTON INDUSTRIES
DATE – FEBRUARY 2015
FOR FURTHER INFORMATION CONTACT BEBBINGTON INDUSTRIES 902-468-8180.

DISCLAIMER:

THE ABOVE INFORMATION IS BELIEVED TO BE CORRECT BUT DOES NOT PURPORT TO BE ALL INCLUSIVE AND SHALL BE USED ONLY AS A GUIDE. BEBBINGTON INDUSTRIES SHALL NOT BE HELD LIABLE FOR ANY DAMAGE OF INJURY RESULTING FROM HANDLING OR FROM CONTACT WITH THE ABOVE PRODUCT. ALL PERSONS USING THIS PRODUCT SHOULD BE TRAINED ACCORDING TO WHMIS REQUIREMENTS.