



560 NORTH 500 WEST  
SALT LAKE CITY, UT 84116  
801/521-0313  
FAX 801/539-0510

## M A T E R I A L   S A F E T Y   D A T A   S H E E T

Product Name: PREMIERE POWER AUTO DISH

Date Prepared: January 3, 2005

### Hazardous Ingredients

Sodium Dichlorocyanurate Dihydrate

OSHA PEL  
5MG/M3

ACGIH TLV  
5MG/M3

As an aid to health and safety personnel this product also contains alkaline carbonates, phosphates and silicates.

### Physical/Chemical Characteristics

Solubility In Water: About 15%

Appearance and odor: White crystalline solid with slight chlorine odor

### Fire And Explosion Hazard Data

Flammability: not flammable.

Extinguishing media: alcohol foam or carbon dioxide or dry chemical.

Hazardous decomposition products: may form toxic materials: chlorine.

Special fire fighting procedures: wear self-contained breathing apparatus with a full face piece operated in pressure-demand or other positive pressure mode when fighting fires.

### Reactivity Data

Materials to avoid:

Contact with easily oxidizable organic material, ammonia, urea, or similar nitrogen containing compounds, inorganic reducing compounds, calcium hypochlorite, alkalis.

Hazardous decomposition products: chlorine-containing gases can be produced. Traces of phosgene can be liberated at temperatures >400 degrees f.

Hazardous polymerization: does not occur.

### Physiological effects summary:

Oral: irritating to severely irritating to mucous membranes.

Skin Irritation: May Be Irritating.

Eye irritation: may be irritating to severely irritating.

Inhalation: dust may be irritating.

### Emergency and first aid procedures:

In Case of Eye Contact: Flood Water For At Least Minutes. Get medical attention.

In case of skin contact: wash off with water.

If swallowed: drink milk, water, or raw egg whites. Call a physician.

### Spill, Leak & Disposal Information:

Waste disposal: flush with large amounts of water to a sewer free of ammonia type products in small increments with excess water.

Spill or leakage procedure: sweep up and place bulk material in clean containers. Flush residue with large amounts of water to a sewer free of ammonia type products.

Industrial Hygiene Control Measures

Ventilation requirements: use adequate local exhaust ventilation if there is excessive dust.

Specific personal protective equipment:

Respiratory: respiration protection is not required under normal use.

Eye: protective goggles or safety glasses with side shields are recommended.

Gloves: gloves are recommended to minimize skin contact.

Special precautions or other comments: containers of this material may be hazardous when emptied since emptied containers retain product residues (vapor, liquid and/or solid), all hazard precautions given in the data sheet must be observed.

Note:

The information accumulated herein is believed to be efficacious and accurate; however, no warranty is made with respect thereto. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances.

Prepared to comply with the OSHA hazard communication standard (29CFR 1910.1200)