



Material Safety Data Sheet

**SAFETY-KLEEN
PREMIUM SOLVENT**

Part Number: 6605

Dear Safety-Kleen Customer,

At Safety-Kleen Corp., supplying material safety data sheets is more than a requirement to us; it is a commitment to our customers and their employees.

The material safety data sheet is a valuable source of product information and should be a part of your hazard communication program. With this in mind, we are providing you, our valued customer, this important product information.

Thank you for showing your concern for the environment by choosing Safety-Kleen Corp. products and services.

Sincerely,

Your friends at Safety-Kleen Corp.



SAFETY-KLEEN PREMIUM SOLVENT
MATERIAL SAFETY DATA SHEET FOR U.S.A. AND CANADA

SECTION 1 -- PRODUCT AND PREPARATION INFORMATION

PRODUCT INFORMATION

IDENTITY (TRADE NAME): SAFETY-KLEEN PREMIUM SOLVENT

SYNONYMS: Stoddard solvent; Naphtha, solvent

SK PART NUMBER(S): 6605

FAMILY/CHEMICAL NAME: Petroleum hydrocarbon

PRODUCT USE: Cleaning and degreasing metal parts.
 If this product is used in combination with other chemicals, refer to the Material Safety Data Sheets for those chemicals.

24-HOUR EMERGENCY TELEPHONE

These numbers are for emergency use only. If you desire non-emergency information about this product, please call a telephone number listed below.

MEDICAL:

1-800-752-7869 (U.S.A.)
 1-312-942-5969 (CANADA)

RUSH POISON CONTROL CENTER
 CHICAGO, ILLINOIS, U.S.A.

TRANSPORTATION:

1-708-888-4660 (U.S.A.)
 SAFETY-KLEEN ENVIRONMENT,
 HEALTH AND SAFETY DEPARTMENT

1-613-996-6666 (CANADA)
 CANUTEC

MANUFACTURER/SUPPLIER: Safety-Kleen Corp. - 777 Big Timber Road - Elgin, IL, U.S.A. 60123
 Telephone number: 1-800-669-5840
 Safety-Kleen Canada Inc. - 3090 Blvd. Le Carrefour - Suite 300 - Chomedey Laval
 Quebec, Canada H7T 2J7 Telephone number: 1-800-363-2260

PREPARATION INFORMATION

MSDS FORM NO.: 82529 **REVISION DATE:** February 11, 1993

ORIGINAL ISSUE DATE: January 7, 1993 **SUPERSEDES:** January 27, 1993

PREPARED BY: Product MSDS Coordinator **APPROVED BY:** MSDS Task Force Chairman

TELEPHONE NUMBER: For Product Technical Information Call 1-312-694-2700 (U.S.A.);
 1-800-363-2260 (Canada)

SECTION 2 -- HAZARDOUS COMPONENTS

NAME	SYNONYM	CAS NO.	WT%*	OSHA PEL		ACGIH TLV		OTHER DATA	
				TWA	STEL	TWA	STEL	LD ^a	LC ^b
Stoddard solvent	Naphtha, solvent	8052-41-3	0-100	100 ppm	N.Av.	100 ppm	N.Av.	>5000	>5500 mg/m ³ /4 hours
Distillates (petroleum) hydrotreated light	Solvent naphtha (petroleum), heavy aliph., hydrotreated	64742-47-8 ^c	0-100	N.Av.	N.Av.	N.Av.	N.Av.	>5000 (Chemlink Co.)	N.Av.

N.Av. = Not Available

*Even though the concentration range does not fall under the ranges prescribed by WHMIS, this is the actual range which varies with each batch of the product.

^aOral-Rat LD50 (mg/kg)

^bInhalation-Rat LC50

^cExxon recommended exposure limit: 300 ppm

SAFETY-KLEEN PREMIUM SOLVENT
MATERIAL SAFETY DATA SHEET FOR U.S.A. AND CANADA

SECTION 3 -- EMERGENCY AND FIRST AID PROCEDURES

- YES:** For direct contact, flush eyes with water for 15 minutes lifting upper and lower lids occasionally. If irritation or redness from exposure to vapor or mist develops, move victim away from exposure into fresh air. Consult physician if irritation or pain persists.
- KIN:** Remove contaminated clothing and shoes. Wash skin twice with soap and water. Consult physician if irritation or pain persists.
- INHALATION:**
Breathing) Remove to fresh air immediately. Use oxygen if there is difficulty breathing or artificial respiration if breathing has stopped. Do not leave victim unattended. Seek immediate medical attention if necessary.
- INGESTION:**
Swallowing) Seek immediate medical attention. Do NOT induce vomiting. If spontaneous vomiting occurs, keep head below hips to avoid aspiration (into lungs).
- SPECIAL NOTE TO PHYSICIAN:** Treat symptomatically and supportively. Administration of gastric lavage, if warranted, should be performed by qualified medical personnel. Contact Rush Poison Control Center (see Section 1) for additional medical information.

SECTION 4 -- HEALTH HAZARD DATA AND TOXICOLOGICAL PROPERTIES

PRIMARY ROUTES OF EXPOSURE: Eye and skin contact; inhalation, ingestion.

EXPOSURE LIMITS: See Section 2.

SIGNS AND SYMPTOMS OF EXPOSURE

ACUTE: *Eyes:* Contact with liquid or exposure to vapors may cause mild to moderate irritation with watering, stinging, or redness.

Skin: Contact with liquid or exposure to vapors tends to remove skin oils, possibly leading to redness, burning, drying and cracking, and damage; may cause dermatitis. No significant skin absorption hazard.

Inhalation (Breathing): High concentrations of vapor or mist may be irritating to the eyes and respiratory tract; may cause nausea, vomiting, coughing with blood, difficulty breathing, lung congestion, and heart attack. High concentrations of vapor or mist may cause headaches, dizziness, incoordination, numbness, unconsciousness, seizures, and other central nervous system effects, including death.

Ingestion (Swallowing): Low order of acute oral toxicity. May cause irritation of the throat, nausea, vomiting, cardiac injury with arrhythmias (irregular heartbeats), and symptoms of central nervous system depression as listed for *ACUTE Inhalation*. Aspiration into the lungs during ingestion or vomiting may cause mild to severe pulmonary injury and possibly death.

CHRONIC: Prolonged or repeated skin contact may cause drying and cracking or dermatitis.

MEDICAL CONDITIONS

AGGRAVATED BY EXPOSURE: Individuals with pre-existing lung, cardiac, central nervous system, or skin disorders may have increased susceptibility to the effects of exposure.

CARCINOGENICITY: Not applicable.

Also see Section 9.

OTHER POTENTIAL HEALTH HAZARDS:

The following information is required by Canadian WHMIS regulations. Irritancy is covered in Signs and Symptoms of Exposure in Section 4. There is no known human sensitization, toxicologically synergistic product, reproductive toxicity, mutagenicity, or teratogenicity associated with this product as a whole.

SAFETY-KLEEN PREMIUM SOLVENT
MATERIAL SAFETY DATA SHEET FOR U.S.A. AND CANADA

SECTION 5 -- FIRE AND EXPLOSION HAZARD DATA

EMERGENCY RESPONSE GUIDE NUMBER:	27 Reference <i>Emergency Response Guidebook</i> (DOT P 5800.5)
FIRE AND EXPLOSION HAZARDS:	Vapor explosion hazard may occur indoors, outdoors, or in sewers. Decomposition and combustion products may be toxic. Heated containers may rupture, explode, or be thrown into the air. Vapors are heavier than air and may travel great distances to ignition source and flash back. Not sensitive to mechanical impact. Material may be sensitive to static discharge, which could result in fire or explosion.
FIRE FIGHTING PROCEDURES:	NFPA 704 Rating 1-2-0 (Health-Fire-Reactivity) Keep storage containers cool with water spray. Positive-pressure, self-contained breathing apparatus (SCBA) and structural firefighters' protective clothing will provide limited protection.
EXTINGUISHING MEDIA:	Carbon dioxide, regular foam, dry chemical, or water spray.
CONDITIONS OF FLAMMABILITY:	Heat, sparks, or flame.
FLASH POINT:	148°F (64°C) (minimum) Tag Closed Cup
AUTOIGNITION TEMPERATURE:	491°F (255°C)
FLAMMABLE LIMITS IN AIR:	LOWER: 0.6 Vol. % UPPER: 8.1 Vol. %
HAZARDOUS COMBUSTION PRODUCTS:	Burning may produce carbon monoxide.

SECTION 6 -- REACTIVITY DATA

STABILITY:	Stable under normal temperatures and pressures, and not reactive with water.
INCOMPATIBILITY (MATERIALS AND CONDITIONS TO AVOID):	Acids, alkalis, oxidizing agents, chlorines, or selected amines may cause a violent reaction. Avoid heat, sparks, or flame.
HAZARDOUS POLYMERIZATION:	Not known to occur under normal temperatures and pressures.
HAZARDOUS DECOMPOSITION PRODUCTS:	None under normal temperatures and pressures.

SECTION 7 -- PREVENTIVE MEASURES

PRECAUTIONS FOR SAFE USE AND HANDLING

HANDLING PRECAUTIONS:	Keep away from heat, sparks, or flame. When material is transferred, metal containers should be grounded and bonded. Avoid contact with eyes, skin, clothing, or shoes. Use in well ventilated area and avoid breathing vapor or mist.
PERSONAL HYGIENE:	Use good personal hygiene. Wash thoroughly with soap and water after handling and before eating, drinking, or using tobacco products. Clean contaminated clothing, shoes, and protective equipment before reuse. Discard contaminated clothing, shoes, or protective equipment if they cannot be thoroughly cleaned.
SHIPPING AND STORING PRECAUTIONS:	Keep container tightly closed when not in use and during transport. Do not pressurize, drill, cut, heat, weld, braze, grind, or expose containers to flame or other sources of ignition. Empty product containers may contain product residue. See Section 9 for Packing Group information.

SAFETY-KLEEN PREMIUM SOLVENT
MATERIAL SAFETY DATA SHEET FOR U.S.A. AND CANADA

SPILL PROCEDURES: Remove all ignition sources. Stop leak if you can do it without risk. Wear protective equipment specified in Section 7, CONTROL MEASURES. Ventilate area and avoid breathing vapor or mist. Water spray may reduce vapor, but it may not prevent ignition in closed spaces. For large spills, isolate area and deny entry; dike far ahead of liquid spill for later disposal. Contain away from surface waters and sewers. If possible, contain as a liquid for possible re-refining or sorb with compatible sorbent material and shovel with a non-sparking tool into closable container for disposal. See *Emergency Response Guidebook* (DOT P 5800.5) Guide Number 27 for more information.

WASTE DISPOSAL METHODS: Dispose in accordance with federal, state, provincial, and local regulations. Contact Safety-Kleen regarding recycling or proper disposal.

CONTROL MEASURES

EYE PROTECTION: Where there is likelihood of eye contact, wear chemical goggles and faceshield. Do NOT wear contact lenses.

PROTECTIVE GLOVES: Use Nitrile, Viton[®], or equivalent gloves to prevent contact with skin. Do NOT use Butyl rubber, natural rubber, or equivalent gloves.

RESPIRATORY PROTECTION: Use NIOSH/MSHA-approved respiratory protective equipment when concentration of vapor or mist exceeds applicable exposure limit. A self-contained breathing apparatus (SCBA) and full protective equipment are required for large spills or fire emergencies. Selection and use of respiratory protective equipment should be in accordance in the U.S.A. with OSHA General Industry Standard 29 CFR 1910.134 or in Canada with CSA Standard Z94.4-M1982.

ENGINEERING CONTROLS: Provide process enclosure or local ventilation needed to maintain concentration of vapor or mist below applicable exposure limits. Where explosive mixtures may be present, systems safe for such locations should be used.

OTHER PROTECTIVE EQUIPMENT: Where spills and splashes are possible, wear appropriate solvent-resistant boots, apron, or other protective clothing. Clean water should be available in work areas for flushing the eyes and skin.

SECTION 8 -- PHYSICAL DATA

PHYSICAL STATE, APPEARANCE AND ODOR: Liquid, clear, green or colorless, with characteristic hydrocarbon odor.

ODOR THRESHOLD: Not available.

SPECIFIC GRAVITY: 0.78 to 0.81 (60°/60°F) (15.6°/15.6°C) (water = 1)

DENSITY: 6.5 to 6.8 lb/US gal (779 to 811 g/l)

VAPOR DENSITY: 4.9 (air = 1) (approximately)

VAPOR PRESSURE: 1 to 2 mm Hg at 68°F (20°C) (maximum)

BOILING POINT: 360° to 478°F (182° to 248°C)

FREEZING POINT: -33°F (-36°C) (approximately)

pH: Not applicable.

VOLATILE ORGANIC COMPOUNDS: (US EPA DEFINITION) 100 WT%; 6.49 to 6.76 lb/US gal; 779 to 811 g/l

EVAPORATION RATE: 0.1 (butyl acetate = 1)

SOLUBILITY IN WATER: Slight.

SAFETY-KLEEN PREMIUM SOLVENT
MATERIAL SAFETY DATA SHEET FOR U.S.A. AND CANADA

**COEFFICIENT OF WATER/OIL
DISTRIBUTION:**

Not available.

MOLECULAR WEIGHT:

142 to 169 (approximately)

SECTION 9 -- OTHER REGULATORY INFORMATION

TRANSPORTATION INFORMATION

DOT PROPER SHIPPING NAME: COMBUSTIBLE LIQUID, N.O.S. (PETROLEUM NAPHTHA)

DOT CLASS: COMBUSTIBLE LIQUID

DOT ID NUMBER: NA1993, PG III

TDG CLASSIFICATION: Naphtha, petroleum, Class 3.3, UN1255, P.G. III

SARA TITLE III:

Product does not contain toxic chemicals subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

Product poses the following physical and health hazards as defined in 40 CFR Part 370 and is subject to the requirements of sections 311 and 312 of Title III of the Superfund Amendments and Reauthorization Act of 1986:

Immediate (Acute) Health Hazard
Delayed (Chronic) Health Hazard
Fire Hazard

WHMIS CLASSIFICATION:

B3, Flammable and Combustible Material, Combustible Liquids;
D2B, Poisonous and Infectious Material, Materials Causing Other Toxic Effects,
Toxic Material

TSCA:

All of the components for this product are listed on, or are exempted from the requirement to be listed on, the TSCA Inventory.

CALIFORNIA:

This product contains a detectable amount of benzene CAS No. 71-43-2. This material is listed by the State of California as a known carcinogen.

This product contains a detectable amount of toluene CAS No. 108-88-3. This material is listed by the State of California as known to cause reproductive toxicity.

User assumes all risks incident to the use of this product. To the best of our knowledge, the information contained herein is accurate. However, Safety-Kleen assumes no liability whatsoever for the accuracy or completeness of the information contained herein. No representations or warranties, either expressed or implied, or merchantability, fitness for a particular purpose or of any other nature are made hereunder with respect to information or the product to which information refers. The data contained on this sheet apply to the material as supplied to the user.



® 1993 Printed in the U.S.A. on Recycled Paper