

**W. R. GRACE**  
**MATERIAL SAFETY DATA SHEET**

Product Name: Procor® 75 Low Viscosity Spray Grade, Part A

MSDS ID Number: M-85684

MSDS Date: 04/23/2001

**SECTION 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION**

**Product Name:** Procor® 75 Low Viscosity Spray Grade, Part A  
**MSDS Number:** M-85684  
**Cancelled MSDS Number:** M-85682  
**MSDS Date:** 04/23/2001  
**Chemical Family Name:** Fluid applied Waterproofing Membranes Made of Naphthenic Oils and Inorganic Fill  
**Product Use:** Waterproofing Products  
**Chemical Formula:** Mixture-NA  
**CAS # (Chemical Abstracts Service Number):** Mixture-NA

**Manufactured by:**

W.R.Grace & Co.-Conn.  
62 Whittemore Avenue  
Cambridge, MA 02140

Grace Canada, Inc.  
294 Clements Road West  
Ajax, Ontario L1S 3C6

**In Case of Emergency Call:**

In USA: (617) 876-1400 In Canada: (905) 683-8561

**SECTION 2 - COMPOSITION/INFORMATION ON INGREDIENTS**

<b>Ingredient</b>	<b>CAS#</b>	<b>Percent (max)</b>
Calcium oxide	001305-78-8	30-45
Castor oil based ester	NJ801415063P	1-5
Distillates, petroleum, hydrotreated light naphthenic	064742-53-6	45-60
Quartz	014808-60-7	1-5
Zinc oxide	001314-13-2	1-5

**W. R. GRACE**  
**MATERIAL SAFETY DATA SHEET**

Product Name: Procor® 75 Low Viscosity Spray Grade, Part A  
MSDS ID Number: M-85684

MSDS Date: 04/23/2001

---

**SECTION 3 - HAZARDS IDENTIFICATION**

**Emergency Overview:**

**Warning!**

Causes eye irritation.

Causes skin irritation.

Causes digestive tract irritation if ingested.

Product reacts with other component and also with water. Reaction is exothermic, releasing heat and fumes. Mixed product contained in the pail may reach temperatures of 291°F.

Contact with hot materials will result in burns.

Do not seal containers once mixed with other component or contaminated with water.

Sealed containers explode due to pressure from the reaction.

**HMIS Rating:**

Health: 1

Flammability: 1

Reactivity: 1

Personal Protective Equipment: B,G (See Section 8)

**Potential Health Effects:**

**Inhalation:**

Not expected to be harmful. However, if mixed material is allowed to set in the container and subsequently inhaled. Temperatures up to 291°F can be reached, liberating water vapor, Carbon Disulfide and other Hydrocarbons.

Prolonged inhalation can cause lung damage.

Effects include: Flu-like symptoms (metal fume fever).

**Eye Contact:**

Eye contact causes irritation.

**Skin Contact:**

Skin contact causes irritation.

**Skin Absorption:**

Not expected to be harmful if absorbed through the skin.

**Ingestion:**

Due to the physical nature of this product, ingestion of this product is not likely.

If ingested, causes irritation to the linings of the mouth, esophagus and stomach.

Effects include the following: Nausea, vomiting, sneezing, coughing, labored breathing and burns.

**W. R. GRACE**  
**MATERIAL SAFETY DATA SHEET**

Product Name: Procor® 75 Low Viscosity Spray Grade, Part A  
MSDS ID Number: M-85684

MSDS Date: 04/23/2001

---

**SECTION 4 - FIRST AID MEASURES:**

**Skin Contact:**

If discomfort or irritation persists, consult a physician.

In case of skin contact, clean fingernails and wash skin with soap and water. If residue remains, clean with waterless handcream or abrasive soap. If irritation develops, consult a physician.

Remove contaminated clothing and wash before reuse.

**Eye Contact:**

If discomfort or irritation persists, consult a physician.

Flush eyes with water for at least 15 minutes while holding eyelids open.

**Ingestion:**

If discomfort or irritation persists, consult a physician.

Never give anything by mouth to an unconscious person.

Do not induce vomiting.

**Inhalation:**

If symptoms develop, get fresh air. If symptoms persist, consult a physician.

If breathing has stopped, give artificial respiration then oxygen if needed.

---

**SECTION 5 - FIRE AND EXPLOSION HAZARD DATA**

<b>Flash Point:</b>	Not Determined
<b>Flash Point Method:</b>	Not Applicable
<b>Lower Explosion Limit:</b>	Not Available
<b>Upper Explosion Limit:</b>	Not Available
<b>Auto-Ignition Temperature:</b>	Not Available

**NFPA Rating:**

<b>Health:</b>	1
<b>Flammability:</b>	1
<b>Reactivity:</b>	1

**Extinguishing Media:** In case of fire, use water spray, dry chemical, Carbon dioxide or alcohol foam.

**W. R. GRACE**  
**MATERIAL SAFETY DATA SHEET**

Product Name: Procor® 75 Low Viscosity Spray Grade, Part A  
MSDS ID Number: M-85684

MSDS Date: 04/23/2001

---

**Special Fire Fighting Procedures:**

Wear self-contained breathing apparatus and complete personal protective equipment when potential for exposure to vapors or products of combustion exist. Water may be used to cool containers to prevent pressure build-up and possible auto-ignition or explosion. Avoid breathing hazardous vapors or products of combustion, keep upwind. Isolate area and keep unnecessary people away. Prevent run-off from fire control or dilution from entering streams or drinking water supplies.

No special procedures specific to this product.

**Unusual Fire and Explosion Hazards:**

None known for this product.

---

**SECTION 6 - ACCIDENTAL RELEASE MEASURES:**

**Spills/Leaks:**

Use proper personal protective equipment. According to EPA (40 CFR § 261.3) waste of this product is not defined as hazardous. Do not flush to sewer or allow to enter waterways. Keep unnecessary people away.

---

**SECTION 7 - HANDLING AND STORAGE**

**Precautionary Measures:**

Avoid contact with eyes, skin and clothing.

Do not take internally.

Practice good personal hygiene to avoid ingestion.

Use only with adequate ventilation.

Wash clothing before reuse.

Wear respiratory protection during spray applications.

Reaction releases heat and fumes if unused mixed product is allowed to sit in pail.

Contact with hot material will result in burns.

Use all product within 30-60 minutes of mixing to avoid an exothermic reaction (release of heat and fumes). Reaction times may vary depending upon temperature and mixing conditions.

Promptly cleanse hands after handling.

**FOR PROFESSIONAL USE ONLY. KEEP OUT OF CHILDREN'S REACH.**

**W. R. GRACE**  
**MATERIAL SAFETY DATA SHEET**

Product Name: Procor® 75 Low Viscosity Spray Grade, Part A

MSDS ID Number: M-85684

MSDS Date: 04/23/2001

**SECTION 8 - EXPOSURE CONTROLS AND PERSONAL PROTECTIVE EQUIPMENT**

**EXPOSURE GUIDELINES (US)**

Ingredient	ACGIH TLV			OSHA PEL			Other
	TWA	STEL	Ceiling	TWA	STEL	Ceiling	
Calcium oxide	2 mg/m3 TWA	-	-	5 mg/m3 TWA (not in effect as a result of reconsider ation)	-	-	-
Castor oil based ester	-	-	-	-	-	-	-
Distillates, petroleum, hydrotreated light naphthenic	-	-	-	-	-	-	-
Quartz	0.05 mg/m3 TWA (this TLV is for the respirable fraction of dust)	-	-	respirable dust: 0.1 mg/m3 TWA	-	-	-
Zinc oxide	5 mg/m3 TWA (fume); 10 mg/m3 TWA (dust) (The value for Zinc oxide "dust" is	10 mg/m3 STEL (fume)	-	fume: 5 mg/m3 TWA; total dust: 10 mg/m3 TWA; respirable fraction: 5 mg/m3 TWA	fume: 10 mg/m3 STEL	-	-

**EXPOSURE GUIDELINES (CANADA)**

Employers should consult provincial regulatory limits for exposure guidelines which may vary locally.

**Engineering Controls:**

Provide local exhaust ventilation to prevent vapor build-up during application. This is particularly important in enclosed or confined areas where natural ventilation may not be adequate. Provide enough ventilation to maintain exposure levels below regulatory limits.

**W. R. GRACE**  
**MATERIAL SAFETY DATA SHEET**

Product Name: Procor® 75 Low Viscosity Spray Grade, Part A  
MSDS ID Number: M-85684

MSDS Date: 04/23/2001

---

**Personal Protective Equipment:**

**Respiratory Protection:** Respiratory protection may not be required in well ventilated areas. However, indoors or where ventilation is inadequate, the use of respirators equipped with organic vapor cartridges is required. During spray applications, the use of a dust/mist respirator such as a 3M Type P-95 or 3M Type P-95 with organic vapor (OV) protection (or equivalent) is required, but the specific respirator(s) may not adequately protect against actual working conditions which must be assessed periodically as work progresses. (See Work/Hygienic Practices.)

**Skin Protection:** Impervious (PVC, latex or nitrile) gloves should be worn anytime direct contact is possible.

**Eye Protection:** Safety glasses or goggles should be worn.

**Work/Hygienic Practices:** Use good personal hygiene practices.

Carbon disulfide and other potentially harmful gases, vapors and fumes may evolve as a result of exothermic reactions ("hot product") when components are mixed. Carbon disulfide may be detected by odor at about 1 ppm, but the ability to smell fatigues (diminishes) rapidly, therefore, odor does not serve as a good warning property. If eye or respiratory irritation is present, or if a foul odor is detected, you may be experiencing exposure to Carbon disulfide and other organics. Leave the area immediately and seek fresh air. Quartz (Crystalline silica) is a naturally-occurring mineral that is commonly contained in materials that are mined from the earth's surface such as sand, limestone, clay and gypsum (Calcium sulfate). Total quartz is a value usually representing the combined fractions of large, nonrespirable sized particles and of respirable sized particles (less than ten microns in aerodynamic diameter). It is only the respirable fraction of total quartz that is recognized as hazardous by professionals in the field of Occupational Health and by most regulatory agencies.. This component contains Calcium Oxide, Zinc Oxide, Titanium Dioxide and Quartz which are dispensed within a liquid medium and therefore non-bio available. However, if the dry finished product is abraded, small amounts of these materials may be released.

# W. R. GRACE

## MATERIAL SAFETY DATA SHEET

Product Name: Procor® 75 Low Viscosity Spray Grade, Part A

MSDS ID Number: M-85684

MSDS Date: 04/23/2001

### **SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES**

<b>Physical State:</b>	Liquid
<b>Appearance/Odor:</b>	A brownish semi-viscous liquid with an aromatic odor.
<b>Odor Threshold:</b> (ppm)	Not Determined
<b>pH:</b>	Not Applicable
<b>Vapor Pressure:</b> (Mm Hg)	Not Determined
<b>Vapor Density:</b> (Air = 1)	Not Determined
<b>Solubility In Water:</b>	Insoluble
<b>Specific Gravity:</b> (Water = 1)	~1.28
<b>Evaporation Rate:</b> (Butyl Acetate = 1)	Not Determined
<b>Boiling Point:</b>	Not Determined
<b>Viscosity:</b>	Unknown
<b>Bulk Density:</b> (Pounds/Cubic Foot)(Pcf)	~83
<b>% Volatiles (gr/L):</b> (70°F) (21°C)	Not Determined

### **SECTION 10 - STABILITY AND REACTIVITY**

<b>Chemical Stability:</b>	Stable
<b>Conditions To Avoid:</b>	Heat, Strong acids, Organic materials, Water, phosphorous pentoxide, magnesium, rubber, linseed oil, hydrogen flouride, boric acid and the reaction process will cause a pressure build up in unvented containers and could result in an explosive release of pressure. Therefore, containers must not be sealed once the reaction has begun. Once the reaction is complete and the product is cured, this material is no longer sensitive to contact with water.
<b>Hazardous Polymerization:</b>	Will not polymerize.
<b>Hazardous Decomposition Products:</b>	Carbon dioxide and toxic fumes of zinc oxide.

**W. R. GRACE**  
**MATERIAL SAFETY DATA SHEET**

Product Name: Procor® 75 Low Viscosity Spray Grade, Part A  
MSDS ID Number: M-85684

MSDS Date: 04/23/2001

---

**SECTION 11 - TOXICOLOGICAL INFORMATION**

<b><u>Ingredient(No data unless listed.)</u></b>	<b><u>CAS Number</u></b>	<b><u>LD50 and LC50</u></b>
Zinc oxide	001314-13-2	Inhalation LC50 Mouse : 2500 mg/m3; Oral LD50 Mouse : 7950 mg/kg

**Carcinogenicity:**

Ingredient	IARC Group 1	IARC Group 2A	IARC Group 2B	NTP Known	NTP Suspect	OSHA
Calcium oxide	No	No	No	No	No	No
Castor oil based ester	No	No	No	No	No	No
Distillates, petroleum, hydrotreated light naphthenic	No	No	No	No	No	No
Quartz	Yes	No	No	Yes	Yes	Yes
Zinc oxide	No	No	No	No	No	No

<b>Mutagenicity:</b>	No information available.
<b>Teratogenicity:</b>	No information available.
<b>Reproductive Toxicity:</b>	No information available.

---

**SECTION 12 - ECOLOGICAL INFORMATION**

<b>Environmental Fate:</b>	No data available for product.
<b>Ecotoxicity:</b>	No data available for product.

---

**SECTION 13 - DISPOSAL CONSIDERATIONS**

<b>Waste Disposal Procedures:</b>	Consult all regulations (federal, state, provincial, local) or a qualified waste disposal firm when characterizing waste for disposal. According to EPA (40 CFR § 261), waste of this product is not defined as hazardous. Dispose of waste in accordance with all applicable regulations.  Oil spills released directly to waterways may be subject to reporting requirements. Immediately contact your company's environmental coordinator or the Grace Environmental Health and Safety Department.
-----------------------------------	---



**W. R. GRACE**  
**MATERIAL SAFETY DATA SHEET**

Product Name: Procor® 75 Low Viscosity Spray Grade, Part A  
MSDS ID Number: M-85684

MSDS Date: 04/23/2001

---

**SECTION 14 - TRANSPORTATION INFORMATION**

<b>Proper Shipping Name:</b>	Not Applicable
<b>UN/NA Number:</b>	Not Applicable
<b>Domestic Hazard Class:</b>	Nonhazardous
<b>Surface Freight Classification:</b>	Not Applicable
<b>Label/Placard Required:</b>	Not Applicable

---

**SECTION 15 - REGULATORY INFORMATION**

**REGULATORY CHEMICAL LISTS:**

**CERCLA (Comprehensive Response Compensation and Liability Act):**  
**(None present unless listed below)**

<b><u>Chemical Name</u></b>	<b><u>CAS #</u></b>	<b><u>Wt %</u></b>	<b><u>CERCLA RQ</u></b>
Zinc compounds	RR-00578-7	2.3	

**SARA Title III (Superfund Amendments and Reauthorization Act)**

**SARA Section 312/Tier I & II Hazard Categories:**

Health Immediate (acute)	Yes
Health Delayed (chronic)	No
Flammable	No
Reactive	No
Pressure	No

**302 Reportable Ingredients (Identification Threshold 1%.):**

<b><u>Chemical Name</u></b>	<b><u>CAS #</u></b>	<b><u>Wt %</u></b>	<b><u>SARA 302</u></b> <b><u>TPQ</u></b>
-----------------------------	---------------------	--------------------	---

**313 Reportable Ingredients (Chemicals present below reporting threshold are exempt):**

<b><u>Chemical Name</u></b>	<b><u>CAS #</u></b>	<b><u>Wt %</u></b>
Zinc compounds	RR-00578-7	2.398

**W. R. GRACE**  
**MATERIAL SAFETY DATA SHEET**

Product Name: Procor® 75 Low Viscosity Spray Grade, Part A  
MSDS ID Number: M-85684

MSDS Date: 04/23/2001

**National Volatile Organic Compound Emission Standards For Architectural Coatings:**

**Volatile Organic Content:** (gr/L) 75 g/l (as applied)

**WHMIS Classification(s):**

D2 B

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR). This MSDS contains all the information required by the CPR.

**State Regulatory Information:**

**California Proposition 65:**

This product may, upon mixing, release small amounts of Carbon disulfide, a substance found on California's Proposition 65 list.

**Massachusetts Hazardous Substance List(Identification threshold 0.001%(1ppm)):**

<u>Chemical Name</u>	<u>CAS #</u>	<u>Wt %</u>
Distillates, petroleum, hydrotreated light naphthenic	064742-53-6	57.93
Quartz	014808-60-7	3.603

**New Jersey Hazardous Substance List(Identification threshold (0.1%)):**

<u>Chemical Name</u>	<u>CAS #</u>	<u>Wt %</u>
Zinc compounds	RR-00578-7	2.3

**Pennsylvania Hazardous Substance List(Identification threshold 0.01%):**

<u>Chemical Name</u>	<u>CAS #</u>	<u>Wt %</u>
----------------------	--------------	-------------

**CHEMICAL INVENTORY STATUS:**

**All chemicals in this product are listed or exempt from listing in the following countries:**

US	CANADA		EUROPE	AUSTRALIA	JAPAN	KOREA	PHILIPPINES
TSCA	DSL	NDSL	EINECS/ELINCS	AICS	ENCS	ECL	PICCS
Yes	No	Yes	Yes	Yes	Yes	Not Determined	Not Determined

**W. R. GRACE**  
**MATERIAL SAFETY DATA SHEET**

Product Name: Procor® 75 Low Viscosity Spray Grade, Part A  
MSDS ID Number: M-85684

MSDS Date: 04/23/2001

---

**SECTION 16 - OTHER INFORMATION**

**Non-Hazardous Ingredient Disclosure:**

**Chemical Name**

Zinc compounds

**CAS Number**

RR-00578-7

**Prepared by:**

EH&S Department

**Approved by:**

EH&S Department

**Approved Date:**

01/19/2001

**Disclaimer:**

"The data included herein are presented in accordance with various environment, health and safety regulations. It is the responsibility of a recipient of the data to remain currently informed on chemical hazard information, to design and update its own program and to comply with all national, federal, state and local laws and regulations applicable to safety, occupational health, right-to-know and environmental protection."

o:\ehsdocs\msds\watprf\Procor 75 Low Viscosity Spray Grade, Part A M-85684.doc