

# **SAFETY DATA SHEET**

# 0124

# 1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

1.1 Product identifier

Product name RIPEGAS

Synonym(s) 0124 - SDS NUMBER • BOC RIPEGAS • PRODUCT CODE: 198

1.2 Uses and uses advised against

Use(s) FRUIT RIPENING • SPACE SPRAY

1.3 Details of the supplier of the product

Supplier name BOC LIMITED (AUSTRALIA)

Address 10 Julius Avenue, North Ryde, NSW, 2113, AUSTRALIA

Telephone 131 262, (02) 8874 4400

Fax 132 427 (24 hours)

Website http://www.boc.com.au

1.4 Emergency telephone number(s)

**Emergency** 1800 653 572 (24/7) (Australia only)

# 2. HAZARDS IDENTIFICATION

## 2.1 Classification of the substance or mixture

CLASSIFIED AS HAZARDOUS ACCORDING TO AUSTRALIAN WHS REGULATIONS

GHS classification(s) Gases Under Pressure: Liquefied gas

2.2 Label elements

Signal word WARNING

Pictogram(s)



Hazard statement(s)

H280 Contains gas under pressure; may explode if heated.

Prevention statement(s)

None allocated.

Response statement(s)

None allocated.

Storage statement(s)

P410 + P403 Protect from sunlight. Store in a well-ventilated place.

Disposal statement(s)

None allocated.

2.3 Other hazards

Asphyxiant. Effects are proportional to oxygen displacement.



SDS Date: 16 Apr 2015

# 3. COMPOSITION/INFORMATION ON INGREDIENTS

#### 3.1 Substances / Mixtures

Ingredient	CAS Number	EC Number	Content (v/v)
ETHYLENE	74-85-1	200-815-3	4 to 5%
CARBON DIOXIDE	124-38-9	204-696-9	Remainder

# 4. FIRST AID MEASURES

#### 4.1 Description of first aid measures

Eye Cold burns: Immediately flush with tepid water or with sterile saline solution. Hold eyelids apart and irrigate

for 15 minutes. Seek medical attention.

Inhalation If inhaled, remove from contaminated area. To protect rescuer, use an Air-line respirator or Self Contained

Breathing Apparatus (SCBA). Apply artificial respiration if not breathing. Give oxygen if available. For advice,

contact a Poison Information Centre on 13 11 26 (Australia Wide) or a doctor.

Skin Cold burns: Remove contaminated clothing and gently flush affected areas with warm water (30°C) for 15

minutes. Apply sterile dressing and treat as for a thermal burn. For large burns, immerse in warm water for

15 minutes. DO NOT apply any form of direct heat. Seek immediate medical attention.

**Ingestion** Due to product form and application, ingestion is considered unlikely.

First aid facilities No information provided.

### 4.2 Most important symptoms and effects, both acute and delayed

In high concentrations may cause asphyxiation. Symptoms may include loss of mobility / consciousness. Victim may not be aware of asphyxiation. Low concentrations of CO2 cause increased respiration and headache.

## 4.3 Immediate medical attention and special treatment needed

Treat for asphyxia and cold burns.

# 5. FIRE FIGHTING MEASURES

## 5.1 Extinguishing media

Use water fog to cool containers from protected area.

# 5.2 Special hazards arising from the substance or mixture

Non flammable. Exposure to fire may cause containers to rupture/explode.

## 5.3 Advice for firefighters

Temperatures in a fire may cause cylinders to rupture. Cool cylinders or containers exposed to fire by applying water from a protected location. Do not approach cylinders or containers suspected of being hot. Remove cool cylinders from the path of the fire. Evacuate the area if unable to keep cylinders cool. Ensure work area is thoroughly ventilated before re-entry.

# 5.4 Hazchem code

2RE

2 Fine Water Spray.

R Wear liquid-tight chemical protective clothing and breathing apparatus. Dilute spill and run-off.

E Evacuation of people in and around the immediate vicinity of the incident should be considered.

# 6. ACCIDENTAL RELEASE MEASURES

## 6.1 Personal precautions, protective equipment and emergency procedures

If the cylinder is leaking, evacuate area of personnel. Inform manufacturer/supplier of leak. Use Personal Protective Equipment (PPE) as detailed in Section 8 of the SDS.

#### 6.2 Environmental precautions

Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous.

#### 6.3 Methods of cleaning up

Carefully move material to a well ventilated remote area, then allow to discharge if safe to do so. Do not attempt to repair leaking valve or cylinder safety devices.

Page 2 of 7

ChemAlert.

SDS Date: 16 Apr 2015

#### 6.4 Reference to other sections

See Sections 8 and 13 for exposure controls and disposal.

# 7. HANDLING AND STORAGE

### 7.1 Precautions for safe handling

Use of safe work practices are recommended to avoid eye or skin contact and inhalation. Do not drag, drop, slide or roll cylinders. The uncontrolled release of a gas under pressure may cause physical harm. Use a suitable hand truck for cylinder movement.

## 7.2 Conditions for safe storage, including any incompatibilities

Do not store near incompatible materials. Cylinders should be stored below 45°C in a secure area, upright and restrained to prevent cylinders from falling. Cylinders should also be stored in a dry, well ventilated area constructed of non-combustible material with firm level floor (preferably concrete), away from areas of heavy traffic and emergency exits.

## 7.3 Specific end use(s)

No information provided.

# 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

#### 8.1 Control parameters

#### **Exposure standards**

Ingredient	Reference	TWA		STEL	
	Kelefelice	ppm	mg/m³	ppm	mg/m³
Carbon dioxide	SWA (AUS)	5000	9000	30000	54000
Carbon dioxide in coal mines	SWA (AUS)	12500	22500	30000	54000
Ethylene	SWA (AUS)	Asphyxiant			

#### **Biological limits**

No biological limit values have been entered for this product.

# 8.2 Exposure controls

Engineering controls Avoid inhalation. Use in well ventilated areas. Where an inhalation risk exists, mechanical extraction

ventilation is recommended. Maintain vapour levels below the recommended exposure standard.

PPE

**Eye / Face** Wear safety glasses.

Hands Wear leather or cotton gloves.Body Wear coveralls and safety boots.

**Respiratory** Where an inhalation risk exists, wear Self Contained Breathing Apparatus (SCBA) or an Air-line respirator.









# 9. PHYSICAL AND CHEMICAL PROPERTIES

# 9.1 Information on basic physical and chemical properties

**COLOURLESS MIST Appearance** Odour **ODOURLESS** NON FLAMMABLE **Flammability** Flash point NOT RELEVANT -78°C (Carbon dioxide) **Boiling point NOT APPLICABLE Melting point Evaporation rate NOT APPLICABLE** Hq **NOT APPLICABLE** 

Vapour density 1.5 (Air = 1)
Specific gravity NOT APPLICABLE

**Solubility (water)** 0.759 cm<sup>3</sup>/cm<sup>3</sup> (Carbon dioxide)



SDS Date: 16 Apr 2015

#### PRODUCT NAME RIPEGAS

9.1 Information on basic physical and chemical properties

Vapour pressure 6300 kPa @ 25°C (Approximately)

**Upper explosion limit** NOT RELEVANT NOT RELEVANT Lower explosion limit Partition coefficient NOT AVAILABLE **Autoignition temperature NOT AVAILABLE** Decomposition temperature **NOT AVAILABLE NOT AVAILABLE** Viscosity **Explosive properties NOT AVAILABLE** Oxidising properties NOT AVAILABLE NOT AVAILABLE **Odour threshold** 

9.2 Other information

% Volatiles 100 %

# 10. STABILITY AND REACTIVITY

## 10.1 Reactivity

Unreactive under normal conditions.

## 10.2 Chemical stability

Stable under recommended conditions of storage.

## 10.3 Possibility of hazardous reactions

Polymerization will not occur.

### 10.4 Conditions to avoid

Avoid shock, friction, heavy impact, heat, sparks, open flames and other ignition sources.

#### 10.5 Incompatible materials

Moist carbon dioxide is corrosive, hence acid resistant materials are required (e.g. stainless steel). Certain properties of some plastics and rubbers may be affected by carbon dioxide (i.e. embrittlement, leaching of plasticisers, etc). Dust of aluminium, chrome and manganese ignite and explode when heated in carbon dioxide. Incompatible with acrylaldehyde, aziridine, metal acetylides, sodium peroxide. Corrosive when moist.

# 10.6 Hazardous decomposition products

This material will not decompose to form hazardous products other than that already present.

# 11. TOXICOLOGICAL INFORMATION

# 11.1 Information on toxicological effects

Acute toxicity Based on available data, the classification criteria are not met. Low concentrations of carbon dioxide cause

increased respiration and headache.

**Skin** Not classified as a skin irritant. Contact with the liquefied material or escaping compressed gas may cause

frostbite injury.

Eye Not classified as an eye irritant. Contact with the liquefied material may cause frostbite injury.

**Sensitization** Not classified as causing skin or respiratory sensitisation.

Mutagenicity Not classified as a mutagen.

Carcinogenicity Not classified as a carcinogen.

**Reproductive** Not classified as a reproductive toxin.

STOT - single Asphyxiant. Effects are proportional to oxygen displacement. Over exposure may result in dizziness,

drowsiness, weakness, fatigue, breathing difficulties and unconsciousness.

STOT – repeated

exposure

exposure

Not classified as causing organ effects from repeated exposure.

**Aspiration** Not classified as causing aspiration.

## 12. ECOLOGICAL INFORMATION

## 12.1 Toxicity

When discharged to the atmosphere in large quantities, carbon dioxide may contribute to the greenhouse effect.



SDS Date: 16 Apr 2015

Page 4 of 7 Version No: 3

#### PRODUCT NAME RIPEGAS

# 12.2 Persistence and degradability

Not applicable.

## 12.3 Bioaccumulative potential

Not applicable.

### 12.4 Mobility in soil

Not applicable.

### 12.5 Other adverse effects

When discharged to the atmosphere, carbon dioxide may contribute to the greenhouse effect.

# 13. DISPOSAL CONSIDERATIONS

#### 13.1 Waste treatment methods

Waste disposal Cylinders should be returned to the manufacturer or supplier for disposal of contents.

**Legislation** Dispose of in accordance with relevant local legislation.

# 14. TRANSPORT INFORMATION

#### CLASSIFIED AS A DANGEROUS GOOD BY THE CRITERIA OF THE ADG CODE



	LAND TRANSPORT (ADG)	SEA TRANSPORT (IMDG / IMO)	AIR TRANSPORT (IATA / ICAO)
14.1 UN Number	3163	3163	3163
14.2 Proper Shipping Name	LIQUEFIED GAS, N.O.S. (Contains carbon dioxide)	LIQUEFIED GAS, N.O.S. (Contains carbon dioxide)	LIQUEFIED GAS, N.O.S. (Contains carbon dioxide)
14.3 Transport hazard class	2.2	2.2	2.2
14.4 Packing Group	None Allocated	None Allocated	None Allocated

# 14.5 Environmental hazards No information provided

# 14.6 Special precautions for user

 Hazchem code
 2RE

 GTEPG
 2C2

 EMS
 F-C, S-V

Other information Ensure cylinder is separated from driver and that outlet of relief device is not obstructed.

# 15. REGULATORY INFORMATION

## 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Poison schedule A poison schedule number has not been allocated to this product using the criteria in the Standard for the

Uniform Scheduling of Medicines and Poisons (SUSMP).

Classifications Safework Australia criteria is based on the Globally Harmonised System (GHS) of Classification and

Page 5 of 7

Labelling of Chemicals.

The classifications and phrases listed below are based on the Approved Criteria for Classifying Hazardous

Substances [NOHSC: 1008(2004)].

Hazard codes None allocated.

Risk phrases None allocated.

Safety phrases None allocated.



SDS Date: 16 Apr 2015

#### Inventory listing(s)

**AUSTRALIA: AICS (Australian Inventory of Chemical Substances)** 

All components are listed on AICS, or are exempt.

# 16. OTHER INFORMATION

#### Additional information

The storage of significant quantities of gas cylinders must comply with AS4332 The storage and handling of gases in cylinders.

Application Method: Cylinders connected to fixed pipework distribution system with spray nozzles and controlled release.

### PERSONAL PROTECTIVE EQUIPMENT GUIDELINES:

The recommendation for protective equipment contained within this report is provided as a guide only. Factors such as method of application, working environment, quantity used, product concentration and the availability of engineering controls should be considered before final selection of personal protective equipment is made.

#### HEALTH EFFECTS FROM EXPOSURE:

It should be noted that the effects from exposure to this product will depend on several factors including: frequency and duration of use; quantity used; effectiveness of control measures; protective equipment used and method of application. Given that it is impractical to prepare a ChemAlert report which would encompass all possible scenarios, it is anticipated that users will assess the risks and apply control methods where appropriate.

#### **Abbreviations**

ACGIH American Conference of Governmental Industrial Hygienists

CAS # Chemical Abstract Service number - used to uniquely identify chemical compounds

CNS Central Nervous System

EC No. EC No - European Community Number

EMS Emergency Schedules (Emergency Procedures for Ships Carrying Dangerous

Goods)

GHS Globally Harmonized System

GTEPG Group Text Emergency Procedure Guide IARC International Agency for Research on Cancer

LC50 Lethal Concentration, 50% / Median Lethal Concentration

LD50 Lethal Dose, 50% / Median Lethal Dose

mg/m³ Milligrams per Cubic Metre
OEL Occupational Exposure Limit

pH relates to hydrogen ion concentration using a scale of 0 (high acidic) to 14 (highly

alkaline).

ppm Parts Per Million

STEL Short-Term Exposure Limit

STOT-RE Specific target organ toxicity (repeated exposure)
STOT-SE Specific target organ toxicity (single exposure)

Page 6 of 7

SUSMP Standard for the Uniform Scheduling of Medicines and Poisons

SWA Safe Work Australia
TLV Threshold Limit Value
TWA Time Weighted Average

#### Report status

This document has been compiled by RMT on behalf of the manufacturer, importer or supplier of the product and serves as their Safety Data Sheet ('SDS').

It is based on information concerning the product which has been provided to RMT by the manufacturer, importer or supplier or obtained from third party sources and is believed to represent the current state of knowledge as to the appropriate safety and handling precautions for the product at the time of issue. Further clarification regarding any aspect of the product should be obtained directly from the manufacturer, importer or supplier.

While RMT has taken all due care to include accurate and up-to-date information in this SDS, it does not provide any warranty as to accuracy or completeness. As far as lawfully possible, RMT accepts no liability for any loss, injury or damage (including consequential loss) which may be suffered or incurred by any person as a consequence of their reliance on the information contained in this SDS.



SDS Date: 16 Apr 2015

# PRODUCT NAME RIPEGAS

Prepared by

Risk Management Technologies 5 Ventnor Ave, West Perth Western Australia 6005 Phone: +61 8 9322 1711 Fax: +61 8 9322 1794 Email: info@rmt.com.au

Web: www.rmt.com.au.

[ End of SDS ]



SDS Date: 16 Apr 2015