Material Safety Data Sheet

May be used to comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200. Standard must be consulted for specific requirements.

U. S. Department of Labor

Occupational Safety and Health Administration (Non-Mandatory Form)
Form Approved
OMB No. 1218-0072

IDENTITY (As Used on Label and List) READY-STRIP SPRAY	Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.			
Section I				
Manufacturer's Name Sunnyside Corporation Manufacturer's Code: 663	Emergency Telephone Number Chem Trec (800) 424-9300			
Address (Number, Street, City, and ZIP Code) 225 Carpenter Avenue Wheeling, IL 60090	Telephone Number for Information (847) 541-5700			
Wheeling, 12 60076	Date Prepared 08/31/10			
	Signature of Preparer (optional)			
Section II-Hazardous Ingredients/Identity Info	ormation			
Hazardous Components (Specific Chemical Identity; C	Common Name(s)) OSHA PEL ACGIH TLV Other Limits % (optional			
N.Methyl-2 Pyrrolidone (872-50-4)	Not Established 30-35%			
Dimethyl Glutarate (1119-40-0)	Not Established 12-15%			
Dimethyl Adipate (627-93-0)	Not Established 5-8%			
Dimethyl Succinate (106-65-0)	Not Established 3-5%			
Monoethanolamine (141-43-5)	3 PPM 3 PPM 1-3%			
Isopropanolamine Mixture (78-96-6, 110-97-4, 122-20-3) 2-5%	(6 PPM STEL) Not Est. 2-5%			
	(500 PPM STEL) (400 PPM STEL)			
Non Toxic/Non Hazardous Components	N/A 45-50%			
Section III- Physical/Chemical Characteristics	<u> </u>			
Boiling Point 205° F	Specific Gravity (H ₂ 0=1) 1.02			
Vapor Pressure (mm Hg.) .2 mm Hg at 20 °c (68° F)	Melting Point N/A			
Vapor Density (AIR =1) 5.5-6	Evaporation Rate (Butyl Acetate=1) .06			
Solubility in Water 100%	VOC: 334 g/L			
Appearance and Odor Mild odor				
Section IV- Fire and Explosion Hazard Data				
Flash Point (Method Used) over 200°F	Flammable Limits LEL 1.1 UEL 8.5			
Extinguishing Media Water fog, spray, dry	y chemical C02			
Special Fire Fighting Procedures Do not enter confined	d fire space without protective equipment including NIOSH approved SCBA.			
Use water spray to co-	pol fire exposed surfaces and to protect personnel.			
Unusual Fire and Explosion Hazards Low when expose	sed to flames. May react with strong oxidizing materials			

Section V-React	tivity Data						
Stability	Unstable		Conditions to Avoid St	ong oxidizing agents, fi	re, flame		
	Stable	X					
	Stable	A					
Incompatibility (M	aterials to Avoid)	Strong	g oxidizing agents				
Hazardous Decomp	position or Byproduc	ts Unlik	ely				
Hazardous	May Occur		Conditions to Avoid N/A				
Polymerization							
	Will Not Occur	X					
Section VI-Heal	th Hazard Data						
Route(s) of Entry: Inhalation?		tion?	Skin?	Ingestion?			
	Not Es	tablished	Not Established	Not Established			
Health Hazards (A	cute and Chronic)	Mildly to	moderately irritating to eyes.				
			exposure to skin may cause irritation				
Carcinogenicity:		NTP?	IARC monograph		egulated?		
		Not listed	Not listed	Not regu	lated		
		•	ration unlikely to reach exposure lim				
Acute Overexposur		wsiness unli	kely due to very slow evaporation. N	Iay cause temporary blu	rring of vision.		
Chronic overexpos	ure: Upper respirat	ory tract irri	tation, lightheadedness.				
Medical Condition	s Generally Aggrava	ted by Expo	osure None established				
Eyes-flush exposed		ities of wate	emove victim to fresh air and provid r. Skin-wash skin with soap and wat				
Section VII-Pre	cautions for Safe	Handling	and Use				
	in Case Material is R			n -reactive absorbant ma	nterial collect in		
			high heat, sparks, flame. Recovered				
Wasta Disposal Ma	thad Dispass of in	aaaardanaa	with all Local, State and Federal reg	nulations			
Waste Disposal Me	•		ŕ				
	Γaken in Handing an		Store at room temperatures between	en 40°F-110°F,keep cont	ainer tightly		
closed. Do not mix with strong oxidants, acids or alkalies. Other Precautions Do not reuse empty containers for other liquids.							
Other Trecautions	Do not reuse	empty conte	miers for other riquids.				
Section VIII-Co	ntrol Measures						
		Ise NIOSH	approved chemical cartridge (organi	c vapor) respiratory equi	inment when		
	all face respirator is re			e vapor) respiratory equi	pinent when		
Ventilation	Local Exhaust Suff	cient to mai	ntain air concentration as required by	y OSHA Special	N/A		
	Mechanical (General) Maintain adequate ventilation			Other	N/A		
Protective Gloves	Butyl rubber, Neopr	ene gloves	Eye Protection Eye protection for application and removal such as chemical goggles.				
		t Impervio	ous coveralls, apron, boots, as necess	ary to prevent skin cont	act.		
Eye wash as needed $N/A = Not$ applicabl							

Section IX-Additional Information

This product contains the following toxic chemicals which are subject to reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

APPROXIMATE

TOXIC CHEMICAL CAS # % BY WEIGHT

N-Methyl-2-Pyrrolidone 872-50-4 32.9%

SARA Title III Hazard Categories: Immediate (Acute) Health Hazard

TRANSPORTATION: Not regulated as DOT Hazardous Material.

California Proposition 65: This product contains N-Methyl Pyrrolidone, a chemical known to the state of California to cause birth defects or other reproductive harm.