

Material Safety Data Sheet (MSDS)

MSDS # 0037
Revision 4

Series:
#0541, #0542, #0544, #0545,
#0548, #0549 Kit
(All Labels)

NFPA Rating: 1-0-0
HMIS Rating: 1-0-0-B

SECTION I

EMERGENCY TELEPHONE NO.

TRADE NAME (IF NONE, PUT CHEMICAL)	ONETIME® Lightweight Spackling Compound	(918) 825-5744 (24 Hrs.)
MANUFACTURER'S NAME AND TELEPHONE NO.	Red Devil, Incorporated	(918) 825-5744
ADDRESS (Number, Street, City, State, Zip Code)	4175 Webb Street, Pryor, Oklahoma 74361	

SECTION II - HAZARDOUS INGREDIENTS

% TLV PEL UNITS

PRODUCT CONSISTS OF:				
Acrylic & Vinyl Acrylic Emulsion Blend (Mixture)	<70	NE	NE	
Mineral Oil Based Anti-Foam (Mixture)	<0.25	NE	NE	
Octylphenol Ethoxylate [9036-19-5]	<0.75	NE	NE	
Non-hazardous ingredients*	<10	NA	NA	
Soda Lime Borosilicate (65997-17-3)	<25	NE	NE	
*Unlisted ingredients are not considered hazardous under the OSHA Hazard Communication Standard (29 CFR 1910.1200). Specific chemical identities withheld as trade secret pursuant to OSHA Haz. Com. Stand. 29 CFR 1910.1200 () VOC: 4%/wt. CARB Compliance: YES. Prop 65 Ingredients: NONE				

SECTION III - PHYSICAL DATA

BOILING POINT (°F)	NE	SPECIFIC GRAVITY (H ₂ O=1)	0.36 – 0.38
VAPOR PRESSURE (MM Hg.)	NE	PERCENT VOLATILES BY VOLUME (%)	<5
VAPOR DENSITY (AIR=1)	<1	pH	9-9.5
SOLUBILITY IN WATER	Appreciable	EVAPORATION RATE	<0.4 (BuAc = 1)
APPEARANCE AND ODOR	White paste; mild acrylic/ammonia odor		

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT (Method used)	> 200F (TOC)	FLAMMABLE LIMITS	LEL	NA	UEL	NA
EXTINGUISHING MEDIA	Use media suitable for adjacent materials.					
SPECIAL FIRE FIGHTING PROCEDURES	No special procedures are required.					
UNUSUAL FIRE AND EXPLOSION HAZARDS	None known.					

NA - Not Applicable

NF - Not Established

UN - Unavailable

SECTION V - HEALTH HAZARD INFORMATION

SYMPTOM/EFFECTS OR OVEREXPOSURE

Inhalation of dust generated from dried product may cause respiratory irritation. Prolonged or repeated contact may cause mild skin and eye irritation.

FIRST AID

EYES

Immediately flush with large amounts of water, holding eyelids open. Get medical attention if irritation persists.

SKIN

Wipe material from skin with cloth or paper towel, then wash exposed area with soap and water. Get medical help if irritation persists.

INHALATION

Move to fresh air. Treat with artificial respiration if needed. Seek medical attention if irritation persists.

INGESTION

Contact local poison control center or physician IMMEDIATELY!!

SECTION VI - REACTIVITY DATA

STABILITY

Stable

INCOMPATIBLE MATERIALS

None known

HAZARDOUS DECOMPOSITION PRODUCTS

Carbon monoxide, carbon dioxide, acrylic acid

SECTION VII - SPILL OR LEAK PROCEDURES

PROCEDURES

Wipe up spilled material. Wash area with detergent.

WASTE DISPOSAL METHOD

Dispose of in accordance with Local, State and Federal regulations.

SECTION VIII - SPECIAL PROTECTION INFORMATION

RESPIRATORY

Not normally required.

EYEWEAR

Wear safety glasses.

CLOTHING/GLOVES

Not normally required; For extended contact, neoprene or other chemical resistant gloves recommended.

VENTILATION

Provide adequate general dilution ventilation.

SECTION IX - SPECIAL PRECAUTIONS

Store in a closed container in cool dry area. Protect from freezing & excessive heat. DOT Proper Shipping Name: Not Regulated by DOT. DOT Hazard Class: None. DOT UN/NA Number: None. PACKING GROUP: None.

Reviewed By: Larry G. Brandon
2004

VP Technology & General Manager

June 24,

NAME

TITLE

DATE

The information contained herein has been developed based upon current available scientific data. New information may be developed from time to time which may render the conclusions of this report obsolete. Therefore, no warranty is extended as to the applicability of this information to the user's intended purpose or for the consequences of its use or misuse.