

# Remington® Rem® Oil with MoistureGuard, Liquid, Original

Revision 1 07/10/20

## 1. PRODUCT AND COMPANY IDENTIFICATION

**Product Name:** Remington® Rem® Oil with MoistureGuard, Liquid, Original

**Recommended Use:** Firearm Lubricant (not for incidental food contact or medical purposes)

Distributor: Remington Arms Company, LLC

1816 Remington Circle SW

Huntsville, AL 35824, USA

Telephone: 1-800-243-9700

**Emergency Telephone:** 1-800-424-9300 (CHEMTREC, 24 hours, Washington, D.C. USA)

#### 2. HAZARDS IDENTIFICATION

Classification: Not hazardous Labeling: Symbol: None

> Signal Word: Warning Hazard statements:

May be harmful if swallowed May cause eye irritation May cause skin irritation

Non-flammable or combustible but may burn if involved in a fire.

Wash hands thoroughly before using tobacco or other products intended to be

burned and inhaled.

#### **Precautionary Statements:**

Use personal protective equipment as required. Wear safety glasses and gloves.

#### 3. COMPOSITION / INFORMATION ON INGREDIENTS

**Chemical Identity:** Distillates (petroleum), light paraffinic; 95-99%

**Common Name:** Light paraffinic mineral oil

**CAS Number:** 64741-50-0

Impurities: No information available

**Chemical Identity:** 2,2-bis{[(9Z)-octadec-9-enoyloxy]methyl}butyl (9Z)-octadec-9-enoate; 1-5%

**Common Name:** Trimethylolpropane trioleate

**CAS Number:** 57675-44-2

Impurities: No information available

**Chemical Identity:** Naphthalenesulfonic acid, dinonyl, barium salt; < 1%

**Common Name:** Barium sulfonate **CAS Number:** 25619-56-1

Impurities: No information available

## 4. FIRST AID MEASURES

Flush eyes with large amounts of water. If signs/symptoms persist, get medical Eve Contact:

attention. Obtain medical attention.

Skin Contact: Wash affected area with soap and water. If signs/symptoms persist, get medical

attention. No need for first aid is anticipated.

If signs/symptoms develop, remove person to fresh air. If signs/symptoms Inhalation:

persist, get medical attention.

If swallowed, do not induce vomiting. If irritation or discomfort occurs, obtain Ingestion:

medical assistance.

#### 5. FIRE FIGHTING MEASURES

**Autoignition Temperature:** >150°C Flash point: >150°C

Flammable Limits (LEL) Not determined Flammable Limits (UEL) Not determined

Suitable Extinguishing Media: On large fires used dry chemical, foam, or water spray. On



# Remington® Rem® Oil with MoistureGuard, Liquid, Original

Revision 1 07/10/20

small fires use carbon dioxide, dry chemical, or water spray.

Water can be used to cool fire exposed containers.

Unsuitable Extinguishing Media: None.

**Specific hazards in case of fire:** Decomposes on heating and produces incompletely burned carbon

compounds. Avoid reaction with oxidizers.

## Special protective equipment and precautions for fire fighters:

No acute hazard. Move container from fire area, if possible. Avoid breathing vapors or dusts. Keep upwind. Use full firefighting gear (bunker gear). Any supplied-air respirator with full face piece and operated in a pressure-demand or other positive pressure mode in combination with a separate escape air supply. Use any self-contained breathing apparatus with a full-face piece.

Alert fire brigade and indicate hazard location. Wear breathing apparatus plus protective clothing. Cool fire exposed containers with water spray from a protected location. Do not approach containers suspected to be hot. If safe to do so, remove containers from path of fire.

#### 6. ACCIDENTAL RELEASE MEASURES

**Personal precautions:** Use appropriate personal protection. (See section 8.)

**Environmental precautions:** For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water. Collect the resulting residue containing solution. Place in a metal container approved for transportation by appropriate authorities. Dispose of collected material as soon as possible.

**Methods for material containment and cleaning up:** Observe precautions from other sections. Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it

appears dry. Collect as much of the spilled material as possible. Clean up residue with an appropriate solvent. Seal the container.

#### 7. HANDLING AND STORAGE

Precautions for safe handling: Avoid contact with skin, inhalation of mist, or ingestion. See Section 8 for personal protection equipment. Practice good personal hygiene to prevent accidental ingestion after handling. Properly dispose of clothing that cannot be decontaminated. Wash hands thoroughly before using tobacco or other products intended to be burned and inhaled.

Conditions for safe storage, including any incompatibilities: Store away from oxidizing materials. Store product in a closed container located in a dry area. Do not store in open, inadequate, or mislabeled packaging. Check that containers are clearly labeled. Use metal cans, metal drums, plastic, or lined fiber containers. Keep away from heat and flame.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

**Control Parameters:** Under most handling conditions, this product will not generate mist or dust. **Engineering Controls:** In most conditions, no special local ventilation is needed. General ventilation recommended. If the product is atomized ventilation should be used.

## Personal Protective Equipment (PPE):

**Eyes:** Safety glasses recommended.

**Skin:** Impermeable gloves should be worn. Petroleum-resistant elastomers are recommended.

**Inhalation:** No respiratory protection required under most conditions. If concentrations exceed

exposure limits, approved respiratory equipment must be used.

#### 9. CHEMICAL AND PHYSICAL PROPERTIES

Physical state: Liquid Color: Amber

Odor: Mild petroleum
Odor Threshold: Not available
pH Value: Not applicable



Remington® Rem® Oil with MoistureGuard, Liquid, Original

Revision 1 07/10/20

Melting Point: -30°C

Freezing Point: Becomes very stiff with decreasing temperature around -50°C

Initial Boiling Point: >150°C
Flash Point: >150°C COC
Evaporation rate: Not available
Flammability (solid, gas): Not applicable
Explosion limits: Not available
Vapor pressure: Negligible at 20°C
Vapor density: Not available

**Solubility:** Insoluble in water at 20°C

Partition coefficient: Not available Auto-ignition temperature: Not available

**Decomposition temperature:** Begins to oxidize at a slow rate at 125°C

#### 10. STABILITY AND REACTIVITY

Chemical stability: Stable under ambient temperatures and pressures

Possibility of hazardous reactions: Can react with strong oxidizers. Other hazardous reactions have

not been identified. Otherwise will not react or polymerize.

**Conditions to avoid:** No specific conditions to avoid have been identified.

Materials to avoid: Oxidizers.

Hazardous decomposition products: Decomposes on heating and produces incompletely burned

carbon compounds

#### 11. TOXICOLOGICAL INFORMATION

General information: ......Not available. Information on likely routes of exposure

Vomiting may increase risk of product aspiration.

criteria for classification.

Skin contact: .....Frequent or prolonged contact may defat and dry the skin, leading to

discomfort and dermatitis.

Eye contact: ......May be irritating to eyes.

Symptoms: ......Not available.

Information on toxicological effects

Acute toxicity:.....Not classified.

Skin corrosion/irritation: ......................Not classified. May cause defatting of the skin but is neither an irritant nor a

sensitizer.

Serious eye damage/eye irritation:.....Not classified.
Respiratory sensation:.....Not classified.
Skin sensation:.....Not classified.

Germ cell mutagenicity: ......Non-mutagenic based on Modified Ames Assay.

Carcinogenicity: .......Meets EU requirement of less than 3% (w/w) DMSO extract for total

polycyclic aromatic compound (PAC) using IP 346.

#### 12. ECOLOGICAL INFORMATION

Toxicity: Not expected to be harmful to aquatic organisms.

Persistence and degradability: Not inherently biodegradable.

Bio accumulative Potential: Bioaccumulation is unlikely to be significant because of the low water

solubility of this product. Partition coefficient n-octanol/water (log Kow) Not

established.

Bioconcentration factor (BCF): Not available.

Mobility in soil: Not available.

Results of PBT and vPvB assessment: Not applicable.

Other adverse effects: No other adverse environmental effects (e.g. ozone depletion,

# Remington.

# **SAFETY DATA SHEET**

# Remington® Rem® Oil with MoistureGuard, Liquid, Original

Revision 1 07/10/20

photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

## 13. DISPOSAL PROCEDURES

**Waste treatment methods:** Waste (substance and container material) shall be recycled/recovered or disposed of as applicable and in accordance with community (EU) and local legislation. Recycle wherever possible. Consult state land waste management authority for disposal. Bury at an approved site. Recycle containers if possible or dispose of in an authorized landfill.

**According to the European Waste Catalogue**, Waste Codes are not product specific but application specific. Waste Codes should be assigned by the user based on the application in which the product is used.

**For USA Disposal:** Waste must be disposed of in accordance with federal, state, and local environmental control regulations.

#### 14. TRANSPORT INFORMATION

Class or Type: US DOT, IMO, ADR, RID, ADN, IMDG, and IATA: Non-hazardous

#### 15. REGULATORY INFORMATION

Safety, health, and environmental regulations/legislation specific for the mixture: Other Information:

## U. S. Regulatory information

| TSCA Inventory Status:                           | Y               |
|--|-----------------|
| TSCA 12 (b) Export Notification:                 | Not listed      |
| CERCLA Section 103 (40 CFR 302.4):               | V               |
| SARA Section 302 (40 CFR 355.30):                | V               |
| SARA Section 304 (40 CFR 355.40):                | V               |
| SARA Section 313 (40 CFR 372.65):                | V               |
| OSHA Process Safety (29 CFR 1910.119):           | V               |
| SARA Hazard Categories, SARA Sections 311/312 (4 | 0 CFR 370.21) - |
| Acute Hazard:l                                   | N               |
| Chronic Hazard:I                                 | V               |
| Fire Hazard:I                                    | V               |
| Reactivity Hazard:                               | V               |
| Sudden Release Hazard:                           | V               |

**State Regulations:** California Safe Drinking Water and Toxic Enforcement Act (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins. **Note –** There are no known safety, health or environmental restrictions or prohibitions in any country where this product is produced, imported, or marketed.

## Chemical Inventories:

| DSL (Canada)                      | . All ingredients listed or exempt |
|-----------------------------------|------------------------------------|
| EINECS (European Union)           | . All ingredients listed or exempt |
| ENCS/ISHL (Japan)                 | . All ingredients listed or exempt |
| IECSC (Peoples Republic of China) | . All ingredients listed or exempt |
| TSCA (United States of America)   | . All ingredients listed or exempt |

#### 16. OTHER INFORMATION

## NFPA Hazard Classification:

| Health:          | 1 |
|------------------|---|
| Flammability:    | 1 |
| Reactivity:      |   |
| Special Hazards: |   |

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency personnel to address the hazards that are presented by short-term, acute exposure to material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products



# Remington® Rem® Oil with MoistureGuard, Liquid, Original

Revision 1 07/10/20

that are known to be generated in significant quantities.

HMIS Hazard Classification:

 Health:
 1

 Flammability:
 1

 Reactivity:
 0

Protection: ..... B (See PPE section)

Hazardous Material Identification System (HMIS) hazard ratings are designed to inform employees of chemical hazards in the workplace. The ratings are based on inherent properties of the material under expected conditions of normal use and are not intended for use in emergency situations.

These data are offered in good faith as typical values and not as product specifications. No warranty, either expressed or implied, is hereby made. The recommended industrial hygiene and safe handling procedures are believed to be generally applicable. However, each user should review these recommendations in the specific context of the intended use and determine whether they are appropriate.

Prepared By: PolySi® Technologies, Inc.

5108 Rex McLeod Dr. Sanford N.C. 27330 Email polysi@polysi.com Phone: (919) 775-4989