Version 4.2 Revision Date 05/12/2020 Print Date 06/01/2020

### **SECTION 1. PRODUCT AND COMPANY IDENTIFICATION**

Material name : RENOWN DUST MOP TREATMENT AEROSOL REN05023-

ΑM

Material number : 00000000001027086

## Manufacturer or supplier's details

#### **DISTRIBUTOR**

Home Depot 701 San Marco Blvd.

Jacksonville, FL 32207

**Customer Service: 866-412-6726** 

## 24 HR. EMERGENCY TELEPHONE NUMBERS

VERISK 3E : 1-800-451-8346 (USA)

1-760-602-8703 (INTERNATIONAL)

### Recommended use of the chemical and restrictions on use

Recommended use : Floor Care

## **SECTION 2. HAZARDS IDENTIFICATION**

#### **Emergency Overview**

| Appearance | Aerosol containing a liquefied gas |  |
|------------|------------------------------------|--|
| Colour     | white                              |  |
| Odour      | characteristic                     |  |

### **GHS Classification**

Gases under pressure : Liquefied gas

**GHS** label elements

Hazard pictograms :

Gas cylinder

Signal word : Warning

Hazard statements : H280 Contains gas under pressure; may explode if heated.

Precautionary statements : **Prevention:** 

P210 Keep away from heat, hot surfaces, sparks, open flames

and other ignition sources. No smoking.

P251 Pressurized container: Do not pierce or burn, even after

use.

Storage:

P410 + P403 Protect from sunlight. Store in a well-ventilated

place.

Version 4.2 Revision Date 05/12/2020 Print Date 06/01/2020

P412 Do not expose to temperatures exceeding 50 °C/ 122 °F.

Disposal:

P501 Dispose of contents/container in accordance with local

regulation.

#### **SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Substance / Mixture : Mixture

### **Hazardous components**

| Chemical name  | CAS-No.    | Concentration [%] |
|--|------------|-------------------|
| Distillates (petroleum), hydrotreated heavy naphthenic | 64742-52-5 | >= 10 - < 30      |
| Distillates (petroleum), hydrotreated light            | 64742-47-8 | >= 5 - < 10       |
| butane   | 106-97-8   | >= 5 - < 10       |
| Solvent naphtha (petroleum), medium aliph.             | 64742-88-7 | >= 5 - < 10       |
| propane  | 74-98-6    | >= 1 - < 5        |

The exact percentages of disclosed substances are withheld as trade secrets.

## **SECTION 4. FIRST AID MEASURES**

General advice : Show this safety data sheet to the doctor in attendance.

Do not leave the victim unattended.

Move out of dangerous area.

If inhaled : If unconscious, place in recovery position and seek medical

advice.

If symptoms persist, call a physician.

In case of skin contact : If skin irritation persists, call a physician.

Wash off immediately with plenty of water for at least 15

minutes.

If on clothes, remove clothes.

: Flush eyes with water as a precaution. In case of eye contact

> Remove contact lenses. Protect unharmed eye.

Keep eye wide open while rinsing.

Rinse immediately with plenty of water for at least 15 minutes. : Clean mouth with water and drink afterwards plenty of water.

Keep respiratory tract clear.

DO NOT induce vomiting unless directed to do so by a

physician or poison control center.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician.

Most important symptoms

and effects, both acute and

delayed

If swallowed

: Effects are immediate and delayed.

Symptoms may include irritation, redness, pain, and rash.

Causes skin irritation.

Review section 2 of SDS to see all potential hazards.

: Treat symptomatically. Symptoms may be delayed. Notes to physician

Version 4.2 Revision Date 05/12/2020 Print Date 06/01/2020

#### **SECTION 5. FIREFIGHTING MEASURES**

Suitable extinguishing media : Alcohol-resistant foam

Carbon dioxide (CO2)

Dry chemical Water spray jet

Unsuitable extinguishing

media

: High volume water jet

Specific hazards during

firefighting

: Do not allow run-off from fire fighting to enter drains or water

courses.

Hazardous combustion

products

: Carbon dioxide (CO2) Carbon monoxide

Smoke

Specific extinguishing

methods

: Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Further information

Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

Special protective equipment

for firefighters

Wear self-contained breathing apparatus for firefighting if

necessary.

#### **SECTION 6. ACCIDENTAL RELEASE MEASURES**

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment. Evacuate personnel to safe areas. Ensure adequate ventilation.

Remove all sources of ignition.

Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

Environmental precautions

Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains, inform

respective authorities.

Methods and materials for containment and cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Sweep up or vacuum up spillage and collect in suitable

container for disposal.

## **SECTION 7. HANDLING AND STORAGE**

Advice on safe handling : Avoid contact with skin and eyes.

For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the

application area.

Take precautionary measures against static discharges. Provide sufficient air exchange and/or exhaust in work rooms.

Always replace cap after use.

Dispose of rinse water in accordance with local and national

regulations.

Do not breathe vapours or spray mist.

Conditions for safe storage : BEWARE: Aerosol is pressurized. Keep away from direct sun

Version 4.2 Revision Date 05/12/2020 Print Date 06/01/2020

exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects.

No smoking.

Observe label precautions.

Electrical installations / working materials must comply with

the technological safety standards.

Keep in a dry, cool and well-ventilated place.

Materials to avoid : Oxidizing agents

## **SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

## Components with workplace control parameters

| Components   | CAS-No.    | Value type<br>(Form of<br>exposure) | Control parameters / Permissible concentration | Basis     |
|--|------------|-------------------------------------|--|-----------|
| Distillates (petroleum), hydrotreated heavy naphthenic | 64742-52-5 | TWA (Mist)                          | 5 mg/m3  | OSHA Z-1  |
|  |            | TWA<br>(Inhalable<br>fraction)      | 5 mg/m3  | ACGIH     |
| Distillates (petroleum), hydrotreated light            | 64742-47-8 | TWA                                 | 500 ppm<br>2,000 mg/m3                         | OSHA Z-1  |
|  |            | TWA                                 | 400 ppm<br>1,600 mg/m3                         | OSHA P0   |
|  |            | TWA (Mist)                          | 5 mg/m3  | OSHA Z-1  |
|  |            | TWA (Mist)                          | 5 mg/m3  | OSHA P0   |
|  |            | TWA (Mist)                          | 5 mg/m3  | NIOSH REL |
|  |            | ST (Mist)                           | 10 mg/m3                                       | NIOSH REL |
|  |            | PEL (particulate)                   | 5 mg/m3  | CAL PEL   |
| butane   | 106-97-8   | TWA                                 | 800 ppm<br>1,900 mg/m3                         | NIOSH REL |
|  |            | TWA                                 | 800 ppm<br>1,900 mg/m3                         | OSHA P0   |
|  |            | PEL                                 | 800 ppm<br>1,900 mg/m3                         | CAL PEL   |
|  |            | STEL                                | 1,000 ppm                                      | ACGIH     |
| propane  | 74-98-6    | TWA                                 | 1,000 ppm<br>1,800 mg/m3                       | NIOSH REL |
|  |            | TWA                                 | 1,000 ppm<br>1,800 mg/m3                       | OSHA Z-1  |
|  |            | TWA                                 | 1,000 ppm<br>1,800 mg/m3                       | OSHA P0   |
|  |            | PEL                                 | 1,000 ppm<br>1,800 mg/m3                       | CAL PEL   |

**Engineering measures** : effective ventilation in all processing areas

Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust

ventilation is provided or exposure assessment demonstrates

Version 4.2 Revision Date 05/12/2020 Print Date 06/01/2020

that exposures are within recommended exposure guidelines.

Hand protection

Material : Protective gloves

Remarks : The suitability for a specific workplace should be discussed

with the producers of the protective gloves.

Eye protection : Safety glasses

Ensure that eyewash stations and safety showers are close to

the workstation location.

Skin and body protection : Impervious clothing

Choose body protection according to the amount and

concentration of the dangerous substance at the work place.

Hygiene measures : When using do not eat or drink.

When using do not smoke.

Wash hands before breaks and at the end of workday.

## **SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance : Aerosol containing a liquefied gas

Colour : white

Odour : characteristic

Odour Threshold : No data available pH : Not applicable

. Not applicable

Boiling point : No data available

Flash point

Melting point/freezing point

Not applicable

: No data available

Evaporation rate : No data available

Flammability (solid, gas,

liquid)

The product is not flammable.

Upper explosion limit : No data available
Lower explosion limit : No data available
Vapour pressure : No data available
Relative vapour density : No data available

Density : 0.93 g/cm3

Solubility(ies)

Water solubility : emulsifiable
Solubility in other solvents : not determined

Partition coefficient: n-

octanol/water

: No data available

Auto-ignition temperature : not determined

Thermal decomposition : No data available

Version 4.2 Revision Date 05/12/2020 Print Date 06/01/2020

Viscosity

Viscosity, kinematic : No data available

#### **SECTION 10. STABILITY AND REACTIVITY**

Reactivity : Stable

Chemical stability : Stable under normal conditions.

Possibility of hazardous

reactions

Conditions to avoid : Heat, flames and sparks.

Extremes of temperature and direct sunlight.

: No decomposition if stored and applied as directed.

Incompatible materials
Hazardous decomposition

products

: Oxidizing agents: Carbon oxides

#### **SECTION 11. TOXICOLOGICAL INFORMATION**

## **Potential Health Effects**

Aggravated Medical

Condition

: None known.

Symptoms of Overexposure : Effects are immediate and delayed.

Symptoms may include irritation, redness, pain, and rash.

Causes skin irritation.

Review section 2 of SDS to see all potential hazards. Treat symptomatically. Symptoms may be delayed.

Carcinogenicity:

IARC No component of this product present at levels greater than or

equal to 0.1% is identified as probable, possible or confirmed

human carcinogen by IARC.

ACGIH No component of this product present at levels greater than or

equal to 0.1% is identified as a carcinogen or potential

carcinogen by ACGIH.

OSHA No component of this product present at levels greater than or

equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP No component of this product present at levels greater than or

equal to 0.1% is identified as a known or anticipated carcinogen

by NTP.

## **Acute toxicity**

**Product:** 

Acute dermal toxicity : Acute toxicity estimate : > 5,000 mg/kg

Method: Calculation method

Version 4.2 Revision Date 05/12/2020 Print Date 06/01/2020

## **Components:**

**Distillates (petroleum), hydrotreated heavy naphthenic:**Acute oral toxicity : LD50 Rat: > 5,000 mg/kg

Acute inhalation toxicity : LC50 Rat: > 5 mg/l

Exposure time: 4 h

Acute dermal toxicity : LD50 Rabbit: > 5,000 mg/kg

Distillates (petroleum), hydrotreated light:

Acute oral toxicity : LD50 Rat: > 5,000 mg/kg

Acute inhalation toxicity : LC50 Rat: > 4.6 mg/l

Exposure time: 6 h

Acute dermal toxicity : LD50 Rat: > 2,000 mg/kg

## Skin corrosion/irritation

### **Product:**

Remarks: May cause skin irritation and/or dermatitis.

## Serious eye damage/eye irritation

## **Product:**

Remarks: May irritate eyes.

## Respiratory or skin sensitisation

No data available

## Germ cell mutagenicity

No data available

## Carcinogenicity

No data available

### Reproductive toxicity

No data available

## STOT - single exposure

No data available

## STOT - repeated exposure

No data available

## **Aspiration toxicity**

No data available

## **Further information**

Version 4.2 Revision Date 05/12/2020 Print Date 06/01/2020

**Product:** 

Remarks: No data available

#### **SECTION 12. ECOLOGICAL INFORMATION**

## **Ecotoxicity**

No data available

#### Persistence and degradability

No data available

## **Bioaccumulative potential**

Product:

Partition coefficient: n-

octanol/water <a href="Components:">Components:</a> <a href="butane">butane</a> :

Partition coefficient: n-

octanol/water

: Remarks: No data available

: Pow: 2.89

Mobility in soil

No data available

## Other adverse effects

No data available **Product:** 

\_\_\_\_\_

Regulation 40 CFR Protection of Environment; Part 82 Protection of

Stratospheric Ozone - CAA Section 602 Class I

Substances

Remarks This product neither contains, nor was manufactured

with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A

+ B).

Additional ecological

information

: No data available

#### **SECTION 13. DISPOSAL CONSIDERATIONS**

### **Disposal methods**

Waste from residues : Dispose of in accordance with local regulations.

The product should not be allowed to enter drains, water

courses or the soil.

Do not contaminate ponds, waterways or ditches with

chemical or used container.

Version 4.2 Revision Date 05/12/2020 Print Date 06/01/2020

Contaminated packaging : Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.

Do not burn, or use a cutting torch on, the empty drum.

#### **SECTION 14. TRANSPORT INFORMATION**

Transportation Regulation: 49 CFR (USA):

UN1950, AEROSOLS, NON-FLAMMABLE, 2.2, - Limited quantity

Transportation Regulation: IMDG (Vessel): UN1950, AEROSOLS, 2.2, - Limited quantity

Transportation Regulation: IATA (Cargo Air):

UN1950, AEROSOLS, NON-FLAMMABLE, 2.2, - Limited quantity

Transportation Regulation: IATA (Passenger Air):

UN1950, AEROSOLS, NON-FLAMMABLE, 2.2, - Limited quantity

Transportation Regulation: TDG (Canada):

UN1950, AEROSOLS, NON-FLAMMABLE, 2.2, - Limited quantity

The product as delivered to the customer conforms to packaging requirements for shipment by road under US Department of Transportation (DOT) regulations. Additional transportation classifications noted above are for reference only, and not a certification or warranty of the suitability of the packaging for shipment under these alternative transport regulations.

### **SECTION 15. REGULATORY INFORMATION**

**TSCA list** : No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification

requirements.

## **EPCRA - Emergency Planning and Community Right-to-Know Act**

#### **CERCLA Reportable Quantity**

| Components | CAS-No.   | Component RQ | Calculated product RQ |
|------------|-----------|--------------|-----------------------|
|            |           | (lbs)        | (lbs)                 |
| xylenes    | 1330-20-7 | 100          | *                     |

<sup>\*:</sup> Calculated RQ exceeds reasonably attainable upper limit.

## SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards : Gases under pressure

SARA 302 : No chemicals in this material are subject to the reporting

requirements of SARA Title III, Section 302.

Version 4.2 Revision Date 05/12/2020 Print Date 06/01/2020

SARA 313 : This material does not contain any chemical components with

known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

California Prop. 65

This product does not contain any chemicals known to State of

California to cause cancer, birth defects, or any other

reproductive harm.

## The components of this product are reported in the following inventories:

**DSL** All components of this product are on the Canadian DSL

TSCA On TSCA Inventory

For information on the country notification status for other regions please contact the manufacturer's regulatory group.

## **Inventory Acronym and Validity Area Legend:**

TSCA (USA), DSL (Canada), NDSL (Canada)

## **SECTION 16. OTHER INFORMATION**

Revision Date 05/12/2020 Print Date 06/01/2020

## **Further information**

## NFPA:

| HEALTH          | 2 |
|-----------------|---|
| FLAMMABILITY    | 1 |
| INSTABILITY     | 0 |
| SPECIAL HAZARD. |   |

0 = not significant, 1 = Slight,

2 = Moderate, 3 = High

4 = Extreme

#### HMIS III:

| HEALTH          | 2 |
|-----------------|---|
| FLAMMABILITY    | 1 |
| PHYSICAL HAZARD | 2 |

0 = not significant, 1 = Slight,

2 = Moderate, 3 = High 4 = Extreme, \* = Chronic

### **OSHA GHS Label Information:**

Hazard pictograms



Gas cylinder Warning:

Signal word Hazard statements Precautionary statements

Contains gas under pressure; may explode if heated.

Prevention: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Pressurized container: Do not pierce or burn, even after use.

Storage: Protect from sunlight. Store in a well-ventilated place. Do not expose to temperatures exceeding 50 °C/ 122 °F.

Disposal: Dispose of contents/container in accordance with local regulation.

| Version:       | 4.2        |
|----------------|------------|
| Revision Date: | 05/12/2020 |
| Print Date:    | 06/01/2020 |

Version 4.2 Revision Date 05/12/2020 Print Date 06/01/2020

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. Users should make their own investigations to determine the suitability and applicability of the information for their particular purposes. This SDS has been prepared by the Compliance Services organization supporting this manufacturer, supplier or distributor.